

Package ‘mypackage’

January 21, 2024

Title Demo Package as an Example
Version 0.0.0.9000
Description This package is used as a demo for a simple package for the course MATH 3190 at Southern Utah University. It contains functions on adding, subtracting, and graphing a simple scatterplot.
License MIT + file LICENSE
URL <https://github.com/rbrown53/mypackage>
Encoding UTF-8
Roxygen list(markdown = TRUE)
RoxygenNote 7.3.0
Depends R (>= 2.10),
ggplot2,
shiny
Imports magrittr,
tidyverse
LazyData true
Suggests knitr,
rmarkdown
Author Rick Brown [aut, cre]
Maintainer Rick Brown <richardbrown1@suu.edu>
VignetteBuilder knitr

R topics documented:

add	2
cranes	2
ggraph	3
hello	3
runCor	4
subtract	4
Index	5

add	<i>This is my addition function</i>
-----	-------------------------------------

Description

This is my addition function

Usage

```
add(x, y)
```

Arguments

x	this is the first value to add
y	this is the second value to add

Value

This function returns the sum of x and y

Examples

```
## Start with something simple
add(1,1)

## Now something more difficult
add(49,60)
```

cranes	<i>Cranes Data Set</i>
--------	------------------------

Description

This data set contains information on the number of cranes at Aransas National Wildlife Refuge in Austwell, Texas by year from 1938 to 2016.

Usage

```
cranes
```

Format

A data frame with 2 variables: cranes and year.

`ggraph`*Create a quick scatter plot in ggplot.*

Description

This will graph two given vectors in a ggplot-style scatter plot with the x-axis labeled "x" and the y-axis labeled "y".

Usage

```
ggraph(x, y, point_color = "black", point_size = 1.5, point_shape = 19)
```

Arguments

<code>x</code>	This is the first vector to be plotted.
<code>y</code>	This is the first vector to be plotted.
<code>point_color</code>	This is the color of the points that will be plotted.
<code>point_size</code>	This is the size of the points that will be plotted. The default is size 1.5.
<code>point_shape</code>	This is the shape of the points that will be plotted. The default is 19: a filled circle.

Value

This function returns a ggplot scatter plot object.

Examples

```
## Create a scatter plot of y vs x.  
x <- rnorm(100)  
y <- x + rnorm(100, 0, 0.3)  
ggraph(x, y)
```

`hello`*This is my hello function. There are no parameters.*

Description

This is my hello function. There are no parameters.

Usage

```
hello()
```

Value

This function returns the message "hello world".

Examples

```
## This is the only thing this function does.  
hello()
```

`runCor`*Correlation App*

Description

This function allows the correlation shiny app to run. The app is a little game where you are presented with a graph and you guess the correlation between the two variables. The true correlation will then be shown and the difference between your guess and the true correlation will be given

Usage

```
runCor()
```

`subtract`*This is my subtract function*

Description

This is my subtract function

Usage

```
subtract(x, y)
```

Arguments

<code>x</code>	this is the first value
<code>y</code>	this is the second value to subtract

Value

This function returns the difference of x and y

Examples

```
## Start with something simple  
subtract(1, 1)  
  
## Now something more difficult  
subtract(49, 60)
```

Index

- * **datasets**
 - cranes, [2](#)
- add, [2](#)
- cranes, [2](#)
- ggraph, [3](#)
- hello, [3](#)
- runCor, [4](#)
- subtract, [4](#)