

#### **COMP2511**

# Object-Oriented Design and Programming User Interface Design

Wayne Wobcke

w.wobcke@unsw.edu.au

© W. Wobcke, 2018

— UNSW Computer Science & Engineering



## Today's Lecture

- Usability
- User Centred Design
- Java GUI Programming
- Observer Pattern
- Model View Controller

— UNSW Computer Science & Engineering



# **Usability Heuristics**

- 1. Visibility of system status
- 2. Match between system and real world
- 3. User control and freedom
- 4. Consistency and standards
- 5. Error prevention
- 6. Recognition rather than recall
- 7. Flexibility and efficiency of use
- 8. Aesthetic and minimalist design
- 9. Help users recognize, diagnose, recover from errors
- 10. Help and documentation

© W. Wobcke, 2018

— UNSW Computer Science & Engineering




## **User Centred Design**

- Personas
  - Who are the users?
  - What are their goals/skills/environment?
- Scenarios
  - How/when will they use the system?
- Use Cases
  - ◆ How will they interact with the system?



# Sudoku Interface Example




© W. Wobcke, 2018

— UNSW Computer Science & Engineering




# Java GUI Programming: Swing



**UNSW** Computer Science & Engineering



# **Layout Managers**




© W. Wobcke, 2018 Image Horstmann, C. Object-Oriented Design and Patterns, © John Wiley and Sons, 2006.

— UNSW Computer Science & Engineering



## Sudoku Interface Components



© W. Wobcke, 2018 Image Horstmann, C. Object-Oriented Design and Patterns, © John Wiley and Sons, 2006.



#### Sudoku View

```
JFrame sudoku = new JFrame();
sudoku.setLayout(new BorderLayout());

SudokuGrid grid = new SudokuGrid(game);
SudokuController sudokuController = new SudokuController(grid, game);
grid.setController(sudokuController);
sudoku.add(sudokuGrid, BorderLayout.CENTER);

ButtonPanel buttonPanel = new ButtonPanel(game, grid);
ButtonController buttonController = new ButtonController(grid, game);
buttonPanel.setController(buttonController);
sudoku.add(buttonPanel, BorderLayout.EAST);
frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
frame.pack();
frame.setVisible(true);

© W. Wobcke, 2018
```

— UNSW Computer Science & Engineering



# Simple Example: Timer

```
JFrame frame = new JFrame();
final JLabel label = new JLabel();
label.setText("Time: " + Calendar.getInstance().getTime);
frame.setLayout(new FlowLayout());
frame.add(label);

Timer t = new Timer(DELAY, new ActionListener() {
    public void actionPerformed(ActionEvent event) {
        label.setText("Time: " + Calendar.getInstance().getTime());
    }
t.start();
frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
frame.pack();
frame.setVisible(true);
```

**UNSW** Computer Science & Engineering



#### Observer Pattern

#### Motivation

 Need a way for a number of objects to be informed of changes in another object

#### ■ Intent


 Have the object maintain a list of the objects that need to be informed, and notify them whenever any change occurs

© W. Wobcke, 2018

**UNSW** Computer Science & Engineering



## **Observer Pattern Implementation**




© W. Wobcke, 2018 9 © W. Wobcke, 2018 11





### **MVC** Architectural Pattern



## ■ Not necessarily needed in the project


© W. Wobcke, 2018 Image http://lkubaski.wordpress.com/2012/12/20/java-se-application-design-with-mvc-with-images/

.

— UNSW Computer Science & Engineering



## Sudoku UML Class Diagram



— UNSW Computer Science & Engineering



## Sudoku Controllers

```
JFrame sudoku = new JFrame();
sudoku.setLayout(new BorderLayout());

SudokuGrid grid = new SudokuGrid(game);
SudokuController sudokuController = new SudokuController(grid, game);
grid.setController(sudokuController);
sudoku.add(sudokuGrid, BorderLayout.CENTER);

ButtonPanel buttonPanel = new ButtonPanel(game, grid);
ButtonController buttonController = new ButtonController(grid, game);
buttonPanel.setController(buttonController);
sudoku.add(buttonPanel, BorderLayout.EAST);
frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
frame.pack();
frame.setVisible(true);
```

UNSW Computer Science & Engineering

© W. Wobcke, 2018



14

## Sudoku Controller Example

```
public class SudokuController implements MouseListener {
public void mousePressed(MouseEvent e)
  {
    JPanel panel = (JPanel) e.getSource();
    Component component = panel.getComponentAt(e.getPoint());
    if (component instanceof GridComponent)
     {
        GridComponent selected = (GridComponent) component;
        // either set selected on view or update model
     }
}
```


© W. Wobcke, 2018 13 © W. Wobcke, 2018 15

#### — UNSW Computer Science & Engineering



## Sudoku Controller

SudokuController implements MouseListener Game extends Observable; SudokuGrid implements Observer grid.setController(sudokuController); game.addObserver(grid);



— UNSW Computer Science & Engineering



## **Next Week**

- Design Patterns and Refactoring
  - ◆ Decorator & Composite Patterns

© W. Wobcke, 2018