

1. Write a Perl program which reads from STDIN a username then a password (not both simultaneously).

It should then check the password matches one stored for user *username* in the file `users/username.password`.

It should print a message indicating the user is unknown if this file does not exist otherwise print an appropriate message indicating whether the password matches.

For example:

```
$ mkdir users
$ echo 'correct horse battery staple' >users/andrewt.password
$ login.pl
username: jas
password: beer
Unkown username!
$ login.pl
username: andrewt
password: 42
Incorrect password!
$ login.pl
username: andrewt
password: correct horse battery staple
You are authenticated.
```

2. How are CGI scripts run?
3. Write a shell CGI script which prints details of the context in which it is run. Here is an example implementation:

show_execution_context.sh.cgi (code/cgi/show_execution_context.sh.cgi)

<p>Execution Environment</p> <pre>pwd: /tmp_amd/kamen/export/kamen/3/cs2041cgi/public_html id: uid=14380(cs2041cgi) gid=14380(cs2041cgi) groups=14380 hostname: dvorak uname -a: Linux dvorak 3.2.0-4-686-pae #1 SMP Debian 3.2.0-4-686-pae</pre>	<pre><html> <head></head> <body> <h2>Execution Environment</h2> <pre>pwd: /tmp_amd/kamen/export/kamen/3/cs2041cgi/public_html id: uid=14380(cs2041cgi) gid=14380(cs2041cgi) groups=14380 hostname: dvorak uname -a: Linux dvorak 3.2.0-4-686-pae #1 SMP Debian 3.2.0-4-686-pae </pre> </body> </html></pre>
--	---

Discuss how security concerns might have affect CSE's choices for configuring how student CGI scripts are run on its web server.

4. Web servers pass some useful information to CGI scripts as environment variables. Write a shell CGI script which prints details of the environment variables it has been passed. Here is an example implementation:

show_environment_variables.sh.cgi (code/cgi/show_environment_variables.sh.cgi)

<p>Environment Variables</p> <pre>SERVER_SIGNATURE= Apache/1.3.34 Ben-SSL/1.55 Server at cgi.cse.unsw.edu.au UNIQUE_ID=WQQ584Fe8h4AAAcjWys REDIRECT_SCRIPT_URL=/~cs2041cgi/16s2/code/cgi/show_environment_variables.sh.cgi HTTP_USER_AGENT=Mozilla/5.0 (Macintosh; Intel Mac OS X 10_6_8) SERVER_PORT=443 REDIRECT_SCRIPT_URI=https://cgi.cse.unsw.edu.au/~cs2041cgi/16s2/code/cgi/show_environment_variables.sh.cgi HTTP_HOST=cgi.cse.unsw.edu.au DOCUMENT_ROOT=/var/apache/1.3.34/cgi-bin SCRIPT_FILENAME=/web/cs2041cgi/16s2/code/cgi/show_environment_variables.sh.cgi HTTPS=on REQUEST_URI=/~cs2041cgi/16s2/code/cgi/show_environment_variables.sh.cgi</pre>	<pre><html> <head></head> <body> <h2>Environment Variables</h2> <pre>SERVER_SIGNATURE=<address>Apache/1.3.34 Ben-SSL/1.55 Server at cgi.cse.unsw.edu.au UNIQUE_ID=WQQ584Fe8h4AAAcjWys REDIRECT_SCRIPT_URL=/~cs2041cgi/16s2/code/cgi/show_environment_variables.sh.cgi HTTP_USER_AGENT=Mozilla/5.0 (Macintosh; Intel Mac OS X 10_6_8) SERVER_PORT=443 REDIRECT_SCRIPT_URI=https://cgi.cse.unsw.edu.au/~cs2041cgi/16s2/code/cgi/show_environment_variables.sh.cgi HTTP_HOST=cgi.cse.unsw.edu.au DOCUMENT_ROOT=/var/apache/1.3.34/cgi-bin SCRIPT_FILENAME=/web/cs2041cgi/16s2/code/cgi/show_environment_variables.sh.cgi HTTPS=on REQUEST_URI=/~cs2041cgi/16s2/code/cgi/show_environment_variables.sh.cgi </pre></pre>
---	---

Discuss what some of these environment variables might indicate.

5. A HTTP request can pass parameters to a web server. The web server passes these on to the CGI script typically in environment variable(s) for GET request and on STDIN for POST requests.

Write a shell CGI script which prints whether it was invoked with a GET request or a POST request and prints details of the parameters it has been passed. Here is an example implementation:

show_input_parameters.sh.cgi?comp2041=best-course-ever (code/cgi/show_input_parameters.sh.cgi?comp2041=best-course-ever)

GET Request - Input Parameters comp2041=best-course-ever	<pre><html> <head> </head> <body> <h2>GET Request - Input Parameters</h2> <pre>comp2041=best-course-ever </pre> </body> </html></pre>
--	--

6. A HTTP request can pass parameters to a web server. The web server passes these on to the CGI script typically in environment variable(s) for GET request and on STDIN for POST requests
- Write a shell CGI script which (given no parameters) prints a form allowing 2 numbers to be entered. The form should run the same CGI script, and the CGI script should print the sum of the numbers and a form allowing two more numbers to be entered and the script to be run again. Here is an example implementation:

sum_two_numbers.sh.cgi (code/cgi/sum_two_numbers.sh.cgi)

<input type="text"/> + <input type="text"/> = ? <input type="button" value="calculate"/>	<pre><html> <head> <title>Sum Two Numbers</title> </head> <body> <form method="GET" action=""> <input type="textfield" name="x" value=""> + <input type="textfield" name="y" value=""> = ? <input type="submit" value="calculate"></pre>
--	---