

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

Mathematics

COMP4128 Programming Challenges

School of Computer Science and Engineering
UNSW Australia

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- 1 Number Theory
 - Primes
 - GCD
 - Modular Inverse
 - Fast Exponentiation

- 2 Combinatorics

- 3 Example problems

- 4 Geometry

- 5 Algebra

- 6 Example problems

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- $a \equiv b \pmod m$ iff there exists some integer k such that $a = b + mk$
- $b \pmod m$ is the remainder of b when divided by m
- In C/C++, the `%` symbol is used for the modulo operator
- Be careful with negative numbers! In C/C++, the behaviour is:
 - $(-4) \% 3 == (-4) \% (-3) == -1$
 - $(-4) \% 5 == (-4) \% (-5) == -4$
 - $4 \% (-3) == 1$
 - $4 \% (-5) == 4$

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- If $a \equiv b \pmod{m}$, then $a + c \equiv b + c \pmod{m}$
- If $a \equiv b \pmod{m}$, then $ac \equiv bc \pmod{m}$
- If $ac \equiv bc \pmod{mc}$, then $a \equiv b \pmod{m}$
- $ac \equiv bc \pmod{m}$ does not necessarily mean $a \equiv b \pmod{m}$!

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- A prime number (or a prime) is a natural number greater than 1 that has no positive divisors other than 1 and itself
- Primes are the fundamental building blocks of all of number theory

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- **Algorithm** For every possible factor F of N , check if it divides. Observing that if an $F_1 > \sqrt{N}$ is a factor, then there must be another $F_2 < \sqrt{N}$ that is also a factor, we need only check factors $F \leq \sqrt{N}$.
- **Complexity** $O(\sqrt{N})$ time

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

● Implementation

```
bool isprime(int x) {  
    if (x < 2) return false;  
  
    for (int f = 2; f*f <= x; f++) {  
        if (x % f == 0) return false;  
    }  
    return true;  
}
```

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- **Algorithm** Starting with 2, mark all multiples of 2 as composite. Then, starting with the next smallest number not marked composite (which therefore must be prime), 3, mark out all its multiples and repeat until we hit the upper bound.
- **Complexity** For some upper bound N and each prime p , we must strike out about $\frac{N}{p}$ multiples, so the amount of work we do is roughly $\frac{N}{p_1} + \frac{N}{p_2} + \dots + \frac{N}{p_P}$. This is clearly less than $N + \frac{N}{2} + \frac{N}{3} + \dots + \frac{N}{N}$, so by harmonic series we can say that this algorithm runs in $O(N \log N)$ time.

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- Note that the $O(N \log N)$ bound is not tight, and the actual time complexity is closer to linear, specifically $O(N \log \log N)$
- However, knowing that we have an upper bound that works is usually sufficient for our purposes
- The algorithm itself can be optimised even more, though this is not usually necessary
 - Throw away the even numbers ($2\times$ speed up)
 - For each prime, start marking at its square because the smaller ones will be marked already

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- $\gcd(a, b)$ is the greatest integer that divides both a and b
- One of the most commonly used tools in solving number theory problems
- A few useful facts
 - $\gcd(a, b) = \gcd(a, b - a)$
 - $\gcd(a, 0) = a$
 - $\gcd(a, b)$ is the smallest positive number in $\{ax + by : x, y \in \mathbb{Z}\}$

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- Can be computed with the Euclidean algorithm, which is the repeated use of the first property above:

$$\gcd(a, b) = \gcd(a, b - a)$$

- Usually, you'll use a similar rule, $\gcd(a, b) = \gcd(a, b \% a)$, although the speed of the two versions is surprisingly close
- This has a complexity of $O(\log(a + b))$

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

• Implementation

```
int gcd(int a, int b) {  
    return b ? gcd(b, a % b) : a;  
}
```

- Some versions of <algorithm> have a `__gcd` function already defined, but it's not always clear when it's available, so usually it's safest to just write it yourself

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- As with the Euclidean algorithm, we incrementally apply the $\gcd(a, b) = \gcd(a, b - a)$ rule until we've found the GCD, but we also explicitly write the intermediate numbers as integer combinations of a and b , i.e. we find x and y where

$$ax + by = \gcd(a, b),$$

which is called *Bézout's identity*

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

● Implementation

```
int gcd(int a, int b, int& x, int& y) {  
    if (a == 0) {  
        x = 0; y = 1;  
        return b;  
    }  
    int x1, y1;  
    int d = gcd(b % a, a, x1, y1);  
    x = y1 - (b / a) * x1;  
    y = x1;  
    return d;  
}
```

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- The inverse a^{-1} of a is an integer such that $a^{-1}a \equiv aa^{-1} \equiv 1 \pmod{m}$
- Only exists if $\gcd(a, m) = 1$
- **Fermat's little theorem** $a^{m-1} \equiv 1 \pmod{m}$ for prime m
- Euler's theorem is a generalisation that works for general modulus, based on the *totient function*¹, $\phi(n)$
- Can also be computed with the Extended Euclidean algorithm for general modulus² (how?)

¹counts the numbers less than n which are coprime to n

²any modulus which is coprime to a

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- We can compute a^n quickly using a kind of divide and conquer in $O(\log n)$ time (assuming constant time multiplication)
- Observe that $a^n = a^{n/2} \times a^{n/2}$ for even n and $a^n = a^{n/2} \times a^{n/2} \times a$ for odd n
- This is equivalent to precomputing each a^{2^m} , and combining powers according to the binary expansion of n

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- Example:

$$a^9 = a^4 \times a^4 \times a$$

$$a^4 = a^2 \times a^2$$

$$a^2 = a \times a$$

- This same idea can be used to compute repeated applications of functions quickly

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

● Implementation

```
typedef long long ll;

ll pow(ll x, ll k) {
    if (k == 0) return 1;

    ll a = pow(x, k/2);
    a = a*a;
    if (k%2 == 1) a = a*x;
    return a;
}
```

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- A sequence generated from two initial values and a second-order recurrence relation as follows:

$$F(0) = 0$$

$$F(1) = 1$$

$$F(n) = F(n-1) + F(n-2) \text{ for } n \geq 2$$

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- Algorithms for Fibonacci from introductory computing courses:
 - **Algorithm 1** Direct computation of the recurrence. This is $O(2^n)$ time and $O(n)$ memory.
 - **Algorithm 2** Using the recurrence, but caching the value of each computation. This is $O(n)$ time and $O(n)$ memory.
 - **Algorithm 3** Using the recurrence with caching, but only keeping around the two most recently computed values. This is still $O(n)$ time, but $O(1)$ memory.

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- **Algorithm 4** Solving the recurrence, we have the closed form

$$F(n) = \frac{\varphi^n - \psi^n}{\varphi - \psi},$$

where $\varphi = \frac{1+\sqrt{5}}{2}$ and $\psi = \frac{1-\sqrt{5}}{2}$.

- “Constant time” - it’s a little more complicated than that
- Precision issues - the numbers in the sequence grow exponentially quickly

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- **Algorithm 5** Using the matrix form of the recurrence:

$$\begin{pmatrix} F_{k+2} \\ F_{k+1} \end{pmatrix} = \begin{pmatrix} 1 & 1 \\ 1 & 0 \end{pmatrix} \begin{pmatrix} F_{k+1} \\ F_k \end{pmatrix}$$

We can get a closed form:

$$\begin{pmatrix} F_{n+1} \\ F_n \end{pmatrix} = \begin{pmatrix} 1 & 1 \\ 1 & 0 \end{pmatrix}^n \begin{pmatrix} 1 \\ 0 \end{pmatrix}$$

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- We arrange the recurrence into a matrix, form, such that the n th power of the matrix will give us $F(n)$. Using fast exponentiation, we can then compute $F(n)$ in $O(\log n)$ time.
- It's not really $O(\log n)$ time - since there are $O(n)$ bits in $F(n)$, the cost to multiply the numbers starts dominating the actual time complexity.

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- This technique, rearranging the recurrence into matrix form so fast exponentiation can be used, is very common
- This is similar to finding closed form solutions to first order homogeneous recurrences (assuming powers can be computed quickly)
- The closed form Fibonacci solution using φ and ψ is actually along the same lines, but using the eigenvalues of the matrix instead of the matrix itself

Mathematics

Number Theory

Primes
GCD
Modular Inverse
Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- 1 Number Theory
 - Primes
 - GCD
 - Modular Inverse
 - Fast Exponentiation

2 Combinatorics

3 Example problems

4 Geometry

5 Algebra

6 Example problems

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- The binomial coefficient $\binom{n}{k}$ is the number of ways to make an unordered selection of k elements out of a set of n distinguishable elements
- One of the most widely used tools in combinatorics

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- **Algorithm 1** Compute directly from the formula

$$\binom{n}{k} = \frac{n!}{k!(n-k)!}$$

- **Complexity** $O(n)$ to compute the factorials, although parts of this can be precomputed for repeated uses. The intermediate values can become very large, however this problem can be avoided by rearranging this formula in terms of alternating multiplication and division

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- **Algorithm 2** Compute from the recurrence

$$\binom{n}{k} = \binom{n-1}{k-1} + \binom{n-1}{k}$$

- **Complexity** There are $O(nk)$ total values of $\binom{n}{k}$, and it takes $O(1)$ time to compute each value, so this takes $O(nk)$ time

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- $|A \cup B| = |A| + |B| - |A \cap B|$
- $|A \cup B \cup C| =$
 $|A| + |B| + |C| - |A \cap B| - |A \cap C| - |B \cap C| + |A \cap B \cap C|$
- In general,

$$|A_1 \cup A_2 \cup \dots \cup A_n| = \sum_{I \subseteq \{1, \dots, n\}, I \neq \emptyset} (-1)^{|I|+1} \left| \bigcap_{i \in I} A_i \right|$$

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- For the most part is solved via counting techniques, or sometimes dynamic programming
- Expectations are linear: for random variables X and Y and a constant c ,

$$\mathbb{E}(X + c) = \mathbb{E}(X) + c$$

$$\mathbb{E}(X + Y) = \mathbb{E}(X) + \mathbb{E}(Y)$$

$$\mathbb{E}(cX) = c\mathbb{E}(X)$$

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- 1 Number Theory
 - Primes
 - GCD
 - Modular Inverse
 - Fast Exponentiation

- 2 Combinatorics

- 3 Example problems

- 4 Geometry

- 5 Algebra

- 6 Example problems

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- **Problem statement** Goldbach's conjecture states that every even integer greater than 2 can be expressed as the sum of two odd primes. For some even integer N , find a pair of odd primes that sums to N .
- **Input** A single integer N , $3 \leq N \leq 1,000,000$
- **Output** A line containing A and B , two odd primes that sum to N , or "Goldbach's conjecture is wrong" if no such numbers exist

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- **Algorithm** We know that we have to do something with primes. So let's start by generating all primes up to N , using the sieve.
- After we generate our list of primes, the remaining problem is "given an integer, find a pair from this list that sums to the integer"

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- We can solve this problem in $O(n)$ time using a set with a fast membership test
- Since our elements are all small integers, we can just use a boolean array
- **Complexity** To create our list of primes, we use our $O(n \log n)$ time, $O(n)$ space sieve to transform this into a simpler problem which we can solve in $O(n)$ time and $O(n)$ space. So this algorithm runs in $O(n \log n)$ time and $O(n)$ space.

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

Implementation

```
#include <stdio>

const int N = 1e6+5;
int primes[N], P, notprime[N];

int main() {
    // sieve
    notprime[0] = 1;
    notprime[1] = 1;
    for (int i = 2; i < N; i++) {
        if (notprime[i]) continue;
        // if i is prime, mark all its multiples as not prime
        primes[P++] = i;
        for (int j = i*i; j < N; j += i) notprime[j] = true;
    }

    int n;
    while (scanf("%d", &n), n) {
        // scan primes[] for pair adding to n
        for (int i = 1; i < P; i++) {
            if (!notprime[n-primes[i]]) {
                printf("%d = %d + %d\n", n, primes[i], n - primes[i]);
                break;
            }
        }
    }
    return 0;
}
```

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- **Problem statement** Compute $\binom{n}{k} \bmod 1,000,000,007$
- **Input** Two integers N and K , $0 \leq K \leq N \leq 1,000,000$
- **Output** A line containing $\binom{n}{k}$

Mathematics

Number
Theory

Primes
GCD
Modular Inverse
Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- **Algorithm** We can't use the recurrence here; $O(NK)$ is too slow when N and K are each up to 1,000,000
- The only viable method is using the formula

$$\binom{n}{k} = \frac{n!}{k!(n-k)!}$$

- We need to be able to divide in our modulus, i.e. compute inverses
- Luckily, 1,000,000,007 is a prime (what a crazy random happenstance!)

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- We can solve the problem in $O(1)$ per query after computing factorials and their inverses, using Fermat's little theorem and fast exponentiation
- We precompute every factorial and its corresponding inverse, since there are only $O(N)$ of either of these.
- **Complexity** After $O(N \log N)$ precomputation, we can answer each query in $O(1)$ time.

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

● Implementation

```

typedef long long ll;

ll f[N];
// modify earlier fast exponentiation algorithm to work modulo c
ll modpow(ll a, ll b, int c);

ll inv(ll x) {
    // By Fermat's little theorem,  $a^{(p-2)}$  is the inverse of  $a$  mod  $p$ 
    return modpow(x, MOD-2, MOD);
}

int main() {
    // factorials
    f[0] = 1;
    for (int i = 1; i < N; i++) f[i] = (i * f[i-1]) % MOD;

    int T;
    scanf("%d", &T);
    for (int i = 0; i < T; i++) {
        int n, k;
        scanf("%d%d", &n, &k);
        printf("Case %d: ", i + 1);
        ll res = (f[n] * inv(f[n-k])) % MOD;
        res = (res * inv(f[k])) % MOD;
        printf("%lld\n", res);
    }
    return 0;
}

```

Mathematics

Number Theory

Primes
GCD
Modular Inverse
Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- 1 Number Theory
 - Primes
 - GCD
 - Modular Inverse
 - Fast Exponentiation

2 Combinatorics

3 Example problems

4 Geometry

5 Algebra

6 Example problems

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- Most of the useful theorems and formulas are taught in high school
 - Coordinate geometry
 - Trigonometry including sine rule and cosine rule
 - Similar triangles
 - Circle geometry

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- For simple geometry problems, usually it suffices to do a lot of scribbling
- Hard geometry problems are probably the most frustrating type of algorithm problem
- Precision is a massive problem

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- Try to keep things in integers as much as possible
- Avoid unnecessary divisions and other arithmetic operations
- Single precision floating point numbers fail very often, but doubles are mostly reliable
 - They are not foolproof though!
 - Going to long doubles is not a panacea

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- When comparing floating point numbers, compare up to a small constant ϵ to allow for rounding errors

```
const double EPS = 1e-8;  
if (fabs(x-y) < EPS) {  
    // equal  
}
```

- Many problems that require floating point answers will specify how many decimal places they want.
If you are e.g. binary searching for an answer, that tells you how small your ϵ needs to be until you can stop.

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- Basic vector operations
 - Norm (length)
 - Rotation by some angle
 - Normal
 - Compositions of operations
 - Reflection
 - Projection

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

```
#define x first
#define y second
typedef pair<double, double> pt;

struct line {
    double a, b, c;
    // coefficients in general form, compare up to constant factor
}

pt operator-(pt u, pt v) { return pt(u.x - v.x, u.y - v.y); }
pt operator+(pt u, pt v) { return pt(u.x + v.x, u.y + v.y); }
pt operator*(pt u, double d) { return pt(u.x * d, u.y * d); }

// dot product
double operator*(pt u, pt v) { return u.x * v.x + u.y * v.y; }
// norm
double operator!(pt p) { return sqrt(p * p); }
// "cross product"
double operator^(pt u, pt v) { return u.x * v.y - u.y * v.x; }
```

Mathematics

Number Theory

Primes
GCD
Modular Inverse
Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- 1 Number Theory
 - Primes
 - GCD
 - Modular Inverse
 - Fast Exponentiation

- 2 Combinatorics

- 3 Example problems

- 4 Geometry

- 5 Algebra

- 6 Example problems

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- Incredibly useful in programming contests!
- We mostly work with 2D points, so we assume the third component is zero:

$$\begin{pmatrix} u_x \\ u_y \\ 0 \end{pmatrix} \times \begin{pmatrix} v_x \\ v_y \\ 0 \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ u_x v_y - u_y v_x \end{pmatrix}$$

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics


Example problems

Geometry

Algebra

Example problems

- Computes the signed area of the parallelogram formed by the two input vectors
 - This is double the area of the triangle
 - The sign depends on the orientation of u and v



Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- Line-line intersection
- Orientation (“ccw”) check
- Triangle area

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- Usually, complicated matrix operations do not come up
- Matrix multiplication or related operations are commonly used
- Solving linear systems using Gaussian elimination is sometimes used

Mathematics

Number Theory

Primes
GCD
Modular Inverse
Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- ① Number Theory
 - Primes
 - GCD
 - Modular Inverse
 - Fast Exponentiation

- ② Combinatorics

- ③ Example problems

- ④ Geometry

- ⑤ Algebra

- ⑥ Example problems

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- **Problem statement** You are given a set of integers which each describe the life cycle of a set of insects. If an insect has a life cycle of x days, a swarm of them will attack your cicadas every x days, starting from the x th day. For how many days over the first N days will your cicadas be free of attacks?
- **Input** An integer N ($1 \leq N \leq 2,000,000,000$) and the set M of integers that describe the life cycle of the insects ($1 \leq |M| \leq 15$, and each individual life cycle will be less than $2,000,000,000$)
- **Output** A single integer describing the number of attack-free days over the first N days

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- The first thing to notice is that N can be large, so we can't even iterate over all the days we need to count
- However, the size of M is relatively small, which suggests we can use an algorithm which could even be exponential in $|M|$
- How can we reformulate the problem so that it's easier to work with?

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- What we need to do is to find the size of the union of the sets of days where the insects will attack:

Let $D_i = \{nx_i : n \in \mathbb{Z}^+, nx_i \leq N\}$ be the set of days on which the i th species will attack.

Then we want to find $\left| \bigcup_{i=1}^M D_i \right|$.

- If we can find a way to quickly compute the intersections of the sets where two or more different insects will attack, then we can just directly use inclusion-exclusion

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- So now the problem we want to solve is, given a set of integers, how many numbers in the range 1 to N are divisible by *all* of them?
- These are exactly the numbers divisible by the lowest common multiple of these numbers, which is just the product divided by the GCD
- Given an integer L , how many numbers in the range 1 to N are divisible by L ?

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

- **Complexity** We need to iterate over all subsets of M , of which there are $2^{|M|}$, and compute the GCD of each of these subsets, which takes $O(|M| \log N)$ time, for a total complexity of $O(|M| 2^{|M|} \log N)$

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

● Implementation

```
ll res = 0;
// iterate through all bitsets of width m
for (int set = 1; set < (1<<m); set++) {
    int size = 0;
    ll l = 1;
    for (int j = 0; j < m; j++) {
        // if the jth bit is a 1, i.e. element j is included in set
        if (set & (1<<j)) {
            size++;
            l = lcm(l, a[j]);
        }
    }
    // inclusion-exclusion: add if set size is odd, subtract if even
    if (size % 2) {
        res += n / l;
    } else {
        res -= n / l;
    }
}
```

Mathematics

Number Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example problems

Geometry

Algebra

Example problems

- There is a unit interval AB . N cuts occur on this interval with uniform probability. What is the expected value of the length of the first segment (the one connected to A) after all cuts are made?

Mathematics

Number
Theory

Primes

GCD

Modular Inverse

Fast Exponentiation

Combinatorics

Example
problems

Geometry

Algebra

Example
problems

Some fun stuff to look at (beyond course scope):

- Grundy numbers
- Surreal numbers
- Blue/Red/Green Hackenbush
- Chinese remainder theorem
- Burnside's lemma
- Pick's theorem
- Euler's totient function
- Simpson's rule
- Minkowski sums
- Karatsuba algorithm
- Möbius inversion formula
- Shank's algorithm
- Cayley's formula
- Kirchhoff's matrix tree theorem
- Catalan numbers
- Stern-Brocot tree
- Continued fractions
- AKS
- Miller-Rabin