

#### **COMP2511**

# Object-Oriented Design and Programming Programming by Contract

Wayne Wobcke

w.wobcke@unsw.edu.au

© W. Wobcke, 2018

— UNSW Computer Science & Engineering



## Today's Lecture

- Java Type System
- **■** Exceptions
- Defensive Programming
- Design by Contract
- Test Driven Development

— UNSW Computer Science & Engineering -



## Java Type System

- Everything is an Object . . .
  - ◆ Except int, float, double, etc., and null
- Assignment b = a is valid if actual type of a is a subtype of declared type of b
- Parameters are references and are called by value

© W. Wobcke, 2018

— UNSW Computer Science & Engineering



#### **Exceptions**

- try throw catch finally
- Hierarchy of exception classes
- **■** Exceptions vs errors
- Checked vs unchecked



## **Defensive Programming**

■ What error checking would you have in BankAccount in first year?

— UNSW Computer Science & Engineering



#### Pre- and Postconditions

- Conditional contract
- If the precondition holds before a method call, then the postcondition holds after the method terminates
- Nothing guaranteed otherwise

© W. Wobcke, 2018

— UNSW Computer Science & Engineering



## **Programming by Contract**

- Pre- and postconditions
- Class invariant
- Don't need to check preconditions in the called method (maybe in caller)
- Exceptions can be part of contract

© W. Wobcke, 2018

— UNSW Computer Science & Engineering

#### **Class Invariant**

- Condition on object state
- Holds after constructor, and before and after each method call – but may not hold during method execution
- Reasoning: If precondition and invariant hold before method call, postcondition and invariant hold afterwards



## Covariance

- If  $s \le t$  then  $f(s) \le f(t)$ 
  - ◆ *s* ≤ *t* means *s* is a subtype of *t*
  - if f(s), f(t) are propositions A, B,
     A ≤ B means A logically implies B
- *f* is postcondition of a method, the result type of a method, or the class invariant

© W. Wobcke, 2018

— UNSW Computer Science & Engineering



#### Contravariance

- If  $s \le t$  then  $f(s) \ge f(t)$ 
  - ◆ *s* ≤ *t* means *s* is a subtype of *t*
  - if f(s), f(t) are propositions A, B,  $A \ge B$  means B logically implies A
- *f* is precondition of a method or the argument type of a method
- Liskov Substitution Principle

— UNSW Computer Science & Engineering



## **Test Driven Development**

- First define a set of tests for all methods, then develop code to pass each test
- Is this a good idea?
- TDD does not just mean "I tested my code"

© W. Wobcke, 2018

— UNSW Computer Science & Engineering



#### **Next Week**

- Object-Oriented Design Process
- Assignment 1