

Informações adicionais

Partida rápida

rcssmonitor --auto-reconnect-mode on

```
rcssserver server::auto_mode = true server::nr_extra_halfs = 0
server::penalty_shoot_outs = false server::synch_mode=true
```

Obs.: Cada comando deve ser executado em um terminal diferente. Inicialmente execute o comando do **auto reconnect**, em seguida, o comando do **server**. Por fim, execute os **times**.

Renomear binário

<https://bitbucket.org/brazil2d/brazil2d/wiki/renamebin>

Resolvendo o seguinte erro:

```
g++ -DHAVE_CONFIG_H -I. -I.. -I../src -I../src/chain_action -I/usr/include -W
-Wall -g -O2 -MT sample_player-tackle_generator.o -MD -MP -MF .deps/sample_playe
r-tackle_generator.Tpo -c -o sample_player-tackle_generator.o `test -f 'chain_ac
tion/tackle_generator.cpp' || echo './`chain_action/tackle_generator.cpp
chain_action/tackle_generator.cpp:71:25: error: 'constexpr' needed for in-class
initialization of static data member 'const double {anonymous}::DeflectingEvalua
tor::not_shoot_ball_eval' of non-integral type [-fpermissive]
 71 |     static const double not_shoot_ball_eval = 10000;
    |                               ^~~~~~
```

1° Acessar a pasta src/chain_action/tackle_generator.cpp

2° Passar a seguinte linha para fora da struct:

```
static const double not_shoot_ball_eval = 10000;
```