

Signage can be multi changeable

2D

Side roads may be sealed or unsealed  
and may be posted or derestricted.




REPEATER SIGNAGE  
TO BE PLACED  
EVERY 500m AND AT  
INTERSECTIONS.


**GENERAL NOTES:**

- 1. This TGS is only to be used as part of the DBCA Generic Traffic Management Plan.
- 2. All sign locations are to be checked prior to setout and positions adjusted to allow for specific site constraints such as vegetation, other signs, roadside furniture and sufficient space on shoulders/emergency lanes.
- 3. The positioning of signs, lengths of tapers or markings shall be:
  - a) Minimum 10% less than the distances or lengths given.
  - b) Maximum 25% more than the distances or lengths given.

**DISCLAIMER:**

It is the responsibility of the user of this traffic guidance scheme to confirm the appropriateness or otherwise for the intended work site based on rigorous risk assessment, review of the requirements of AS1742.3 and Main Roads WA Traffic Management for Works on Roads Code of Practice. All responsibility will remain with the user to ensure compliance with relevant standards and the provision of the necessary level of protection for work personnel and work site.

Drawn: Samantha Keys  
AWTM Cert. No: KTS-AWTM-18-43242-02  
Signed: 

Reviewed by: Brad Brooksby  
AWTM Cert. No: AUS-AWTM-16-1183-05  
Signed: 




OR



Signage can be multi changeable

2D



OR



VALUE OF DIMENSION 'D'	
Speed of Traffic km/h	Dimension 'D' m
55 or less	15
56 to 65	45
Greater than 65	Speed of traffic, in Km/h

UNATTENDED WORKSITE SMOKE HAZARD WARNING		
DATE: 09/04/2019	REV No: 09	DBCA - 19 - 022