



 	
TYPICAL TRAFFIC CONTROL DIAGRAM	
ROUTINE OPERATIONS	
TASK: Mobile Works Operation	
NOTES	
1: All vehicles shall display vehicle mounted warning signs and have vehicle mounted warning devices operational. 2: All Workers on Foot shall have communications with the Lead and Tail vehicles at all times. 3: All vehicle mounted warning signs and devices shall be removed from display or deactivated when the vehicle is no longer working becomes part of the normal traffic stream. 4: Use a standard approach to reduce speed in 20km/h increments as per AS1742.3	
SIGNAGE SPACING	
"D" (metres), for the positioning of signs, is related to the speed of traffic as follows	
DIMENSION "D"	
Speed of traffic km/h	Dimension "D" m
55 or less	15
56 - 65	45
Greater than 65	Equal to posted speed of traffic
SIGNAGE REQUIREMENTS	
SIGN	QUANTITY
ROAD PLANT AHEAD	4
CONTROLLED BURN	4
END CONTROLLED BURN	1
DRIVE SAFELY	2
ROAD PLANT AHEAD	1
END CONTROLLED BURN	1

TCD No: DPAW PB 007

Rev No: 1

Date: 02/05/2016

Drawn By: Jade Saunders
AWTM: KTS-AWTM-14-39792-04Signed: Amended By: Joel Rebello
AWTM: KTS-AWTM-15-43243-02Designed By: Paul Cassidy
AWTM: KTS-AWTM-14-34767-02Signed: 