PIN Checker by PIN

By KRA

https://sbx.kra.go.ke/checker/v1/pinb…

Simulate API

Documentation

📌 Overview

To successfully invoke this API, you must first generate an **access token** via the Authorization API. This token must be included as a Bearer token in the Authorization header of your API request.

This guide includes:

- How to generate the access token
- How to use the token in the API request
- Request/response examples
- Error handling

- Sample data section for testing

🔐 Step 1: Generate Access Token (Authorization API)

Request Details

Use your `Consumer Key` and `Consumer Secret` as **Basic Auth** credentials (`username` and `password`) to generate an access token.

Endpoint:

```
GET https://sbx.kra.go.ke/v1/token/generate?grant_type=client_credentials
GET https://api.kra.go.ke/v1/token/generate?grant_type=client_credentials
```

Headers:

`Authorization: Basic <Base64Encoded(Consumer_Key:Consumer_Secret)>`

Success Response

```
{
  "access_token": "qblts2rRqMKBG7mvP7AkLZfnWjER",
  "expires_in": "3599"
}
```

Field	Description
access_token	Token to be used as Bearer token in API requests
expires_in	Time in seconds before the token expires (e.g. 3600)

Error Response

```
{
    "requestId": "83f2-4b48-bdf5-4c7e1a67dbcb39076",
    "errorCode": "401",
    "errorMessage": "Client credentials are invalid"
}
```

errorCode	errorMessage
401	Client credentials are invalid

⚠️ **Note:** No need to create a separate app for Authorization. Use the same app created for this API.

✅ Step 2: Invoke PIN Checker by PIN API

Endpoint:

```
POST https://sbx.kra.go.ke/checker/v1/pinbypin - Sandbox Endpoint
POST https://api.kra.go.ke//checker/v1/pinbypin - Production Endpoint
```

Request Example

`POST https://sbx.kra.go.ke/checker/v1/pinbypin`

Headers:

```
{
  "Content-Type": "application/json",
  "Authorization": "Bearer qblts2rRqMKBG7mvP7AkLZfnWjER"
}
```

Body:

```
{
    "KRAPIN": "P318295670X"

}
```

Request Parameters

No.	Field Name	Data Type	Description
1	KRAPIN	STRING	PIN of the taxpayer to be validated by another system. Format: Starts with “A” or “P”, followed by 9 digits, ending with any alphabet.

Possible Responses

Successful response

```
{
    "ResponseCode": "23000",
    "Message": "Valid PIN",
    "Status": "OK",
    "PINDATA": {
        "KRAPIN": "P318295670X",
        "TypeOfTaxpayer": "Non Individual",
```

```
        "Name": "T. AN 052318TEST NA NA",
        "StatusOfPIN": "Active"
    }
}
```

Below table describes each field in the above JSON

No.	Field/Attribute	Description
1	ResponseCode	Represents the code for different messages which can be sent to other organization systems.
2	Message	Represents the description of the ResponseCode sent to the system.
3	Status	OK/NOK.
4	KRAPIN	PIN of the taxpayer which was requested to be validated.
5	TypeOfTaxpayer	Type of the taxpayer (Possible values: Individual / Non Individual).
6	Name	Name of the taxpayer. For Non Individual taxpayers, this contains the full name.
9	StatusOfPIN	Status of the PIN (Mandatory). Possible values: • Active • Suspended • Cancelled • Stopped

Exceptions

Response Code	Status	Message
19005	NOK	Invalid PIN

🧪 Sample Data (For Testing)

KRAPIN

`A744610021G`

`A521040203F`

`P318295670X`

📎 **Tip:** Use the My Apps section to get your app credentials.

Use case

For validating taxpayer information in the iTax system using KRA PIN

PRODUCT

APIs
Documentation
Developer Market
My Apps

SUPPORT

Contact Support
FAQs

LEGAL

Privacy Policy
Terms & Conditions

Join our newsletter mailing list

Enter your email he

Subscribe

Location

Times Tower, Haile Selassie Avenue,
P.O. Box 48240 - 00100 GPO
Nairobi Email: apisupport@kra.go.ke

Government of Kenya 2026 Copyright. All rights reserved.

Back To Top