Authorization

By KRA

https://sbx.kra.go.ke/v1/token/genera…

Simulate API

Documentation

📌 Overview

To successfully invoke any API, you must first generate an **access token** via the Authorization API. This token must be included as a Bearer token in the Authorization header of your PIN Checker request.

This guide includes:

- How to generate the access token
- How to use the token in the PIN Checker request
- Request/response examples
- Error handling

- Sample data section for testing

🔐 Step 1: Generate Access Token (Authorization API)

Request Details

Use your `Consumer Key` and `Consumer Secret` as **Basic Auth** credentials (`username` and `password`) to generate an access token.

Endpoint:

```
GET https://sbx.kra.go.ke/v1/token/generate?grant_type=client_credentials
```

Headers:

`Authorization: Basic <Base64Encoded(Consumer_Key:Consumer_Secret)>`

Success Response

```
{
  "access_token": "qblts2rRqMKBG7mvP7AkLZfnWjER",
  "expires_in": "3599"
}
```

Field	Description
access_token	Token to be used as Bearer token in API requests
expires_in	Time in seconds before the token expires (e.g. 3600)

Error Response

```
{
    "requestId": "83f2-4b48-bdf5-4c7e1a67dbcb39076",
    "errorCode": "401",
    "errorMessage": "Client credentials are invalid"
}
```

errorCode	errorMessage
401	Client credentials are invalid

⚠️ **Note:** You do need to create an app for the Authorization API. This endpoint is accessible from every app created for all other APIs on this platform.

✅ Step 2: Using the bearer token to access other APIs

In your request, add the `access_token` you received from the authentication to your Authorization Headers as follows:

Headers:

```
{
  "Content-Type": "application/json",
  "Authorization": "Bearer {{access_token}}"
}
```


Government of Kenya 2026 Copyright. All rights reserved.