Candidate's Number .....

## THE UNITED REPUBLIC OF TANZANIA MINISTRY OF EDUCATION NATIONAL FORM II EXAMINATION - NOVEMBER, 1986

0084

ELECTRICAL ENGINEERING

TIME: 2 Hours.

This paper consists of sections A and B. Section A comprises questions from CIVIL, ELECTRICAL and MECHANICAL Engineering.

Attempt ALL questions from both sections.

You are advised not to spend more than 2 minutes per question in section A and not more than 4 minutes in section B.

This paper consists of 8 printed pages.

							-
x.			· + to day to the property of the control of the co	andida	te's Number	••••	
			Questions 1 - 14 are of multiple correct answer and insert the co the space provided.	choice orrespo	e. Choose tonding letter	he in	
	1.	The	ratio used in mortar of 1:1:3 is for:		ē:		
		A.	Lime-sand mortar				
		в.	Cement-soil mortar				3
		C.	Cement-lime-sand mortar			1	
		D.	Lime-sand-soil mortar.		10		
	2.	The	following tool is not any of the	2000			1
		A.	following tool is not one of the markin Spirit level	ng and r	neasuring to	ol,	
		В.	Flat scraper				
		C.	Solid square				
		D.	Bever and bevel protractor.				
	3.	A m	agnet has the properties of:				(a)
		A.	Pointing North and South when free!				
				У			
		В.	Pointing West and East when freel suspended.	У			-
		c.	Withstanding the corrosive effects				
		D.	Attracting papers and woods.				
	4.	An A	A.C. welding transformer can work or	als:			į.
		A.	By using d.c. motor and generator	,,,			
		в.	When there is a supply of electricity from the mains.				
		C.	By using a burning forge				
		D.	When there is a supply of hydrogen.				C-A
	5.	Man	domestic electric appliances, such as ric cookers, contain heating-elements	laundr	y iron, the k	ettle,	
		A.	Pure metals	are m	ade from:		
		в.	Copper or aluminium materials	5 0			
		c.	Nichrome or one of the other Nickel a	alloys	1		
		D.	Carbon,	8 6		4	1
	6.	Elec	tricity inside a battery is a follow of:	r,	4		- 9
		A.	Neutrons				
*		в.	Protons				
		c.	Electrons				
		D.	lons.	**			- 1
		10	5 77 1000	4.14.0	the San	20	- 1
					191	e i	
- /AC				1		21	2 (
				4.10	./3.		4
					- 3	1	1
			War ye		4 1 1	2 - 1	# 11

	7		
¥.1		- 3 - Candidatels	Number
	The w	vorker who operates one machine is a:	100
	A.	Mechanic	
1	в.	Machinist	
(	c.	Man with broadworkshop experience	, T
	D.	Specialist.	, ) , W.
	When	n you lean against the machine while it is runn	ing what will happen?
в.	A.	The machine will slow down	
	В.	The rate of feed will vary	
	c.	The teacher will think that you are asleep	
	D.	An accident may occur.	
		12.	
9.		machinist uses a hammer as chisel in:	
	Α.	Tightening nuts	
	в.	Loosening nuts	
	C.	Removing metal	
	D.	Identing graduations.	
10.	Wel	ding goggles protect the:	
	A.	Welder's face	
	в.	Welder's wrist	
	c.	Welder's head	
	D.	Welder's eyes.	
11.	. At	ool used for cutting when making joints on timbe	r Is a
	A.	Hammer	
	в.	Hacksaw	
	c.	Tenon saw	1 44
	D.		
12		marking knife is used for:	
	Α.	Taranganganganganganganganganganganganganga	
	в.	wood usually across the grains.	2 2
	c.		
	D.	Marking circles only.  the tool which is not used in checking the vertica	lity (plumbness) of a
13	3. TI	all is:	
	A.	A line together with a pin	<u> </u>
	в.	The state of the s	
	c.	Plumb-bob	
	D.		= 11
14	. · A	tool used for cleaning rough timber is a:	
	Α.	Bench hook	
	в.	/	
	c.	File	0 8
	D.	a thing plane.	

	- 4 - Candidate's Number
	Questions 15 - 20 require short answers. Write the answers in the space provided.
15. Nam	ne any five tools which are commonly used in brick-work:
(i)	
(ii)	
(iii)	
(iv)	
(v)	
16. Nam	ne any three sources of electricity:
(i)	
(ii)	
(iii)	
7453	
18. Lie	
(i)	t four types of lampholders mainly used in Tanzania:
(i) (ii)	four types of lampholders mainly used in Tanzania:
(i) (ii) (iii)	t four types of lampholders mainly used in Tanzania:
(i) (ii)	four types of lampholders mainly used in Tanzania:
(i) (ii) (iii) (iv)	four types of lampholders mainly used in Tanzania:
(i) (ii) (iii) (iv)	four types of lampholders mainly used in Tanzania:
(i) (ii) (iii) (iv) 19. Nan	four types of lampholders mainly used in Tanzania:
(i) (ii) (iii) (iv) 19. Nam (i)	t four types of lampholders mainly used in Tanzania:  me the hand tools used in the following operations:  Tenoning
(i) (ii) (iv) 19. Nan (i) (ii) (iii)	t four types of lampholders mainly used in Tanzania:  Tene the hand tools used in the following operations:  Tenoning  Testing straightness of timber  Gauging for mortises
(i) (ii) (iii) (iv) 19. Nam (i) (ii)	t four types of lampholders mainly used in Tanzania:  Tene the hand tools used in the following operations:  Tenoning  Testing straightness of timber  Gauging for mortises
(i) (ii) (iv) 19. Nan (i) (ii) (iii)	t four types of lampholders mainly used in Tanzania:  Tene the hand tools used in the following operations:  Tenoning  Testing straightness of timber  Gauging for mortises
(i) (ii) (iv) 19. Nan (i) (ii) (iii)	four types of lampholders mainly used in Tanzania:  me the hand tools used in the following operations:  Tenoning  Testing straightness of timber  Gauging for mortises  is used to coat dark surfaces for laying the table provided.
(i) (ii) (iv) 19. Nan (i) (ii) (iii)	Tenoning  Testing straightness of timber  Gauging for mortises  Is used to coat dark surfaces for layinnes.  For questions 21 and 22, match the following terms from list B, by completing the table provided.
(i) (ii) (iii) (iv)  19. Nam (i) (iii) (iii)  20. outli	t four types of lampholders mainly used in Tanzania:  The the hand tools used in the following operations:  Tenoning  Testing straightness of timber  Gauging for mortises  is used to coat dark surfaces for laying the table provided.  Each of the following terms from the

(c)

(a)

(b)

... /5

A marking gauge is used.

to mark a line for rebate

for boring holes in the timber

to test the slope of wood work piece

for smoothing timber

for cutting tenon.

(d)

A.

в.

C.

D.

E.

List B

		- 5 - Ca	indidate's Numbe	г
2. L	ist			
		Side cutter plier		
()	5)	Electric drill	LIST A	LIST
(	c)		(-)	
		Do not operate any machine without the authority of work-	(a)	
,	-1	"icharge.	(b)	
,	d)	Fuse.	(c)	
1	_ist	В	1	
	۸.	Tool used by fitters	(d)	
	в.	Protective device		
	c.			
	D.	CIRCUIT BREAKER		
	E.	Workshop rule Power tool		
	F.			
		Hand tool.		
		For questions 23 to 26		
		For questions 23 to 26, write true of provided.	r false in the sp	ace
	P.V	ctrons.  C. cable is used for underground in unit of measurement of power is a jou		
		For questions 27 to 29, match the folist A with correct meaning from list the table provided.	ollowing terms fro	
27	LIS			
27.	Δ	Open circuit		
27.	A. B.	Open circuit	LIST A	LIST B
27.	в.		LIST A	LIST B
27.		Open circuit Transformer Final sub circuit Rewirable fuses, H.B.C.		LIST B
27.	в.	Open circuit Transformer Final sub circuit	A	LIST B
27.	B. C. D.	Open circuit Transformer Final sub circuit Rewirable fuses, H.B.C. fuses and catridge fuses.	A B C	LIST B
27.	B. C. D.	Open circuit Transformer Final sub circuit Rewirable fuses, H.B.C. fuses and catridge fuses.	A	LIST B
27.	B. C. D.	Open circuit Transformer Final sub circuit Rewirable fuses, H.B.C. fuses and catridge fuses.  St B Will carry current	A B C	LIST B
27.	B. C. D.	Open circuit Transformer Final sub circuit Rewirable fuses, H.B.C. fuses and catridge fuses.  St B Will carry current Profective device	A B C	LIST B
27.	B. C. D.	Open circuit Transformer Final sub circuit Rewirable fuses, H.B.C. fuses and catridge fuses.  St B Will carry current Profective device Instruments	A B C	LIST B

Cannot carry current

Parallel circuits.

(f)

(g)

A.	LA	LIST A	LIST B
	Fusing current		
В.	Fuse rating	A	
C.	Three heat switch	В	
D.	Portable Electric drill.	С	
List	В	D	
(a)	A current which operates a fuse in time.		
(b)	A switch with low and high, medium		
(c)	a current which fuses can carry without over heating.		
(d)	a device fixed at one place		
(e)	a device which can be moved here and the	ere.	
Li	st A		
A			
В		LIST A	LIST B
С		A	
D		В	
E		-	
		С	
	lst B	D	
(a	installation.	E	
(Ь	situation installation.		
(c	to of a caple		
(d			
(e	Alex of empley		
(1)	conduit bend.		
(g	field having direction and force which surrounds a charged coil.		
TI	ne effects of an electric current are:		
	an electric current are:		
(1)			
(ii)			

The materials used for each component part of a M.1.C.S. cable are  (i)  (ii)  (iii)  38. The colour code of cables used for wiring a three pin plug are  (i)		- 7 - Candidate's Number
Three capacitors of 3 micro Faradays, 2 micro Faradays and 6 micro Faradays are connected in series. The equivalent capacitance is  Give three types of faults which are likely to occur always in electric circuits:  (i)  (ii)  The current rating of fuse protecting a ring circuit is and the conductor size is respectively.  The difference between a flexible cable and flexible cord is  7. The materials used for each component part of a M. I. C. S. cable are  (i)  (ii)  (iii)  35. The colour code of cables used for wiring a three pin plug are  (i)  (ii)  or  (iii)  7. The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.	For a copper	temperature increase the resistance of pure metals, such as will be
Three capacitors of 3 micro Faradays, 2 micro Faradays and 6 micro Faradays are connected in series. The equivalent capacitance is  Give three types of faults which are likely to occur always in electric circuits:  (i)  (ii)  (iii)  The current rating of fuse protecting a ring circuit is respectively.  The difference between a flexible cable and flexible cord is  The materials used for each component part of a M.1.C.S. cable are  (i)  (ii)  (iii)  35. The colour code of cables used for wiring a three pin plug are  (i) or  (ii) or  (iii) or  19. The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.		
Give three types of faults which are likely to occur always in electric circuits:  (i)  (ii)  (iii)  The current rating of fuse protecting a ring circuit is respectively.  The difference between a flexible cable and flexible cord is  The materials used for each component part of a M.I.C.S. cable are  (i)  (ii)  (iii)  38. The colour code of cables used for wiring a three pin plug are  (i)  (ii)  (iii)  or  (iii)  19. The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.  41. Name three electrical measuring instruments used on live circuits  (ii)  (iii)		1
Give three types of faults which are likely to occur always in electric circuits:  (i)  (ii)  (iii)  The current rating of fuse protecting a ring circuit is and the conductor size is respectively.  The difference between a flexible cable and flexible cord is  The materials used for each component part of a M.1.C.S. cable are  (i)  (ii)  (iii)  38. The colour code of cables used for wiring a three pin plug are  (i) or  (ii) or  (iii) or  39. The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.	micro	Faradays are connected in series. The equition
Give three types of faults which are likely to occur always in electric circuits:  (i)  (ii)  (iii)  The current rating of fuse protecting a ring circuit is and the conductor size is respectively.  The difference between a flexible cable and flexible cord is  The materials used for each component part of a M.1.C.S. cable are  (i)  (ii)  (iii)  38. The colour code of cables used for wiring a three pin plug are  (i) or  (ii) or  (iii) or  39. The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.		
Give three types of faults which are likely to occur always in electric circuits:  (i)  (ii)  (iii)  The current rating of fuse protecting a ring circuit is and the conductor size is respectively.  The difference between a flexible cable and flexible cord is  The materials used for each component part of a M.1.C.S. cable are  (i)  (ii)  (iii)  38. The colour code of cables used for wiring a three pin plug are  (i) or  (ii) or  (iii) or  The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.		
(ii)  The current rating of fuse protecting a ring circuit is and the conductor size is	Giv	e three types of faults which are likely to occur always in electric
(ii)  The current rating of fuse protecting a ring circuit is and the conductor size is	(i)	
The current rating of fuse protecting a ring circuit is and the conductor size is respectively.  The difference between a flexible cable and flexible cord is  The materials used for each component part of a M.1.C.S. cable are  (i)  (ii)  (iii)  38. The colour code of cables used for wiring a three pin plug are  (i) or  (ii) or  (iii) or  (iii) or  The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.	(ii)	,
The difference between a flexible cable and flexible cord is  The materials used for each component part of a M. I. C. S. cable are  (i)  (ii)  (iii)  38. The colour code of cables used for wiring a three pin plug are  (i) or or  (iii) or  39. The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.  41. Name three electrical measuring instruments used on live circuits  (ii)	(iii)	
The difference between a flexible cable and flexible cord is  The materials used for each component part of a M. I. C. S. cable are  (i)  (ii)  (iii)  38. The colour code of cables used for wiring a three pin plug are  (i) or or  (iii) or  39. The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.  41. Name three electrical measuring instruments used on live circuits  (ii)		assument rating of fuse protecting a ring circuit is
The difference between a flexible cable and flexible cord is  The materials used for each component part of a M.I.C.S. cable are  (i)  (ii)  (iii)  38. The colour code of cables used for wiring a three pin plug are  (i)	an	d the conductor size isrespectively.
The materials used for each component part of a M.1.C.S. cable are  (i)  (ii)  (iii)  38. The colour code of cables used for wiring a three pin plug are  (i)		
(i) (iii)  38. The colour code of cables used for wiring a three pin plug are (i)		flouible cable and Health
(i) (iii)  38. The colour code of cables used for wiring a three pin plug are (i)	6. T	he difference between a flexible cable and flexible com-
(i) (iii)  38. The colour code of cables used for wiring a three pin plug are (i)	6. T	he difference between a flexible cable and flexible cable
(ii)  35. The colour code of cables used for wiring a three pin plug are  (i)	-	
(ii)  (iii)  35. The colour code of cables used for wiring a three pin plug are  (i)  (ii)  (iii)  39. The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.  41. Name three electrical measuring instruments used on live circuits  (i)  (ii)	-	The materials used for each component part of a M.I.C.S. cable are
35. The colour code of cables used for wiring a three pin plug are  (i)	37,	The materials used for each component part of a M.I.C.S. cable are
(i) (ii) or or (iii)  39. The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area	37.	The materials used for each component part of a M.I.C.S. cable are  (i)
(i) (ii) or or (iii)  39. The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area	37.	The materials used for each component part of a M.I.C.S. cable are  (ii)  (iii)
(ii) or  The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.  41. Name three electrical measuring instruments used on live circuits (i)	37.	The materials used for each component part of a M.I.C.S. cable are  (i)  (ii)  (iii)
The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.  41. Name three electrical measuring instruments used on live circuits (i)	37.	The materials used for each component part of a M.I.C.S. cable are  (ii)  (iii)  The colour code of cables used for wiring a three pin plug are  or
in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.  41. Name three electrical measuring instruments used on live circuits  (i)	37.	The materials used for each component part of a M.I.C.S. cable are  (i)  (ii)  The colour code of cables used for wiring a three pin plug are  (i)  or
in an electric circuit area respectively.  40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.  41. Name three electrical measuring instruments used on live circuits  (i)	37.	The materials used for each component part of a M.I.C.S. cable are  (i)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)  or  or
40. How many units of electricity are used if a refrigerator rated at 250 is run for 12 hours.  41. Name three electrical measuring instruments used on live circuits  (i)	37.	The materials used for each component part of a M.I.C.S. cable are  (i)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)  or  (ii)  or  (iii)
41. Name three electrical measuring instruments used on live circuits  (i)	37.	The materials used for each component part of a M.I.C.S. cable are  (i)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)
41. Name three electrical measuring instruments used on live circuits  (i)	37.	The materials used for each component part of a M.I.C.S. cable are  (i)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)  (ii)  or  (iii)  The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area
A1. Name three electrical measuring instruments used on live circuits  (i)	35.	The materials used for each component part of a M.I.C.S. cable are  (i)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)  (ii)  or  (iii)  The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area
A1. Name three electrical measuring instruments used on live circuits  (i)	35.	The materials used for each component part of a M.I.C.S. cable are  (i)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)  (ii)  or  (iii)  The use of miniature circuit breaker and earth leakage circuit break in an electric circuit area
(i)	35.	The materials used for each component part of a M.I.C.S. cable are  (i)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)
(i)	35.	The materials used for each component part of a M.I.C.S. cable are  (ii)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)
(;;)	37. () 38. 39.	The materials used for each component part of a M.1.C.S. cable are  (i)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)
(11)	37. () 38. 39.	The materials used for each component part of a M.I.C.S. cable are  (i)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)
	37. () 38. 39.	The materials used for each component part of a M.I.C.S. cable are  (i)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)
	37. () 38. 39.	The materials used for each component part of a M.I.C.S. cable are  (i)  (iii)  The colour code of cables used for wiring a three pin plug are  (i)

Candidate's Number 42. In the figure above find the current in the 4 ohms resistor (ie  $R_3$ ). How do the poles of two magnets with their N-pole and S-pole facing 43. each other behave when placed close to one another? Name three types of single pole switches used for lighting in dome-44. stic installation. (1) (ii) (111) What is a conductor? 45. A wattmeter is a combination of two instruments: 46. (i)