Lab Five-Six – Data Wrangling in R

Tips

- Complete the tasks below. Make sure to start your solutions in on a new line that starts with "**Solution**:".
- Make sure to use the Quarto Cheatsheet. This will make completing and writing up the lab *much* easier.
- Make sure to use "enter" to make your code readable, so it doesn't run off the page. I switched the Quarto document to automatically render to .pdf, so you can see what you're submitting by default. You can switch back for the highlighting by moving the html block above the pdf block in the YAML header.
- Use the pipe operator (`|>`). It makes the data wrangling tasks much easier to write.
- Use `head(...)` or `glimpse(...)` often to ensure your code did what you wanted it to and that you haven't accidentally deleted their entire dataset with a bad filter.
- Don't forget that you can copy-and-paste code when you're doing something similar as we did in class!

Timeline

- Week of 2/16: Aim to complete the data wrangling sections
- Week of 2/23: Aim to complete the data summaries sections

1 Biomedical Science Data

Kitsberg et al. (2025) collect data on the Human Cytomegalovirus (HCMV). HCMV is a member of the herpesvirus family – the same family that includes: chickenpox, mononucleosis (mono), and cold sores. Prevalence is high with a worldwide seroprevalence of 24% to 100% (Gupta and Shorman 2025). The virus persists in a dormant state for the entire life of those infected. Primary cytomegalovirus infection is often asymptomatic but can present with flu-like symptoms. The infection can reactivate due to stress, aging, or a weakened immune system.

The researchers obtained blood samples from healthy donors, males and females, aged 25-45. They infected the cells of primary (human donor's blood) or THP1 (purchased cell lines) monocytes ($n = 87$ and $n = 112$, respectively) and macrophages ($n = 93$ and $n = 170$, respectively) and counted the number of viral genomes in the nuclei.

Note that the original donor of the THP-1 cell line was a 1-year-old Japanese boy. He was treated for Acute Monocytic Leukemia at Tohoku Hospital Pediatrics (THP-1; the first cell line there). Because they are malignant cancer cells, they can divide indefinitely, breaking the usual cell managment that usually reigns in rogue cells. Therefore, these cells can divide indefinitely in a lab environment. THP-1 cells, and those like them, serve as such a reliable, uniform model for medical research and improve reproducability.

Preliminary Question: Are THP-1 cells a good stand-in for human cells?

Research Question: Is the virus more prevalent in the nucleus of monocytes or macrophages, explaining why HCMV stays dormant in monocytes but goes active in macrophages?

1.1 Data Wrangling

1.1.1 Part A

Go to the website and download the source data https://www.nature.com/articles/s41467-025-68063-y#Sec30.

Describe the process – do not leave out any steps – for how you can load the data for Figure 3b from the manuscript into `R`.

Hint: You can use packages like `readxl` (Wickham and Bryan 2025) but you will find it substantially easier to open the `.xls` file using your computer's spreadsheet software and create a new `.csv` file with the data you need.

Solution: Installed packages `tidyverse` and `patchwork` Downloaded the souce data and moved the file to my working directory (in the lab folder) Made the `xlxs` file rectangular for effecient use in `R` by stacking duplicate columns. Converted it to a csv file to make it easier to read and work with. Loaded the file using `.csv`

```
biomed.dat<-read.csv("BiomedData.csv")
```

1.1.2 Part B

The data need to be cleaned. Note that the sample type (Healthy Donor or THP-1), cell type (Monocytes or Macrophages), and treatment (12 Hours Post-Infection or Uninfected) are all recorded in one column `sample`, separated with underscores. Use `separate(...)` from the `tidyverse` package to separate the `sample` column into the `SampleType`, `CellType`, `Treatment` columns. Save the object as `dat.kitsberg.cleaned`.

Hint: Use `?separate(...)` to see how it works.

Solution:

Used the `seperate()` function to split the data uder `sample` into `SampleType`, `CellType`, `Treatment` columns. Saved it in `dat.kitsberg.cleaned`

```
dat.kitsberg.cleaned<- biomed.dat |>
  separate(col="sample", into=c("SampleType", "CellType", "Treatment"), sep="_")
```

1.1.3 Part C

The researchers are only interested in observations in the treatment group (12hpi). Remove uninfected samples from the data. Update `dat.kitsberg.cleaned` with the result.

Hint: I would use the `filter(...)` function.

Solution:

Used `filter(...)` to get only the treatment group with `12hpi`

```
dat.kitsberg.cleaned <- filter(dat.kitsberg.cleaned, Treatment=="12hpi")
```

1.1.4 Part D

When `CellType` is "MDM", it is a Monocyte-Derived Macrophages. That is, the cell type should be macrophages which is coded as "mac". Update `dat.kitsberg.cleaned` with the result.

Hint: I would use the `mutate(...)` function. You will likely find `if_else(...)` or `case_when(...)` helpful.

Solution:

Used the `mutate(...)` function to change the `MDM` types to `mac` types. Used `if_else` conditional statements for this.

```
dat.kitsberg.cleaned <- dat.kitsberg.cleaned |>
  mutate(CellType = if_else(CellType=="MDM", "mac", CellType))
```

1.2 Part E

The researchers are only interested in monocytes and macrophages. Remove any other cell types. Update `dat.kitsberg.cleaned` with the result.

Hint: I would use the `filter(...)` function.

Solution:

Using `filter(...)` function to seperate only monocytes and macrophages.

```
dat.kitsberg.cleaned<- filter(dat.kitsberg.cleaned, CellType=="mono" | CellType=="mac")
```

1.3 Part F

Clean up the data entry. Replace the shorthand the researchers used with the neat sample type (Healthy Donor or THP-1), cell type (Monocytes or Macrophages), and treatment (12 Hours Post-Infection or Uninfected). Update `dat.kitsberg.cleaned` with the result.

Hint: I would use the `mutate(...)` function. You will likely find `if_else(...)` or `case_when(...)` helpful.

Solution:

Used `mutate` to replace shorthand notations with the neat types.

```
# replacing labels using mutate
dat.kitsberg.cleaned <- dat.kitsberg.cleaned |>
  mutate(SampleType = if_else(SampleType=="primary", "Healthy Donor", "THP-1")) |>
  mutate(CellType = if_else(CellType=="mono", "Monocytes", "Macrophages")) |>
  mutate(Treatment = if_else(Treatment=="12hpi", "12 Hours Post-Infection", "Uninfected"))
```

1.4 Part G

In an `R` code block, combine your answers into one code block that completes the full cleaning process. Save the object as `dat.kitsberg.cleaned`.

Note: You will use this in the next section

Solution:

Combined my answers into one block of code for the next section

```
# full cleaning code
dat.kitsberg.cleaned<- biomed.dat |>
  separate(col="sample", into=c("SampleType", "CellType", "Treatment"), sep="_") |> # seperate samples into different tupes
  filter(Treatment=="12hpi")|> # filter by 12hpi
  mutate(CellType = if_else(CellType=="MDM", "mac", CellType))|>
  filter(CellType=="mono" | CellType=="mac")|>
  mutate(SampleType = if_else(SampleType=="primary", "Healthy Donor", "THP-1")) |> # remaming sample types
  mutate(CellType = if_else(CellType=="mono", "Monocytes", "Macrophages")) |> # renaming cell types
  mutate(Treatment = if_else(Treatment=="12hpi", "12 Hours Post-Infection", "Uninfected")) # renaming treatments

head(dat.kitsberg.cleaned)
```

```
     SampleType  CellType               Treatment viruses.within.nucleus
1 Healthy Donor Monocytes 12 Hours Post-Infection                      0
2 Healthy Donor Monocytes 12 Hours Post-Infection                      0
3 Healthy Donor Monocytes 12 Hours Post-Infection                      0
4 Healthy Donor Monocytes 12 Hours Post-Infection                      0
5 Healthy Donor Monocytes 12 Hours Post-Infection                      0
6 Healthy Donor Monocytes 12 Hours Post-Infection                      0
```

1.5 Data Summaries

1.5.1 Part A

Recreate Figure 3b as depicted in the paper (see https://www.nature.com/articles/s41467-025-68063-y#Fig3). You can ignore the significance comparison because we haven't done that yet.

Hint: I would use `geom_violin(...)` for Figure 3b I also expect your plots to look nicer – better labels, better scaling, etc. Don't forget to use the proper formatting using the syntax in the Quarto cheatsheet.

Solution:

Used the function `geom_violin` of `ggplot` to plot a violin graph visualisation of the HCMV genomes detected in the nucleus and cytoplasm of infected monocytes compared to macrophages.

```
glimpse(dat.kitsberg.cleaned)
```

```
Rows: 462
Columns: 4
$ SampleType             <chr> "Healthy Donor", "Healthy Donor", "Healthy Dono~
$ CellType               <chr> "Monocytes", "Monocytes", "Monocytes", "Monocyt~
$ Treatment              <chr> "12 Hours Post-Infection", "12 Hours Post-Infec~
$ viruses.within.nucleus <int> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,~
```

```
ggplot(data= dat.kitsberg.cleaned) +
  geom_violin(aes(x= CellType, y= viruses.within.nucleus), width = 1) +
  theme_bw() +
  facet_wrap(~SampleType) +
  labs(
    x= "Cell Types",
    caption= "Fig 3b: HCMV genomes detected in the nucleus and cytoplasm of infected monocytes compared to macrophages.",
    y = "Viral genomes detected in nucleus"
  )
```



genomes detected in the nucleus and cytoplasm of infected monocytes compared to macrophages.

1.5.2 Part B

Compute a table containing relevant numerical summaries for Figure 3b.

Hint: I would use `group_by(...)` and `summarize(...)` to complete this. Don't forget to use the proper formatting using `knitr::kable(...)` as described in the Quarto Cheatsheet.

Solution:

Used `group_by(...)` and `summarize(...)` to create a summary of the relevant numerical summaries in `dat.kitsberg.cleaned` data.

```
# numerical summary for the data grouped by cell type
dat.kitsberg.summary <- dat.kitsberg.cleaned |>
  group_by(CellType) |> # get celltype summaries
  summarize(
    n = n(), # number
    Missing = sum(is.na(viruses.within.nucleus)), # missing values
    Mean = mean(viruses.within.nucleus, na.rm = T),
    SD = sd(viruses.within.nucleus, na.rm = T),
    Median = median(viruses.within.nucleus, na.rm = T),
    IQR = IQR(viruses.within.nucleus, na.rm = T)
  )
```

Used the `knitr::kable(...)` function and adding `#| echo: false` to print the table nicely is hidden by setting `echo: false` in the header

Table 1: Viral genomes detected in nucleus in Sample Types.

CellType	n	Missing	Mean	SD	Median	IQR
Macrophages	263	0	0.34	0.58	0	1
Monocytes	199	0	0.03	0.20	0	0

2 Ship Valuation

Figure 1: This is a ship-shipping ship shipping shipping ships.

Bal, Akan, and Gencer (2025) aim to build a model for predicting the value of Supramax and Ultramax ships using both current and past market data. Their goal was to build a model that only uses information anyone can easily look up.

The researchers collected 17 years of real ship sale prices (2005–2022), covering $n = 1819$ Supramax and Ultramax ship sales.

Research Question: Can we predict Supramax and Ultramax ship prices?

2.1 Data Wrangling

2.1.1 Part A

I downloaded the data from linked in the article (https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0319073). I have included the data in this lab folder as `ShipValuation-Bal25.csv`. Load the data into `R`.

Solution:

Loaded the downloaded data from the lab folder using `read_csv(...)`

```
ship.data<-read.csv("ShipValuation-Bal25.csv")
```

2.1.2 Part B

The price of each Supramax and Ultramax ship is reported on the $\log_{10}$ scale. Create a new column called `price` that contains the price in millions of dollars.

$$\text{Price} = \frac{10^{\text{SPLog}}}{1000000}$$

Save the object as `dat.bal.cleaned`.

Hint: I would use the `mutate(...)` function.

Solution:

Used the `mutate(...)` function to create a new column `price` containing ship prices in millions of dollars. Saved the object as `dat.bal.cleaned`

```
dat.bal.cleaned<-ship.data |>
  mutate(Price= (10^SPLog)/1000000) # add price column
```

2.1.3 Part C

The authors recorded the country that each Supramax or Ultramax ship was built in in the columns `Japan`, `China, People's Republic Of`, `Philippines`, `Korea, South`, `Others Country Build`. These columns are marked `1` to indicate that is the country of origin and `0` otherwise. Create a new column called `OriginCountry` that contains a clean labels for the country in which the ship was built. Update `dat.bal.cleaned` with the result.

Hint: I would use the `mutate(...)` function. You will likely find `if_else(...)` or `case_when(...)` helpful.

Solution:

Used `case_when` and `mutate(...)` functions to find the the origin countries marked with 1 the updated `dat.bal.cleaned`.

```
# new origincountry column with renamed countries
dat.bal.cleaned <- dat.bal.cleaned |>
  mutate(OriginCountry= case_when(
    Japan==1 ~ "Japan",
    China..People.s.Republic.Of ==1 ~ "China",
    Philippines ==1 ~ "Philippines",
    Korea..South == 1 ~ "South Korea",
    Others.Country.Build ==1 ~ "Other",
    TRUE ~ NA
  ))
```

2.1.4 Part D

The authors recorded each Supramax and Ultramax ship's main engine manufacturer in the columns `Caterpillar`, `MAN-B&W`, `Wartsila`, `Mitsubishi`. These columns are marked `1` to indicate that is the manufacturer and `0` otherwise. Create a new column called `Manufacturer` that contains a clean labels for the manufacturer. Update `dat.bal.cleaned` with the result.

Hint: Follow the logic of the previous question.

Solution:

Used `mutate(...)` and `case_when(...)` to create a new column `Manufacturer` containing the labels for manufacturers

```
# new manufacturer column with renamed manufaturer labels
dat.bal.cleaned <- dat.bal.cleaned |>
  mutate(Manufacturer= case_when(
    Caterpillar==1 ~ "Caterpillar",
    MAN.B.W ==1 ~ "MAN.B.W",
    Wartsila ==1 ~ "Wartsila",
    Mitsubishi == 1 ~ "Mitsubishi",
    TRUE ~ NA
  ))
```

2.1.5 Part E

The researchers recorded whether each Supramax and Ultramax ship is currently covered by a Protection and Indemnity (P&I) Club. This can be an indicator that a ship meets the minimum seaworthiness and safety requirements of the insurer.

The authors recorded P&I clubs in the columns `Japan P&I Club`, `Gard`, `West of England`, `North of England`, `UK P&I`, `Britannia P&I`, `London P&I Club`, `Skuld`, `Steamship Mutual`, `Others`, `Unknown`. These columns are marked `1` to indicate that the ship is insured by that P&I club and `0` otherwise. Create a new column called `PI.club` that contains a clean labels for the P&I club. Update `dat.bal.cleaned` with the result.

Hint: Follow the logic of the previous questions.

Solutions:

Used `mutate(...)` and `case_when(...)` to create a new column `PI.club` containing labels for the P&I club

```
# new PIclub column with renamed labels
dat.bal.cleaned <- dat.bal.cleaned |>
  mutate(PI.club= case_when(
    Japan.P.I.Club==1 ~ "Japan P.I Club",
    Gard ==1 ~ "Gard",
    West.of.England ==1 ~ "West of England",
    North.of.England == 1 ~ "North of England",
    Britannia.P.I==1 ~ "Britannia P.I",
```

```
    London.P.I.Club ==1 ~ "London P.I Club",
    Skuld ==1 ~ "Skuld",
    Steamship.Mutual == 1 ~ "Steamship Mutual",
    Others ==1 ~ "Others",
    Unknown == 1 ~ "Unknown",
    TRUE ~ NA
  ))
```

2.1.6 Part F

The researchers recorded whether each Supramax and Ultramax ship is classed by a society that requires a ship to be safe, structurally sound, and built/maintained to specific engineering standards.

The authors recorded class society in the columns `Nippon Kaiji Kyokai (IACS)`, `Lloyd's Register`, `Bureau Veritas (IACS)`, `Det Norske Veritas (IACS)`, `American Bureau of Shipping (IACS)`, `Others Class`, `With Two Classes`, `Disclassed`. These columns are marked `1` to indicate that the ship is classed by that soceity and `0` otherwise. Create a new column called `Class` that contains a clean labels for the class. Update `dat.bal.cleaned` with the result.

Hint: Follow the logic of the previous questions.

Solutions:

Used `mutate(...)` and `case_when(...)` to create a new column `Class` containing labels for class

```
# new class column with renamed class labels
dat.bal.cleaned <- dat.bal.cleaned |>
  mutate(Class= case_when(
    Nippon.Kaiji.Kyokai..IACS.==1 ~ "Nippon Kaiji Kyokai (IACS)",
    Lloyd.s.Register ==1 ~ "Lloyd's Register",
    Bureau.Veritas..IACS. ==1 ~ "Bureau Veritas (IACS)",
    Det.Norske.Veritas..IACS. == 1 ~ "Det Norske Veritas (IACS)",
    American.Bureau.of.Shipping..IACS.==1 ~ "American Bureau of Shipping (IACS)",
    Others.Class ==1 ~ "Others",
    With.Two.Classes ==1 ~ "With Two Classes",
    Disclassed ==1 ~ "Disclassed",
    TRUE ~ NA
  ))
```

2.1.7 Part G

The researchers recorded the flag state of each Supramax and Ultramax ship. Each flag state enforces its own set of safety, environmental, and crew welfare rules and regulations. Ships under certain flag states may be more or less valuable depending on how much the flag affects the buyer's trust in the condition of the boat.

The authors recorded flag states in the columns `Panama`, `Marshall Islands`, `Liberia`, `Malta`, `Hong Kong`, `China`, `Singapore`, `Others Flag`, `With two flags`. These columns are marked `1` to indicate that the ship has that flag state and `0` otherwise. Create a new column called `FlagState` that contains a clean labels for the flag state. Update `dat.bal.cleaned` with the result.

Hint: Follow the logic of the previous questions.

Solutions:

Used `mutate(...)` and `case_when(...)` to create a new column `FlagState` containing labels for flag state

```
# new flagstate columns with renamed flagstate labels
dat.bal.cleaned <- dat.bal.cleaned |>
  mutate(FlagState= case_when(
    Panama==1 ~ "Panama",
    Marshall.Islands ==1 ~ "Marshall Islands",
    Liberia ==1 ~ "Liberia",
    Malta == 1 ~ "Malta",
    Hong.Kong..China==1 ~ "Hong Kong, China",
    Singapore ==1 ~ "Singapore",
    Others.Flag ==1 ~ "Others Flag",
    With.two.flags==1 ~ "With two flags",
    TRUE ~ NA
  ))
```

2.2 Part H

In an `R` code block, combine your answers into one code block that completes the full cleaning process. Save the object as `dat.bal.cleaned`.

Note: You will use this in the next section

Solution:

Combined my answers into one block of code for the next section

```r
ship.data<-read.csv("ShipValuation-Bal25.csv")

# combined cleaning code
dat.bal.cleaned<-ship.data |>
  mutate(Price= (10^SPLog)/1000000) |> # price
  mutate(OriginCountry= case_when( # origincountry column
    Japan==1 ~ "Japan",
    China..People.s.Republic.Of ==1 ~ "China",
    Philippines ==1 ~ "Philippines",
    Korea..South == 1 ~ "South Korea",
    Others.Country.Build ==1 ~ "Other",
    TRUE ~ NA
  )) |>
  mutate(Manufacturer= case_when( # manufacturer column
    Caterpillar==1 ~ "Caterpillar",
    MAN.B.W ==1 ~ "MAN.B.W",
    Wartsila ==1 ~ "Wartsila",
    Mitsubishi == 1 ~ "Mitsubishi",
    TRUE ~ NA
  )) |>
  mutate(PI.club= case_when( # PIClub column
    Japan.P.I.Club==1 ~ "Japan P.I Club",
    Gard ==1 ~ "Gard",
    West.of.England ==1 ~ "West of England",
    North.of.England == 1 ~ "North of England",
    Britannia.P.I==1 ~ "Britannia P.I",
    London.P.I.Club ==1 ~ "London P.I Club",
    Skuld ==1 ~ "Skuld",
    Steamship.Mutual == 1 ~ "Steamship Mutual",
    Others ==1 ~ "Others",
    Unknown == 1 ~ "Unknown",
    TRUE ~ NA
  )) |>
  mutate(Class= case_when( # class column
    Nippon.Kaiji.Kyokai..IACS.==1 ~ "Nippon Kaiji Kyokai (IACS)",
    Lloyd.s.Register ==1 ~ "Lloyd's Register",
    Bureau.Veritas..IACS. ==1 ~ "Bureau Veritas (IACS)",
    Det.Norske.Veritas..IACS. == 1 ~ "Det Norske Veritas (IACS)",
    American.Bureau.of.Shipping..IACS.==1 ~ "American Bureau of Shipping (IACS)",
    Others.Class ==1 ~ "Others",
    With.Two.Classes ==1 ~ "With Two Classes",
    Disclassed ==1 ~ "Disclassed",
    TRUE ~ NA
  )) |>
  mutate(FlagState= case_when( # flagstate column
    Panama==1 ~ "Panama",
    Marshall.Islands ==1 ~ "Marshall Islands",
    Liberia ==1 ~ "Liberia",
    Malta == 1 ~ "Malta",
    Hong.Kong..China==1 ~ "Hong Kong, China",
    Singapore ==1 ~ "Singapore",
    Others.Flag ==1 ~ "Others Flag",
    With.two.flags==1 ~ "With two flags",
    TRUE ~ NA
  ))
```

2.3 Data Summaries

First, I provide a short description of the other variables in their data. Note that the size ordering of types of ships discussed below is:

$$\text{Handysize} < \text{Supramax} < \text{Ultramax} < \text{Panamax} < \text{Capesize}$$

- `DWT`: The deadweight tonnage, which is the maximum weight each Supramax and Ultramax ship can safely carry in metric tons. This gives a measure of how much cargo, fuel, fresh water, ballast water, provisions, and crew a ship can handle.
- `Yas`: The age in years. New Supramax and Ultramax ships were recorded as having age 1.

- `Enginges RPM`: Revolutions per minute of each Supramax and Ultramax ship's main propulsion engine. Generally speaking, lower-RPM engines are more expensive because they are more fuel efficient.
- `BACI`: The Baltic Capesize Index. This describes freight rates for Capesize dry bulk ships, which reflects supply and demand. When BACI is high, Capesize ships are more profitable in shipping, which could positively affect Supramax and Ultramax ship values as demand for dry bulk commodities might be high and large shipments could be split into several Supramax and Ultramax shipments.
  Note: This reports the current BACI. The data also contain the BACI form 1, 2, and 3 months before the sale (`BACI-1`, `BACI-2`, `BACI-3`).
- `BPNI`: The Baltic Panamax Index. This describes the cost to ship dry bulk commodities (e.g., coal or grain) on Panamax class ships. When BPNI is high, we expect Panamax ship prices to go up. Supramax and Ultramax ship values tend to follow this trend as charterers switch to these smaller vessels when Panamax rates become too expensive.
  Note: This reports the current BPNI. The data also contain the BPNI form 1, 2, and 3 months before the sale (`BPNI-1`, `BPNI-2`, `BPNI-3`).
- `BSIS`: The Baltic Supramax Index. This describes freight rates for Supramax vessels, which reflects supply and demand. When BSIS is high, Supramax and Ultramax prices are usually higher because they are more profitable in shipping.
  Note: This reports the current BSIS. The data also contain the BSIS form 1, 2, and 3 months before the sale (`BSIS-1`, `BSIS-2`, `BSIS-3`).
- `BHSI`: The Baltic Handysize Index. This describes freight rates for handysize vessels. When BHSI is high, Supramax and Ultramax ship prices are usually higher because the prices move together.
  Note: This reports the current BHSI. The data also contain the BHSI form 1, 2, and 3 months before the sale (`BHSI-1`, `BHSI-2`, `BHSI-3`).
- `LIBOR`: The London InterBank Offered Rate. This describes the average reported interest rate at which banks would lend US dollars for 3 months.

2.3.1 Part A

Choose a categorical variable. Create a plot and corresponding numerical summary to assess whether or how ship prices vary across the levels of the selected categorical variable.

Solution:

Used the function `geom_violin` of `ggplot` to plot a violin graph visualisation of a ships origin country in relation to the prices.

```r
dat.bal.cleaned<- dat.bal.cleaned |>
  drop_na()


ggplot(data= dat.bal.cleaned) +
  geom_violin(aes(x= OriginCountry, y= Price), width = 1) +
  geom_boxplot(aes(x= OriginCountry,y= Price),width=0.3) +
  theme_bw() +
  labs(
    x= "Origin countries",
    title= "Violin graph visualisation of a ships origin country in relation to the prices.",
    y = "Ship prices",
  )
```



Used `group_by(...)` and `summarize(...)` to create a summary of the relevant numerical summaries in `dat.bal.cleaned` data.

```
dat.bal.summary <- dat.bal.cleaned |>
  group_by(OriginCountry) |>
  summarize(
    n = n()
  ) |>
  mutate(proportion= n/sum(n))
```

Used the `knitr::kable(...)` function and adding `#| echo: false` to print the table nicely is hidden by setting `echo: false` in the header

Table 2: Ships origin country in relation to the prices.

OriginCountry	n	proportion
China	554	0.35
Japan	796	0.50
Other	74	0.05
Philippines	121	0.08
South Korea	60	0.04

2.3.2 Part B

Choose a quantitative variable. Create a plot and corresponding numerical summary to assess whether or how ship prices vary with the selected quantitative variable.

Solution:

Used the function `geom_point` of `ggplot` to plot a scatter plot visualisation of a ships' Yas in relation to the prices.

```
ggplot(data= dat.bal.cleaned) +
  geom_point(aes(x= Yas, y= Price), width = 1) +
  theme_bw() +
  labs(
    x= "Yas",
    title= "Scatter plot visualisation of a ships' Yas in relation to the prices.",
    y = "Ship prices",
  )
```



Used `group_by(...)` and `summarize(...)` to create a summary of the relevant numerical summaries in `dat.kitsberg.cleaned` data.

```
dat.bal.summary <- dat.bal.cleaned |>
  group_by(Yas) |>
  summarize(
    n = n(),
    Missing = sum(is.na(Price)),
    Mean = mean(Price, na.rm = T),
    SD = sd(Price, na.rm = T),
    Median = median(Price, na.rm = T),
    IQR = IQR(Price, na.rm = T)
  )
```

Used the `knitr::kable(...)` function and adding `#| echo: false` to print the table nicely is hidden by setting `echo: false` in the header

Table 3: Ships Yas in relation to the prices

Yas	n	Missing	Mean	SD	Median	IQR
1	96	0	32.71	13.63	30.50	11.00
2	57	0	27.82	11.34	24.90	9.00
3	84	0	26.29	12.16	26.00	12.00
4	93	0	21.85	10.51	20.50	10.70
5	93	0	21.48	11.71	18.95	13.30
6	113	0	20.78	13.23	18.00	13.00
7	120	0	17.33	8.95	15.35	8.67
8	112	0	14.94	5.28	14.15	6.89
9	107	0	14.01	4.93	13.40	7.16
10	135	0	13.10	4.71	12.50	6.10
11	84	0	12.72	4.72	12.05	6.65
12	76	0	12.98	4.33	12.75	7.99
13	53	0	11.33	5.32	10.50	9.40
14	38	0	8.86	4.43	8.00	4.15
15	55	0	8.88	4.19	7.80	5.00
16	39	0	9.37	5.11	7.50	9.35
17	53	0	9.87	5.14	8.50	4.00
18	36	0	8.79	4.65	6.60	5.43
19	16	0	9.16	4.56	7.40	8.93

Table 3: Ships Yas in relation to the prices

Yas	n	Missing	Mean	SD	Median	IQR
20	11	0	8.99	3.32	9.20	5.88
21	5	0	11.88	6.11	12.25	5.30
22	6	0	14.33	11.37	9.75	18.25
23	12	0	17.09	10.82	15.00	14.78
24	17	0	12.07	9.83	8.00	5.20
25	22	0	12.03	9.03	10.00	8.84
26	18	0	11.13	7.17	8.00	9.01
27	21	0	5.72	1.96	5.00	3.00
28	13	0	5.42	0.92	5.20	1.20
29	8	0	5.92	0.57	6.00	0.63
30	6	0	4.60	0.87	4.85	1.02
31	5	0	5.50	1.62	5.00	1.29
34	1	0	2.41	NA	2.41	0.00

References

Bal, Elif Tuçe, Ercan Akan, and Huseyin Gencer. 2025. "A Novel Approach to Ship Valuation Prediction: An Application to the Supramax and Ultramax Secondhand Markets." *PLoS One* 20 (5): e0319073.

Gupta, Mohit, and Mahmoud Shorman. 2025. "Cytomegalovirus Infections." In *StatPearls [Internet]*. StatPearls Publishing.

Kitsberg, Yaarit, Aharon Nachshon, Tamar Arazi, Karin Broennimann, Tal Fisher, Alexander Wainstein, Yaara Finkel, Noam Stern-Ginossar, and Michal Schwartz. 2025. "Viral Entry Shapes HCMV Latency Establishment." *Nature Communications*.

Wickham, Hadley, and Jennifer Bryan. 2025. *Readxl: Read Excel Files*. https://doi.org/10.32614/CRAN.package.readxl.