

Towards a miniKanren with fair search strategies

KUANG-CHEN LU, Indiana University, USA

WEIXI MA, Indiana University, USA

DANIEL P. FRIEDMAN, Indiana University, USA

We describe fairness levels in disjunction and conjunction implementations. Specifically, a disjunction implementation can be fair, almost-fair, or unfair. And a conjunction implementation can be fair or unfair. We compare the fairness level of four search strategies: the standard miniKanren interleaving depth-first search, the balanced interleaving depth-first search, the fair depth-first search, and the standard breadth-first search. The two non-standard depth-first searches are new. And we present a new, more efficient and shorter implementation of the standard breadth-first search. Using quantitative evaluation, we argue that each depth-first search is a competitive alternative to the standard one, and that our improved breadth-first search implementation is more efficient than the current one.

1 INTRODUCTION

miniKanren is a family of relational programming languages. Friedman et al. [3, 4] introduce miniKanren and its implementation in *The Reasoned Schemer* and *The Reasoned Schemer, 2nd Ed* (TRS2). After Hemann et al. [5] describe microKanren, a minimal core of miniKanren comprised of only 54 LOC, miniKanren has been implemented in many other languages, including multiple ones using the same language (e.g. OCanren[7]). As demonstrated in Byrd et al. [2], miniKanren can be used to naturally express difficult computations, such as using an interpreter to perform example-based program synthesis, or using a proof checker as a theorem prover. The papers, talks, and tutorials on miniKanren.org present many other unusual problems, and their solutions in miniKanren.

A subtlety arises when a `conde` contains many clauses: not every clause has an equal chance of contributing to the result. As an example, consider the following relation `repeato` and its invocation.

```
(defrel (repeato x out)
  (conde
    ((≡ `(,x) out))
    ((fresh (res)
      (≡ `(,x . ,res) out)
      (repeato x res))))))
> (run 4 q
  (repeato 'x q))
'((*) (*) (*) (*) (* * * *))
```

Next, consider the following disjunction of invoking `repeato` with four different letters.

Authors' addresses: Kuang-Chen Lu, Indiana University, USA, kl13@iu.edu; Weixi Ma, Indiana University, USA, mvc@iu.edu; Daniel P. Friedman, Indiana University, USA, dfried@indiana.edu.

This work is licensed under a Creative Commons “Attribution-ShareAlike 4.0 International” license.



© 2019 Copyright held by the author(s).
miniKanren.org/workshop/2019/8-ART1

```

48      > (run 12 q
49         (conde
50           ((repeato 'a q))
51           ((repeato 'b q))
52           ((repeato 'c q))
53           ((repeato 'd q))))
54

```

cond^e intuitively relates its clauses with logical or. And thus an unsuspecting beginner would expect each letter to contribute equally to the result, as follows.

```

57      '((a) (b) (c) (d)
58        (a a) (b b) (c c) (d d)
59        (a a a) (b b b) (c c c) (d d d)))
60

```

The cond^e in TRS2, however, generates a less expected result.

```

63      '((a) (a a) (b) (a a a)
64        (a a a a) (b b)
65        (a a a a a) (c)
66        (a a a a a a) (b b b)
67        (a a a a a a a) (d))
68

```

The miniKanren in TRS2 implements interleaving DFS (DFS_i), the cause of this unexpected result. With this search strategy, each cond^e clause takes half of its received computational resources and passes the other half to its following clauses, except for the last clause that takes all resources it receives. In the example above, the a clause takes half of all resources. And the b clause takes a quarter. Thus c and d barely contribute to the result.

DFS_i is sometimes powerful for an expert. By carefully organizing the order of cond^e clauses, a miniKanren program can explore more “interesting” clauses than those uninteresting ones, and thus use computational resources efficiently.

DFS_i is not always the best choice. For instance, it might be less desirable for novice miniKanren users—understanding implementation details and fiddling with clause order is not their first priority. There is another reason that miniKanren could use more search strategies than just DFS_i. In many applications, there does not exist one order that serves all purposes. For example, a relational dependent type checker contains clauses for constructors that build data and clauses for eliminators that use data. When the type checker is generating simple and shallow programs, the clauses for constructors had better be at the top of the cond^e expression. When performing proof searches for complicated programs, the clauses for eliminators had better be at the top of the cond^e expression. With DFS_i, these two uses cannot be efficient at the same time. In fact, to make one use efficient, the other one must be more sluggish. Boskin et al. [1] propose and implement a means to eliminate or re-order disjunctive clauses to accommodate varying search needs such as these.

The specification that gives every clause in the same cond^e equal “search priority” is fair disj. And search strategies with almost-fair disj give every clause similar priority. Fair conj, a related concept, is more subtle. We cover it in the next section.

Our research compares four search strategies with different features in fairness (Table 1). To summarize our contributions, we

- propose and implement **balanced** interleaving depth-first search (DFS_{bi})
- propose and implement **fair** depth-first search (DFS_f)

- implement in a new way the standard breath-first search (BFS) by Seres et al. [9] We refer to BFS_{ser} as their implementation and BFS_{imp} as our new one. We formally prove that the two implementations are semantically equivalent, however, BFS_{imp} runs faster in all benchmarks and is shorter.

| Search Strategies | disj | conj |
|-------------------|-------------|--------|
| DFS_i | unfair | unfair |
| DFS_{bi} | almost-fair | unfair |
| DFS_f | fair | unfair |
| BFS | fair | fair |

Table 1. Fairness of all search strategies

2 SEARCH STRATEGIES AND FAIRNESS

In this section, we define fairness levels in disjunction and conjunction implementations. Specifically, a disjunction implementation can be fair, almost-fair, or unfair. And a conjunction implementation can be fair or unfair. Fairness, intuitively, measures how evenly a search strategy allocates computational resource to “sibling” spaces.

Before going further into fairness, we give a short review of the terms: *state*, *space*, and *goal*. A *state* is a collection of constraints. (Here, we restrict constraints to unification constraints.) Every answer corresponds to a state. A *space* is a collection of states. And a *goal* is a function from a state to a space. Every state in the output space includes the input state and possibly more constraints.

Now we elaborate fairness by running more queries about `repeato`. We never use `run*` in this paper because fairness is more interesting when we have an unbounded number of answers. It is perfectly fine, however, to use `run*` with any search strategy.

2.1 Fair disj

Given the following program, it is natural to expect lists of each letter to constitute 1/4 in the answer list. DFS_i , TRS2’s search strategy, however, results in many more lists of `a` than lists of other letters. And some letters (e.g. `c` and `d`) are rarely seen. The more clauses, the worse the situation.

```
;; DFSi (unfair disj)
> (run 12 q
  (conde
    ((repeato 'a q))
    ((repeato 'b q))
    ((repeato 'c q))
    ((repeato 'd q))))
'((a) (a a) (b) (a a a)
  (a a a a) (b b)
  (a a a a a) (c)
  (a a a a a a) (b b b)
  (a a a a a a a) (d))
```

Under the hood, the `conde` here allocates computational resources to four trivially different spaces. The unfair `disj` in DFS_i allocates many more resources to the first space. On the contrary, fair `disj` would allocate resources evenly to each space.

| | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre> 142 ;; DFS_f (fair disj) 143 > (run 12 q 144 (cond^e 145 ((repeat^o 'a q)) 146 ((repeat^o 'b q)) 147 ((repeat^o 'c q)) 148 ((repeat^o 'd q)))) 149 '((a) (b) (c) (d) 150 (a a) (b b) (c c) (d d) 151 (a a a) (b b b) (c c c) (d d d)) </pre> | <pre> ;; BFS (fair disj) > (run 12 q (cond^e ((repeat^o 'a q)) ((repeat^o 'b q)) ((repeat^o 'c q)) ((repeat^o 'd q)))) '((a) (b) (c) (d) (a a) (b b) (c c) (d d) (a a a) (b b b) (c c c) (d d d)) </pre> |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Running the same program again with almost-fair disj (e.g. DFS_{bi}) gives the same result. Almost-fair, however, is not completely fair, as shown by the following example.

```

155 ;; DFSbi (almost-fair disj)
156 > (run 16 q
157   (conde
158     ((repeato 'a q))
159     ((repeato 'b q))
160     ((repeato 'c q))
161     ((repeato 'd q))
162     ((repeato 'e q))))
163 '((b) (c) (d) (a)
164   (b b) (c c) (d d) (e)
165   (b b b) (c c c) (d d d) (a a)
166   (b b b b) (c c c c) (d d d d) (e e))

```

DFS_{bi} is fair only when the number of goals is a power of 2, otherwise, it allocates some goals with twice as many resources as the others. In the above example, where the cond^e has five clauses, DFS_{bi} allocates more resources to the clauses of b, c, and d.

We end this subsection with precise definitions of all levels of disj fairness. Our definition of *fair* disj is slightly more general than the one in Seres et al. [9], which is only for binary disjunction. We generalize it to a multi-arity one.

DEFINITION 2.1 (FAIR disj). *A disj is fair if and only if it allocates computational resources evenly to spaces produced by goals in the same disjunction (i.e., clauses in the same cond^e).*

DEFINITION 2.2 (ALMOST-FAIR disj). *A disj is almost-fair if and only if it allocates computational resources so evenly to spaces produced by goals in the same disjunction that the maximal ratio of resources is bounded by a constant.*

DEFINITION 2.3 (UNFAIR disj). *A disj is unfair if and only if it is not almost-fair.*

2.2 Fair conj

Given the following program, it is natural to expect lists of each letter to constitute 1/4 in the answer list. Search strategies with unfair conj: DFS_i, DFS_{bi}, and DFS_f, however, results in many more lists of a than lists of other letters. And some letters are rarely seen. Here again, as the number of clauses grows, the situation worsens.

Although some strategies have a different level of fairness in `disj`, they have similar behavior when there is no call to a relational definition in `conde` clauses, including this case. (The only potential difference is that `DFSbi` might reorder states.)

| | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>;; DFS_i (unfair conj) > (run 12 q (fresh (x) (cond^e ((≡ 'a x)) ((≡ 'b x)) ((≡ 'c x)) ((≡ 'd x))) (repeat^o x q))) '((a) (a a) (b) (a a a) (a a a a) (b b) (a a a a a) (c) (a a a a a a) (b b b) (a a a a a a a) (d))</pre> | <pre>;; DFS_f (unfair conj) > (run 12 q (fresh (x) (cond^e ((≡ 'a x)) ((≡ 'b x)) ((≡ 'c x)) ((≡ 'd x))) (repeat^o x q))) '((a) (a a) (b) (a a a) (a a a a) (b b) (a a a a a) (c) (a a a a a a) (b b b) (a a a a a a a) (d))</pre> | <pre>;; DFS_{bi} (unfair conj) > (run 12 q (fresh (x) (cond^e ((≡ 'a x)) ((≡ 'b x)) ((≡ 'c x)) ((≡ 'd x))) (repeat^o x q))) '((a) (a a) (c) (a a a) (a a a a) (c c) (a a a a a) (b) (a a a a a a) (c c c) (a a a a a a a) (d))</pre> |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Under the hood, the `conde` and the call to `repeato` are connected by `conj`. The `conde` goal outputs a space including four trivially different states. Applying the next conjunctive goal, `(repeato x q)`, produces four trivially different spaces. In the examples above, all search strategies allocate more computational resources to the space of `a`. On the contrary, fair `conj` would allocate resources evenly to each space. For example,

```
;; BFS (fair conj)
> (run 12 q
   (fresh (x)
    (conde
      ((≡ 'a x))
      ((≡ 'b x))
      ((≡ 'c x))
      ((≡ 'd x)))
    (repeato x q)))
'((a) (b) (c) (d)
  (a a) (b b) (c c) (d d)
  (a a a) (b b b) (c c c) (d d d))
```

A more interesting situation is when the first conjunct produces an unbounded number of states. Consider the following example: a naive specification of fair `conj` might require search strategies to produce all sorts of singleton lists, but there would not be any lists of length two or longer, which makes the strategies incomplete. A search strategy is *complete* if and only if “every correct answer would be discovered after some finite time” [9], otherwise, it is *incomplete*. In the context of miniKanren, a search strategy is complete means that every correct answer has a position in large enough answer lists.

```

236      ;; naively fair conj
237      > (run 6 q
238         (fresh (xs)
239            (conde
240               ((repeato 'a xs))
241               ((repeato 'b xs)))
242            (repeato xs q)))
243      '(((a)) ((b)))
244        ((a a)) ((b b))
245        ((a a a)) ((b b b)))

```

Our solution requires a search strategy with *fair conj* to organize states in buckets in spaces, where each bucket is a finite collection of states and every space contains possibly infinite buckets, and to allocate resources evenly among spaces derived from states in the same bucket. It is up to a search strategy designer to decide by what criteria to put states in the same bucket, and how to allocate resources among spaces related to different buckets.

BFS puts states of the same cost in the same bucket, and allocates resources carefully among spaces related to different buckets such that it produces answers in increasing order of cost. The *cost* of an answer is its depth in the search tree (i.e., the number of calls to relational definitions required to find the answer) [9]. In the above examples, the cost of each answer is equal to their lengths because we need to apply *repeat^o* n times to find an answer of length n . In the following example, every answer is a list of a list of symbols, where inner lists in the same outer list are identical. Here the cost of each answer is equal to the length of its inner lists plus the length of its outer list. For example, the cost of $((a) (a))$ is $1 + 2 = 3$.

```

260      ;; BFS (fair conj)
261      > (run 12 q
262         (fresh (xs)
263            (conde
264               ((repeato 'a xs))
265               ((repeato 'b xs)))
266            (repeato xs q)))
267      '(((a)) ((b)))
268        ((a) (a)) ((b) (b))
269        ((a a)) ((b b))
270        ((a) (a) (a)) ((b) (b) (b))
271        ((a a) (a a)) ((b b) (b b))
272        ((a a a)) ((b b b)))

```

We end this subsection with precise definitions of all levels of conj fairness.

DEFINITION 2.4 (FAIR conj). A conj is *fair* if and only if it allocates computational resources evenly to spaces produced from states in the same bucket. A bucket is a finite collection of states. And search strategies with *fair conj* should represent spaces with possibly unbounded collections of buckets.

DEFINITION 2.5 (UNFAIR conj). A conj is *unfair* if and only if it is not fair.

```

283 #| Goal × Goal → Goal |#
284 (define (disj2 g1 g2)
285   (lambda (s)
286     (append∞ (g1 s) (g2 s))))
287
288 #| Space × Space → Space |#
289 (define (append∞ s∞ t∞)
290   (cond
291     ((null? s∞) t∞)
292     ((pair? s∞)
293      (cons (car s∞)
294            (append∞ (cdr s∞) t∞)))
295     (else (lambda ()
296              (append∞ t∞ (s∞))))))
297
298
299 (define-syntax disj
300   (syntax-rules ()
301     ((disj) (fail))
302     ((disj g0 g ...) (disj+ g0 g ...))))
303
304
305 (define-syntax disj+
306   (syntax-rules ()
307     ((disj+ g) g)
308     ((disj+ g0 g1 g ...) (disj2 g0 (disj+ g1 g ...))))
309
310

```

Fig. 1. implementation of DFS_i (Part I)

3 INTERLEAVING DEPTH-FIRST SEARCH

In this section, we review the implementation of interleaving depth-first search (DFS_i). We focus on parts that are relevant to this paper. TRS2, chapter 10 and the appendix, “Connecting the wires”, provide a comprehensive description of the miniKanren implementation but limited to unification constraints (\equiv). Fig. 1 and Fig. 2 show parts that are later compared with other search strategies. We follow some conventions to name variables: *ss* name states; *gs* (possibly with subscript) name goals; variables ending with [∞] name spaces. Fig. 1 shows the implementation of *disj*. The first function, *disj₂*, implements binary disjunction. It applies the two disjunctive goals to the input state *s* and composes the two resulting spaces with *append[∞]*. The following syntax definitions say *disj* is right-associative. Fig. 2 shows the implementation of *conj*. The first function, *conj₂*, implements binary conjunction. It applies the *first* goal to the input state, then applies the second goal to states in the resulting space. The helper function *append-map[∞]* applies its input goal to states in its input space and composes the resulting spaces. It reuses *append[∞]* for space composition. The following syntax definitions say *conj* is also right-associative.

```

330 #| Goal × Goal → Goal |#
331 (define (conj2 g1 g2)
332   (lambda (s)
333     (append-map∞ g2 (g1 s))))
334
335 #| Goal × Space → Space |#
336 (define (append-map∞ g s∞)
337   (cond
338     ((null? s∞) '())
339     ((pair? s∞)
340      (append∞ (g (car s∞))
341                (append-map∞ g (cdr s∞))))
342     (else (lambda ()
343              (append-map∞ g (s∞))))))
344
345
346 (define-syntax conj
347   (syntax-rules ()
348     ((conj) (fail))
349     ((conj g0 g ...) (conj+ g0 g ...))))
350
351
352 (define-syntax conj+
353   (syntax-rules ()
354     ((conj+ g) g)
355     ((conj+ g0 g1 g ...) (conj2 g0 (conj+ g1 g ...))))
356
357
358
359

```

Fig. 2. implementation of DFS_i (Part II)

4 BALANCED INTERLEAVING DEPTH-FIRST SEARCH

The strategy **balanced interleaving** DFS (DFS_{bi}) has an almost-fair disj and unfair conj. The implementation of DFS_{bi} differs from DFS_i's in the disj macro. When there are one or more disjunctive goals, the new disj builds a balanced binary tree whose leaves are the goals and whose nodes are disj₂s, hence the name of this search strategy. In contrast, the disj in DFS_i constructs the binary tree in a particularly unbalanced form. We list the new disj with its helper in Fig. 3. The new helper, disj+, takes two additional 'arguments'. They accumulate goals to be put in the left and right subtrees. The first clause handles the case where there is only one goal. In this case, the tree is the goal itself. When there are more goals, we partition the list of goals into two sublists of roughly equal lengths and recur on the two sublists. We move goals to the accumulators in the last clause. As we are moving two goals each time, there are two base cases: (1) no goal remains; (2) one goal remains. We handle these two new base cases in the second clause and the third clause, respectively.

5 FAIR DEPTH-FIRST SEARCH

Fair DFS (DFS_f) has fair disj and unfair conj. The implementation of DFS_f differs from DFS_i's in disj₂ (Fig. 4). The new disj₂ calls a new and fair version of append[∞]. append[∞]_{fair} immediately calls its helper, loop, with the


```

377 (define-syntax disj
378   (syntax-rules ()
379     ((disj) fail)
380     ((disj g ...) (disj+ (g ...) () ())))))
381
382 (define-syntax disj+
383   (syntax-rules ()
384     ((disj+ () () g) g)
385     ((disj+ (gl ...) (gr ...))
386      (disj2 (disj+ () () gl ...)
387              (disj+ () () gr ...)))
389     ((disj+ (gl ...) (gr ...) g0)
390      (disj2 (disj+ () () gl ... g0)
391              (disj+ () () gr ...)))
392     ((disj+ (gl ...) (gr ...) g0 g1 g ...)
393      (disj+ (gl ... g0) (gr ... g1) g ...)))
394
395
396
397

```

Fig. 3. implementation of DFS_{bi}

```

398 #| Goal  $\times$  Goal  $\rightarrow$  Goal |#
399 (define (disj2 g1 g2)
400   (lambda (s)
401     (appendfair∞ (g1 s) (g2 s))))
402
403
404 #| Space  $\times$  Space  $\rightarrow$  Space |#
405 (define (appendfair∞ s∞ t∞)
406   (let loop ((s? #t) (s∞ s∞) (t∞ t∞))
407     (cond
408       ((null? s∞) t∞)
409       ((pair? s∞)
410        (cons (car s∞)
411              (loop s? (cdr s∞) t∞)))
412       (s? (loop #f t∞ s∞))
413       (else (lambda ()
414                (loop #t (t∞) (s∞)))))))
415
416
417
418
419

```

Fig. 4. implementation of DFS_f

first argument, $s?$, initialized to $\#t$, which indicates that we haven't swapped s^∞ and t^∞ . The swapping happens at the third `cond` clause in `loop`, where $s?$ is updated accordingly. The first two `cond` clauses essentially copy the cars and stop recursion when one of the input spaces is obviously finite. The third clause, as we mentioned

```

424 #| Goal  $\times$  Space  $\rightarrow$  Space |#
425 (define (append-map∞fair g s∞)
426   (cond
427     ((null? s∞) '())
428     ((pair? s∞)
429      (append∞fair (g (car s∞))
430                    (append-map∞fair g (cdr s∞))))
431     (else (lambda ()
432              (append-map∞fair g (s∞)))))))
433
434
435

```

Fig. 5. stepping-stone toward BFS_{imp} (based on DFS_f)

above, is just for swapping. When the fourth and last clause runs, we know that both s^∞ and t^∞ end with thunks, and that we have swapped them. In this case, we construct a new thunk. The new thunk swaps back the two spaces in the recursive call to loop. This is unnecessary for fairness—we do it to produce answers in a more readable order.

6 BREADTH-FIRST SEARCH

BFS has both fair disj and fair conj . Our first BFS implementation (Fig. 5) serves as a “stepping-stone” toward BFS_{imp} . It is so similar to DFS_f (not DFS_i) that we only need to apply two changes: (1) rename append-map^∞ to $\text{append-map}^\infty_{\text{fair}}$ and (2) replace append^∞ with $\text{append}^\infty_{\text{fair}}$ in $\text{append-map}^\infty_{\text{fair}}$ ’s body.

This implementation can be improved in two ways. First, as mentioned in subsection 2.2, BFS puts answers in buckets and answers of the same cost are in the same bucket. In the above implementation, however, it is not obvious how we manage cost information—the cars of a space have cost 0 (i.e., they are all in the same bucket), and every thunk indicates an increment in cost. It is even more subtle that $\text{append}^\infty_{\text{fair}}$ and the $\text{append-map}^\infty_{\text{fair}}$ respects the cost information. Second, $\text{append}^\infty_{\text{fair}}$ is extravagant in memory usage. It makes $O(n + m)$ new cons cells every time, where n and m are the sizes of the first buckets of two input spaces. DFS_f is also space extravagant.

In the following paragraphs, we first describe BFS_{imp} implementation that manages cost information in a more clear and concise way and is less extravagant in memory usage. Then we compare BFS_{imp} with BFS_{ser} .

We simplify the cost information by changing the Space type, modifying related function definitions, and introducing a few more functions. The new type of Space is a pair whose car is a list of answers (the bucket), and whose cdr is either #f or a thunk returning a space. The #f here means the space is obviously finite, just like empty list in other implementations. We list functions related to the pure subset in Fig. 6. The first three functions are space constructors. none makes an empty space; unit makes a space from one answer; and step makes a space from a thunk. The remaining functions are as before. Luckily, the change in $\text{append}^\infty_{\text{fair}}$ also fixes the miserable space extravagance—the use of append helps us to reuse the first bucket of t^∞ . Functions implementing impure features are in Fig. 7. The first function, elim, takes a space s^∞ and two continuations fk and sk. When s^∞ contains no answers, it calls fk. Otherwise, it calls sk with the first answer and the rest of the space. This function is similar to an eliminator of spaces, hence the name. The remaining functions are as before.

Kiselyov et al. [6] have demonstrated that a *MonadPlus* hides in implementations of logic programming systems. BFS_{imp} is not an exception: $\text{append-map}^\infty_{\text{fair}}$ is like bind, but takes arguments in reversed order; none, unit, and $\text{append}^\infty_{\text{fair}}$ correspond to mzero, unit, and mplus, respectively.

```

471 #|  $\rightarrow$  Space |#
472 (define (none)
473   `(() . #f))
474
475 #| State  $\rightarrow$  Space |#
476 (define (unit s)
477   `((,s) . #f))
478
479
480 #|  $(\rightarrow$  Space)  $\rightarrow$  Space |#
481 (define (step f)
482   `(() . ,f))
483
484 #| Space  $\times$  Space  $\rightarrow$  Space |#
485 (define (appendfair∞ s∞ t∞)
486   (cons (append (car s∞) (car t∞))
487         (let ((t1 (cdr s∞)) (t2 (cdr t∞)))
488           (cond
489             ((not t1) t2)
490             ((not t2) t1)
491             (else (lambda () (appendfair∞ (t1) (t2))))))))))
492
493
494 #| Goal  $\times$  Space  $\rightarrow$  Space |#
495 (define (append-mapfair∞ g s∞)
496   (foldr
497     (lambda (s t∞)
498       (appendfair∞ (g s) t∞))
499     (let ((f (cdr s∞)))
500       (step (and f (lambda () (append-mapfair∞ g (f))))))
501     (car s∞)))
502
503
504 #| Maybe Nat  $\times$  Space  $\rightarrow$  [State] |#
505 (define (take∞ n s∞)
506   (let loop ((n n) (vs (car s∞)))
507     (cond
508       ((and n (zero? n)) '())
509       ((pair? vs)
510        (cons (car vs)
511              (loop (and n (sub1 n)) (cdr vs)))))
512     (else (let ((f (cdr s∞)))
513             (if f (take∞ n (f)) '()))))))))
514
515
516
517

```

Fig. 6. New and changed functions in BFS_{imp} that implements pure features

```

518 #| Space × (State × Space → Space) × (→ Space) → Space |#
519 (define (elim s∞ fk sk)
520   (let ((ss (car s∞)) (f (cdr s∞)))
521     (cond
522       ((pair? ss) (sk (car ss) (cons (cdr ss) f)))
523       (f (step (lambda () (elim (f) fk sk))))
524       (else (fk)))))
525
526
527 #| Goal × Goal × Goal → Goal |#
528 (define (ifte g1 g2 g3)
529   (lambda (s)
530     (elim (g1 s)
531           (lambda () (g3 s))
532           (lambda (s0 s∞)
533             (append-mapfair∞ g2
534               (appendfair∞ (unit s0) s∞))))))
535
536
537 #| Goal → Goal |#
538 (define (once g)
539   (lambda (s)
540     (elim (g s)
541           (lambda () (none))
542           (lambda (s0 s∞) (unit s0))))))
543
544

```

Fig. 7. New and changed functions in BFS_{imp} that implement impure features

Now we compare the pure subset of BFS_{imp} with BFS_{ser} . We focus on the pure subset because BFS_{ser} is designed for a pure relational programming system. We prove in Coq that these two search strategies are semantically equivalent, since the result of $(run\ n\ ?\ g)$ is the same either way. (See supplements for the formal proof.) To compare efficiency, we translate BFS_{ser} 's Haskell code into Racket (See supplements for the translated code). The translation is direct due to the similarity of the two relational programming systems. The translated code is longer than BFS_{imp} . And it runs slower in all benchmarks. Details about differences in efficiency are in section 7.

7 QUANTITATIVE EVALUATION

In this section, we compare the efficiency of the search strategies. A concise description is in Table 2. A hyphen means “running out of 500 MB memory”. The first two benchmarks are from TRS2. `reverso` is from Rozplokh and Boulytchev [8]. The next two benchmarks about generating quines are based on a similar test case in Byrd et al. [2]. We modify the relational interpreters because we don't have disequality constraints (e.g. `absento`). The sibling benchmarks differ in the `conde` clause order of their relational interpreters. The last two benchmarks are about synthesizing expressions that evaluate to `'(I love you)`. They are also based on a similar test case in Byrd et al. [2]. Again, we modify the relational interpreters for the same reason. And the sibling benchmarks differ in the `conde` clause order of their relational interpreters. The first one has elimination rules (i.e. application,

| benchmark | size | DFS _i | DFS _{bi} | DFS _f | BFS _{imp} | BFS _{ser} |
|-----------------------------|--------|------------------|-------------------|------------------|--------------------|--------------------|
| very-recursive ^o | 100000 | 166 | 103 | 412 | 451 | 1024 |
| | 200000 | 283 | 146 | 765 | 839 | 1875 |
| | 300000 | 429 | 346 | 2085 | 1809 | 4408 |
| append ^o | 100 | 17 | 18 | 17 | 17 | 65 |
| | 200 | 145 | 137 | 137 | 142 | 121 |
| | 300 | 388 | 384 | 387 | 429 | 371 |
| revers ^o | 10 | 3 | 4 | 3 | 18 | 36 |
| | 20 | 35 | 35 | 33 | 3070 | 3695 |
| | 30 | 329 | 333 | 315 | 75079 | 107531 |
| quine-1 | 1 | 13 | 14 | 10 | - | - |
| | 2 | 30 | 34 | 25 | - | - |
| | 3 | 41 | 48 | 33 | - | - |
| quine-2 | 1 | 22 | 21 | 12 | - | - |
| | 2 | 51 | 46 | 24 | - | - |
| | 3 | 72 | 76 | 32 | - | - |
| '(I love you)-1 | 999 | 78 | 70 | 59 | 254 | 605 |
| | 1998 | 152 | 154 | 109 | 315 | 635 |
| | 2997 | 430 | 440 | 266 | 317 | 643 |
| '(I love you)-2 | 999 | 631 | 173 | 61 | 253 | 605 |
| | 1998 | 1233 | 511 | 111 | 308 | 659 |
| | 2997 | 2145 | 682 | 269 | 307 | 642 |

Table 2. The results of a quantitative evaluation: running times of benchmarks in milliseconds

car, and cdr) at the end, while the other has them at the beginning. We conjecture that DFS_i would perform badly in the second case because elimination rules complicate the problem when synthesizing (i.e., our evaluation supports our conjecture.)

In general, variants of DFS usually performs better than BFS. The reason might be that BFS tends to remember more states at the same time. Among the three variants of DFS, which all have unfair conj, DFS_f is most resistant to clause permutation in quines and '(I love you)s, followed by DFS_{bi} then DFS_i. Thus, we consider DFS_{bi} and DFS_f competitive alternatives to DFS_i. Among the two implementations of BFS, BFS_{imp} constantly performs as well or better.

8 RELATED WORKS

In this section, we describe related works. Yang [10] points out that a disjunct complex would be 'fair' if it were a full and balanced tree. Seres et al. [9] describe a breadth-first search strategy. We present another implementation. Our implementation is semantically equivalent to theirs. But, ours is shorter and performs better in comparison with a straightforward translation of their Haskell code. Rozplochas and Boulytchev [8] address the non-commutativity of conjunction, while our work about disj fairness addresses the non-commutativity of disjunction.

9 CONCLUSION

We analyze the definitions of fair disj and fair conj, then propose a new definition of fair conj. Our definition of fair conj is orthogonal with completeness.

We devise two new search strategies (i.e., balanced interleaving DFS (DFS_{bi}) and fair DFS (DFS_f)) and devise a new implementation of BFS (BFS_{imp}). These strategies have different features in fairness: DFS_{bi} has an almost-fair disj and unfair conj. DFS_f has fair disj and unfair conj. BFS has both fair disj and fair conj. No search strategy in this paper combines unfair disj and fair conj. This is because we haven't seen a case where this kind of search strategies would be interesting.

Our quantitative evaluation shows that DFS_{bi} is a competitive alternative to DFS_i , the current miniKanren search strategy, and that BFS_{imp} is more practical than BFS_{ser} .

We prove formally that BFS_{imp} is semantically equivalent to BFS_{ser} . But, BFS_{imp} is shorter and performs better in comparison with a straightforward translation of their Haskell code.

Although there are very few benchmarks, this is preliminary work where we are making a point that certain levels of fairness come without cost in some cases, and that each of the search strategies: DFS_i , DFS_{bi} , DFS_f , and BFS, can co-exist inside one's head. Constructing a miniKanren with all levels of fairness is future work.

ACKNOWLEDGMENTS

REFERENCES

- [1] Benjamin Strahan Boskin, Weixi Ma, David Thrane Christiansen, and Daniel P. Friedman. 2018. A Surprisingly Competitive Conditional Operator: for miniKanrenizing the Inference Rules of Pie (*Scheme '18*). St Louis, MO, USA.
- [2] William E Byrd, Michael Ballantyne, Gregory Rosenblatt, and Matthew Might. 2017. A unified approach to solving seven programming problems (functional pearl). *Proceedings of the ACM on Programming Languages* 1, ICFP (2017).
- [3] Daniel P. Friedman, William E. Byrd, and Oleg Kiselyov. 2005. *The Reasoned Schemer*. The MIT Press.
- [4] Daniel P. Friedman, William E. Byrd, Oleg Kiselyov, and Jason Hemann. 2018. *The Reasoned Schemer, Second Edition*.
- [5] Jason Hemann, Daniel P. Friedman, William E. Byrd, and Matthew Might. 2016. A small embedding of logic programming with a simple complete search. In *Proceedings of the 12th Symposium on Dynamic Languages - DLS 2016*. ACM Press. <https://doi.org/10.1145/2989225.2989230>
- [6] Oleg Kiselyov, Chung-chieh Shan, Daniel P. Friedman, and Amr Sabry. 2005. Backtracking, interleaving, and terminating monad transformers:(functional pearl). *ACM SIGPLAN Notices* 40, 9 (2005), 192–203.
- [7] Dmitry Kosarev and Dmitry Boulytchev. 2018. Typed embedding of a relational language in OCaml. *arXiv preprint arXiv:1805.11006* (2018).
- [8] Dmitri Rozplochas and Dmitri Boulytchev. 2018. Improving Refutational Completeness of Relational Search via Divergence Test. In *Proceedings of the 20th International Symposium on Principles and Practice of Declarative Programming*. ACM, 18.
- [9] Silvija Seres, J Michael Spivey, and C. A. R. Hoare. 1999. Algebra of Logic Programming.. In *ICLP*. 184–199.
- [10] Edward Z. Yang. 2010. Adventures in Three Monads. *The Monad. Reader Issue* 15 (2010), 11.