

XSR 0.9 | Khitan Small Script

Type A: fixed order, original outlines

The default Type A cluster begins with two signs side by side. Signs are read left to right, then top to bottom. A final odd sign is centered. The glyphs below retain their original Noto size and shape; the stack grows by rows.

Single sign	一
2 signs	一丁
3 signs	一丁 千
4 signs	一丁 千一
5 signs	一丁 千一 丁
6 signs	一丁 千一 丁千
7 signs	一丁 千一 丁千 一
8 signs	一丁 千一 丁千 一丁

The last example occupies four intrinsic rows. No stack is squeezed into one em.

XSR 0.9 | Khitan Small Script

Type B and cluster boundaries

U+16FE4 after the first sign changes a cluster to Type B: its first sign is centered above the remaining paired rows. The filler itself has no outline.

Type B, 2 signs 𐰇

Type B, 3 signs 𐰇𐰆

Type B, 4 signs 𐰇𐰆𐰇

Type B, 7 signs 𐰇𐰆𐰇𐰆𐰇𐰆𐰇

SPACE versus ZERO WIDTH SPACE

The first pair uses a narrow XSR gap of 0.2 em. The second has no visible gap. Both are legal break opportunities between indivisible clusters.

U+0020 SPACE 𐰇 𐰇

U+200B ZWSP 𐰇𐰇

Iteration mark 𐰇𐰇

U+18B00 is rendered as its own sign; semantic repetition is not duplicated graphically.

XSR 0.9 | Khitan Small Script

Horizontal text and intrinsic line height

Each cluster is an upright atomic box aligned at the bottom of the text line. Only a line containing a tall cluster requires extra vertical extent.

Line one: ordinary Latin text and normal spacing.

Line two: ordinary Latin text and normal spacing.

一丁
千一
丁千
一丁

Line three: a four-row cluster 一丁 in a Latin sentence.

Line four: ordinary Latin text resumes.

Line five: ordinary Latin text resumes.

A two-cluster run in a sentence: before 一丁一丁 after. The source SPACE becomes the narrow Khitan separator, while surrounding Latin spaces remain ordinary spaces.

A zero-width boundary: before 一丁一丁 after.

The same internal stack can later be embedded in a vertical host flow.

XSR 0.9 | Khitan Small Script

Reference comparison with Noto native shaping

The upper row in each pair is XSR's unscaled base outlines in fixed Unicode slots. The lower row asks XeTeX to apply Noto's contextual rclt feature. Noto may use positional alternates and optical refinements; XSR does not.

Type A, three signs

XSR: 
Noto native: 

Type A, six signs

XSR: 
Noto native: 

Type B, four signs

XSR: 
Noto native: 

Repeated signs, eight positions

XSR: 
Noto native: 

Native Noto shaping is a reference only. XSR works without Khitan GSUB.

XSR 0.9 | Khitan Small Script

Noto vs Khitan Small Linear

These rows use the same XSR Unicode parser and fixed slots with two different selected-font outline files. Both retain their native glyph shape and 12pt scale.

Type A, two signs

Noto: 一𐰇 Linear: 一𐰇

Type A, five signs (odd final row)

Noto: 一𐰇
𐰇一
𐰇 Linear: 一𐰇
𐰇一
𐰇

Type A, eight signs (four rows)

Noto: 一𐰇
𐰇一
𐰇𐰇
一𐰇 Linear: 一𐰇
𐰇一
𐰇𐰇
一𐰇

Type B, four signs (centered first and last)

Noto: 一𐰇
𐰇 Linear: 一𐰇
𐰇

Iteration mark

Noto: 𐰇一
𐰇 Linear: 𐰇一
𐰇

Missing/unidentified sign U+18CFF

Linear: 一□ (Noto v1.000 has no outline for this codepoint.)

Khitan Small Linear is supplied externally and its TTF is not included in XSR.