

ANU Guide Star Laser Interface

Alex Dalton, Brian Ma, Chris Leow, Paul Apelt, Steve Lonergan, Wenjie Mu

ENGN4221 Systems Engineering Project



Australian
National
University



Project Summary

A **Guide Star Laser** (GSL) creates an artificial star in the atmosphere known as a **Laser Guide Star** (LGS), which enables the measurement of light distortion caused by atmospheric turbulence. **Adaptive Optics** (AO) systems use these measurements to correct for this distortion and improve imaging quality.

The ANU and Electric-Optic Systems (EOS) are currently designing two GSL systems for **Space Debris Tracking and Pushing**. The objective of this project was to develop the **concept design** for the system interface with the **1.8m telescope** at Mount Stromlo. This is the second phase of this student led project, with the first phase involving the development of a comprehensive requirements document.

ANU Aux Electronics

The ANU laser **auxiliary electronics** cabinet is placed directly under the laser enclosure due to **cable length constraints**.

The AEC requires at most **800W of cooling** at two different temperatures.


EOS Oscillators

The EOS Oscillators are sensitive to vibrations and have been relocated to an **external clean room**. This requires approx 35 m of **additional wiring** to connect the oscillators to the observation level.


Environmental Control

Two **30W heaters**, **insulation panels**, a **radiator** and a **fan** are used to keep the temperature in the laser enclosure between 10°C and 30°C.

A **HEPA filter** is installed to maintain ISO 7 standard air quality.




Heater and fan arrangement



1.8 m telescope building cross-section

[1] - Image courtesy of EOS

Vibration Analysis




Telescope vibration spectrum was tested with the dome moving. Further testing of GSL required.

Conclusion


Review and additional development of the **interface requirements** was undertaken by the team. **Conceptual designs** for the various **subsystems** were then developed. The designs and recommendations were provided to the client in a **Concept Design Report** and **Subsystem Design Reports**. The **next phase** of the project will involve the development of **detailed designs**. The team produced a **handover document** that introduces the new team to project and outlines the recommended next steps.

Laser Enclosure

A **frame** was designed to mount the GSL Laser Heads to the 1.8m telescope. The frame accommodates **two optical breadboards** and is constructed from DragonPlate **Carbon Fibre/Epoxy** components, steel inserts and various fasteners.



Mounting frame



FEA stress analysis


EOS Aux Electronics

The EOS **auxiliary cabinet** will be placed on the **entry level**, with cabling running to the laser enclosure on the observation deck. The cabinet contains **coolers**, **heaters** and **control electronics** for the laser head.

The EOS GSL is powered from a single General Power Outlet (GPO), connected via a **CAN bus**, and cooled by a **400W chiller**.

Cooling System

Both GSLs operate at **different temperatures**, requiring separate coolers to operate.



Acknowledgements

The team would like to thank our supervisor, Celine d'Orgeville, Gerard Kennedy, the team tutor, as well as James Webb, Mark Blundell, Jordan Davis and all others at ANU, AITC and EOS who made this project possible.