Bảng thông số sản phẩm

Thông số kỹ thuật





Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V, 9A, 220V AC 50/60Hz coil, screw clamp terminals

LC1D09M7

Main

Range of product	TeSys Deca
Product or component type	Contactor
Device short name	LC1D
contactor application	Motor control Resistive load
Utilisation category	AC-4 AC-3 AC-1 AC-3e
poles description	3P
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC
[le] rated operational current	9 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 25 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 9 A (at <60 °C) at <= 440 V AC AC-3e for power circuit
[Uc] control circuit voltage	220 V AC 50/60 Hz

Complementary

,	
Motor power kW	2.2 kW at 220230 V AC 50/60 Hz (AC-3)
	4 kW at 380400 V AC 50/60 Hz (AC-3)
	4 kW at 415440 V AC 50/60 Hz (AC-3)
	5.5 kW at 500 V AC 50/60 Hz (AC-3)
	5.5 kW at 660690 V AC 50/60 Hz (AC-3)
	2.2 kW at 400 V AC 50/60 Hz (AC-4)
	2.2 kW at 220230 V AC 50/60 Hz (AC-3e)
	4 kW at 380400 V AC 50/60 Hz (AC-3e)
	4 kW at 415440 V AC 50/60 Hz (AC-3e)
	5.5 kW at 500 V AC 50/60 Hz (AC-3e)
	5.5 kW at 660690 V AC 50/60 Hz (AC-3e)
Motor power hp	1 hp at 230/240 V AC 50/60 Hz for 1 phase motors
	2 hp at 200/208 V AC 50/60 Hz for 3 phases motors
	2 hp at 230/240 V AC 50/60 Hz for 3 phases motors
	5 hp at 460/480 V AC 50/60 Hz for 3 phases motors
	7.5 hp at 575/600 V AC 50/60 Hz for 3 phases motors
	0.33 hp at 115 V AC 50/60 Hz for 1 phase motors
Compatibility code	LC1D
Pole contact composition	3 NO
Protective cover	With
[Ith] conventional free air thermal	25 A (at 60 °C) for power circuit
current	10 A (at 60 °C) for signalling circuit
Irms rated making capacity	250 A at 440 V for power circuit conforming to IEC 60947
	140 A AC for signalling circuit conforming to IEC 60947-5-1
	250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated breaking capacity	250 A at 440 V for power circuit conforming to IEC 60947

22 thg 9, 2024 Life Is On Schneider

[Icw] rated short-time withstand current	105 A 40 °C - 10 s for power circuit 210 A 40 °C - 1 s for power circuit
	30 A 40 °C - 10 min for power circuit
	61 A 40 °C - 1 min for power circuit 100 A - 1 s for signalling circuit
	120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
	25 A gG at <= 690 V coordination type 1 for power circuit 20 A gG at <= 690 V coordination type 2 for power circuit
Average impedance	
Average impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit
Power dissipation per pole	1.56 W AC-1
	0.2 W AC-3 0.2 W AC-3e
[Ui] rated insulation voltage	
[OI] Tated insulation voltage	Power circuit: 690 V conforming to IEC 60947-4-1 Power circuit: 600 V CSA certified
	Power circuit: 600 V UL certified
	Signalling circuit: 690 V conforming to IEC 60947-1
	Signalling circuit: 600 V CSA certified
	Signalling circuit: 600 V UL certified
Overvoltage category	III
Pollution degree	3
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO
	13849-1
Mechanical durability	15 Mcycles
Electrical durability	0.6 Mcycles 25 A AC-1 at Ue <= 440 V
	2 Mcycles 9 A AC-3 at Ue <= 440 V 2 Mcycles 9 A AC-3e at Ue <= 440 V
<u> </u>	·
Control circuit type	AC at 50/60 Hz standard
Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz
	0.81.1 Uc (-4060 °C):operational AC 50 Hz
	0.851.1 Uc (-4060 °C):operational AC 60 Hz 11.1 Uc (6070 °C):operational AC 50/60 Hz
Inrush power in VA	70 VA 60 Hz cos phi 0.75 (at 20 °C)
·	70 VA 50 Hz cos phi 0.75 (at 20 °C)
Hold-in power consumption in VA	7.5 VA 60 Hz cos phi 0.3 (at 20 °C)
	7 VA 50 Hz cos phi 0.3 (at 20 °C)
Heat dissipation	23 W at 50/60 Hz
Operating time	1222 ms closing
	419 ms opening
Maximum operating rate	3600 cyc/h 60 °C
Maximum operating rate	3600 cyc/h at 60 °C

Connections - terminals	Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without		
	cable end		
	Power circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end		
	Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable		
	end Power circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with		
	cable end		
	Power circuit: screw clamp terminals 1 14 mm ² - cable stiffness: solid without cable end		
	Power circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without cable		
	end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without		
	cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without		
	cable end		
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end		
	Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with		
	cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without		
	cable end		
	Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: solid without cable end		
	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm		
	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2		
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2		
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2		
	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2		
Auxiliary contact composition	1 NO + 1 NC		
Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1		
Signalling circuit frequency	25400 Hz		
Minimum switching voltage	17 V for signalling circuit		
Minimum switching current	5 mA for signalling circuit		
Insulation resistance	> 10 MOhm for signalling circuit		
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact		
Mounting support	Plate Rail		
Environment			
Standards	CSA C22.2 No 14		
	EN 60947-4-1		
	EN 60947-5-1 IEC 60947-4-1		
	IEC 60947-4-1 IEC 60947-5-1		
	UL 60947-4-1		
	IEC 60335-1:Clause 30.2		
	IEC 60335-2-40:Annex JJ UL 60335-2-40:Annex JJ		
	CSA C22.2 No 60947-4-1		
product certifications	UL		
	CCC CSA		
	Marine		
	UKCA		
	EAC CB Scheme		
IP degree of protection	IP20 front face conforming to IEC 60529		
Protective treatment	TH conforming to IEC 60068-2-30		
Climatic withstand	conforming to IACS E10 exposure to damp heat		
	conforming to IEC 60947-1 Annex Q category D exposure to damp heat		

conforming to IEC 60947-1 Annex Q category D exposure to damp heat

Permissible ambient air temperature around the device	-4060 °C 6070 °C with derating				
Operating altitude	03000 m				
Fire resistance	850 °C conforming to IEC 60695-2-1				
Flame retardance	V1 conforming to UL 94				
Mechanical robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor open (10 Gn for 11 ms) Shocks contactor closed (15 Gn for 11 ms)				
Height	77 mm				
Width	45 mm				
Depth	86 mm				
Net weight	0.32 kg				

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	9.200 cm
Package 1 Length	11.500 cm
Package 1 Weight	350.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	7.282 kg
Unit Type of Package 3	P06
Number of Units in Package 3	320
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	123.500 kg

Contractual warranty

Warranty 18 months



Nhãn **Green PremiumTM** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO₂ thấp.

Hướng dẫn đánh giá tính bền vững của sản phẩm là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhãn sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

Tìm hiểu thêm về Green Premium >

Hướng dẫn đánh giá về sự bền vững của sản phẩm >







Bao bì bền vững Minh bạch RoHS/REACh

Hiệu suất tài nguyên



Sustainable Packaging

Hiệu suất sức khoể

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Ye

Pvc Free

Chứng nhận & Tiêu chuẩn

Reach Regulation

Eu Rohs Directive

Compliant

EU RoHS Declaration

China Rohs Regulation

China Rohs declaration

Pro-active China Rohs declaration (out of China Rohs legal scope)

Environmental Disclosure

Product Environmental Profile

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins


Circularity Profile

End of Life Information

LC1D09M7

Dimensions Drawings

Dimensions



- (1) Including LAD 4BB
- (2) Minimum electrical clearance


LC1		D09D18	D093D123	D099D129	
b	without add-on blocks	77	99	80	
b1	with LAD 4BB	94	107	95.5	
	with LA4 D●2	₁₁₀ (1)	123 ⁽¹⁾	_{111.5} (1)	
	with LA4 DF, DT	₁₁₉ (1)	132 ⁽¹⁾	_{120.5} (1)	
	with LA4 DW, DL	₁₂₆ (1)	139(1)	_{127.5} (1)	
С	without cover or add-on blocks	84	84	84	
	with cover, without add-on blocks	86	86	86	
с1	with LAD N or C (2 or 4 contacts)	117	117	117	
c2	with LA6 DK10, LAD 6K10	129	129	129	
с3	with LAD T, R, S	137	137	137	
	with LAD T, R, S and sealing cover	141	141	141	
(1)	Including LAD 4BB.				

Bảng thông số sản phẩm

LC1D09M7

Connections and Schema

Wiring



Bảng thông số sản phẩm

LC1D09M7

Offer Marketing Illustration

Product benefits / Features



Bảng thông số sản phẩm

LC1D09M7

Image of product / Alternate images

Alternative







