9001 Series

DIN41612 C Type Female



Material:

Housing: Thermoplastic Polyester Glass Filled UL94V-0.
Contacts: Copper Alloy.

Electrical Characteristics:

Current Rating: 2 A.
Dielectric Withstanding Voltage: AC 1000V.
Insulator Resistance: 1000MΩ min.
Contact Resistance: 20mΩ max.
Operating Temperature: -55°C ~ +125°C.

Features:

* Mates with Male 3Row
  9001-1196,1164 C Type.
  9001-1396,1364 R Type.





Dip Type



Press Fit Type







P.C. Board Layout

	Length	1	2	W1	W2
	X	4.0	2.5	13	17
	Y	4.6	6.3	13	17

Pitch	Position	Rows with Contacts	Contact Arrange
2.54mm	96	a b c	c b a 1 2 3 4
	64	a – c	c b a 1 2 3 4
	32	a – –	c b a 1 2 3 4
5.08mm	48	a b c	c b a 1 2 3 4
	32	a – c	c b a 1 2 3 4
	16	a – –	c b a 1 2 3 4

Ordering information

9001-	1	2	96	1	C	00	P	L1	A
Series	1: 2.54mm 2: 5.08mm	2: Female	Position	1: Dip Length 2: Dip Length W1: Dip Length W2: Dip Length	C: Selective Gold Plated	00: G/F	Blank: Dip P: Press Fit	Blank: W/O Lock L1: With Lock See Page CA03	A: Tray Package