

LOAD SECUREMENT POLICY

1. Load bars must be installed in a level position, behind the rearmost pallets, and securely locked into the rectangular slots on either side of the trailer wall. Pull on them to ensure they're positively locked in place.
2. If the load bars do not contact the rearmost pallet (If they are over 2 cm from the rearmost pallet), Place old pallets in the upright position between the rear most pallets and the load bar to brace the load. If you have more than one load bar, use 2, 3 or 4 load bars to brace the loads.
3. Use ratcheting logistics straps to brace and secure odd shaped objects such as drums, computer desks, furniture, etc. to prevent them from falling over.
4. Never dispose of or attempt to dispose of a leaking drum or container or any damaged product without the approval of dispatch. Do not offer a leaking container to anyone willing to take it.

I hereby declare that I have read and understand the above procedures regarding load securement policy and agree to comply with every requirement.

Drivers Name: _____

Signature: _____

Date: _____

DVIR MEMO

Both the Highway Traffic Act and the Federal Motor Carrier Safety Administration require that commercial drivers conduct pre-trip inspections on their equipment at the outset of each trip and once within each 24 hours while on the road. 9739190 CANADA INC. requires drivers follow all laws contained in the Highway Traffic Act and the Federal Motor Carrier Safety Administration with respect to pre-trip inspections. Every 9739190 CANADA INC. Employee, Driver or Owner-Operator is expected to follow the National Safety Code Standard 13 "**Vehicle Inspection Procedures**", with regards to conducting proper pre-trip inspections. There are no exceptions. Drivers running under 9739190 CANADA INC. are required to both understand and follow **Schedule 1 of The National Safety Code 13**, with regards to minor and major defects, as outlined below:

Minor Defects: As part of this policy each driver is expected, as per Schedule 1, to note minor and major defects found during pre-trip inspections, on their Daily Inspection Report. Minor defects must be noted and repaired at the earliest opportunity. **Note: the law states that minor defects must be repaired prior to the next dispatch.**

Major Defects: As part of this policy each driver is expected, as per Schedule 1, to note on their Daily Inspection Report, any equipment that may have major defects. Any equipment found with major defects must be put out of service until repairs have been completed and signed off on by a person qualified to do so. **Note: the law states no truck or trailer with a major defect found will be allowed to be operated until properly repaired.**

As part of this policy, drivers are required to use Schedule 1 as a guide while conducting their Pre-Trip, Post Trip and on Route Inspections. Drivers are required to note all defects found during pre-trip inspections on the Daily Inspection Report. It's also the driver's responsibility to ensure minor or major defects found on trucks or trailers returning to our facility or to any other location are reported to the Company, in order to expedite repairs prior to the next dispatch.

Drivers Name: _____

Signature: _____

Date: _____