

SECURITY AWARENESS PLAN

Seal Policy

Policy: In order to comply with security initiatives 9739190 CANADA INC. is instituting a seal policy to ensure the integrity of our trailers while crossing international borders. All seal numbers will be tracked internally as assigned to drivers. All seal numbers used must be reported to dispatch.

Procedure: All loaded trailers must be sealed with a high security seal issued by 9739190 CANADA INC. Drivers may not break seals except in the presence of the receiving customer or when requested by an enforcement official. The seal numbers will be recorded in an electronic database maintained by 9739190 CANADA INC. Upon completion of loading a trailer destined for the border, the driver will seal the trailer and record the seal number on the Bill of Lading in the presence of the shipper.

In the case of pre-loaded trailers, the driver will report the seal number via cell phone or two-way communication to dispatch. If the customer provides a seal for the loaded trailer the driver will use that seal as well as a high security seal and follow the same reporting requirements. If the load is sealed by customs (US or Canada) the original seal must remain intact and the seal number issued by Customs must also be recorded as above (on the Bill of lading and via phone to dispatch) If the seal is broken, lost or destroyed while in transit It must be reported immediately to 9739190 CANADA INC.

The load must be checked for integrity and security purposes. If any issues are noticed that would compromise the load or there has been any foreign product added to the trailer or any product missing, it must be reported immediately. 9739190 CANADA INC. will in turn notify the proper authorities. Upon arrival at the customer for delivery, the customer must verify and sign for the load being received with the seal intact. If the seal is missing, the driver must notify dispatch immediately.

Other information:

New Federal regulations on load security require drivers to inspect their cargo for Securement within 80 km or 50 miles from their initial starting point. However, if the load is sealed and the driver has been instructed not to open the trailer or break the seal as specified above, the driver is exempt from this requirement. A copy of this policy must be kept with the driver at all times and produced upon demand of an Enforcement officer.

If a seal is broken by Customs, MTO, DOT, Police or other enforcement personnel they must sign the Bill of Lading and replace the seal after completion of the inspection. This seal number must be recorded on the Bill of Lading and dispatch informed via phone of the change.

I _____, acknowledge that I have received Seal Training and I am aware that I have to strictly adhere to this policy.

Signature

Date