

CSE 12 – Basic Data Structures and Object-Oriented Design

Lecture 14

Greg Miranda, Fall 2020

Announcements

- Quiz 14 due Friday @ 9am
- Survey 5 due Friday @ 11:59pm
- PA4 due today @ 11:59pm
- PA5 released tomorrow → *closed PA*
- Degree Planning EC (due 11/13)

Topics

- Sorting Wrapup
- Questions on Lecture 14?



```
import java.util.Arrays;

public class Sort {
    static void selectionSort(int[] arr) {
        for(int i = 0; i < arr.length; i += 1) {
            int minIndex = i;
            for(int j = i; j < arr.length; j += 1) {
                if(arr[minIndex] > arr[j]) { minIndex = j; }
            }
            int temp = arr[i];
            arr[i] = arr[minIndex];
            arr[minIndex] = temp;
        }
    }
}
```

```
static void insertionSort(int[] arr) {
    for(int i = 0; i < arr.length; i += 1) {
        for(int j = i; j > 0; j -= 1) {
            if(arr[j] < arr[j-1]) {
                int temp = arr[j-1];
                arr[j-1] = arr[j];
                arr[j] = temp;
            }
            else { break; } // new! exit inner loop early
        }
    }
}
```

```
import java.util.Arrays;
public class SortFaster {

    static int[] combine(int[] p1, int[] p2) {...}

    static int[] mergeSort(int[] arr) {
        int len = arr.length
        if(len <= 1) { return arr; }
        else {
            int[] p1 = Arrays.copyOfRange(arr, 0, len / 2);
            int[] p2= Arrays.copyOfRange(arr, len / 2, len);
            int[] sortedPart1 = mergeSort(p1);
            int[] sortedPart2 = mergeSort(p2);
            int[] sorted = combine(sortedPart1, sortedPart2);
            return sorted;
        }
    }
}
```

```
static int partition(String[] array, int l, int h) {...}

static void qsort(String[] array, int low, int high) {
    if(high - low <= 1) { return; }
    int splitAt = partition(array, low, high);
    qsort(array, low, splitAt);
    qsort(array, splitAt + 1, high);
}

public static void sort(String[] array) {
    qsort(array, 0, array.length);
}

}
```

	Insertion	Selection	Merge	Quick
Best case time	Sorted Array $\Theta(n)$	$\Theta(n^2)$	$\Theta(n \times \log_2(n))$	$\Theta(n \times \log_2(n))$
Worst case time	Reverse-sorted Array $\Theta(n^2)$	$\Theta(n^2)$	$\Theta(n \times \log_2(n))$	$\Theta(n^2)$ * avg $\Theta(n \times \log(n))$
Key operations	swap(a, j, j-1) (until in the right place)	swap(a, i, indexOfMin) (after finding minimum value)	l = copy(a, 0, len/2) r = copy(a, len/2, len) ls = sort(l) rs = sort(r) merge(ls, rs)	p = partition(a, l, h) sort(a, l, p) sort(a, p + 1, h)

Questions on Lecture 14?