

# CSE 12 – Basic Data Structures and Object-Oriented Design

## Lecture 14

Greg Miranda, Fall 2020

# Announcements

- Quiz 13 due Wednesday @ 9am
- Survey 5 due Friday @ 11:59pm
- PA4 due today @ 11:59pm
- PA5 released tomorrow
- Degree Planning EC (due 11/13)

# Topics

- Sorting Wrapup
- Questions on Lecture 14?

```
import java.util.Arrays;

public class Sort {
    static void selectionSort(int[] arr) {
        for(int i = 0; i < arr.length; i += 1) {
            int minIndex = i;
            for(int j = i; j < arr.length; j += 1) {
                if(arr[minIndex] > arr[j]) { minIndex = j; }
            }
            int temp = arr[i];
            arr[i] = arr[minIndex];
            arr[minIndex] = temp;
        }
    }
}
```

```
static void insertionSort(int[] arr) {
    for(int i = 0; i < arr.length; i += 1) {
        for(int j = i; j > 0; j -= 1) {
            if(arr[j] < arr[j-1]) {
                int temp = arr[j-1];
                arr[j-1] = arr[j];
                arr[j] = temp;
            }
            else { break; } // new! exit inner loop early
        }
    }
}
```

```
import java.util.Arrays;

public class SortFaster {

    static int[] combine(int[] p1, int[] p2) {...}

    static int[] mergeSort(int[] arr) {
        int len = arr.length
        if(len <= 1) { return arr; }
        else {
            int[] p1 = Arrays.copyOfRange(arr, 0, len / 2);
            int[] p2= Arrays.copyOfRange(arr, len / 2, len);
            int[] sortedPart1 = mergeSort(p1);
            int[] sortedPart2 = mergeSort(p2);
            int[] sorted = combine(sortedPart1, sortedPart2);
            return sorted;
        }
    }
}
```

```
static int partition(String[] array, int l, int h) {...}

static void qsort(String[] array, int low, int high) {
    if(high - low <= 1) { return; }
    int splitAt = partition(array, low, high);
    qsort(array, low, splitAt);
    qsort(array, splitAt + 1, high);
}

public static void sort(String[] array) {
    qsort(array, 0, array.length);
}

}
```

|                 | Insertion                                     | Selection                                               | Merge                                                                                             | Quick                                                        |
|-----------------|-----------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| Best case time  | Sorted Array<br>$\Theta(n)$                   | $\Theta(n^2)$                                           | $\Theta(n \times \log_2(n))$                                                                      | $\Theta(n \times \log_2(n))$                                 |
| Worst case time | Reverse-sorted Array<br>$\Theta(n^2)$         | $\Theta(n^2)$                                           | $\Theta(n \times \log_2(n))$                                                                      | $\Theta(n^2)$<br>* avg<br>$\Theta(n \times \log(n))$         |
| Key operations  | swap(a, j, j-1)<br>(until in the right place) | swap(a, i, indexOfMin)<br>(after finding minimum value) | l = copy(a, 0, len/2)<br>r = copy(a, len/2, len)<br>ls = sort(l)<br>rs = sort(r)<br>merge(ls, rs) | p = partition(a, l, h)<br>sort(a, l, p)<br>sort(a, p + 1, h) |

Questions on Lecture 14?