

Method	Syntax	Description
read	<code>read(size=-1)</code>	Reads and returns up to <code>size</code> characters/bytes. Reads until EOF if negative or omitted.
readline	<code>readline(size=-1)</code>	Reads and returns a single line from the file.
readlines	<code>readlines(hint=-1)</code>	Reads and returns a list containing all the lines of the file.
write	<code>write(string_or_bytes)</code>	Writes text or bytes to the stream. Returns the number of characters written.
writelines	<code>writelines(lines)</code>	Writes an iterable (like a list) of lines to the stream. Does not add newlines automatically.
flush	<code>flush()</code>	Flushes the internal write buffers, forcing pending data to be written to disk.
tell	<code>tell()</code>	Returns the current cursor position in the file as an integer (byte offset).
seek	<code>seek(offset, whence=0)</code>	Moves the cursor to a specific byte <code>offset</code> . <code>whence</code> : 0=start, 1=current, 2=end.
truncate	<code>truncate(size=None)</code>	Resizes the file to <code>size</code> bytes. Truncates at the current position if <code>size</code> is omitted.

readable	<code>readable()</code>	Returns True if the file stream was opened in a mode that allows reading.
writable	<code>writable()</code>	Returns True if the file stream was opened in a mode that allows writing.
seekable	<code>seekable()</code>	Returns True if the file stream supports random access (<code>seek</code> and <code>tell</code>).
isatty	<code>isatty()</code>	Returns True if the stream is connected to a terminal device (e.g., standard input/output).
fileno	<code>fileno()</code>	Returns the underlying operating system file descriptor (integer).
close	<code>close()</code>	Flushes and closes the file stream. Any further operations will raise a ValueError .