Rethinking Machine Ethics in the Age of Ubiquitous Technology

Jeffrey White
KAIST, South Korea

Rick Searle
IEET, USA

A volume in the Advances in Human and Social Aspects of Technology (AHSAT) Book Series

Information Science REFERENCE
An Imprint of IGI Global

Managing Director: Lindsay Johnston
Managing Editor: Austin DeMarco
Director of Intellectual Property & Contracts: Jan Travers
Acquisitions Editor: Kayla Wolfe
Development Editor: Caitlyn Martin
Cover Design: Jason Mull

Published in the United States of America by
Information Science Reference (an imprint of IGI Global)
701 E. Chocolate Avenue
Hershey PA, USA 17033
Tel: 717-533-8845
Fax: 717-533-8661
E-mail: cust@igi-global.com
Web site: http://www.igi-global.com

Copyright © 2015 by IGI Global. All rights reserved. No part of this publication may be reproduced, stored or distributed in any form or by any means, electronic or mechanical, including photocopying, without written permission from the publisher. Product or company names used in this set are for identification purposes only. Inclusion of the names of the products or companies does not indicate a claim of ownership by IGI Global of the trademark or registered trademark.

Library of Congress Cataloging-in-Publication Data

Rethinking machine ethics in the age of ubiquitous technology / Jeffrey White and Rick Searle, editors.
pages cm
Includes bibliographical references and index.
ISBN 978-1-4666-8592-5 (hardcover) -- ISBN 978-1-4666-8593-2 (ebook) 1. Technology--Moral and ethical aspects. 2. Automation--Social aspects. I. White, Jeffrey, 1969- II. Searle, Rick, 1972-
BJ59.R48 2015
174'.96--dc23

2015019973

This book is published in the IGI Global book series Advances in Human and Social Aspects of Technology (AHSAT) (ISSN: 2328-1316; eISSN: 2328-1324)

British Cataloguing in Publication Data
A Cataloguing in Publication record for this book is available from the British Library.

All work contributed to this book is new, previously-unpublished material. The views expressed in this book are those of the authors, but not necessarily of the publisher.

For electronic access to this publication, please contact: eresources@igi-global.com.

Chapter 5
Semantic Analysis of Bloggers Experiences as a Knowledge Source of Average Human Morality

Rafal Rzepka
Hokkaido University, Japan

Kenji Araki
Hokkaido University, Japan

ABSTRACT

This chapter introduces an approach and methods for creating a system that refers to human experiences and thoughts about these experiences in order to ethically evaluate other parties', and in a long run, its own actions. It is shown how applying text mining techniques can enrich machine's knowledge about the real world and how this knowledge could be helpful in the difficult realm of moral relativity. Possibilities of simulating empathy and applying proposed methods to various approaches are introduced together with discussion on the possibility of applying growing knowledge base to artificial agents for particular purposes, from simple housework robots to moral advisors, which could refer to millions of different experiences had by people in various cultures. The experimental results show efficiency improvements when compared to previous research and also discuss the problems with fair evaluation of moral and immoral acts.

INTRODUCTION

In this chapter we describe the latest findings from experiments performed with our system. The system is grounded in an assumption, that the majority of people express ethically correct opinions about behavior of others. Research proceeding from this assumption was introduced during the first AAAI symposium on Machine Ethics (Rzepka, & Araki, 2005). On this course, we have created a shallow knowledge acquisition module for an Artificial Moral Agent (AMA) that mimics our ethical decisions

DOI: 10.4018/978-1-4666-8592-5.ch005

Copyright © 2015, IGI Global. Copying or distributing in print or electronic forms without written permission of IGI Global is prohibited.

by borrowing knowledge from Internet users. The agent utilizes opinion mining and sentiment analysis techniques to decide what is moral and what is not by adopting a moral position supported by more than 2/3 of retrieved sentences. The agent takes no position where the survey result is not above this threshold. Ignoring cases in which distinct polarities are absent allows the system to create a safety valve, leaving moral judgment over morally ambiguous situations to a human user. These ambiguous cases are not forgotten, however, as the system keeps these ambiguous sentences in the knowledge base for further contextual analysis. The system utilizes only a very simple set of shallow searching techniques and the results have been impressive. That said, as we show in this chapter, more reliable Natural Language Processing tools and techniques alongside human-coded moral lexicons working together to increase integration of available information, should be expected to improve results of future trials. At the core of our system are lexicons, sets of selected keywords, based on different philosophical ideas as Bentham's Felicific Calculus (Bentham, 1789) for estimating average emotional outcomes of acts, and Kohlberg's stages of moral development for retrieving possible social consequences (Rzepka & Araki, 2012).

Internet as Knowledge Source about Human Behaviors

Our methods should be attractive to researchers from humanities, especially sociologists, cognitive scientists and psychologists who study bloggers' behavior, or who study for example a role of gossip and other forms of criticism and its role in moral development. Until recently, the WWW has been treated as a massive garbage can full of sex and violence which is not useful for intelligent machines. With this chapter we want to attract the Machine Ethics (ME) community's attention to the fact that computers with constantly improving NLP tools and minimal human input (only 258 keywords divided into two categories on the proposed method) are capable of:

1. Filtering meaningless noise;
2. Reading stories of people whose majority, surprisingly for many, seems to represent healthy common sense;
3. Reusing the discovered knowledge in existing or newly created moral solutions.

Packed with descriptions of unreal worlds and games where killing is fun, the WWW is "knowledge soup" in which our machines can slowly learn how to distinguish fantasy from more realistic stories, avoiding logical yet unreasonable conclusions such as "people can fly on broomsticks because Harry Potter can". This capacity, to distinguish useful from non-useful information, is made more difficult by the fact that, when bloggers create different worlds and write of knights and princesses and evil wizards, they share their human emotions, describe punishments for evil deeds and emphatically react to happy and unhappy moments. Rather than explude all of this information as noise, we see this information as useful knowledge about what people care about, as simulations of reality suggesting what one would do if one's object of care faced danger. This is the core idea of our approach.

Universality of the Proposed Method

To recreate our system in other languages one would need a set of positive and negative effects (lexicon), a morphological parser (if the character of a given language requires it) and vast text resources describing human experiences (as big as possible). We have tested our approach with Japanese language and a

relatively small (when compared to the data accessible through commercial search engines) set of blogs (approximately 5 billion words). Previously, using shallow Natural Language Processing, we tested 68 acts, and the system agreed with human subjects in 77.8% of moral judgments. Currently we experiment with deeper analysis to improve the algorithm's capabilities for dealing with actors, patients and with negations, conditionals, etc. We do this in order to further minimize incorrect interpretations of acquired statements. In this chapter we review these latest results, suggesting that the quality of retrievals can be preserved even with smaller sets of examples if the text-mining process is more thorough. The structure of this chapter is as follows. First, after describing our hypothesis, we introduce our method and compare it with different approaches taken in creating moral machines. Then we present our system and experiments. After analysis of the results and errors, we finish the chapter with discussion about possible applications to devices for everyday usage.

Theoretical Basis of the Approach

Experience Driven Morality Acquisition

Our approach is strongly influenced by the social intuitionism of Haidt (2012) which suggests that human beings are born with a set of unconscious affective heuristics and that our ethical theories appear to us *after* and by way of these mechanisms. Hence our assumption is as follows: if we create a program capable of reverse engineering our decisions and their consequences by analyzing as big a set of cases as possible, then theoretically an ethical logic could be developed without a need to understand the mechanisms of its production. Assuming that a child equipped with build-in functions and observational powers over a limited number of cases is able to reason about what is wrong or right, we can hypothesize that a machine with similar information may perform similarly.

We are interested in inborn mechanisms and the process of acquiring moral rules, for example as described by Kohlberg (1981), but concentrate on the knowledge needed for ethical reasoning rather than modeling the production of these reasons, themselves. Therefore we try not to directly depend on specific philosophical theories, but rather seek to provide a method against which predictions due these theories can be measured. Utilizing the WWW in this way, being as it is a vast knowledge database of human experiences, could also help other researchers and engineers to enhance their systems. Our method takes advantage of the fact that, for the time being, the only constantly growing data that is relatively easy to process is textual. In the future, as automatic image and video processing evolves, even bigger data sets of human experiences should become available and help to enrich the learning process. It must be underlined that basically our system is not (yet) meant to learn by machine learning techniques *per se* but by using and manipulating lexical "big data" in order to find similar situations, interpret their outcomes and reconfirm its findings. We want to suggest that such system could, at least in theory, become more ethical in its judgments than humans flawed by individual biases (Tenbrunsel & Messick, 2004), because we are not able to remember and instantly investigate millions of experiences, especially written in different languages by people from various cultures.

Empathy as One of the Key Functions for Moral Development

Although we have plenty of theories about possible mechanisms underlying our ethical decisions, we are still not sure how our brains decide what is good or bad for us. Most probably, evolution equipped us

with emotional reactions that were originally meant for survival, and then to flourish as societies (Hess & Thibault, 2009). One still not fully understood but important pro-social phenomena is *empathy*. Currently, scientists perform empirical experiments in order to understand how empathy makes us happy or unhappy and how it helps us to coexist and how it influences our ethical behavior. The development of empathic skills is seen as one of the most important mechanisms in our moral development. Experiments show, for example, that when a subject observes somebody being pierced, the subject's brain reacts as if the subject himself was pierced, that people feel disgust when they see others smell an object with bad odor, and that they have a sensation of being touched when they see others being scratched (c.f. Thagard, 2007). Some neuroscientists suggest that the neural basis of such behavior involves *mirror neurons* (Preston & de Waal, 2002; Gallese & Goldman, 1998), brain cells in frontal area F5 that respond both when a macaque monkey makes active movements and when it observes the experimenter making meaningful movements. Further research shows that the human's premotor cortex and the inferior parietal cortex are also active when such simulative empathy occurs (Pellegrino et al., 1992). Scanning animal brains revealed the same activities in cases of, for example, eating a banana and observing other animal eating a banana. However, this does not occur if we only pretend to eat, or to use a fake food (Brooks, 2011). Whilst the hypothesis is not regarded as certain (Hickok, 2009), the concept itself offers clues for simulating empathic behavior by referring to human emotional reactions shared in the Web.

Possibility of a Universal Artificial Empathy

A "universal artificial empathy" is our ultimate goal. A system with such capability could reason about any given situation and recognize if such situation has moral connotations. Then, after gaining all available additional contextual data, it could estimate its ethical rightness or wrongness and offer this judgment as advice for action. Eventually, automatically translating and combining experiences written by people from different cultures could achieve universality of the judgments. This could help confirming the assumption that we all are born with the same emotional mechanisms, or not. Interculturally valid rules of a thumb approach could also become a way to help a machine avoid ethical fopahs. After all, what is "uncommon" in a modern civilized world may remain a norm in many corners of the globe. That said, we limit our research to Internet bloggers, relying on the global, public nature of the blogosphere to buffer extremes that may not be recognized as praiseworthy worldwide. At the same time, we agree with Pinker (2011) that violence has been decreasing globally and further project that, as access to the WWW expands, criticisms of inhuman customs will spread among young people in more and more rural areas of the planet.

Discovering Reciprocity Online

It is often said that morality is build on two pillars. One of them is empathy (compassion), the other one is reciprocity (fairness). Teaching computers what is fair and what kinds of rules make our societies stable is a difficult task. In order to simplify this task around what is important, our system focuses on emotional as well as social cues to moral consequences. Attention to fairness is observed also in other animals (Brosnan and De Waal, 2003), and is confirmed in human emotions, as well, so until recently we concentrated mostly on emotional reactions. Although our system does not yet deal with "ought to do",

"must do" or "should do" sentences while analyzing effects of actions, the proposed version broadens its search by seeking parallels with moral associations observed in societies of primates. To achieve this, we added keywords for praise and punishment, awards and penalties. A search for these terms results in a database of term-use associations, data that may usefully inform:

1. *Utilitarian approaches* utilizing so called "moral arithmetic";
2. *Egoist approaches* concentrating on knowing needs or desires and
3. *Care ethics approaches* dealing with relationships, vulnerability, and already discussed empathy.

On the other hand, gathering social effects may also help building knowledge bases for *deontological duty-based* and *virtue ethics approaches* which use reasoning and exemplars to establish what *ought to* be done.

Knowledge about harm and appreciation that follow an act may be helpful for example in understanding the common sense approach of Ross (Ross, 1930). In his view, *prima facie* duties based on commonsensical intuition prioritize non-injury, fidelity, reparation, gratitude, beneficence, justice and self-improvement. On this view, our laws are built from a similar basis, and thus they also should be a useful resource for machines reverse-engineering morality as do ours. We have already experimented with calculating common court verdicts for similar cases (Rzepka et al, 2008) and believe that when language understanding techniques advance sufficiently, adding written laws and rules to the search scope of our system should increase its judgment efficiency.

This invites a note about the limited nature of the lexicon employed in these experiments. The lexicon of social consequences was originally created according to Kohlberg's stages of moral development, but further research constantly provides us with new lexicon entries. The lexicons should be more effective when equally balanced, therefore numbers of keywords and their frequencies in a corpus should be similar. Because the balancing process takes time and limits the number of keywords, we set the same number of categories and merge lexicons of emotional and social consequences to ensure wider coverage. Both of lexicons are described in more detail later in the chapter.

COMPARISON WITH RELATED WORK

The possibility of actually *building* an empathic machine has been discussed (c.f. Picard and Klein, 2002). Studies vary from purely theoretical (Dumouchel & Damiano, 2011) to experimental involving embodied robots (Asada et al., 2012) and systems that learn inductively from ethicists (Anderson and Anderson, 2014b). A wide range of research is done on Machine Ethics, however the field is still young and attempts to build a system able to deal with a wide range of situations are very rare. GenEth, the inductively learning system mentioned above, is theoretically able to use specialists' decisions to learn how to judge novel inputs. However, the teaching (supervising) process would be very laborious and costly. Moreover, the indefinite number of contextual conditions causes problems not only for creators but also for the learning process itself. We are interested in the Andersons' utilitarian approach because it also aims at being general (universal) and could be useful for testing the moral knowledge base we are building. GenEth utilizes a case-based approach, and our system also belongs to this category.

Our System and Other Case-Based Approaches

Anderson & Anderson (2014b) describe our method as the extreme casuistry. It is true that our system can be treated as a case-based reasoner that can easily find many cases where e.g. *lying* is a better choice than saying the painful truth. However, we assume that this is what people do every day, and in fact being perfectly truthful is a very difficult task for human beings. Moore (1903, p.57) wrote in *Principia Ethica*: "The defects of casuistry are not defects of principle; no objection can be taken to its aim and object. It has failed only because it is far too difficult a subject to be treated adequately in our present state of knowledge". To this, he also adds: "Casuistry is the goal of ethical investigation. It cannot be safely attempted at the beginning of our studies, but only at the end". We interpret this *goal* as a hypothetical moment in the future when our enhanced brains (machine-aided or machines themselves) are able to analyze all possible past happenings and their consequences available to processing, and *then* decide what is good and bad. This is the most distinct difference between Artificial General Intelligence based approaches, such as ours, and other approaches. Although the association with technological singularity may be strong, we believe that such an approach can one day be used for extending also human knowledge and improving human moral decision skills.

The case-based approaches are, in our opinion, easier to implement on machines, and before GenEth (Anderson & Anderson, 2014b) there have been several attempts to create a program that uses annotated cases to analyze new ones. For instance, SIROCCO (McLaren, 2003) applies methods from legal case-based reasoning to the field of ethics, and deals with professional engineering ethic cases in order to prove that "extensionally defined principles, as well as cited past cases, can help in predicting the principles and cases that might be relevant in the analysis of new cases". SCIROCCO operates on a closed set of data, and employs specialists' explanations that allow the program to account for a particular novel case. Explanation is not possible in the simple recurrent network used by Guarini (2006) who trained his system using sentences about "killing" and "allowing to die" as associated with *acceptable* or *unacceptable*. For example "Jill kills Jack to defend the innocent" or "Jill kills Jack; extreme suffering is relieved" are marked as *acceptable* and "Jack kills Jill out of revenge" and "Jack allows Jill to die; many innocents die" are *unacceptable*. When "Jill allows Jack to die in self-defense and to defend the innocent; extreme suffering is relieved, the lives of many innocents are saved, and freedom from an imposed burden results" is input, the system, after the learning process, is able to mark the output as *acceptable*. And *unacceptable* is the output for "Jack allows Jill to die out of revenge, to make money, and to eliminate the competition; many innocents suffer, and many innocents die". As authors of both systems underline, "what we want isn't just the ability to classify cases, receive arguments, and make arguments, but also the ability to come up with creative suggestions or compromises" (Guarini, 2006). We hope that by extending the range of retrievals to possible solutions proposed by people in the open dataset that is the WWW, our system may be able to extract such suggestions automatically. We also agree with Guarini that both consequences and motives are crucial for moral judgment, therefore we are now working also with a lexicon of instincts (Rzepka and Araki, 2013a) based on McDougall (1923).

Comparison with Other Approaches

Numerous theoretical works were introduced broadly in (Allen et al., 2008; Wallach & Allen, 2009, Anderson & Anderson, 2006). Some interesting implementation ideas were introduced by Sun (2013) and White (2010), but there are only several attempts to actually program and test the concepts. Except

above mentioned examples of (Guarini, 2006; McLaren, 2006; Anderson & Anderson & Anderson, 2014), there are applications of deontic logic (Bringsjord et al., 2006), nonmonotonic logic (Powers, 2006), prospective logic (Pereira & Saptawijaya, 2007) and calculating expected utilities of possible actions by looking at the goal-states (Pontier & Hoorn, 2012). However, these attempts are limited to specific structured environments, requiring that a set of "correct" answers be prepared beforehand. Our goal is to deliver solutions to moral problems without depending on any particular ethicist or framework. That said, present work does employ utility calculation as a means for retrieving effects of a given action (how a patient can feel, what consequences are expected). And, we are working on employing Bentham's Felicific Calculus (Bentham, 1789) to weight factors by *intensity* (by recognizing adverbs), *duration* (by using calculations based on time descriptions) or *extent* (by recognizing how many people are involved). This weighting scheme is not fully implemented, yet, so we do not describe them here (c.f. Rzepka & Araki, 2013b).

Our method is not yet able to solve complicated moral dilemmas. It aims at everyday life situations available to current or near future devices with natural language processing capabilities, which we describe at the end of this chapter. For the time being, it is easier for a machine to deal with many examples than with abstract moral definitions of "good" or the semantically wide rules of Kant or Asimov. Our approach is to avoid sophisticated algorithms for now, and concentrate on automatically collecting and analyzing descriptions of human behaviors with the help of NLP and handcrafted lexicons. The originality of our approach comes mainly not from the method, but rather from the data we utilize, collect and process. Human beings are born with empathy mechanisms, we instinctively feel urges to punish free riders, and we tend to avoid behaviors that would not be pleasant to ourselves. If we still do not fully understand mechanisms behind moral judgments, we can try to make hypotheses and test them with various algorithms. For such simulations, we need the most realistic data possible. And, in return, we believe that our fully automatic approach based on opinion mining and knowledge acquisition can provide insights into human decision-making, as well.

In our case, these are not machine decisions, they are still (average) human decisions. The motto for our algorithms is "always try to make your user happy and never violate common sense". The Internet is a great resource on both happiness and common sense. And utilizing this "Wisdom of Crowds" in informing moral decision-making databases is - to the best knowledge of the authors – novel.

PROPOSED METHOD

As stated in the *Introduction*, we use Natural Language Processing techniques to retrieve and analyze unrestricted, mostly colloquial text. In opposition to most Machine Ethics research, our interest in the field came from the problems we encountered while developing software for more or less practical, everyday use. We had never dealt with devices with military purposes, because their development is prohibited in Japan. (Ed.: In contrast to the West, see Gaillot and especially Searle, this volume.) Usually, we reprogram toy robots, vacuum cleaning robots or create dialog systems for elderly care or companion robots. The moral dilemmas that our systems face are not about killing. For example, when we experimented with a dialog system (Rzepka et al, 2005) that uses common sense knowledge and automatic pun generation capability, we faced a problem of timing. Joking is a very sophisticated act not only because of the contents but also because of the contextual dependencies, i.e. situations when one *should* or *should not* joke. There are harming puns (e.g. politically incorrect ones) and conversational

topics where even black humor is out of place (e.g. when an interlocutor's close relative dies). Due to the unlimited scenarios hosting unrestricted conversation, we were forced to seek solutions outside of existing knowledge bases and topologies such as WordNet (Miller, 1995) which does not deal with such knowledge, or ConceptNet (Liu & Singh, 2004), which has insufficient entries to cover most topics. Especially, Japanese language that we are working with is limiting. Therefore, we began using classic opinion mining and knowledge acquisition techniques utilizing commercial search engines to automatically extract required knowledge from the WWW. Unfortunately, although coverage and speed are very good, commercial search engines limit daily use. This forced us to crawl through a part of the Japanese blogosphere, and concentrate on precision rather than scope.

When it comes to colloquial language, Natural Language Processing (NLP) tools are still far from perfect, and morphological and dependency parsers cause constant problems because of omitted subjects, slang words, emoticons, etc. Thus we try to enhance existing tools with the data itself. When a program has easy access to millions of examples, the parsing errors can be partially overcome by assuring correctness of retrieved knowledge by additional analysis of the extracted sentences and neighboring phrases. For example "stealing one's heart" is not recognized as *unethical* triggered by the "stealing" keyword, because using grammatical patterns of causes and effects allows the system to discover that it is an idiomatic expression. And, depending on context, it should not be counted as a negative act, at all.

This deep, multidimensional and context sensitive search of human experiences is the basis for our world knowledge-retrieving module and is not limited to the moral knowledge. Many philosophers, including (Dennett, 1997), suggest that interactions with the *real* world are needed to achieve any *truly* intelligent agent. Although we agree that direct interaction-based experiences are crucial for rich and natural knowledge acquisition, we argue that experiences can be borrowed and shared. Currently, this is necessary, as approximating human experience within a fully robotic Ai us currently impossible. Having said so, current progress in deep learning and systems that automatically describe images and videos using natural language represent promising new sources of knowledge. Our approach pursues the promise that a program can find ethical answers, in the way that IBM's Watson does, becoming more accurate than the best humans in answering questions on a TV quiz (Rzepka, 2014a).

In following subsections, we introduce the key modules of our systems and the results of the latest trials with more thorough sentence chunking using a semantic tagger in order to disambiguate erroneous judgments from previous experiments.

Module for Retrieving Consequences of Acts

The details of the basic algorithm for acquiring human experiences and its performance with different lexicons are presented in our previous work (Rzepka & Araki, 2012). Here we give a simplified explanation of the system and its current improvements.

- **Input and queries generation.** Basically, our program accepts any phrase in Japanese language but because currently it uses the whole input as a query without analyzing it, long sentences do not match any useful data. This is also due to the still small corpus we utilize - a 5.5 billion word corpus of Japanese blogs (Ptaszynski et al, 2012), which is currently being extended to cover more blogs than the 2006 snapshot of the Ameba blog service that we have used so far. For the first trials, we input phrases based on examples from applied ethics textbooks (e.g. "stealing money", "having an abortion", etc.) mixed with a few common acts (e.g. "driving a car"). The basic list of

Table 1. List of 68 input phrases from the previous experiments

accepting a bribe	helping a friend	making one drink alcohol
avoiding war	hiding a crime	making a minor drink alcohol
becoming an egoist	hiring a foreigner	buying a prostitute
being deceived	hurting somebody	performing mercy killing
being fired	ignoring a crime	preventing conception
being tricked	kidnapping a kid	prostituting oneself
being unfaithful	killing a bacteria	revenging oneself
brand new car being stolen	killing a cow	stealing a bicycle
causing war	killing a criminal	stealing a brand new car
choose anesthesia	killing a dog	stealing a car
deceiving a friend	killing a dolphin	stealing a jalopy
deceiving somebody	killing a germ	stealing a letter
drinking alcohol	killing somebody	stealing an apple
driving a car	killing a pig	stealing cash
driving after drinking	killing a president	stealing money
eating a cow	killing a virus	stealing something
eating a hamburger	killing Hitler	stealing a present
eating a pig	killing an animal	stopping war
fire somebody	killing a child	taking one's girlfriend
going to love hotel	killing mother	taking one's money
having a quarrel with a friend	killing one	taking one's woman
having an abortion	killing ten	throwing away bread
having sex	killing many	

inputs is shown in Table 1, and they are almost identical to the set used in previous experiments (Rzepka & Araki, 2012 - three examples were omitted due to the incorrect Japanese language usage). As the first step, the system divides an input using the morphological parser MeCab (Kudo, 2005) into a triplet consisting of a noun, a modifying particle, and a verb.

- **Storing example sentences in the knowledge base.** In the next step a directory tree is built. The verb becomes the top directory as a core of an act; a particle subdirectory goes inside and a noun subdirectory under it. So, for example, in a *Kill* directory there are subdirectories for object indicating particle *wo* and tool indicating particle *de*. The first could contain nouns as *man* or *dolphin*, and the latter *knife* or *gun*. The next step transforms verbs into their if-forms (15 in total, including past tense for the widest possible range of retrievals) and after adding every transformed verb to the noun and particle from the input, 15 queries are sent as an exact match query to the Apache SOLR engine (lucene.apache.org/solr) which is set to bring up to 100 snippets containing every query from the blog corpus.

Each blog snippet is then filtered by a cleaning module that:

1. Replaces emoticons with periods, as Japanese bloggers very often use smileys as sentence endings,
2. Ignores a sentence if it contains bracketed explanations,
3. Ignores a sentence if it is too short or too long (we experimentally set range from 30 to 250 bytes).

Then a semantic role tagger ASA (Takeuchi et al., 2010) divides sentences into semantically meaningful chunks. Though it slows down the extraction process, we use it because MeCab, while much faster, cuts words (mainly verb phrases) into small morphological parts which make processing more difficult (for instance negation expressions are placed in chunks of various positions depending on a verb type). Next, the chunked sentences are saved to the noun directory together with the preceding and following sentences (if they exist). This process is for storing once retrieved and chunked data to avoid unnecessary searches of already processed inputs and to allow further error analysis.

- **Matching and counting phrases from lexicons.** As mentioned before, we utilize two lexicons. One is for discovering emotional consequences and one for social ones. The first is inspired by Bentham's hedonic calculus and uses emotive expressions collected by Nakamura (1993); the second is based on the Kohlberg's theory of moral development (Kohlberg, 1981) and was manually crafted by the first author. As our previous experiments showed (Rzepka & Araki, 2012), limiting keywords to the most frequent ones helped to increase the system's precision, so this time we performed further alternations and unified both sets to a single lexicon divided into negative and positive keywords (original lexicons had 10 different categories each). By choosing so we were able to compare performance of the proposed set with other ones used in opinion mining and sentiment analysis tasks of Japanese language. One of such sets was introduced by (Takamura et. al, 2005) who used lexical networks to automatically compute the semantic orientations of words. Their method assigned a real value in the range -1 to +1, where the words assigned with values close to -1 are supposed to be negative, and the words assigned with values close to +1 are supposed to be positive. Our preliminary experiments with this set showed that the closer the values are to zero, the more noise they cause during matching. Therefore we took only the most distinctly positive and negative keywords, leaving only 5,756 expressions out of 55,125 (ones with value higher than 0.9 and lower than -0.9). Another lexicon used, for comparison, is JAppraisal (Sano, 2011) and we used its full set of 9,590 words divided into positive and negative, according to Appraisal theory. When compared to our proposed lexicons (258 expressions in total, see Table 2.), the two other sets are very big, but as we will show in the results section, using them has clear disadvantages.

Words from these lexicons are searched for in the sentences from the blog corpus and a total count of positive and negative matches informs the final judgment. There are three restrictions while searching the text:


Table 2. Examples of positive and negative keywords used for matching

Positive Keywords Examples (106 Words)	Negative Keywords Examples (152 Words)
pleasant, happy, safe, like, love, peaceful, enjoy, thankful, grateful (from Nakamura, 39 words) *award, praise, bonus, correct, legal, prize* (based on Kohlberg's theory, 65 words)	*unpleasant, sad, painful, worrisome, terrifying* (from Nakamura dictionary, 66 words) *scolded, sentenced, illegal, lynched, a fine* (based on Kohlberg's theory, 86 words)

1. Searched keyword is matched only if it appears after the verb in the if-form. This is to avoid situations for example wherein, with a "to marry a nice girl" input, a sentence "he was **unhappy** for long time but *after* he *married a nice girl* his life changed for better" is retrieved, with the word "unhappy" informing the machine decision that marriage is negative,
2. If the analyzed chunk with a lexicon word has a negation, the sentence is ignored and the word is not counted,
3. If there are exactly the same sentences from one blog entries, only one of them is saved to the knowledge base.

These restrictions were not implemented in our previous system (Rzepka & Araki, 2012) and to see if they (among others) are effective factors improving the performance of the new version (see Figure 1), we conducted the series of experiments explained below.

Figure 1. System flowchart; from the phrase input to the final score calculation



EVALUATION EXPERIMENT

In previous work (Rzepka & Araki, 2012), we showed that a small corpus size and that lack of access to commercial search engines could be overcome by loosening the search conditions. We achieved that goal mostly by stemming input verbs, instead of creating their if-forms, when forming search queries for retrieving actions. This brute-force approach helped to achieve an f-score minimally better than when the Yahoo engine was used, but this method caused an increase in what we call *explicit errors*. We define such errors as those completely opposite to judgments of human subjects. To decrease the number of such explicit errors, we returned to using verb if-forms and decided to apply above-mentioned conditions - to add semantic chunking, to alter existing lexicons and to test different lexicons. We have also changed the text search engine from HyperEstraier (fallabs.com/hyperestraier) to SOLR, as SOLR supports exact matching, using sentences preceding (PREC) and following (FOLL) a matched sentence.

Human Evaluation

In our previous study we asked 7 Japanese information science students (22-29 years old, 6 males and one female) to rate input actions (explained in "Input and queries generation" subsection) on an 11-point morality scale where -5 is the most immoral and +5 is the most moral. Except assigning 0 as "no ethical valence", subjects could also mark "context dependent" reflecting that fact that many if not most of our behaviors can be treated differently depending on context. If marked both "no ethical valence" and "context dependent", act interpretation was "ambiguous" (AMB) for the sake of easier processing.

On 68 evaluations, there were only two disagreements between subjects (when evaluating "revenging oneself" and "going to a love hotel"). After analyzing the data, we decided to count an action as a negative when an average mark was below -2.5 and as a positive when it was above +2.5. Scores between -2.5 and +2.5 were treated as "ambiguous" (AMB). These ambiguous acts are problematic because they heavily depend on context and show how different attitude toward a survey a subject can have. Some of them treated the inputs lightly and used common associations (e.g. "driving a car" is for commuting or giving oneself and other people pleasure, so should be considered moral), others tended to imagine negative sides of acts (e.g. "driving a car" can surely cause harm to people). There were also subjects who always thought about two sides of an act. They seemed to assume that because there are people in the world who think that "eating pork" is unethical, it is safer to mark "eating a pig" as morally ambiguous. Because such evaluations get scattered throughout the scale, we decided to treat *neighboring agreements* as semi-correct, i.e. when most of the subjects evaluated something as bad and the system chose ambiguity, we counted it as 0.5, a value between *full agreement* (subjects' "bad" evaluated as "bad" and "good" as "good") which gets 1 point, and *full disagreemen*t ("explicit error") where the system judged an act as "good" while it was "bad" for most of the subjects (0 points).

Newly Added Inputs

To see how a bigger number of inputs can change the results, we asked two male information science students (both 23 years old) who did not participate in the first experiment to create new inputs, and to evaluate the morality of the other party's set. We acquired 61 from participant A and 78 inputs from participant B. After deleting doublets, we added them to the previous 68 inputs creating three sets:

1. Basic one (68 phrases)
2. Middle size one (127 phrases)
3. Bigger one (207 phrases)

The participants were shown the previously used set as an example, causing many new inputs to be variations of existing ones. However, we came to the conclusion that it does not make the task easier. In fact, many of the new phrases were rare just because of this tendency to mimic or mix the existing ones. For instance "eating beef" inspired by "eating a cow" could surely be helpful for the system's recall, but "eating a car" inspired by "driving a car" and "eating a cow" obviously could not. Both new sets are presented in the Appendix.

Experimental Results

We ran the system after altering data sets and parameters to observe changes in the results. The first factor we investigated was the influence of discovering polarity words also in sentences that precede (PREC) and follow (FOLL) the conditional one (which contains the query formed by noun, particle and verb in if-form) to decide if they should be used or not. Small and medium sets showed that using both helps to keep relatively high precision in case of **strict** evaluation (where *neighboring agreement* is counted as 0, not 0.5) and **semi**-correct evaluation (*neighboring agreement* counted as 0.5). But when all 207 inputs were fed to the system, this tendency was not so obvious anymore, and we chose only following sentences (FOLL) to be used in further experiments. This is because that scenario had the highest number of correct and semi-correct moral estimations and the highest **loose** evaluation. We use the loose evaluation mostly to see how many *full disagreements* a given run produces (it is calculated by giving semi-correct estimations 1 point). The detailed results are shown in Figure 2. The high score for preceding sentences (PREC) was surprising and gave us ideas for using word lexicons to discover intentions of acts as mentioned earlier in the chapter. Preliminary results of using them to match McDougall's 18 categories of instincts are shown in (Rzepka & Araki, 2013a, Rzepka & Araki, 2014b).

The next step was to see if our margin for ambiguity set for the previous system (below 33.3% is minority and above 66.6% is majority, anything else is ambiguous) influences the results. We recalculated the agreement between subjects and the system (version using following sentences) in four additional scenarios where:

1. Minority is below 49% and majority above 51% (no ambiguity allowed)
2. Minority is below 40% and majority above 60% (slight ambiguity allowed)
3. Minority is below 30% and majority above 70% (big ambiguity allowed)
4. Minority is below 20% and majority above 80% (very big ambiguity allowed).

As shown in Figure 3, precision for strict and semi-strict evaluation is best when the ambiguity margin is smaller (40%-60%) than the "1/3 positive 1/3 ambiguous 1/3 negative" approach used in previous research. However, because the differences are not that significant, we need to continue experiments with different ranges and sets of inputs. Naturally, enlarging ambiguity margins (see red frames in Figure 3) is beneficial for decreasing explicit errors because it is less probable that the system and subjects diametrically oppose one another. Why they still occur, we explain later in the error analysis section.

Figure 2. Comparison of system performance when preceding (PREC) and following (FOLL) sentences are included in scoring

		68 inputs			127 inputs			207 inputs		
		strict	semi	loose	strict	semi	loose	strict	semi	loose
No PREC No FOLL	precision	0.442	0.702	0.962	0.536	0.761	0.986	0.538	0.739	0.940
	recall	0.258	0.356	0.431	0.227	0.294	0.351	0.240	0.302	0.355
	f-score	0.326	0.472	0.595	0.319	0.424	0.517	0.332	0.429	0.515
With PREC With FOLL	precision	0.585	0.774	0.962	0.643	0.807	0.971	0.551	0.729	0.907
	recall	0.320	0.383	0.436	0.265	0.311	0.352	0.249	0.305	0.353
	f-score	0.413	0.513	0.600	0.375	0.449	0.517	0.343	0.430	0.508
No PREC With FOLL	precision	0.500	0.731	0.962	0.609	0.790	0.971	0.539	0.761	0.983
	recall	0.283	0.365	0.431	0.251	0.304	0.349	0.232	0.299	0.355
	f-score	0.361	0.487	0.595	0.356	0.439	0.513	0.325	0.429	0.522
With PREC No FOLL	precision	0.547	0.764	0.981	0.629	0.807	0.986	0.534	0.729	0.924
	recall	0.302	0.377	0.437	0.259	0.310	0.354	0.241	0.303	0.355
	f-score	0.389	0.505	0.605	0.367	0.448	0.521	0.332	0.428	0.513

Figure 3. Differences in results depending on how the ambiguity margin is set

		68 inputs			127 inputs			207 inputs		
		strict	semi	loose	strict	semi	loose	strict	semi	loose
Minority 20% Majority 80% (No PREC With FOLL)	precision	0.462	0.721	0.981	0.522	0.754	0.986	0.504	0.748	0.991
	recall	0.264	0.359	0.432	0.222	0.292	0.351	0.220	0.295	0.356
	f-score	0.336	0.479	0.600	0.312	0.421	0.517	0.306	0.423	0.524
Minority 30% Majority 70% (No PREC With FOLL)	precision	0.462	0.712	0.962	0.565	0.768	0.971	0.513	0.748	0.983
	recall	0.267	0.359	0.431	0.238	0.298	0.349	0.223	0.296	0.355
	f-score	0.338	0.477	0.595	0.335	0.429	0.513	0.311	0.424	0.522
Minority 33.3% Majority 66.6% (No PREC With FOLL)	precision	0.500	0.731	0.962	0.609	0.790	0.971	0.539	0.761	0.983
	recall	0.283	0.365	0.431	0.251	0.304	0.349	0.232	0.299	0.355
	f-score	0.361	0.487	0.595	0.356	0.439	0.513	0.325	0.429	0.522
Minority 40% Majority 60% (No PREC With FOLL)	precision	0.571	0.765	0.959	0.628	0.797	0.965	0.582	0.768	0.955
	recall	0.298	0.362	0.416	0.303	0.356	0.401	0.241	0.295	0.342
	f-score	0.392	0.492	0.580	0.409	0.492	0.567	0.340	0.426	0.504
Minority 49% Majority 51% (No PREC With FOLL)	precision	0.500	0.712	0.923	0.580	0.768	0.957	0.557	0.748	0.939
	recall	0.289	0.366	0.429	0.244	0.299	0.347	0.242	0.301	0.351
	f-score	0.366	0.484	0.585	0.343	0.431	0.510	0.338	0.429	0.511

The final comparison we performed was to see if we managed to keep the precision without decreasing f-scores and at the same time to decrease the number of explicit errors, errors which are not so context dependent as semi-correct ones. Simultaneously, we compared how different lexicons, described earlier in the chapter, influence the results. It appeared that the proposed system with enhanced Nakamura and Kohlberg-based lexicons decreased the number of full disagreements from 6 to 2. All the 6 problematic judgments were automatically evaluated as correct or semi-correct, however two new "explicit errors" appeared. For the details, see Figure 4. By enhancing the lexicon, we mean deleting some Chinese characters which caused problems as noticed in (Rzepka & Araki, 2012) and adding more keywords describing social consequences. For instance "being arrested" usually is a consequence of some unsocial behavior, but "being killed" is just a very bad outcome, much like "being executed" with a wider recall. These enhancements improved performance.

Figure 4. Results comparison of previous and proposed system with different lexicon used

		68 inputs		
	Minority: 33.3% Majority: 66.6%	semi	explicit errors	matching time
Best of previous systems (Nakamura based lexicon), no preceding sentences	precision	0.777	6	N/A
	recall	0.333		
	f-score	0.467		
Best of proposed systems (Nakamura and Kohlberg based lexicon)	precision	0.731	2	4s 388ms
	recall	0.365		
	f-score	0.487		
Best of proposed systems (Nakamura based lexicon)	precision	0.474	31	3s 728ms
	recall	0.238		
	f-score	0.317		
Best of proposed systems (Kohlberg based lexicon)	precision	0.565	15	4s 709ms
	recall	0.254		
	f-score	0.351		
Best of proposed systems (Takamura based lexicon)	precision	0.754	4	2m 23s 384ms
	recall	0.315		
	f-score	0.445		
Best of proposed systems (J-Appraisal lexicon)	precision	0.548	16	3m 38s 46ms
	recall	0.263		
	f-score	0.355		
Best of proposed systems (all lexicons combined)	precision	0.643	6	3m 58s 153ms
	recall	0.287		
	f-score	0.397		

The best of our systems in the 33.3% vs. 66.6% setup was not the fastest one, but acquired much better precision than the fastest one using only the limited Nakamura lexicon. Interestingly, Takamura's lexicon achieved the best precision, however because of its size (even after shrinking it to 1/10 of the original dictionary), accessing the knowledge base was more that 36 times slower. This is unacceptable if the algorithm is intended for devices communicating with people in real time. Latest experiments were performed on a CentOS Linux machine with two 6-core Intel Xeon 2.66Ghz, 48GB memory and SSD hard disks.

ERROR ANALYSIS

Most of the errors in our experiments are due to the lack of deeper context processing, which is necessary for better natural language processing. However, two explicit errors from the system comparison show that our system did a sufficient job of recognizing bad from good. It was limited by insufficient example sentences retrieved. One error came from specific tendencies in the retrieved blog entries. Another error came from weaknesses of the setup.

"Preventing conception" was the first input judged differently by the system and the human subjects. It appeared that most of the bloggers expressing consequences of this act were writing about how *their pets* reacted to it. It is not unusual for Japanese to write about their pets on the Internet, and this example perfectly illustrates the urgent need for further semantic analysis that recognizes and categorizes agents and patients of acts. It can be done with one of the tools that we already use – a semantic tag tagger, ASA, but it needs further improvements.

The second sentence that had an opposite polarity was "avoiding / preventing a war". This error was caused by an insufficient number of examples, and by one sentence saying "for preventing wars it is not enough to tell our children that >>war is a misery<<, >>war is a tragedy<< and so on!" This sentence included two negative keywords (*misery* and *tragedy*) which tipped the scales in favor of negative consequences. Firstly, the sentences with citations should probably be ignored for now as ones with bracketed explanations. Secondly, the if-form "tame" that was used here has also the meaning of purpose in Japanese language, hence we may need to look closer at the particular conditional forms and evaluate separately their individual performances.

Finally, we also must decide what categories of agents (act doers, actors) and patients (act receivers, objects) should be used. Simple human / animal / object categorization is insufficient, because, as Bentham already noticed centuries ago, one's mother's ethical value is definitely different when compared to the value of a complete stranger (but still human).

Possible Usage Examples for Our Method

As mentioned earlier in the chapter, we work on devices that require natural language understanding in order to recognize their user's needs. One such application is a dialog system (Higuchi et al, 2008) and other is Twimba, a Roomba robot that is able to use its Twitter account as a communication channel (Takagi et al, 2011). The latter uses a database of tweets to search what people usually do in given situations. So for example, when somebody tweets that his or her room is dirty, the robot searches for consequences of having a dirty room and what people usually do about it. If an action is possible for the agent (here: "cleaning") is discovered, it offers its help to the user. By knowing its own name ("Roomba)

and function (“vacuum cleaning”), the robot can also “read” what is a possible action for its “kin”. Hence if one asks it to clean a pool, it will refuse after not finding examples confirming that the task could be performed by similar devices. This example shows how the Internet can enrich a robot’s knowledge about the world and about itself.

One example of “moral dilemmas” that a vacuum cleaner faces is described and dealt with by Takagi. As the robot operated in a laboratory with almost 20 users, there were possible conflicts of interest. When one student is studying hard and other student suddenly spills something on the floor, whose request is more important? The order to remain silent, or the request to quickly clean up the place? Similar problems could arise in a home environment when the priority of cleaning (e.g. because friends are coming to visit) should probably be overridden by the current state of a baby who just fell asleep. For our robot, it is not necessary to hear any reasons, because “baby is sleeping!” is understood as a “stop cleaning” command. On the contrary, the robot can explain its choices because it operates on knowledge stored in natural language. This is a rather problematic feature for the most machine learning based systems.

In the future, with language understanding and searching technologies progressing rapidly, we expect to see multicultural knowledge bases of different cases (real life, historical, legal, scientific) available through a personal assistant / advisor. Such software could be implemented in wearable devices like glasses. Perhaps it could bring a solution for the problems caused by cognitive biases described, among others, by Kahneman - from unnecessary gambling to sharing harming opinions which come from overconfidence in one’s own knowledge. We believe that the Machine Ethics field is not only about life and death matters, but also about improving our everyday lives through intelligent - and even caring - devices.

This does not mean that we are not eager to test our methods with existing systems in solving serious dilemmas, such as that those confronting GenEth (Anderson & Anderson, 2014) or McLaren’s model (2003), wherein health and killing are the main topics for testing. Not many will agree that the masses of lay people could be superior in dealing with moral dilemmas, but replacing ethicists with the Wisdom of the Crowd is an interesting trial. If successful, such an approach could replace specialists in many fields, from legal consulting to medicine. On the other hand, implementing agents with dialog functionality in mobile devices connected to constantly growing knowledge resources, this could lead to interesting human-machine conversations and additional data gathering, because most moral judgments require context specific input with as many details as possible. Broadening input resources, alongside deepening semantic analysis, is a part of our future work described in the final section below.

CONCLUSION AND FUTURE WORK

In this chapter, we presented our original approach to building an AMA using Natural Language Processing techniques and tools for retrieving written descriptions of bloggers’ experiences and opinions in order to equip the AMA with knowledge about common consequences of acts. This approach simplifies the processing, but also causes errors that need to be dealt with by the algorithm. Here, we introduced the first step that moves our research from the most shallow keyword matching level into a version that handles negations, conditionality and uses less ambiguous phrases for recognizing the polarity of consequences. We discovered that many words taken from the Nakamura dictionary of emotive expressions cause noise, and that the lexicon of words inspired by Kohlberg can be extended with new phrases newly discovered during the experiments. For instance, sentences describing lives of women who had to “sell their bodies” (one of the input acts) bring new descriptions of tragic lives, and these descriptions can

be reused as new lexicon entries if they appear often in strongly negative sentences. Also, staying with the example of "selling a body" input, the reasons for desperation could tell the machine more about a difference between "doing it to become a Hollywood star" and "doing it to feed her children". This influence of context is very important for arriving at fair conclusions. Also, as mentioned earlier, we need to deepen the analysis and are working on applying vectors of Bentham's Felicific Calculus (Rzepka & Araki 2013b, Rzepka & Araki, 2014b) to our system.

In this chapter, we showed that even a few techniques for more thorough analysis, although more time consuming, can provide precision without Google-sized indices. Nonetheless, when it comes to implementing our method on e.g. a dialog agent, low recall is one of the biggest drawbacks of our system. But since it is difficult for academia to utilize super fast computers and millions of gigabytes of disk space, we plan not only to crawl more texts but also to use other existing NLP methods in order to improve the recall. For instance, none of the sentences extracted by "killing a president" input, contained a lexicon keyword. This can be improved by finding more sentences with words similar to "president" or by using a second layer of search where chunks of sentences describing the process of murdering a country's leader become inputs themselves. This approach, which is already being tested, could be beneficial not only for the recognition but also for growing the knowledge base, because now only an input triggers a search for new examples and storing processes. Another interesting possibility that we want to test is wider usage of JAppraisal dictionary, in which the evaluative expressions are classified not only according to polarity (positive/negative attitude) but also in terms of evaluative criteria such as affection, desire, morality, honesty, peacefulness, etc.

Problems with Fair Evaluation

Another important future work is further research on evaluating moral decisions, and tests with different types of surveys. Shortly stated acts, even with a micro-context of what or who is an object, patient, target, etc. are difficult to judge. Every subject, with his or her baggage of experiences, imagines things differently. Therefore, probably it would be more natural to utilize micro story-type questionnaires that enable subjects to grasp details of the morally ambiguous situations. But for that, we need to expand input and search processes, which will take some time. It is often said that, in affect recognition, people agree only in 80% of cases. There is a possibility that, for ethical evaluation, the agreement is even lower, so we also need to seek new ways of evaluating machine decisions. The subjects should not only vary according to sex, age or social status. To ensure universality of artificial morality, we also need opinions from different cultures.

Other Future Possibilities

We believe that the strength of our approach lays in its universality and plasticity. For that reason, we plan to make the retrieved data and the system itself available not only for using but also for altering the searching parameters and lexicons. This is because we see the possibility for other fields (from psychology to economics and marketing) to utilize it as a tool for comparing traditional surveys or field studies with automatically gathered judgments and behavior patterns. Error analysis of our system, described in the experiment section, suggests that usually utilized surveys leave a large margin for misinterpretations and a characteristic bias due to:

1. Limited space and time for explaining and answering questions;
2. Natural prejudices;
3. Imagination limited to the subject's particular experiences.

As dual process theory shows (Kahneman, 2002, 2003), our immediate emotional or intuitive reactions are faster than our deliberative ones and subjects may tend to fill in surveys or answer questions intuitively, without a second thought. For that reason, we concentrate on blogs, not microblogs like Twitter where users often react quickly and sometimes regret their opinions later, after rethinking or some criticism from followers. Naturally, many opinions on blogs are false or profit-oriented, but during the search it is often enough to use several simple heuristics like avoiding counting sentences that reappear on different pages (most often they are spam). In the future, it would be ideal to create a module that tries to confirm or filter out disputable statements by searching trustworthy scientific resources, for instance.

REFERENCES

Allen, C., Smit, I., & Wallach, W. (2005). Artificial morality: Top-down, bottom-up, and hybrid approaches. *Ethics and Information Technology*, *7*(3), 149–155. doi:10.1007/s10676-006-0004-4

Anderson, M., & Anderson, S. L. (2011). *Machine Ethics*. Cambridge University Press. doi:10.1017/CBO9780511978036

Anderson, M., & Anderson, S. L. (2014a, April). Toward Ethical Intelligent Autonomous Healthcare Agents: A Case-Supported, Principle-Based Behavior Paradigm. *Proceedings of the 50th Annual Convention of the Society for the Study of Artificial Intelligence and the Simulation of Behaviour (AISB-50) Symposium on Machine Ethics in the Context of Medical and Care Agents*, London, UK.

Anderson, M., & Anderson, S. L. (2014b, July 27-31). GenEth: A General Ethical Dilemma Analyzer. *Proceedings of the Twenty-Eighth AAAI Conference on Artificial Intelligence*, Quebec City, Quebec, Canada, (pp. 253-261).

Asada, M., Nagai, Y., & Ishihara, H. (2012). Why not artificial sympathy? In ShuzhiSam Ge, Oussama Khatib, John-John Cabibihan, Reid Simmons, and Mary-Anne Williams, (Eds.), Social Robotics, 7621, (pp. 278–287). doi:10.1007/978-3-642-34103-8_28

Bentham, J. (1789). *An Introduction to the Principles and Morals of Legislation*. London: T. Payne. doi:10.1093/oseo/instance.00077240

Brooks, D. (2011). *The Social Animal: The Hidden Sources of Love, Character, and Achievement*. Random House Publishing Group.

Brosnan, S. F., & De Waal, F. B. (2003). Monkeys reject unequal pay. *Nature*, *425*(6955), 297–299. doi:10.1038/nature01963 PMID:13679918

Dennett, D. C. (1997). Consciousness in human and robot minds. In M. Io, Y. Miyashita, & E. T. Rolls (Eds.), *Cognition, Computation & Consciousness* (pp. 17–29). Oxford University Press.

Dumouchel, P., & Damiano, L. (2011). Artificial empathy, imitation and mimesis. *Ars Vivendi Journal*, *1*, 18–31.

Gallese, V.Gallese & Goldman. (1998). Mirror neurons and the simulation theory. *Trends in Cognitive Sciences*, *2*(12), 493–501. doi:10.1016/S1364-6613(98)01262-5 PMID:21227300

Guarini, M. (2006). Particularism and the Classification and Reclassification of Moral Cases. *IEEE Intelligent Systems*, *21*(4), 22–28. doi:10.1109/MIS.2006.76

Haidt, J. (2012). *The righteous mind*. Pantheon.

Hess, U., & Thibault, P. (2009). Darwin and Emotion Expression". *The American Psychologist*, *64*(2), 120–128. doi:10.1037/a0013386 PMID:19203144

Hickok, G. (2009). Eight problems for the mirror neuron theory of action understanding in monkeys and humans. *Journal of Cognitive Neuroscience*, *21*(7), 1229–1243. doi:10.1162/jocn.2009.21189 PMID:19199415

Higuchi, S., Rzepka, R., & Araki, K. (2008). A Casual Conversation System Using Modality and Word Associations Retrieved from the Web. *Proceedings of the 2008 Conference on Empirical Methods in Natural Language Processing*, Honolulu, USA, (pp. 382-390). doi:10.3115/1613715.1613765

Kahneman, D. (2002). Nobel prize lecture: Maps of Bounded Rationality: a perspective on intuitive judgment and choice. In T. Frangsmyr (Ed.), *Nobel Prizes 2002: Nobel Prizes, Presentations, Biographies, & Lectures* (pp. 416–499). Stockholm: Almqvist & Wiksell Int.

Kahneman, D. (2003). A perspective on judgment and choice. *The American Psychologist*, *58*(9), 697–720. doi:10.1037/0003-066X.58.9.697 PMID:14584987

Kohlberg, L. (1981). *The Philosophy of Moral Development*. Harper and Row.

Kudo, T. (2005). *MeCab: Yet Another Part-of-Speech and Morphological Analyzer*. http://mecab.sourceforge.net/

Liu, H., & Singh, P. (2004). ConceptNet: A Practical Commonsense Reasoning Toolkit. *BT Technology Journal*, *22*(4), 211–226. doi:10.1023/B:BTTJ.0000047600.45421.6d

McDougall, W. (1923). *Outline of psychology*. London.

McLaren, B. M. (2003). Extensionally Defining Principles and Cases in Ethics: An AI Model. *Artificial Intelligence Journal*, *150*(Nov.), 145–181. doi:10.1016/S0004-3702(03)00135-8

Miller, G. (1995). WordNet: A Lexical Database for English. *Communications of the ACM*, *38*(11), 39–41. doi:10.1145/219717.219748

Nakamura, A. (1993). *Kanjo hyogen jiten* [Dictionary of Emotive Expressions]. Tokyodo Publishing.

Pellegrino, G., Fadiga, L., Fogassi, L., Gallese, V., & Rizzolatti, G. (1992). Understanding motor events: A neurophysiological study. *Experimental Brain Research*, *91*(1), 176–180. doi:10.1007/BF00230027 PMID:1301372

Pereira, L. M., & Saptawijaya, A. (2007). Modelling morality with prospective logic. *Proceedings of the 13th Portuguese International Conference on Artificial Intelligence (EPIA'07)*. (pp. 1-28).

Picard, R. W., & Klein, J. (2002). Computers that recognise and respond to user emotion: Theoretical and practical implications. *Interacting with Computers*, *14*(2), 141–169. doi:10.1016/S0953-5438(01)00055-8

Pinker, S. (2011). *The Better Angels of Our Nature: Why Violence Has Declined*. Penguin Group.

Pontier, M. A., & Hoorn, J. F. (2012). *Toward Machines that Behave Ethically Better than Humans Do.* Proceedings of the *34th International Annual Conference of the Cognitive Science Society, CogSci*, Sapporo, Japan.

Preston, S., & de Waal, F. (2002). Empathy: Its ultimate and proximate bases. *Behavioral and Brain Sciences*, *25*, 1–72. PMID:12625087

Ptaszynski, M., Rzepka, R., Araki, K., & Momouchi, Y. (2012). Annotating Syntactic Information on 5 Billion Word Corpus of Japanese Blogs. *Proceedings of The Eighteenth Annual Meeting of The Association for Natural Language Processing (NLP-2012)*, pp. 14-16.

Ross, W. D. (1930). *The Right and the Good*. Oxford: Oxford University Press.

Rzepka, R., & Araki, K. (2005). What Statistics Could Do for Ethics? - The Idea of Common Sense Processing Based Safety Valve. *AAAI Fall Symposium on Machine Ethics, FS-05-06*.

Rzepka, R. & Araki, K. (2012). Polarization of consequence expressions for an automatic ethical judgment based on moral stages theory. *IPSJ SIG Notes 2012-NL-207(14).* (pp. 1-4).

Rzepka, R., & Araki, K. (2013a). Web-based five senses input simulation – ten years later. In Technical Reports of Japanese Society of AI SIG-LSE B301, 5, pp. 25–33.

Rzepka, R., & Araki, K. (2013b). Possible Usage of Sentiment Analysis for Calculating Vectors of Felicific Calculus, *IEEE 13th International Conference on Data Mining Workshop "SENTIRE"*, Dallas, USA, (pp. 967-970).

Rzepka, R., & Araki, K. (2014a). Experience of Crowds as a Guarantee for Safe Artificial Self. *AAAI Spring Symposium on Implementing Selves with Safe Motivational Systems & Self-Improvement*, Stanford, USA. (pp. 40-44).

Rzepka, R., & Araki, K. (2014b). ELIZA Fifty Years Later: An Automatic Therapist Using Bottom-Up and Top-Down Approaches. (To appear in) Intelligent Systems, Control and Automation: Science and Engineering, 74, van Rysewyk, Simon Peter, Pontier, Matthijs (Eds.)

Rzepka, R., Ge, Y., & Araki, K. (2005). Naturalness of an Utterance Based on the Automatically Retrieved Commonsense. Proceedings of *IJCAI 2005 - Nineteenth International Joint Conference on Artificial Intelligence*, Edinburgh, Scotland. (pp. 1696-1697.)

Rzepka, R., Shibuki, H., Kimura, Y., Takamaru, K., Matsuhara, M., & Murakami, K. (2008). Judicial Precedents Processing Project for Supporting Japanese Lay Judge System. *Workshop on Semantic Processing of Legal Texts, LREC 2008*, Marrakech, Morocco. (pp.33-41).

Sano, M. (2011). *Japanese dictionary of appraisal -attitude-* (JAppraisal Dictionary ver1.1.2). Tokyo: Gengo Shigen Kyokai. Retrieved from http://www.gsk.or.jp/catalog_e.html

Sun, R. (2013). Moral Judgment, Human Motivation, and Neural Networks. *Cognitive Computation*, *5*(4), 566–579. doi:10.1007/s12559-012-9181-0

Takagi, K., Rzepka, R., & Araki, K. (2011). *Just Keep Tweeting, Dear: Web-Mining Methods for Helping a Social Robot Understand User Need.* Proceedings of Help Me Help You, Symposium of AAAI Spring 2011. (pp. 60-65).

Takamura, H., Inui, T., & Okumura, M. (2005). Extracting Semantic Orientations of Words using Spin Model. *Proceedings of the 43rd Annual Meeting of the Association for Computational Linguistics (ACL2005)*. (pp. 133-140). doi:10.3115/1219840.1219857

Takeuchi, K., Tsuchiyama, S., Moriya, M., & Moriyasu, Y. (2010). Construction of Argument Structure Analyzer toward Searching Same Situations and Actions. *IEICE Technical Report*, *109*(390), 1–6.

Tenbrunsel, A. E., & Messick, D. M. (2004). Ethical fading: The role of self deception in unethical behavior. *Social Justice Research*, *17*(2), 223–236. doi:10.1023/B:SORE.0000027411.35832.53

Thagard, P. (2007). I feel your pain: Mirror neurons, empathy, and moral motivation. *Journal of Cognitive Science*, *8*, 109–136.

Wallach, W., & Allen, C. (2009). *Moral Machines: Teaching Robots Right from Wrong*. Oxford: Oxford University Press. doi:10.1093/acprof:oso/9780195374049.001.0001

White, J. B. (2010). Understanding and augmenting human morality: An introduction to the ACTWith model of conscience. *Studies in Computational Intelligence*, *314*, 607–621.

KEY TERMS AND DEFINITIONS

Artificial Moral Judgment: Machine's ability to behave morally due to a proper recognition of moral and immoral acts.

Semantic Analysis: Here by this term we mean automatic recognition of semantic features of a written text. Lexical layer is divided into meaningful chunks by semantic role tagger to perform retrievals beyond classical lexical level.

Sentiment Analysis: Here - specific subtask of text mining where polarity (positive and negative) consequences of input acts are recognized due to co-occurrences of these acts with lexicon words which are divided into positive and negative categories.

Text-Mining: In this research text-mining is a set of natural language processing techniques using manually crafted lexicons used for finding and ranking patterns in a blog corpus.

Wisdom of Crowd: In our approach it is a phenomenon showing that majority of us own common sense and a computer, by comparing opinions, reactions, acts, reasons, etc. of people, is able (to some extent) guess what is treated as ethical or unethical by a given society.

APPENDIX

1. **New Set of Free Inputs (Subject A):** Abandoning a child, abandoning a friend, abandoning a woman, arresting a child, becoming a prostitute, being a prostitute, breaking things, buying a friend, buying alcohol, carry out sexual harassment, choosing a child, choosing a foreigner, choosing a friend, choosing alcohol, choosing prostitution, curing a body, curing an illness, deciding for love hotel, eating a child, eating body, eating curry and rice, eating people, eating things, euthanizing oneself, forcing abortion, forcing to cooperate, forcing to have sex, giving a present, having a stomachache, helping people, hiding alcohol, hiding money, hitting a foreigner, hitting a friend, hitting a prostitute, hitting a woman, hitting an animal, killing a foreigner, killing a friend, killing a prostitute, killing a woman, making a body, making a hamburger, making alcohol, making curry and rice, praising a child, quitting drinking, receiving money, stabbing with a knife, stealing alcohol, stealing an animal, stealing bread, stealing money, stopping a friend, taking away alcohol, throwing away alcohol, throwing away money, waking up a child, waking up a woman, working as a prostitute
2. **New Set of Free Inputs (Subject B):** A mother being arrested, allowing a crime, arresting a mother, arresting a policeman, being killed by animal, being killed by enemy, being raped, being slapped by someone, being told a lie, breaking a car, breaking a relation, building a hospital, building a house, causing a crime, causing war, cheating (cribbing), choosing war, clapping hands, climbing mountain, climbing stairs, committing a crime, committing a sin, creating a cat, creating a dog, curing a cat, destroying a house, divorcing, doing drugs, dumping war, eating a car, eating a cat, eating a dog, eating beef, eating pork, forcing contraception, forcing to commit a crime, getting a salary, getting married, getting on a car, giving a car, going into a hot spring, going to pachinko, going to war, having a car repair, having a car stolen, helping a friend, helping a policeman, helping the police, helping to a friend, hitting a dog, interfering, killing a policeman, killing an enemy, letting somebody have an affair, making a car, making a house dirty, mending a relation, passing a bribe, handing a present, handing a salary, handing money, preventing a crime, quitting drugs, raping somebody, repairing a car, running away from home, saving a policeman, saying bad things about somebody, selling body, shaking hands, stabbing with a knife, stealing a dog, stealing a salary, swimming in a pool, taking a bath, taking a shower, telling a lie