USB input power selector (jumper)



Li-Po Battery Charger



Automatic power path selection



USB power detect

Vusb_min = 4.4V
Vusb_max = 5.25V
Vusb_det_min = 2.66V
Vusb_det_max = 3.22V



Li-Po Battery Connector (Molex or JST)



+3V3 high efficiency buck regulator



Battery Voltage Measurement



Power on button and microcontroller hold (always on when USB connected)



Fiducials

- H14 Fiducial 1mm
- H16 Fiducial 1mm
- H19 Fiducial 1mm
- H21 Fiducial 1mm

Mounting Holes



GND Test Points



BOM

PCB1

P0014

PCB NAME: PX-HERO Board		PCB NUMBER: P0012
SCH PAGE TITLE: Power Supply		PCB REV: D
SHEET: 1 OF 3	DATE: 2019-02-26	VARIANT: [No Variations]
DRAWN BY: Pieter Conradie	PROJECT E NGINEER: Pieter Conradie	TEMPLATE REV: 02

PRINT 2019-06-10 08:00:13

STM32 ARM Cortex M0+ Microcontroller

Reset Button



USB Device Port



Serial Flash



Program & Debug



Standard ARM Cortex Debug Connector



UART Header



PCB NAME: PX-HERO Board			PCB NUMBER: P0012
SCH PAGE TITLE: Microcontroller			PCB REV: D
SHEET: 2 OF 3	DATE: 2019-02-26		VARIANT: [No Variations]
DRAWN BY: Pieter Conradie	PROJECT E NGINEER: Pieter Conradie		TEMPLATE REV: 02

PRINT 2019-06-10 08:00:13

USB-Serial bridge



USB-Serial partial power-down isolation (USB2 disconnected)



STM32 PA10 is a 5V tolerant pin (FTf I/O structure in datasheet), so there is no parasitic ("phantom") current sourcing path via ESD diode to VCC (+3V3) when U6 is powered via USB2, but board is not powered.

LCD



Micro SD Card



(option to disconnect SD CD from GPIO7)

Buzzer



ADC scale and filter circuitry



Peripheral connector



Sparkfun QWIIC Connector



LCD LED



LCD Buttons



(pull-up resistors on micro must be enabled)

Seeed Grove I2C Connector



PCB NAME: PX-HERO Board		PCB NUMBER: P0012
SCH PAGE TITLE: Peripherals		PCB REV: D
SHEET: 3 OF 3	DATE: 2019-02-26	VARIANT: [No Variations]
DRAWN BY: Pieter Conradie	PROJECT E NGINEER: Pieter Conradie	TEMPLATE REV: 02

PRINT 2019-06-10 08:00:13

USB input power selector (jumper)



Li-Po Battery Charger



Automatic power path selection



USB power detect

Vusb_min = 4.4V
Vusb_max = 5.25V
Vusb_det_min = 2.66V
Vusb_det_max = 3.22V



Li-Po Battery Connector (Molex or JST)



+3V3 high efficiency buck regulator



Battery Voltage Measurement



Power on button and microcontroller hold (always on when USB connected)



Fiducials

- H14 Fiducial 1mm
- H16 Fiducial 1mm
- H19 Fiducial 1mm
- H21 Fiducial 1mm

Mounting Holes



GND Test Points



BOM

PCB1

P0014

PCB NAME: PX-HERO Board			PCB NUMBER: P0012
SCH PAGE TITLE: Power Supply			PCB REV: D
SHEET: 1 OF 3	DATE: 2019-02-26		VARIANT: lite edition
DRAWN BY: Pieter Conradie	PROJECT E NGINEER: Pieter Conradie		TEMPLATE REV: 02

PRINT 2019-06-10 08:00:15

STM32 ARM Cortex M0+ Microcontroller

32kHz Crystal

Boot select

Reset Button



USB Device Port



Serial Flash



Program & Debug



Standard ARM Cortex Debug Connector



UART Header



PCB NAME: PX-HERO Board			PCB NUMBER: P0012
SCH PAGE TITLE: Microcontroller			PCB REV: D
SHEET: 2 OF 3	DATE: 2019-02-26		VARIANT: lite edition
DRAWN BY: Pieter Conradie	PROJECT E NGINEER: Pieter Conradie		TEMPLATE REV: 02

PRINT 2019-06-10 08:00:15

USB-Serial bridge



USB-Serial partial power-down isolation (USB2 disconnected)



STM32 PA10 is a 5V tolerant pin (FTf I/O structure in datasheet), so there is no parasitic ("phantom") current sourcing path via ESD diode to VCC (+3V3) when U6 is powered via USB2, but board is not powered.

LCD



Micro SD Card



(option to disconnect SD CD from GPIO7)

Buzzer



ADC scale and filter circuitry



Peripheral connector



Sparkfun QWIIC Connector



LCD LED



LCD Buttons



(pull-up resistors on micro must be enabled)

Seeed Grove I2C Connector



PCB NAME: PX-HERO Board		PCB NUMBER: P0012
SCH PAGE TITLE: Peripherals		PCB REV: D
SHEET: 3 OF 3	DATE: 2019-02-26	VARIANT: lite edition
DRAWN BY: Pieter Conradie	PROJECT E NGINEER: Pieter Conradie	TEMPLATE REV: 02

PRINT 2019-06-10 08:00:15

USB input power selector (jumper)



Li-Po Battery Charger



Automatic power path selection



USB power detect

Vusb_min = 4.4V
Vusb_max = 5.25V
Vusb_det_min = 2.66V
Vusb_det_max = 3.22V



Li-Po Battery Connector (Molex or JST)



+3V3 high efficiency buck regulator



Battery Voltage Measurement



Power on button and microcontroller hold (always on when USB connected)



Fiducials

- H14 Fiducial 1mm
- H16 Fiducial 1mm
- H19 Fiducial 1mm
- H21 Fiducial 1mm

Mounting Holes



GND Test Points



BOM

PCB1

P0014

PCB NAME: PX-HERO Board			PCB NUMBER: P0012
SCH PAGE TITLE: Power Supply			PCB REV: D
SHEET: 1 OF 3	DATE: 2019-02-26		VARIANT: deluxe edition
DRAWN BY: Pieter Conradie	PROJECT E NGINEER: Pieter Conradie		TEMPLATE REV: 02

PRINT 2019-06-10 08:00:16

STM32 ARM Cortex M0+ Microcontroller

32kHz Crystal

Boot select

Reset Button



USB Device Port



Serial Flash



Program & Debug



Standard ARM Cortex Debug Connector



UART Header



PCB NAME: PX-HERO Board			PCB NUMBER: P0012
SCH PAGE TITLE: Microcontroller			PCB REV: D
SHEET: 2 OF 3	DATE: 2019-02-26		VARIANT: deluxe edition
DRAWN BY: Pieter Conradie	PROJECT E NGINEER: Pieter Conradie		TEMPLATE REV: 02

PRINT 2019-06-10 08:00:17

USB-Serial bridge



USB-Serial partial power-down isolation (USB2 disconnected)



STM32 PA10 is a 5V tolerant pin (FTf I/O structure in datasheet), so there is no parasitic ("phantom") current sourcing path via ESD diode to VCC (+3V3) when U6 is powered via USB2, but board is not powered.

LCD



Micro SD Card



(option to disconnect SD CD from GPIO7)

Buzzer



ADC scale and filter circuitry



Peripheral connector



Sparkfun QWIIC Connector



Seeed Grove I2C Connector



LCD LED



LCD Buttons



(pull-up resistors on micro must be enabled)

PCB NAME: PX-HERO Board		PCB NUMBER: P0012
SCH PAGE TITLE: Peripherals		PCB REV: D
SHEET: 3 OF 3	DATE: 2019-02-26	VARIANT: deluxe edition
DRAWN BY: Pieter Conradie	PROJECT E NGINEER: Pieter Conradie	TEMPLATE REV: 02

PRINT 2019-06-10 08:00:17