# Lesser known gems of the standard library

The No. 6 and A23s of "batteries included"

#### Kenneth Nielsen<sup>1</sup>

<sup>1</sup>Center for Individual Nanoparticle Functionality (CINF) Institute of Physics Technical University of Denmark (DTU)

> Python and beers presentation, Aprils 29, 2015



#### About me

- My name is Kenneth Nielsen and I work at CINF
- Free and open source software (FOSS) enthusiast
- Use way too much time on python conference presentations on youtube

### Slides and examples

git clone https://github.com/KennethNielsen/presentations.git

https://github.com/KennethNielsen/presentations http://bit.ly/1FclzDR

#### Outline

A peak into some of the (maybe) lesser known gems of the standard library

- Convenient containers (... and more)
  - defaultdict, Counter
- Special operators for key functions (get rid of lambdas)
  - itemgetter, attrgetter
- Function tools
  - partial
- Part way between anonymous data and full classes
  - namedtuple
- Random stuff ;)
  - choice

#### defaultdict

```
from collections import defaultdict
groups = defaultdict(default_callable)
```

A dictionary that will fill in values for unknown keys with defaults supplied by a callable

- ► Useful e.g. for grouping, where you would otherwise have to write annoying first-item-init code
- Supply a callable when creating it, that will be called to ask for a default value

LIVE! Example ex1\_default\_dict.py

#### Counter

```
from collections import Counter
counter = Counter()
```

A default dict with default value 0 (and some special counter relevant math)

- Useful for counting!
- Can be added and subtracted
- Flattens out at 0 when subtracted

LIVE! Example ex2\_counter.py

### itemgetter and attrgetter

from operator import itemgetter, attrgetter

Gives you a function that returns an element from an iterable or dict or a specific attribute from an object

- EXTREMELY usefull as key functions for sort, sorted, min and max ...
- ... especially because they make it possible to get rid of those pesky unreadable lambda expressions

LIVE! Example ex3\_itemgetter\_attrgetter.py

### partial

from functools import partial

From original functions create new ones, where certain values in the original functions calls are already filled out

- ➤ To call the same function a lot of times with one spcific argument
- ➤ To create custom functions that calls others with an argument filled out

LIVE! Example ex4\_partial.py
LIVE! Example ex5\_partial\_valve\_control.py

### namedtuple

from collections import namedtuple

Named tuples can be used to give your tuple like data structures a name and make it possible to access its values by names instead of index WITHOUT writing a class by hand for it

- Usefull for naming data structures
- Usefull for getting . access instead of []

LIVE! Example ex6\_namedtuple.py

#### choise

from random import choice

Pick an element from an iterable at random.

LIVE! Example ex7\_choice.py

## Summary

- ▶ The standard library has lots of little tools
- It is worth it to look for them, when needing them instead of rolling your own