

Lesser known gems of the standard library

The ?? and ??s of “batteries included”

Kenneth Nielsen¹

¹Center for Individual Nanoparticle Functionality (CINF)
Institute of Physics
Technical University of Denmark (DTU)

Python and beers presentation,
Aprils 29, 2015

About me

- ▶ My name is Kenneth Nielsen and I work at CINF
- ▶ Free and open source software (FOSS) enthusiast
- ▶ Use way too much time on python conference presentations on youtube

Slides and examples

```
git clone https://github.com/KennethNielsen/presentations.git
```

```
https://github.com/KennethNielsen/presentations
```

```
http://bit.ly/1FcIzDR
```

About me

- ▶ Name is Kenneth Nielsen and I work at CINF
- ▶ Free and open source software (FOSS) enthusiast
- ▶ Long time FOSS translator
- ▶ BIG TIME Pythonista
- ▶ PyG3T <https://launchpad.net/pyg3t>. Tools for the translation workflow.
- ▶ PoProofRead <https://launchpad.net/poproofread>. Translation proofreading tool
- ▶ SoCo <https://github.com/SoCo/SoCo>. Driver for Sonos speakers.
- ▶ PyExpLabSys <https://github.com/CINF/PyExpLabSys>.

Python Experimental Lab Systems (Best acronym ever!)

- ▶ Drivers for experimental equipment
- ▶ File parsers for 3-rd party data files
- ▶ Infrastructure for a network driven, decentralized, lab:
 - ▶ Database logging
 - ▶ Wrappers around sockets and socket servers
 - ▶ Modules for live data transfer to webpages

Outline

A peak into some of the lesser known (at least in the circle of scientists) gems of the standard library

- ▶ Convenient containers (... and more)
 - ▶ defaultdict, Counter
- ▶ Special operators for key functions (get rid of lambdas)
 - ▶ itemgetter, attrgetter
- ▶ Function tools
 - ▶ partial
- ▶ Part way between anonymous data and full classes
 - ▶ namedtuple
- ▶ Random stuff ;)
 - ▶ choice

Defaultdict

```
from collections import defaultdict  
groups = defaultdict(default_callable)
```

A dictionary that will fill in values for unknown keys with defaults supplied by a callable

- ▶ Useful e.g. for grouping, where you would otherwise have to write annoying first-item-init code
- ▶ Supply a callable when creating it, that will be called to ask for a default value

LIVE! Example `ex1_default_dict.py`

Counter

```
from collections import Counter  
counter = Counter()
```

A default dict with default value 0 (and some special counter relevant math)

- ▶ Useful for counting!
- ▶ Can be added and subtracted
- ▶ Flattens out at 0 when subtracted

LIVE! Example `ex2_counter.py`