EXERCISE 2:

1) Define an integer array. Declare an integer pointer and initialize it to point the first element of the array. Use pointer arithmetic to traverse the array and print the elements.

```
#include <stdio.h>
int main()
{
    int arr[10], n, i;
    int *p = arr;
    printf("Enter n: ");
    scanf("%d", &n);
   printf("Enter elements: ");
    for(i = 0; i < n; i++)
    {
        scanf("%d", arr + i);
    }
     printf("Array elements: ");
     for(i = 0; i < n; i++)
    {
        printf("%d ", *(arr + i));
    }
   return 0;
  }
```

OUTPUT:
Enter n: 4
Enter elements:
10 30 40 70
Array elements: 10 30 40 70

2) Calculate string length using pointer.

```
#include <stdio.h>
int main()
{
char str[100];
 int i = 0;
  char *p;
  printf("Enter a string: ");
  scanf("%s", str);
  p = str;
  while(*(p + i) != '\0')
```

```
    {
       i++;
    }
 printf("Length of string: %d", i);
  return 0;
}
```

OUTPUT:

Enter a string: KENNI

Length of string: 5

3) Write a function that calculates both the sum and product of two numbers. Return these two results using pointers passed as arguments to the function.

```
#include <stdio.h>
void calc(int n1, int n2, int *s, int *p)
{
    *s = n1 + n2;
    *p = n1 * n2;
}
int main()
{
    int a, b, sum, prod;
    printf("Enter two numbers: ");
    scanf("%d %d", &a, &b);

    calc(a, b, &sum, &prod);
    printf("Sum: %d\n", sum);
    printf("Product: %d\n", prod);
   return 0;
}
```

OUTPUT:

Enter two numbers: 4 5

Sum: 9

Product: 20

4) Create an array of structures. Use dynamic memory allocation to allocate memory space and use a structure pointer with pointer arithmetic to iterate and access/modify members.

```
#include <stdio.h>
#include <stdlib.h>
struct stud
{
int rno;
char name[20];
};
int main()
{
struct stud *s, *ptr;
int n, i;
printf("Enter n: ");
scanf("%d", &n);

s = (struct stud *)malloc(n * sizeof(struct stud));
if(s == NULL)
{
printf("Memory allocation failed");
return 1;
}
ptr = s;
printf("---- Enter Student Details ----\n");
for(i = 0; i < n; i++)
{
printf("Roll no: ");
scanf("%d", &(ptr + i)->rno);
printf("Name: ");
```

```
scanf("%s", (ptr + i)->name);
}
printf("\n---- Displaying Student Details ----\n");
for(i = 0; i < n; i++)
{
printf("\nStudent %d:\n", i + 1);
printf("Roll no: %d\n", (ptr + i)->rno);
printf("Name: %s\n", (ptr + i)->name);
}
free(s);
return 0;
}
```

OUTPUT:

```
Enter n: 3
---- Enter Student Details ----
Roll no: 10
Name: ANU
Roll no: 52
Name: CRISS
Roll no: 94
Name: KENNI
---- Displaying Student Details ----
Student 1:
Roll no: 10
Name: ANU
Student 2:
Roll no: 52
Name: CRISS
Student 3:
Roll no: 94
Name: KENNI
=== Code Execution Successful ===
```

5) Define two functions with same signature. Declare a function pointer and use the pointer to call both functions.

```
#include <stdio.h>
int add(int a, int b)
{
return a + b;
}
int multiply(int a, int b)
{
return a * b;
}
int main()
{
int (*operation_ptr)(int, int);
int num1 = 5, num2 = 4;
int result;
operation_ptr = add;
result = operation_ptr(num1, num2);
printf("Addition result: %d\n", result);
operation_ptr = multiply;
result = operation_ptr(num1, num2);
printf("Multiplication result: %d\n", result);
return 0;
}
```

OUTPUT:

Addition result: 9

Multiplication result: 20

6) Declare an integer, a pointer to it and a double pointer. Print the values and addresses at each level.

```
#include <stdio.h>
```

```
int main()
{
int num = 10;
int *p;
int **pp;
p = &num;
pp = &p;
printf("num: %d\n", num);
printf("Address of num: %p\n", (void *)&num);
printf("*p (value stored in num): %d\n", *p);
printf("p: %p\n", (void *)p);
printf("&p: %p\n", (void *)&p);
printf("**pp: %d\n", **pp);
printf("*pp: %p\n", (void *)*pp);
printf("pp: %p\n", (void *)pp);
printf("Address of pp: %p\n", (void *)&pp);
return 0;
}
```

OUTPUT:

```
num: 10
Address of num: 0x7ffe5137cfbc
*p (value stored in num): 10
p: 0x7ffe5137cfbc
&p: 0x7ffe5137cfb0
**pp: 10
*pp: 0x7ffe5137cfbc
pp: 0x7ffe5137cfb0
Address of pp: 0x7ffe5137cfa8
```

7) Sort an array of floating point number using selection sort.

```
#include<stdio.h>
#include <stdlib.h>
int main()
```

```
{
float *arr, temp;
int i, j, n, smallest;
printf("Enter size: ");
scanf("%d", &n);
arr = (float *)malloc(n * sizeof(float));
if(arr == NULL)
{
printf("Memory allocation failed");
return 1;
}
printf("Enter elements: ");
for(i = 0; i < n; i++)
{
scanf("%f", &arr[i]);
}
for(i = 0; i < n - 1; i++)
{
smallest = i;
for(j = i + 1; j < n; j++)
{
if(arr[j] < arr[smallest])
{
smallest = j;
}
}
temp = arr[i];
arr[i] = arr[smallest];
arr[smallest] = temp;
}
printf("Sorted array: ");
for(i = 0; i < n; i++)
```

```
{
printf("%.2f ", arr[i]);
}
free(arr);
return 0;
}
```

OUTPUT:

Enter size: 4

Enter elements: 35 57 53 30

Sorted array: 30.00 35.00 53.00 57.00

8) Define a structure student with fields such as id, name and grade. Create an array of student structures and sort them based on different fields.

```
#include <stdio.h>
#include <string.h>
struct Student
{
    int id;
    char name[20];
    float grade;
};
int main()
{
    struct Student s[5], temp;
    int n, i, j, choice;
    printf("Enter number of students: ");
    scanf("%d", &n);
    printf("\nEnter student details:\n");
     for(i = 0; i < n; i++)
    {
        printf("\nStudent %d\n", i + 1);
```

```
    printf("ID: ");
    scanf("%d", &s[i].id);
    printf("Name: ");
    scanf("%s", s[i].name);
    printf("Grade: ");
    scanf("%f", &s[i].grade);
  }
  printf("\nSort by:\n");
  printf("1. ID\n");
  printf("2. Name\n");
  printf("3. Grade\n");
  printf("Enter your choice: ");
  scanf("%d", &choice);
 for(i = 0; i < n - 1; i++)
  {
    for(j = i + 1; j < n; j++)
    {
       if((choice == 1 && s[i].id > s[j].id) ||
          (choice == 2 && strcmp(s[i].name, s[j].name) > 0) ||
          (choice == 3 && s[i].grade > s[j].grade))
       {
          temp = s[i];
          s[i] = s[j];
          s[j] = temp;
       }
    }
  }
printf("\nSorted Student Details:\n");
 for(i = 0; i < n; i++)
  {
    printf("ID: %d Name: %s Grade: %.2f\n",
          s[i].id, s[i].name, s[i].grade);
```

```
    }
  return 0;
}
```

OUTPUT:

```
Enter number of students: 3
Enter student details:
Student 1
ID: 10
Name: ANU
Grade: 9.4
Student 2
ID: 94
Name: KENNI
Grade: 9.0
Student 3
ID: 52
Name: CRISS
Grade: 9.9
Sort by:
1. ID
2. Name
3. Grade
Enter your choice: 1
Sorted Student Details:
ID: 10 Name: ANU Grade: 9.40
ID: 52 Name: CRISS Grade: 9.90
ID: 94 Name: KENNI Grade: 9.00
```

9) Sort a set of negative numbers using radix sort.

```
#include <stdio.h>
int getMax(int arr[], int n)
{
```

```
int max = arr[0];
int i;
for(i = 1; i < n; i++)
{
if(arr[i] > max)
max = arr[i];
}
return max;
}
void countingSort(int arr[], int n, int exp)
{
int output[100];
int count[10] = {0};
int i;
for(i = 0; i < n; i++)
count[(arr[i] / exp) % 10]++;
for(i = 1; i < 10; i++)
count[i] = count[i] + count[i - 1];
for(i = n - 1; i >= 0; i--)
{
output[count[(arr[i] / exp) % 10] - 1] = arr[i];
count[(arr[i] / exp) % 10]--;
}
for(i = 0; i < n; i++)
arr[i] = output[i];
}
void radixSort(int arr[], int n)
{
int i, j, k = 0;
int positive[100], negative[100];
int p = 0, q = 0;
for(i = 0; i < n; i++)
```

```
{
if(arr[i] < 0)
negative[q++] = -arr[i];
else
positive[p++] = arr[i];
}
if(p > 0)
{
int max = getMax(positive, p);
for(int exp = 1; max / exp > 0; exp *= 10)
countingSort(positive, p, exp);
}
if(q > 0)
{
int max = getMax(negative, q);
for(int exp = 1; max / exp > 0; exp *= 10)
countingSort(negative, q, exp);
}
for(i = q - 1; i >= 0; i--)
arr[k++] = -negative[i];

for(j = 0; j < p; j++)
arr[k++] = positive[j];
}
int main()
{
int arr[100], n, i;
printf("Enter number of elements: ");
scanf("%d", &n);
printf("Enter elements: ");
for(i = 0; i < n; i++)
scanf("%d", &arr[i]);
```

```
radixSort(arr, n);
printf("Sorted array: ");
for(i = 0; i < n; i++)
printf("%d ", arr[i]);
return 0;
}
```

OUTPUT:

```
Enter number of elements: 3
Enter elements: 6 -9 7
Sorted array: -9 6 7
```

10) Write a C program to copy one array to another using pointers.

```
#include <stdio.h>
int main()
{
    int arr1[100], arr2[100];
    int n, i;
    int *p, *q;
    printf("Enter number of elements: ");
    scanf("%d", &n);
    printf("Enter elements of first array: ");
    for(i = 0; i < n; i++)
    {
        scanf("%d", &arr1[i]);
    }
   /* Assign addresses of arrays to pointers */
    p = arr1;
    q = arr2;
   /* Copy first array to second array using pointers */
    for(i = 0; i < n; i++)
    {
        *(q + i) = *(p + i);
```

```
    }
    printf("First array: ");
    for(i = 0; i < n; i++)
    {
        printf("%d ", *(p + i));
    }
    printf("\nCopied array: ");
    for(i = 0; i < n; i++)
    {
        printf("%d ", *(q + i));
    }
    return 0;
  }
```

OUTPUT:

Enter number of elements: 3

Enter elements of first array: 4 5 6

First array: 4 5 6

Copied array: 4 5 6