ME 759
High Performance for Engineering Applications
Assignment 4
Due Thursday 02/25/2021 at 9:00 PM

Submit responses to all tasks which don't specify a file name to Canvas in a file called assignment4.{txt, docx, pdf, rtf, odt} (choose one of these formats). Submit all plots (if any) on Canvas. Do not zip your Canvas submission.

All *source files* should be submitted in the `HW04` subdirectory on the `master` branch of your `git` repo. For this assignment, your `HW04` folder should contain `task1.cu`, `task2.cu`, `matmul.cu`, and `stencil.cu`.

All commands or code must work on *Euler* with only the `cuda` module loaded. The commands may behave differently on your computer, so be sure to test on *Euler* before you submit.

Please submit clean code. Consider using a formatter like clang-format.

IMPORTANT: Before you begin, copy any provided files from `2021Spring/Assignments/HW04` directory of the ME759 Resource Repo. Do not change any of the provided files since these files will be overwritten with clean, reference copies when grading.

---

1. (a) Implement in a file called `matmul.cu` the `matmul` and `matmul_kernel` functions as declared and described in `matmul.cuh`.

   (b) Write a program `task1.cu` which will complete the following (some memory management steps are omitted for clarity, but you should implement them in your code):
   - Create matrices (as 1D row major arrays) `A` and `B` of size `n` $\times$ `n` on the host.
   - Fill these matrices with random numbers in the range [-1, 1].
   - Prepare arrays that are allocated as device memory (they will be passed to your `matmul` function.)
   - Call your `matmul` function.
   - Print the last element of the resulting matrix.
   - Print the time taken to perform the multiplication in *milliseconds* using CUDA events.
   - Compile: `nvcc task1.cu matmul.cu -Xcompiler -O3 -Xcompiler -Wall -Xptxas -O3 -std c++17 -o task1`
   - Run (where `n` and `threads_per_block` are positive integers): `./task1 n threads_per_block`
   - Example expected output:
     ```
     11.36
     1.23
     ```

   (c) On an Euler *compute node*, run `task1` for each value `n` $= 2^5, 2^6, \cdots, 2^{14}$ and generate a plot `task1.pdf` which plots the time taken by your algorithm as a function of `n` when `threads_per_block` $= 1024$. Overlay another plot which plots the same relationship with a different choice of `threads_per_block`.

2. (a) Implement in a file called `stencil.cu` the `stencil` and `stencil_kernel` functions as declared and described in `stencil.cuh`. These functions should produce the 1D convolution of `image` and `mask` as the following:

$$\texttt{output}[i] = \sum_{j=-R}^{R} \texttt{image}[i+j] * \texttt{mask}[j+R] \qquad i = 0, \cdots, \texttt{n} - 1 \ .$$

Assume that $\texttt{image}[i] = 1$ when $i < 0$ or $i > \texttt{n} - 1$. Pay close attention to what data you are asked to store and compute in shared memory.

(b) Write a program `task2.cu` which will complete the following (some memory management steps are omitted for clarity, but you should implement them in your code):

- Create arrays `image` (length `n`), `output` (length `n`), and `mask` (length `2 * R + 1`) on the host.
- Fill the `image` and `mask` array with random numbers in the range [-1, 1].
- Prepare arrays that are allocated as device memory (they will be passed to your `stencil` function.)
- Call your `stencil` function.
- Print the last element of the resulting `output` array.
- Print the time taken to perform the convolution in *milliseconds* using CUDA events.
- Compile: `nvcc task2.cu stencil.cu -Xcompiler -O3 -Xcompiler -Wall -Xptxas -O3 -std c++17 -o task2`
- Run (where `n`, `R`, and `threads_per_block` are positive integers):
  `./task2 n R threads_per_block`
- Example expected output:
  `11.36`
  `1.23`

(c) On an Euler *compute node*, run `task2` for each value $\texttt{n} = 2^{10}, 2^{11}, \cdots, 2^{29}$ and generate a plot `task2.pdf` which plots the time taken by your algorithm as a function of `n` when `threads_per_block` $= 1024$ and `R` $= 128$. Overlay another plot which plots the same relationship with a different choice of `threads_per_block`.