

Data Structures – Week #1



Introduction



- 1- Introduction and a review (Objectives, Math Review and static vs dynamic D/S)
- 2- Basic Algorithm Analysis + Recurrences
- 3- Elementary data structures (LLs, Stacks, Queues, etc)
- 5- Trees
- 6- Special Trees
- 7- Graphs & Graph Algorithms
- 8- Hashing
- 9- Heaps - Priority Queues
- 10- Sorting Techniques



Reference Books:

- Among many reference books, We will mostly use the two below:

1- Thomas H. Cormen, Charles E. Leiserson, Ronald L. Livest and Clifford Stein, *Introduction to Algorithms*, 3rd edition, MIT Press, 2009

2- Mark Allen Weiss, *Data Structures & Algorithms Analysis in C* 2nd edition, Addison-Wesley Publishing Company, 1999

March 10, 2021

Borahan Tümer, Ph.D.

3




Grading: (tentative)

- | | | |
|---------------------|------------|---------------------|
| ■ Midterm | 20% | |
| ■ Final | 40% | (covers all) |
| ■ Attendance | 10% | |
| ■ Quizes | 10% | |
| ■ Projects | 20% | |

March 10, 2021

Borahan Tümer, Ph.D.


4



Important Points

- **Do all of your projects by yourselves.**
- **Data Structures course is one of the main core courses of Computer Engineering.**
- **So, please try to build a strong Computer Science background from the points of both theory and programming practices by doing projects by yourselves.**
- **Your source code will be checked against cheating very strictly. We use cheating detection software that detects the cheaters. Cheating will be strictly punished by our department.**

March 10, 2021 Borahan Tümer, Ph.D. 5




Important Points

- **Submission of all projects is mandatory to pass the class.**
- **Attendance is mandatory**

March 10, 2021 Borahan Tümer, Ph.D. 6

Components of a Computer and their Interconnections



March 10, 2021

Borahan Tümer, Ph.D.

7


Goals

- We will learn methods of how to
 - (*explicit goal*) organize or **structure large amounts of data in the main memory (MM)** considering efficiency; i.e.,
 - *memory space* and
 - *execution time*
 - (*implicit goal*) gain additional experience on
 - what data structures to use for solving what kind of problems
 - programming

March 10, 2021

Borahan Tümer, Ph.D.

8




Goals continued...1

- **Explicit Goal**
 - We look for answers to the following question:

“*How do we store data in MM* such that

 1. *execution time* grows as *slow* as possible with the growing size of input data, and
 2. data uses up *minimum memory space*?”

March 10, 2021 Borahan Tümer, Ph.D. 9




Goals continued...2

- As a tool to calculate the execution time of algorithms, we will learn the basic principles of **algorithm analysis**.
- To efficiently structure data in MM, we will thoroughly discuss the
 - *static*, (arrays)
 - *dynamic* (structures using pointers)
 ways of *memory allocations*, two fundamental implementation tools for data structures.

March 10, 2021 Borahan Tümer, Ph.D. 10

Representation of Main Memory



March 10, 2021

Borahan Tümer, Ph.D.

11

Examples for efficient vs. inefficient data structures

- 8-Queen problem
 - 1D array vs. 2D array representation results in saving memory space
 - Search for proper spot (square) using horse moves save time over square-by-square search
- Fibonacci series: A lookup table avoids redundant recursive calls and saves time

March 10, 2021

Borahan Tümer, Ph.D.

12

Examples for efficient vs. inefficient data structures

8-Queen problem (4-queen and 5-queen versions)

	x		
			x
x			
		x	



		x	
x			
			x
	x		

x			
		x	
			x
	x		
			x



	x		
			x
		x	
x			
			x

March 10, 2021

Borahan Tümer, Ph.D.

13

Examples for efficient vs. inefficient data structures

8-Queen problem (4-q and 5-q versions)

	x		
			x
x			
		x	



```
int a[4][4];
....
a[0][1]=1;
a[1][3]=1;
a[2][0]=1;
a[3][2]=1;
```

inefficient:
more memory
space (16 bytes
for 4-q version)
required

x			
		x	
			x
	x		
			x



```
int a[5];
....
a[0]=0;
a[1]=2;
a[2]=4;
a[3]=1;
a[4]=3;
```

efficient:
less memory
space (5 bytes
for 5-q version)
required

March 10, 2021

Borahan Tümer, Ph.D.

14



Math Review

- Exponents

$$x^a x^b = x^{a+b}; \quad \frac{x^a}{x^b} = x^{a-b}; \quad (x^a)^b = x^{ab};$$

- Logarithms


$$y = x^a \Leftrightarrow \log_x y = a, \quad y > 0; \quad \log_x y = \frac{\log_z y}{\log_z x}, \quad z > 0;$$

$$\log xy = \log x + \log y; \quad \log \frac{1}{x} = -\log x; \quad \log x^a = a \log x$$

March 10, 2021

Borahan Tümer, Ph.D.

15



Math Review

- Arithmetic Series: Series where the variable of summation is the base.

$$\sum_{i=1}^{k+1} i = \frac{k(k+1)}{2} + k+1 = \frac{(k+1)(k+2)}{2};$$

$$\frac{k(k+1)}{2} + \frac{2(k+1)}{2} = \frac{(k+1)(k+2)}{2}$$

March 10, 2021

Borahan Tümer, Ph.D.

16



Math Review

- Geometric Series: Series at which the variable of summation is the exponent.

$$\sum_{i=0}^n a^i = \frac{1-a^{n+1}}{1-a}, \quad 0 < a < 1; \quad \sum_{i=0}^n a^i = \frac{a^{n+1}-1}{a-1}, \quad a \in \mathbb{N}^+ - \{1\};$$

$$\lim_{n \rightarrow \infty} \sum_{i=0}^n a^i = \frac{1}{1-a}, \quad 0 < a < 1;$$

$$s = \lim_{n \rightarrow \infty} \sum_{i=0}^n a^i = 1 + a + a^2 + a^3 + a^4 + \dots = \frac{1}{1-a};$$

$$as = \lim_{n \rightarrow \infty} a \sum_{i=0}^n a^i = a + a^2 + a^3 + a^4 + \dots = \frac{a}{1-a};$$

$$\Rightarrow s - as = s(1-a) = 1$$

March 10, 2021

Borahan Tümer, Ph.D.

17



Math Review

- Geometric Series...cont'd
- An example to using above formulas to calculate another geometric series

$$s = \sum_{i=1}^{\infty} \frac{i}{2^i};$$

$$s = \frac{1}{2} + \frac{2}{2^2} + \frac{3}{2^3} + \dots + \frac{i}{2^i} + \dots$$

$$2s = 1 + \frac{2}{2} + \frac{3}{2^2} + \frac{4}{2^3} + \dots + \frac{i}{2^{i-1}} + \dots$$

$$s = 2s - s = 1 + \frac{1}{2} + \frac{1}{2^2} + \frac{1}{2^3} + \dots + \frac{1}{2^i} + \dots$$

$$s = \sum_{i=0}^{\infty} \frac{1}{2^i} = 2;$$

March 10, 2021

Borahan Tümer, Ph.D.

18

Math Review

■ Proofs

■ Proof by Induction

■ Steps

1. Prove the base case ($k=1$)
2. Assume hypothesis holds for $k=n$
3. Prove hypothesis for $k=n+1$

■ Proof by counterexample

- Prove the hypothesis wrong by an example

■ Proof by contradiction ($A \Rightarrow B \Leftrightarrow \sim B \Rightarrow \sim A$)

- Assume hypothesis is wrong,
- Try to prove this
- See the contradictory result

March 10, 2021

Borahan Tümer, Ph.D.

19

Math Review

■ Proof examples (Proofs... cont'd)

■ Proof by Induction

■ Hypothesis

$$\sum_{i=1}^n i = \frac{n(n+1)}{2}$$

■ Steps

1. Prove true for $n=1$:
2. Assume true for $n=k$:
3. Prove true for $n=k+1$:

$$\sum_{i=1}^1 i = 1$$

$$\sum_{i=1}^k i = \frac{k(k+1)}{2}$$

$$\sum_{i=1}^{k+1} i = \frac{k(k+1)}{2} + k+1 = \frac{(k+1)(k+2)}{2};$$

$$\frac{k(k+1)}{2} + \frac{2(k+1)}{2} = \frac{(k+1)(k+2)}{2}$$

March 10, 2021

Borahan Tümer, Ph.D.

20

Arrays

- Static data structures that
 - represent **contiguous** memory locations holding **data of same type**
 - provide **direct access** to data they hold
 - have a **constant size** determined up front (at the beginning of) the run time


March 10, 2021

Borahan Tümer, Ph.D.

21

Arrays... cont'd

- An **integer array example in C**
- `int arr[12]; //12 integers`



March 10, 2021

Borahan Tümer, Ph.D.

22




Multidimensional Arrays

- To represent data with multiple dimensions, multidimensional array may be employed.
- Multidimensional arrays are structures specified with
 - the data value, and
 - as many indices as the dimensions of array
- Example:
 - `int arr2D[r][c];`

March 10, 2021

Borahan Tümer, Ph.D.

23



Multidimensional Arrays


$$\begin{bmatrix}
 m[0][0] & m[0][1] & m[0][2] & \cdots & m[0][c-1] \\
 m[1][0] & m[1][1] & m[1][2] & \cdots & m[1][c-1] \\
 m[2][0] & m[2][1] & m[2][2] & \cdots & m[2][c-1] \\
 \vdots & \vdots & \vdots & \vdots & \vdots \\
 m[r-1][0] & m[r-1][1] & m[r-1][2] & \cdots & m[r-1][c-1]
 \end{bmatrix}$$

- **m** : a two dimensional (2D) array with r rows and c columns
- **Row-major** representation: 2D array is implemented **row-by-row**.
- **Column-major** representation: 2D array is implemented **column-first**.
- In **row-major** rep., $m[i][j]$ is the entry of the above matrix m at $i+1^{\text{st}}$ row and $j+1^{\text{st}}$ column. “ i ” and “ j ” are row and column indices, respectively.
- How many elements? $n = r * c$ elements

March 10, 2021

Borahan Tümer, Ph.D.

24



Row-major Implementation

- Question: How can we store the matrix in a 1D array in a row-major fashion or how can we map the 2D array m to a 1D array a ?


l elements

a	...	$m[0][0]$...	$m[0][c-1]$...	$m[r-1][0]$...	$m[r-1][c-1]$...
-----	-----	-----------	-----	-------------	-----	-------------	-----	---------------	-----

index: $k \rightarrow$ $k=l$ $k=l+c-1$ $k=l+(r-1)c+0$ $k=l+(r-1)c+c-1$

In general, $m[i][j]$ is placed at $a[k]$ where $k=l+ic+j$.


March 10, 2021
Borahan Tümer, Ph.D.
25



Implementation Details of Arrays

- Array names are pointers* that point to the first byte of the first element of the array.
 - `double vect[row_limit];` // vect is a pointer!!!
- Arrays* may be efficiently *passed to functions* using their *name* and their *size* where
 - the name specifies the beginning address of the array
 - the size states the bounds of the index values.
- Arrays can only be copied element by element.

March 10, 2021
Borahan Tümer, Ph.D.
26




Implementation Details... cont'd

```

#define maxrow ...;
#define maxcol ...;
...
int main()
{
    int minirow;
    double min;
    double probability_matrix[maxrow][maxcol];
    ... ; //probability matrix initialized!!!
    min=minrow(probability_matrix,maxrow,maxcol,&minirow);
    ...
    return 0;
}

```

March 10, 2021 Borahan Tümer, Ph.D. 27



Implementation Details... cont'd

```

double minrow(double darr[][maxcol], int xpos, int ypos, int *ind)
{ // finds minimum of sum of rows of the matrix and returns the sum
  // and the row index with minimum sum.
  double mn;
  ...
  mn=<a large number>;
  for (i=0; i<=xpos; i++) {
      sum=0;
      for (j=0; j<=ypos; j++)
          sum+=darr[i][j];
      if (mn > sum) { mn=sum; *ind=i; } // call by reference!!!
  }
  return mn;
}

```

March 10, 2021 Borahan Tümer, Ph.D. 28



Records

- As opposed to **arrays** in which we keep **data of the same type**, we keep related data of various types in a **record**.
- **Records** are used to encapsulate (keep together) **related data**.
- **Records** are composite, and hence, **user-defined data types**.
- In **C**, records are formed using the reserved word **“struct.”**

March 10, 2021

Borahan Tümer, Ph.D.

29



Struct


- We declare as an example a student record called **“stdType”**.
- We declare first the data types required for individual fields of the record **stdType**, and then the record **stdType** itself.

March 10, 2021

Borahan Tümer, Ph.D.

30

Struct... Example



```
enum genderType = {female, male}; // enumerated type declared...
typedef enum genderType genderType; // name of enumerated type shortened...
struct instrType {
    ...                               //left for you as exercise!!!
}


typedef struct instrType instrType;
struct classType { // fields (attributes in OOP) of a course declared...
    char classCode[8];
    char className[60];
    instrType instructor;
    struct classtype *clsptr;
}
typedef struct classType classType; // name of structure shortened...
```

March 10, 2021

Borahan Tümer, Ph.D.

31

Struct... Example continues



```
struct stdType {
    char id[8]; //key
    //personal info
    char name[15];
    char surname[25];
    genderType gender; //enumerated type
    ...
    //student info
    classType current_classes[10]; //...or class_type *cur_clsptr
    classType classes_taken[50]; //...or class_type *taken_clsptr
    float grade;
    unsigned int credits_earned;
    ...
    //next record's first byte's address
    struct stdType *sptr; //address of next student record
}
```

March 10, 2021

Borahan Tümer, Ph.D.

32




Memory Issues

- Arrays can be used within records.
 - Ex: `classType current_classes[10];` // from previous slide
- Each element of an array can be a record.
 - `stdType students[1000];`
- Using an array of `classType` for keeping taken classes wastes memory space (Why?)
 - Any alternatives?
- How will we keep student records in MM?
 - In an array?
 - Advantages?
 - Disadvantages?

March 10, 2021

Borahan Tümer, Ph.D.

33



Array Representation

Advantages

1. Direct access (i.e., faster execution)

Disadvantages

1. Not suitable for changing number of student records
 - The higher the extent of memory waste the smaller the number of student records required to store than that at the initial case.
 - The (constant) size of array requires extension which is impossible for static arrays in case the number exceeds the bounds of the array.

The other alternative is **pointers** that provide **dynamic memory allocation**

indices	0	1	2	n-3	n-2	n-1
students	std 1	std 2	std 3	std n-2	std n-1	std n

Array Representation

March 10, 2021

Borahan Tümer, Ph.D.

34



Pointers

- Pointers are variables that hold memory addresses.
- Declaration of a pointer is based on the type of data of which the pointer holds the memory address.
- Ex: `stdtype *stdptr;`


March 10, 2021

Borahan Tümer, Ph.D.


35



Linked List Representation



Value of header=**2E450**





March 10, 2021

Borahan Tümer, Ph.D.

36

Dynamic Memory Allocation

```
header=(*stdtype) malloc(sizeof(stdtype));
//Copy the info of first student to node pointed to by header
s =(*stdtype) malloc(sizeof(stdtype));
//Copy info of second student to node pointed to by header
Header->sptr=s;
...
```



March 10, 2021

Borahan Tümer, Ph.D.

37

Arrays vs. Pointers (LL)

- | | |
|--|--|
| ■ Static data structures | ■ Dynamic data structures |
| ■ Represented by an index and associated value | ■ Represented by a record of information and address of next node |
| ■ Consecutive memory cells | ■ Randomly located in heap (cause for need to keep address of next node) |
| ■ Direct access (+) | ■ Sequential access (-) |
| ■ Constant size (-) | ■ Flexible size (+) |
| ■ Memory not released during runtime (-) | ■ Memory space allocatable and releasable during runtime (+) |

March 10, 2021

Borahan Tümer, Ph.D.

38