



CUPTI contains below changes as part of the CUDA Toolkit 8.0 release.

- Sampling of the program counter (PC) is enhanced to point out the true latency issues, it indicates if the stall reasons for warps are actually causing stalls in the issue pipeline. Field latencySamples of new activity record CUpti_ActivityPCSampling2 provides true latency samples. This field is valid for devices with compute capability 6.0 and higher. See section PC Sampling for more details.
- ▶ Support for NVLink topology information such as the pair of devices connected via NVLink, peak bandwidth, memory access permissions etc is provided through new activity record CUpti_ActivityNvLink. NVLink performance metrics for data transmitted/received, transmit/receive throughput and respective header overhead for each physical link. See section NVLink for more details.
- ► CUPTI now supports profiling of OpenACC applications. OpenACC profiling information is provided in the form of new activity records CUpti_ActivityOpenAccData, CUpti_ActivityOpenAccLaunch and CUpti_ActivityOpenAccOther. This aids in correlating OpenACC constructs on the CPU with the corresponding activity taking place on the GPU, and mapping it back to the source code. New API cuptiOpenACCInitialize is used to initialize profiling for supported OpenACC runtimes. See section OpenACC for more details.
- Unified memory profiling now provides GPU page fault events on devices with compute capability 6.0 and 64 bit Linux platforms. Enum CUpti_ActivityUnifiedMemoryAccessType lists memory access types for GPU page fault events and enum CUpti_ActivityUnifiedMemoryMigrationCause lists migration causes for data transfer events.
- Unified Memory profiling support is extended to Mac platform.
- ▶ Support for 16-bit floating point (FP16) data format profiling. New metrics inst_fp_16, flop_count_hp_add, flop_count_hp_mul, flop_count_hp_fma, flop_count_hp, flop_hp_efficiency, half_precision_fu_utilization are supported. Peak FP16 flops per cycle for device can be queried using the enum CUPTI_DEVICE_ATTR_FLOP_HP_PER_CYCLE added to CUpti DeviceAttribute.
- Added new activity kinds CUPTI_ACTIVITY_KIND_SYNCHRONIZATION,
 CUPTI_ACTIVITY_KIND_STREAM and CUPTI_ACTIVITY_KIND_CUDA_EVENT,
 to support the tracing of CUDA synchronization constructs such as context,
 stream and CUDA event synchronization. Synchronization details are provided
 in the form of new activity record CUpti_ActivitySynchronization. Enum
 CUpti_ActivitySynchronizationType lists different types of CUDA
 synchronization constructs.

- ► APIs cuptiSetThreadIdType()/cuptiGetThreadIdType() to set/get the mechanism used to fetch the thread-id used in CUPTI records. Enum CUpti ActivityThreadIdType lists all supported mechanisms.
- ▶ Added API cuptiComputeCapabilitySupported() to check the support for a specific compute capability by the CUPTI.
- Added support to establish correlation between an external API (such as OpenACC, OpenMP) and CUPTI API activity records.

 APIs cuptiActivityPushExternalCorrelationId() and cuptiActivityPopExternalCorrelationId() should be used to push and pop external correlation ids for the calling thread. Generated records of type CUpti_ActivityExternalCorrelation contain both external and CUPTI assigned correlation ids.
- Added containers to store the information of events and metrics in the form of activity records CUpti_ActivityInstantaneousEvent,

 CUpti_ActivityInstantaneousEventInstance,

 CUpti_ActivityInstantaneousMetric and

 CUpti_ActivityInstantaneousMetricInstance. These activity records are not produced by the CUPTI, these are included for completeness and ease-of-use.

 Profilers built on top of CUPTI that sample events may choose to use these records to store the collected event data.
- ► Support for domains and annotation of synchronization objects added in NVTX v2. New activity record CUpti_ActivityMarker2 and enums to indicate various stages of synchronization object i.e. CUPTI_ACTIVITY_FLAG_MARKER_SYNC_ACQUIRE, CUPTI_ACTIVITY_FLAG_MARKER_SYNC_ACQUIRE_SUCCESS, CUPTI_ACTIVITY_FLAG_MARKER_SYNC_ACQUIRE_FAILED and CUPTI_ACTIVITY_FLAG_MARKER_SYNC_RELEASE are added.
- ▶ Unused field runtimeCorrelationId of the activity record CUpti_ActivityMemset is broken into two fields flags and memoryKind to indicate the asynchronous behaviour and the kind of the memory used for the memset operation. It is supported by the new flag CUPTI_ACTIVITY_FLAG_MEMSET_ASYNC added in the enum CUpti ActivityFlag.
- ► Added flag CUPTI_ACTIVITY_MEMORY_KIND_MANAGED in the enum CUpti_ActivityMemoryKind to indicate managed memory.
- ▶ API cuptiGetStreamId has been deprecated. A new API cuptiGetStreamIdEx is introduced to provide the stream id based on the legacy or per-thread default stream flag.

TABLE OF CONTENTS

Chapter 1. Usage	1
1.1. CUPTI Compatibility and Requirements	1
1.2. CUPTI Initialization	1
1.3. CUPTI Activity API	1
1.3.1. SASS Source Correlation	2
1.3.2. PC Sampling	3
1.3.3. NVLink	4
1.3.4. OpenACC	4
1.4. CUPTI Callback API	
1.4.1. Driver and Runtime API Callbacks	
1.4.2. Resource Callbacks	7
1.4.3. Synchronization Callbacks	8
1.4.4. NVIDIA Tools Extension Callbacks	8
1.5. CUPTI Event API	9
1.5.1. Collecting Kernel Execution Events	11
1.5.2. Sampling Events	12
1.6. CUPTI Metric API	
1.7. Samples	50
Chapter 2. Modules	
2.1. CUPTI Version	51
cuptiGetVersion	51
CUPTI_API_VERSION	52
2.2. CUPTI Result Codes	
CUptiResult	
cuptiGetResultString	
2.3. CUPTI Activity API	55
CUpti_Activity	56
CUpti_ActivityAPI	
CUpti_ActivityAutoBoostState	
CUpti_ActivityBranch	
CUpti_ActivityBranch2	56
CUpti_ActivityCdpKernel	56
CUpti_ActivityContext	56
CUpti_ActivityCudaEvent	56
CUpti_ActivityDevice	
CUpti_ActivityDevice2	56
CUpti_ActivityDeviceAttribute	56
CUpti_ActivityEnvironment	
CUpti_ActivityEvent	56
CUpti_ActivityEventInstance	57

CUpti_ActivityExternalCorrelation	57
CUpti_ActivityFunction	57
CUpti_ActivityGlobalAccess	57
CUpti_ActivityGlobalAccess2	57
CUpti_ActivityInstantaneousEvent	57
CUpti_ActivityInstantaneousEventInstance	57
CUpti_ActivityInstantaneousMetric	57
CUpti_ActivityInstantaneousMetricInstance	57
CUpti_ActivityInstructionCorrelation	57
CUpti_ActivityInstructionExecution	
CUpti_ActivityKernel	57
CUpti_ActivityKernel2	57
CUpti_ActivityKernel3	
CUpti_ActivityMarker	58
CUpti_ActivityMarker2	58
CUpti_ActivityMarkerData	58
CUpti_ActivityMemcpy	
CUpti_ActivityMemcpy2	58
CUpti_ActivityMemset	
CUpti_ActivityMetric	58
CUpti_ActivityMetricInstance	58
CUpti_ActivityModule	58
CUpti_ActivityName	58
CUpti_ActivityNvLink	58
CUpti_ActivityObjectKindId	58
CUpti_ActivityOpenAcc	
CUpti_ActivityOpenAccData	59
CUpti_ActivityOpenAccLaunch	59
CUpti_ActivityOpenAccOther	59
CUpti_ActivityOverhead	59
CUpti_ActivityPCSampling	59
CUpti_ActivityPCSampling2	59
CUpti_ActivityPCSamplingConfig	59
CUpti_ActivityPCSamplingRecordInfo	59
CUpti_ActivityPreemption	59
CUpti_ActivitySharedAccess	59
CUpti_ActivitySourceLocator	59
CUpti_ActivityStream	59
CUpti_ActivitySynchronization	60
CUpti_ActivityUnifiedMemoryCounter	60
CUpti_ActivityUnifiedMemoryCounter2	60
CUpti_ActivityUnifiedMemoryCounterConfig	60
CUpti ActivityAttribute	60

CUpti_ActivityComputeApiKind	61
CUpti_ActivityEnvironmentKind	61
CUpti_ActivityFlag	61
CUpti_ActivityInstructionClass	63
CUpti_ActivityKind	65
CUpti_ActivityMemcpyKind	70
CUpti_ActivityMemoryKind	70
CUpti_ActivityObjectKind	71
CUpti_ActivityOverheadKind	71
CUpti_ActivityPartitionedGlobalCacheConfig	72
CUpti_ActivityPCSamplingPeriod	72
CUpti_ActivityPCSamplingStallReason	73
CUpti_ActivityPreemptionKind	
CUpti_ActivityStreamFlag	74
CUpti_ActivitySynchronizationType	74
CUpti_ActivityThreadIdType	75
CUpti_ActivityUnifiedMemoryAccessType	75
CUpti_ActivityUnifiedMemoryCounterKind	75
CUpti_ActivityUnifiedMemoryCounterScope	76
CUpti_ActivityUnifiedMemoryMigrationCause	76
CUpti_DevType	77
CUpti_EnvironmentClocksThrottleReason	
CUpti_ExternalCorrelationKind	
CUpti_LinkFlag	78
CUpti_OpenAccConstructKind	78
CUpti_OpenAccEventKind	79
CUpti_BuffersCallbackCompleteFunc	80
CUpti_BuffersCallbackRequestFunc	80
cuptiActivityConfigurePCSampling	80
cuptiActivityConfigureUnifiedMemoryCounter	81
cuptiActivityDisable	82
cuptiActivityDisableContext	82
cuptiActivityEnable	83
cuptiActivityEnableContext	83
cuptiActivityFlush	84
cuptiActivityFlushAll	85
cuptiActivityGetAttribute	86
cuptiActivityGetNextRecord	86
cuptiActivityGetNumDroppedRecords	87
cuptiActivityPopExternalCorrelationId	88
cuptiActivityPushExternalCorrelationId	
cuptiActivityRegisterCallbacks	89
cuptiActivitySetAttribute	90

	cuptiComputeCapabilitySupported	.91
	cuptiFinalize	.91
	cuptiGetAutoBoostState	. 92
	cuptiGetContextId	. 92
	cuptiGetDeviceId	93
	cuptiGetLastError	.94
	cuptiGetStreamId	. 94
	cuptiGetStreamIdEx	. 95
	cuptiGetThreadIdType	. 95
	cuptiGetTimestamp	96
	cuptiSetThreadIdType	. 96
	CUPTI_AUTO_BOOST_INVALID_CLIENT_PID	.97
	CUPTI_CORRELATION_ID_UNKNOWN	. 97
	CUPTI_GRID_ID_UNKNOWN	. 97
	CUPTI_NVLINK_INVALID_PORT	97
	CUPTI_SOURCE_LOCATOR_ID_UNKNOWN	.97
	CUPTI_SYNCHRONIZATION_INVALID_VALUE	97
	CUPTI_TIMESTAMP_UNKNOWN	. 97
2.	4. CUPTI Callback API	.97
	CUpti_CallbackData	. 98
	CUpti_ModuleResourceData	. 98
	CUpti_NvtxData	. 98
	CUpti_ResourceData	.98
	CUpti_SynchronizeData	. 98
	CUpti_ApiCallbackSite	. 98
	CUpti_CallbackDomain	
	CUpti_CallbackIdResource	.99
	CUpti_CallbackIdSync	. 99
	CUpti_CallbackFunc	100
	CUpti_CallbackId	100
	CUpti_DomainTable	100
	CUpti_SubscriberHandle	100
	cuptiEnableAllDomains	101
	cuptiEnableCallback	101
	cuptiEnableDomain	102
	cuptiGetCallbackName	103
	cuptiGetCallbackState	104
	cuptiSubscribe	105
	cuptiSupportedDomains	106
	cuptiUnsubscribe	106
2.	5. CUPTI Event API	107
	CUpti_EventGroupSet	107
	CUpti EventGroupSets	107

CUpti_DeviceAttribute	.107
CUpti_DeviceAttributeDeviceClass	108
CUpti_EventAttribute	109
CUpti_EventCategory	109
CUpti_EventCollectionMethod	110
CUpti_EventCollectionMode	110
CUpti_EventDomainAttribute	111
CUpti_EventGroupAttribute	111
CUpti_ReadEventFlags	112
CUpti_EventDomainID	112
CUpti_EventGroup	.112
CUpti_EventID	112
CUpti_KernelReplayUpdateFunc	112
cuptiDeviceEnumEventDomains	113
cuptiDeviceGetAttribute	114
cuptiDeviceGetEventDomainAttribute	114
cuptiDeviceGetNumEventDomains	116
cuptiDeviceGetTimestamp	116
cuptiDisableKernelReplayMode	117
cuptiEnableKernelReplayMode	117
cuptiEnumEventDomains	118
cuptiEventDomainEnumEvents	119
cuptiEventDomainGetAttribute	119
cuptiEventDomainGetNumEvents	121
cuptiEventGetAttribute	121
cuptiEventGetIdFromName	122
cuptiEventGroupAddEvent	123
cuptiEventGroupCreate	124
cuptiEventGroupDestroy	125
cuptiEventGroupDisable	126
cuptiEventGroupEnable	126
cuptiEventGroupGetAttribute	127
cuptiEventGroupReadAllEvents	128
cuptiEventGroupReadEvent	130
cuptiEventGroupRemoveAllEvents	131
cuptiEventGroupRemoveEvent	132
cuptiEventGroupResetAllEvents	133
cuptiEventGroupSetAttribute	.133
cuptiEventGroupSetDisable	134
cuptiEventGroupSetEnable	135
cuptiEventGroupSetsCreate	
cuptiEventGroupSetsDestroy	137
cuptiGetNumEventDomains	137

cuptiKernelReplaySubscribeUpdate	138
cuptiSetEventCollectionMode	138
CUPTI_EVENT_INVALID	139
CUPTI_EVENT_OVERFLOW	139
2.6. CUPTI Metric API	139
CUpti_MetricValue	140
CUpti_MetricAttribute	140
CUpti_MetricCategory	140
CUpti_MetricEvaluationMode	141
CUpti_MetricPropertyDeviceClass	141
CUpti_MetricPropertyID	
CUpti_MetricValueKind	
CUpti_MetricValueUtilizationLevel	
CUpti_MetricID	143
cuptiDeviceEnumMetrics	143
cuptiDeviceGetNumMetrics	
cuptiEnumMetrics	
cuptiGetNumMetrics	145
cuptiMetricCreateEventGroupSets	145
cuptiMetricEnumEvents	
cuptiMetricEnumProperties	147
cuptiMetricGetAttribute	
cuptiMetricGetIdFromName	149
cuptiMetricGetNumEvents	149
cuptiMetricGetNumProperties	150
cuptiMetricGetRequiredEventGroupSets	
cuptiMetricGetValue	151
cuptiMetricGetValue2	153
Chapter 3. Data Structures	156
CUpti_Activity	159
kind	159
CUpti_ActivityAPI	159
cbid	160
correlationId	160
end	160
kindkind	160
processId	160
returnValue	160
start	160
threadId	160
CUpti_ActivityAutoBoostState	161
enabled	161
pid	161

CUpti_ActivityBranch	161
correlationId	161
diverged	161
executed	161
kind	161
pcOffset	162
sourceLocatorId	162
threadsExecuted	162
CUpti_ActivityBranch2	162
correlationId	162
diverged	162
executed	162
functionId	162
kind	162
pad	162
pcOffset	163
sourceLocatorId	163
threadsExecuted	163
CUpti_ActivityCdpKernel	163
blockX	163
blockY	163
blockZ	163
completed	163
contextld	163
correlationId	163
deviceld	164
dynamicSharedMemory	164
end	164
executed	164
gridldgridld	164
gridX	164
gridY	164
gridZ	164
kind	164
localMemoryPerThread	164
localMemoryTotal	165
name	165
parentBlockX	165
parentBlockY	165
parentBlockZ	
parentGridId	
queued	
registersPerThread	165

	requested	165
	sharedMemoryConfig	165
	start	166
	staticSharedMemory	166
	streamId	166
	submitted	166
C	Upti_ActivityContext	166
	computeApiKind	166
	contextld	166
	deviceld	166
	kind	166
	nullStreamId	167
C	Upti_ActivityCudaEvent	167
	contextld	167
	correlationId	167
	eventId	167
	kind	167
	pad	167
	streamld	167
C	Upti_ActivityDevice	167
	computeCapabilityMajor	168
	computeCapabilityMinor	168
	constantMemorySize	168
	coreClockRate	168
	flags	168
	globalMemoryBandwidth	168
	globalMemorySize	168
	id	168
	kind	168
	l2CacheSize	168
	maxBlockDimX	169
	maxBlockDimY	169
	maxBlockDimZ	169
	maxBlocksPerMultiprocessor	169
	maxGridDimX	169
	maxGridDimY	169
	maxGridDimZ	.169
	maxIPC	169
	maxRegistersPerBlock	.169
	maxSharedMemoryPerBlock	169
	maxThreadsPerBlock	170
	maxWarpsPerMultiprocessor	170
	name	170

numMemcpyEngines	170
numMultiprocessors	170
numThreadsPerWarp	170
CUpti_ActivityDevice2	170
computeCapabilityMajor	170
computeCapabilityMinor	170
constantMemorySize	171
coreClockRate	171
eccEnabled	171
flagsflags	171
globalMemoryBandwidth	171
globalMemorySize	171
id	171
kind	171
l2CacheSize	171
maxBlockDimX	171
maxBlockDimY	172
maxBlockDimZ	172
maxBlocksPerMultiprocessor	172
maxGridDimX	172
maxGridDimY	172
maxGridDimZ	172
maxIPC	172
maxRegistersPerBlock	172
maxRegistersPerMultiprocessor	172
maxSharedMemoryPerBlock	172
maxSharedMemoryPerMultiprocessor	173
maxThreadsPerBlock	173
maxWarpsPerMultiprocessor	173
name	173
numMemcpyEngines	173
numMultiprocessors	173
numThreadsPerWarp	173
pad	173
uuid	173
CUpti_ActivityDeviceAttribute	174
attribute	174
deviceld	174
flagsflags	174
kind	174
value	174
CUpti_ActivityEnvironment	175
clocksThrottlePeasons	175

	cooling	175
	deviceld	175
	environmentKind	175
	fanSpeed	175
	gpuTemperature	175
	kind	175
	memoryClock	175
	pcieLinkGen	176
	pcieLinkWidth	176
	power	176
	power	176
	powerLimit	176
	smClock	176
	speed	176
	temperature	.176
	timestamp	176
Cι	lpti_ActivityEvent	.177
	correlationId	177
	domain	177
	id	.177
	kind	177
	value	177
Cι	Jpti_ActivityEventInstance	177
	correlationId	178
	domain	178
	id	178
	instance	178
	kind	178
	pad	178
	value	178
Cι	Jpti_ActivityExternalCorrelation	178
	correlationId	
	externalld	.179
	externalKind	.179
	kind	179
	reserved	179
Cι	Jpti_ActivityFunction	179
	contextId	
	functionIndex	
	id	
	kind	
	moduleId	
		180

CUpti_ActivityGlobalAccess	180
correlationId	180
executed	180
flags	180
kind	180
l2_transactions	180
pcOffset	181
sourceLocatorId	181
threadsExecuted	181
CUpti_ActivityGlobalAccess2	181
correlationId	181
executed	181
flags	181
functionId	181
kind	181
l2_transactions	181
_ pad	
pcOffset	
sourceLocatorld	182
theoreticalL2Transactions	
threadsExecuted	
CUpti_ActivityInstantaneousEvent	182
deviceld	
id	182
kind	183
reserved	
timestamp	
value	
CUpti_ActivityInstantaneousEventInstance	
deviceld	
id	
instance	184
kind	
pad	184
timestamp	
value	
CUpti_ActivityInstantaneousMetric	
deviceld	
flags	
id	
kind	
pad	
timestamp	

value	185
CUpti_ActivityInstantaneousMetricInstance	185
deviceld	186
flags	186
id	186
instance	186
kind	186
pad	186
timestamp	186
value	186
CUpti_ActivityInstructionCorrelation	187
flags	187
functionId	187
kind	187
pad	187
pcOffset	187
sourceLocatorId	187
CUpti_ActivityInstructionExecution	188
correlationId	188
executed	188
flags	188
functionId	188
kind	188
notPredOffThreadsExecuted	188
pad	188
pcOffset	189
sourceLocatorId	189
threadsExecuted	189
CUpti_ActivityKernel	189
blockX	189
blockY	189
blockZ	189
cacheConfigExecuted	189
cacheConfigRequested	190
contextld	190
correlationId	190
deviceld	
dynamicSharedMemory	190
end	
gridXgridX	190
gridY	
gridZ	
kind	100

	localMemoryPerThread	191
	localMemoryTotal	.191
	name	191
	pad	191
	registersPerThread	191
	reserved0	191
	runtimeCorrelationId	191
	start	191
	staticSharedMemory	191
	streamld	191
Cι	Jpti_ActivityKernel2	192
	blockX	192
	blockY	192
	blockZ	192
	completed	192
	contextld	192
	correlationId	192
	deviceld	192
	dynamicSharedMemory	192
	end	193
	executed	193
	gridld	193
	gridX	193
	gridY	193
	gridZ	193
	kind	193
	localMemoryPerThread	193
	localMemoryTotal	.193
	name	193
	registersPerThread.	194
	requested	194
	reserved0	194
	sharedMemoryConfig	.194
	start	194
	staticSharedMemory	194
	streamld	194
cι	Jpti_ActivityKernel3	194
	blockX	
	blockY	195
	blockZ	
	completed	
	contextId	
		195

deviceld	195
dynamicSharedMemory	195
end	195
executed	195
gridld	195
gridX	196
gridY	196
gridZ	196
kind	196
localMemoryPerThread	196
localMemoryTotal	196
name	196
partitionedGlobalCacheExecuted	196
partitionedGlobalCacheRequested	196
registersPerThread	197
requested	197
reserved0	197
sharedMemoryConfig	197
start	197
staticSharedMemory	197
streamld	197
CUpti_ActivityMarker	197
flags	197
id	198
kind	198
name	198
objectId	198
objectKind	198
timestamp	198
CUpti_ActivityMarker2	198
domain	198
flags	199
id	199
kind	199
name	199
objectId	199
objectKind	199
pad	199
timestamp	199
CUpti_ActivityMarkerData	200
category	200
color	200
flags	200

	id	200
	kind	200
	payload	200
	payloadKind	200
Cl	Jpti_ActivityMemcpy	200
	bytes	201
	contextld	201
	copyKind	201
	correlationId	201
	deviceld	201
	dstKind	201
	end	201
	flags	201
	kind	202
	reserved0	202
	runtimeCorrelationId	202
	srcKind	202
	start	202
	streamld	202
Cl	Jpti_ActivityMemcpy2	202
	bytes	202
	contextld	203
	copyKind	203
	correlationId	203
	deviceld	203
	dstContextId	203
	dstDeviceId	203
	dstKind	203
	end	203
	flags	204
	kind	204
	pad	204
	reserved0	204
	srcContextId	204
	srcDeviceId	204
	srcKind	204
	start	204
	streamld	204
Cι	Jpti_ActivityMemset	205
	bytes	205
	contextld	
	correlationId	205
	deviceld	205

	end	205
	flags	205
	kind	205
	memoryKind	206
	reserved0	206
	start	206
	streamld	206
	value	206
Cι	Jpti_ActivityMetric	206
	correlationId	206
	flags	206
	id	207
	kind	207
	pad	207
	value	207
cι	Jpti_ActivityMetricInstance	.207
	correlationId	
	flags	207
	id	208
	instance	208
	kind	208
	pad	208
	value	208
cι	Jpti_ActivityModule	208
	contextId	208
	cubin	208
	cubinSize	208
	id	208
	kind	209
	pad	209
cι	Jpti_ActivityName	209
	kind	
	name	209
	objectId	209
	objectKind	
	Jpti_ActivityNvLink	
	bandwidth	
	domainId	
	flag	
	idDev0	
	idDev1	
	index	
	kind	210

	nvlinkVersion	210
	physicalNvLinkCount	210
	portDev0	210
	portDev1	211
	typeDev0	.211
	typeDev1	.211
C١	Jpti_ActivityObjectKindId	.211
	dcs	211
	pt	211
Cι	Jpti_ActivityOpenAcc	211
	cuContextId	212
	cuDeviceId	212
	cuProcessId	212
	cuStreamId	212
	cuThreadId	212
	end	212
	eventKind	212
	externalld	.213
	kind	213
	parentConstruct	213
	start	213
	threadId	213
CI	Jpti_ActivityOpenAccData	213
	bytes	213
	cuContextId	213
	cuDeviceId	214
	cuProcessId	214
	cuStreamId	214
	cuThreadId	214
	devicePtr	
	end	214
	eventKind	214
	externalld	.214
	hostPtr	214
	kind	
	pad1	215
	start	
	threadld	
CI	Jpti_ActivityOpenAccLaunch	
	cuContextId	
	cuDeviceId	
	cuProcessId	
	cuStreamld	215

cuThreadId	215
end	216
eventKind	216
externalld	216
kind	216
numGangs	216
numWorkers	216
pad1	216
start	216
threadld	216
vectorLength	217
CUpti_ActivityOpenAccOther	217
cuContextId	217
cuDeviceId	217
cuProcessId	
cuStreamId	217
cuThreadId	
end	217
eventKind	
externalld	
kind	
start	
threadld	
CUpti_ActivityOverhead	
end	
kind	
objectId	
objectKind	
overheadKind	
start	
CUpti_ActivityPCSampling	
correlationId.	
flags	
functionId	
kind	
pcOffset	
samples	
sourceLocatorId	
stallReason	
CUpti_ActivityPCSampling2	
correlationId	
flags	
functionId	220 220

kind	220
latencySamples	220
pcOffset	220
samples	221
sourceLocatorId	221
stallReason	221
CUpti_ActivityPCSamplingConfig	221
samplingPeriod	221
size	221
CUpti_ActivityPCSamplingRecordInfo	222
correlationId	222
droppedSamples	222
kind	222
samplingPeriodInCycles	222
totalSamples	222
CUpti_ActivityPreemption	222
blockX	223
blockY	223
blockZ	223
gridldgridld	223
kind	223
pad	223
preemptionKind	223
timestamp	223
CUpti_ActivitySharedAccess	223
correlationId	224
executed	224
flagsflags	224
functionId	224
kind	224
pad	224
pcOffset	
sharedTransactions	224
sourceLocatorId	224
theoreticalSharedTransactions	224
threadsExecuted	225
CUpti_ActivitySourceLocator	225
fileName	
id	
kind	
lineNumber	
CUpti_ActivityStream	
contextId	225

flag	225
kind	226
pad	226
priority	226
streamld	226
CUpti_ActivitySynchronization	226
contextId	226
correlationId	226
cudaEventId	226
end	226
kind	227
start	227
streamld	227
type	227
CUpti_ActivityUnifiedMemoryCounter	227
counterKind	227
deviceld	227
kind	228
pad	228
processId	228
scope	228
timestamp	228
value	228
CUpti_ActivityUnifiedMemoryCounter2	228
address	229
counterKind	229
dstld	229
end	229
flags	229
kind	230
pad	230
processId	230
srcId	230
start	230
streamld	230
value	230
CUpti_ActivityUnifiedMemoryCounterConfig	231
deviceld	231
enable	231
kind	231
scope	
CUpti_CallbackData	
callbackSite	222

context	232
contextUid	232
correlationData	232
correlationId	232
functionName	232
functionParams	232
functionReturnValue	233
symbolName	233
CUpti_EventGroupSet	233
eventGroups	233
numEventGroups	233
CUpti_EventGroupSets	233
numSets	233
sets	234
CUpti_MetricValue	234
CUpti_ModuleResourceData	234
cubinSize	234
moduleId	234
pCubin	234
CUpti_NvtxData	234
functionName	235
functionParams	235
CUpti_ResourceData	235
context	235
resourceDescriptor	235
stream	235
CUpti_SynchronizeData	235
context	236
stream	236
Chapter 4. Data Fields	237
Chapter 5. Limitations	
Chapter 6. Changelog	

LIST OF TABLES

Table 1	Capability 2.x Metrics	. 14
Table 2	Capability 3.x Metrics	. 21
Table 3	Capability 5.x Metrics	.31
Table 4	Capability 6.x Metrics	. 40

Chapter 1. USAGE

The *CUDA Profiling Tools Interface* (CUPTI) enables the creation of profiling and tracing tools that target CUDA applications. CUPTI provides four APIs: *the Activity API*, the *Callback API*, the *Event API*, and the *Metric API*. Using these APIs, you can develop profiling tools that give insight into the CPU and GPU behavior of CUDA applications. CUPTI is delivered as a dynamic library on all platforms supported by CUDA.

1.1. CUPTI Compatibility and Requirements

New versions of the CUDA driver are backwards compatible with older versions of CUPTI. For example, a developer using a profiling tool based on CUPTI 7.0 can update to a more recently released CUDA driver. However, new versions of CUPTI are not backwards compatible with older versions of the CUDA driver. For example, a developer using a profiling tool based on CUPTI 7.0 must have a version of the CUDA driver released with CUDA Toolkit 7.0 (or later) installed as well. CUPTI calls will fail with CUPTI_ERROR_NOT_INITIALIZED if the CUDA driver version is not compatible with the CUPTI version.

1.2. CUPTI Initialization

CUPTI initialization occurs lazily the first time you invoke any CUPTI function. For the Activity, Event, Metric, and Callback APIs there are no requirements on when this initialization must occur (i.e. you can invoke the first CUPTI function at any point). See the CUPTI Activity API section for more information on CUPTI initialization requirements for the activity API.

1.3. CUPTI Activity API

The CUPTI Activity API allows you to asynchronously collect a trace of an application's CPU and GPU CUDA activity. The following terminology is used by the activity API.

Activity Record

CPU and GPU activity is reported in C data structures called activity records. There is a different C structure type for each activity kind (e.g. CUpti_ActivityMemcpy). Records are generically referred to using the CUpti_Activity type. This type contains only a kind field that indicates the kind of the activity record. Using this kind, the object can be cast from the generic CUpti_Activity type to the specific type representing the activity. See the printActivity function in the activity_trace_async sample for an example.

Activity Buffer

An activity buffer is used to transfer one or more activity records from CUPTI to the client. CUPTI fills activity buffers with activity records as the corresponding activities occur on the CPU and GPU. The CUPTI client is responsible for providing empty activity buffers as necessary to ensure that no records are dropped.

An asynchronous buffering API is implemented by cuptiActivityRegisterCallbacks and cuptiActivityFlushAll.

It is not required that the activity API be initalized before CUDA initialization. All related activities occuring after initializing the activity API are collected. You can force initialization of the activity API by enabling one or more activity kinds using cuptiActivityEnable or cuptiActivityEnableContext, as shown in the initTrace function of the activity_trace_async sample. Some activity kinds cannot be directly enabled, see the API documentation for for CUpti_ActivityKind for details. Functions cuptiActivityEnable and cuptiActivityEnableContext will return CUPTI_ERROR_NOT_COMPATIBLE if the requested activity kind cannot be enabled.

The activity buffer API uses callbacks to request and return buffers of activity records. To use the asynchronous buffering API you must first register two callbacks using <code>cuptiActivityRegisterCallbacks</code>. One of these callbacks will be invoked whenever CUPTI needs an empty activity buffer. The other callback is used to deliver a buffer containing one or more activity records to the client. To minimize profiling overhead the client should return as quickly as possible from these callbacks. Function <code>cuptiActivityFlushAll</code> can be used to force CUPTI to deliver any activity buffers that contain completed activity records. Functions <code>cuptiActivityGetAttribute</code> and <code>cuptiActivitySetAttribute</code> can be used to read and write attributes that control how the buffering API behaves. See the API documentation for more information.

The activity_trace_async sample shows how to use the activity buffer API to collect a trace of CPU and GPU activity for a simple application.

1.3.1. SASS Source Correlation

While high-level languages for GPU programming like CUDA C offer a useful level of abstraction, convenience, and maintainability, they inherently hide some of the details of the execution on the hardware. It is sometimes helpful to analyze performance problems

for a kernel at the assembly instruction level. Reading assembly language is tedious and challenging; CUPTI can help you to build the correlation between lines in your high-level source code and the executed assembly instructions.

Building SASS source correlation for a PC can be split into two parts -

- Correlation of the PC to SASS instruction subscribe to any one of CUPTI_CBID_RESOURCE_MODULE_LOADED or CUPTI_CBID_RESOURCE_MODULE_UNLOAD_STARTING or CUPTI_CBID_RESOURCE_MODULE_PROFILED callbacks. This returns a CUpti_ModuleResourceData structure having the CUDA binary. The binary can be disassembled using nvdisasm utility that comes with the CUDA toolkit. An application can have multiple functions and modules, to uniquely identify there is a functionId field in all source level activity records. This uniquely corresponds to a CUPTI_ACTIVITY_KIND_FUNCTION which has the unique module ID and function ID in the module.
- ► Correlation of the SASS instruction to CUDA source line every source level activity has a sourcelocatorId field which uniquely maps to a record of kind CUPTI_ACTIVITY_KIND_SOURCE_LOCATOR containing the line and file name information. Please note that multiple PCs can correspond to single source line.

When any source level activity (global access, branch, PC Sampling etc) is enabled, source locator record is generated for the PCs that have the source level results. Record <code>CUpti_ActivityInstructionCorrelation</code> can be used along with source level activities to generate SASS assembly instructions to CUDA C source code mapping for all the PCs of the function and not just the PCs that have the source level results. This can be enabled using activity kind <code>CUPTI_ACTIVITY_KIND_INSTRUCTION_CORRELATION</code>.

The sass_source_map sample shows how to map SASS assembly instructions to CUDA C source.

1.3.2. PC Sampling

CUPTI supports device-wide sampling of the program counter (PC). The PC Sampling gives the number of samples for each source and assembly line with various stall reasons. Using this information you can pinpoint portions of your kernel that are introducing latencies and the reason for the latency. Samples are taken in round robin order for all active warps at a fixed number of cycles regardless of whether the warp is issuing an instruction or not.

From compute capability > 6.0, a new feature is added to get latency samples along with total samples. Latency samples are the samples collected when no warp is issuing, which gives the most probable reason for stalls in issue pipeline.

Activity record CUpti_ActivityPCSampling2 enabled using activity kind CUPTI ACTIVITY KIND PC SAMPLING outputs stall reason along with PC and

other related information. Enum CUpti_ActivityPCSamplingStallReason lists all the stall reasons. Sampling period is configurable and can be tuned using API cuptiActivityConfigurePCSampling. Activity record CUpti_ActivityPCSamplingRecordInfo provides the total and dropped samples for each kernel profiled for PC sampling. This feature is available on devices with compute capability 5.2.

The pc_sampling sample shows how to use the these APIs to collect PC Sampling profiling information for a kernel.

1.3.3. NVLink

NVIDIA NVLink is a high-bandwidth, energy-efficient interconnect that enables fast communication between the CPU and GPU, and between GPUs. CUPTI provides NVLink topology information and NVLink transmit/receive throughput metrics.

Activity record Cupti_ActivityNVLink enabled using activity kind CUPTI_ACTIVITY_KIND_NVLink outputs NVLink topology information in terms of logical NVLinks. A logical NVLink is connected between 2 devices, the device can be of type NPU (NVLink processing unit which can be CPU) or GPU. Each device can support upto 4 NVLinks hence one logical link can comprise of 1 to 4 physical NVLinks. physicalNvLinkCount field gives number of physical links in this logical link. portDev0 and portDev1 fields give information about the slot in which physical NVLinks are connected for a logical link. This port is same as instance of NVLink metrics profiled from a device. So port and instance information should be used to correlate the perinstance metric values with the physical NVLinks and in turn to the topology. flag field gives the properties of a logical link, whether the link has access to system memory or peer device memory, and have capabilities to do system memory or peer memmory atomics. bandwidth gives the bandwidth of the logical link in kilobytes/sec.

CUPTI also provides some metrics for each physical links. Metrics are provided for data transmitted/received, transmit/receive throughput and header versus user data overhead for each physical NVLink. These metrics are also provided per packet type (read/write/ atomics/response) to get more detailed insight in the NVLink traffic.

This feature is available on devices with compute capability 6.0.

The nvlink_bandwidth sample shows how to use the these APIs to collect NVLink metrics and topology and how to correlate the metrics with topology.

1.3.4. OpenACC

On Linux x86_64, CUPTI supports collecting information for OpenACC applications using the OpenACC tools interface implementation of the PGI runtime. In addition to being available only on 64bit Linux platforms, this feature also requires PGI runtime version 15.7 or higher.

Activity records CUpti_ActivityOpenAccData, CUpti_ActivityOpenAccLaunch and CUpti_ActivityOpenAccOther are created, representing the three groups of callback events specified in the OpenACC tools interface. CUPTI_ACTIVITY_KIND_OPENACC_DATA, CUPTI_ACTIVITY_KIND_OPENACC_LAUNCH and CUPTI_ACTIVITY_KIND_OPENACC_OTHER can be enabled to collect the respective activity records.

Due to restrictions of the OpenACC tools interface, CUPTI cannot record OpenACC records from within the client application. Instead, a shared library that exports the acc_register_library function defined in the OpenACC tools interface specification must be implemented. Parameters passed into this function from the OpenACC runtime can be used to initialize CUPTI OpenACC measurement using cuptiOpenACCInitialize. Before starting the client application, the environment variable ACC PROFLIB must be set to point to this shared library.

cuptiOpenACCInitialize is defined in cupti_openacc.h, which is included by cupti_activity.h. Since the CUPTI OpenACC header is only available on supported platforms, CUPTI clients must define CUPTI_OPENACC_SUPPORT when compiling.

The openacc_trace sample shows how to use CUPTI APIs for OpenACC data collection.

1.4. CUPTI Callback API

The CUPTI Callback API allows you to register a callback into your own code. Your callback will be invoked when the application being profiled calls a CUDA runtime or driver function, or when certain events occur in the CUDA driver. The following terminology is used by the callback API.

Callback Domain

Callbacks are grouped into domains to make it easier to associate your callback functions with groups of related CUDA functions or events. There are currently four callback domains, as defined by CUpti_CallbackDomain: a domain for CUDA runtime functions, a domain for CUDA driver functions, a domain for CUDA resource tracking, and a domain for CUDA synchronization notification.

Callback ID

Each callback is given a unique ID within the corresponding callback domain so that you can identify it within your callback function. The CUDA driver API IDs are defined in <code>cupti_driver_cbid.h</code> and the CUDA runtime API IDs are defined in <code>cupti_runtime_cbid.h</code>. Both of these headers are included for you when you include <code>cupti.h</code>. The CUDA resource callback IDs are defined by <code>CUpti_CallbackIdResource</code> and the CUDA synchronization callback IDs are defined by <code>CUpti_CallbackIdSync</code>.

Callback Function

Your callback function must be of type <code>CUpti_CallbackFunc</code>. This function type has two arguments that specify the callback domain and ID so that you know why the callback is occurring. The type also has a <code>cbdata</code> argument that is used to pass data specific to the callback.

Subscriber

A subscriber is used to associate each of your callback functions with one or more CUDA API functions. There can be at most one subscriber initialized with cuptiSubscribe() at any time. Before initializing a new subscriber, the existing subscriber must be finalized with cuptiUnsubscribe().

Each callback domain is described in detail below. Unless explicitly stated, it is not supported to call any CUDA runtime or driver API from within a callback function. Doing so may cause the application to hang.

1.4.1. Driver and Runtime API Callbacks

Using the callback API with the CUPTI_CB_DOMAIN_DRIVER_API or CUPTI_CB_DOMAIN_RUNTIME_API domains, you can associate a callback function with one or more CUDA API functions. When those CUDA functions are invoked in the application, your callback function is invoked as well. For these domains, the cbdata argument to your callback function will be of the type CUpti CallbackData.

It is legal to call cudaThreadSynchronize(), cudaDeviceSynchronize(), cudaStreamSynchronize(), cuCtxSynchronize(), and cuStreamSynchronize() from within a driver or runtime API callback function.

The following code shows a typical sequence used to associate a callback function with one or more CUDA API functions. To simplify the presentation error checking code has been removed.

First, cuptiSubscribe is used to initialize a subscriber with the my_callback callback function. Next, cuptiEnableDomain is used to associate that callback with all the CUDA runtime API functions. Using this code sequence will cause my_callback to be called twice each time any of the CUDA runtime API functions are invoked, once on entry to the CUDA function and once just before exit from the CUDA function. CUPTI callback API functions cuptiEnableCallback and cuptiEnableAllDomains can also be used to associate CUDA API functions with a callback (see reference below for more information).

The following code shows a typical callback function.

In your callback function, you use the <code>CUpti_CallbackDomain</code> and <code>CUpti_CallbackID</code> parameters to determine which <code>CUDA</code> API function invocation is causing this callback. In the example above, we are checking for the <code>CUDA</code> runtime <code>cudaMemcpy</code> function. The <code>cbdata</code> parameter holds a structure of useful information that can be used within the callback. In this case we use the <code>callbackSite</code> member of the structure to detect that the callback is occurring on entry to <code>cudaMemcpy</code>, and we use the <code>functionParams</code> member to access the parameters that were passed to <code>cudaMemcpy</code>. To access the parameters we first cast <code>functionParams</code> to a structure type corresponding to the <code>cudaMemcpy</code> function. These parameter structures are contained in <code>generated_cuda_runtime_api_meta.h</code>, <code>generated_cuda_meta.h</code>, and a number of other files. When possible these files are included for you by <code>cupti.h</code>.

The **callback_event** and **callback_timestamp** samples described on the samples page both show how to use the callback API for the driver and runtime API domains.

1.4.2. Resource Callbacks

Using the callback API with the CUPTI_CB_DOMAIN_RESOURCE domain, you can associate a callback function with some CUDA resource creation and destruction events. For example, when a CUDA context is created, your callback function will be invoked with a callback ID equal to CUPTI_CBID_RESOURCE_CONTEXT_CREATED. For this domain, the cbdata argument to your callback function will be of the type CUpti ResourceData.

Note that, APIs cuptiActivityFlush and cuptiActivityFlushAll will result in deadlock when called from stream destroy starting callback identified using callback ID CUPTI_CBID_RESOURCE_STREAM_DESTROY_STARTING.

1.4.3. Synchronization Callbacks

Using the callback API with the CUPTI_CB_DOMAIN_SYNCHRONIZE domain, you can associate a callback function with CUDA context and stream synchronizations. For example, when a CUDA context is synchronized, your callback function will be invoked with a callback ID equal to CUPTI_CBID_SYNCHRONIZE_CONTEXT_SYNCHRONIZED. For this domain, the cbdata argument to your callback function will be of the type CUpti_SynchronizeData.

1.4.4. NVIDIA Tools Extension Callbacks

Using the callback API with the CUPTI_CB_DOMAIN_NVTX domain, you can associate a callback function with NVIDIA Tools Extension (NVTX) API functions. When an NVTX function is invoked in the application, your callback function is invoked as well. For these domains, the cbdata argument to your callback function will be of the type CUpti_NvtxData.

The NVTX library has its own convention for discovering the profiling library that will provide the implementation of the NVTX callbacks. To receive callbacks you must set the NVTX environment variables appropriately so that when the application calls an NVTX function, your profiling library recieve the callbacks. The following code sequence shows a typical initialization sequence to enable NVTX callbacks and activity records.

```
/* Set env so CUPTI-based profiling library loads on first nvtx call. */
char *inj32_path = "/path/to/32-bit/version/of/cupti/based/profiling/library";
char *inj64_path = "/path/to/64-bit/version/of/cupti/based/profiling/library";
setenv("NVTX_INJECTION32_PATH", inj32_path, 1);
setenv("NVTX_INJECTION64_PATH", inj64_path, 1);
```

The following code shows a typical sequence used to associate a callback function with one or more NVTX functions. To simplify the presentation error checking code has been removed.

First, cuptiSubscribe is used to initialize a subscriber with the my_callback callback function. Next, cuptiEnableDomain is used to associate that callback with all the NVTX functions. Using this code sequence will cause my_callback to be called once each time any of the NVTX functions are invoked. CUPTI callback API functions cuptiEnableCallback and cuptiEnableAllDomains can also be used to associate NVTX API functions with a callback (see reference below for more information).

The following code shows a typical callback function.

In your callback function, you use the <code>CUpti_CallbackDomain</code> and <code>CUpti_CallbackID</code> parameters to determine which NVTX API function invocation is causing this callback. In the example above, we are checking for the <code>nvtxNameOsThreadA</code> function. The <code>cbdata</code> parameter holds a structure of useful information that can be used within the callback. In this case, we use the <code>functionParams</code> member to access the parameters that were passed to <code>nvtxNameOsThreadA</code>. To access the parameters we first cast <code>functionParams</code> to a structure type corresponding to the <code>nvtxNameOsThreadA</code> function. These parameter structures are contained in <code>generated_nvtx_meta.h</code>.

1.5. CUPTI Event API

The CUPTI Event API allows you to query, configure, start, stop, and read the event counters on a CUDA-enabled device. The following terminology is used by the event API.

Event

An event is a countable activity, action, or occurrence on a device.

Event ID

Each event is assigned a unique identifier. A named event will represent the same activity, action, or occurrence on all device types. But the named event may have different IDs on different device families. Use <code>cuptiEventGetIdFromName</code> to get the ID for a named event on a particular device.

Event Category

Each event is placed in one of the categories defined by CUpti_EventCategory. The category indicates the general type of activity, action, or occurrence measured by the event.

Event Domain

A device exposes one or more event domains. Each event domain represents a group of related events available on that device. A device may have multiple instances of a domain, indicating that the device can simultaneously record multiple instances of each event within that domain.

Event Group

An event group is a collection of events that are managed together. The number and type of events that can be added to an event group are subject to device-specific limits. At any given time, a device may be configured to count events from a limited number of event groups. All events in an event group must belong to the same event domain.

Event Group Set

An event group set is a collection of event groups that can be enabled at the same time. Event group sets are created by cuptiEventGroupSetsCreate and cuptiMetricCreateEventGroupSets.

You can determine the events available on a device using the cuptiDeviceEnumEventDomains and cuptiEventDomainEnumEvents functions. The **cupti_query** sample described on the samples page shows how to use these functions. You can also enumerate all the CUPTI events available on any device using the cuptiEnumEventDomains function.

Configuring and reading event counts requires the following steps. First, select your event collection mode. If you want to count events that occur during the execution of a kernel, use <code>cuptiSetEventCollectionMode</code> to set mode <code>CUPTI_EVENT_COLLECTION_MODE_KERNEL</code>. If you want to continuously sample the event counts, use mode <code>CUPTI_EVENT_COLLECTION_MODE_CONTINUOUS</code>. Next determine the names of the events that you want to count, and then use the <code>cuptiEventGroupCreate</code>, <code>cuptiEventGetIdFromName</code>, and <code>cuptiEventGroupAddEvent</code> functions to create and initialize an event group with those events. If you are unable to add all the events to a single event group then you will need to create multiple event groups. Alternatively, you can use the <code>cuptiEventGroupSetsCreate</code> function to automatically create the event group(s) required for a set of events.

To begin counting a set of events, enable the event group or groups that contain those events by using the <code>cuptiEventGroupEnable</code> function. If your events are contained in multiple event groups you may be unable to enable all of the event groups at the same time, due to device limitations. In this case, you can gather the events across multiple executions of the application or you can enable kernel replay. If you enable kernel replay using <code>cuptiEnableKernelReplayMode</code> you will be able to enabled any number of event groups and all the contained events will be collect.

Use the cuptiEventGroupReadEvent and/or cuptiEventGroupReadAllEvents functions to read the event values. When you are done collecting events, use the cuptiEventGroupDisable function to stop counting of the events contained in an event group. The callback_event sample described on the samples page shows how to use these functions to create, enable, and disable event groups, and how to read event counts.

In a system with multiple GPUs, events can be collected simultaneously on all the GPUs i.e. event profiling doesn't enforce any serialization of work across GPUs. The event_multi_gpu sample shows how to use the CUPTI event and CUDA APIs on such setups.

1.5.1. Collecting Kernel Execution Events

A common use of the event API is to count a set of events during the execution of a kernel (as demonstrated by the **callback_event** sample). The following code shows a typical callback used for this purpose. Assume that the callback was enabled only for a kernel launch using the CUDA runtime (i.e. by cuptiEnableCallback(1, subscriber, CUPTI_CB_DOMAIN_RUNTIME_API, CUPTI_RUNTIME_TRACE_CBID_cudaLaunch_v3020). To simplify the presentation error checking code has been removed.

```
static void CUPTIAPI
getEventValueCallback(void *userdata,
                     CUpti CallbackDomain domain,
                     CUpti CallbackId cbid,
                     const void *cbdata)
 const CUpti CallbackData *cbData =
             CUpti CallbackData *)cbdata;
 if (cbData->callbackSite == CUPTI API ENTER) {
   cudaDeviceSynchronize();
   cuptiSetEventCollectionMode(cbInfo->context,
                               CUPTI EVENT COLLECTION MODE KERNEL);
   cuptiEventGroupEnable(eventGroup);
 if (cbData->callbackSite == CUPTI API EXIT) {
   cudaDeviceSynchronize();
   cuptiEventGroupReadEvent(eventGroup,
                            CUPTI_EVENT_READ_FLAG_NONE,
                            eventId,
                            &bytesRead, &eventVal);
   cuptiEventGroupDisable(eventGroup);
```

Two synchronization points are used to ensure that events are counted only for the execution of the kernel. If the application contains other threads that launch kernels, then additional thread-level synchronization must also be introduced to ensure that those threads do not launch kernels while the callback is collecting events. When the cudaLaunch API is entered (that is, before the kernel is actually launched on the device), cudaDeviceSynchronize is used to wait until the GPU is idle. The event collection mode is set to CUPTI_EVENT_COLLECTION_MODE_KERNEL so that the event counters are automatically started and stopped just before and after the kernel executes. Then event collection is enabled with cuptiEventGroupEnable.

When the cudaLaunch API is exited (that is, after the kernel is queued for execution on the GPU) another cudaDeviceSynchronize is used to cause the CPU thread

to wait for the kernel to finish execution. Finally, the event counts are read with cuptiEventGroupReadEvent.

1.5.2. Sampling Events

The event API can also be used to sample event values while a kernel or kernels are executing (as demonstrated by the **event_sampling** sample). The sample shows one possible way to perform the sampling. The event collection mode is set to CUPTI_EVENT_COLLECTION_MODE_CONTINUOUS so that the event counters run continuously. Two threads are used in **event_sampling**: one thread schedules the kernels and memcpys that perform the computation, while another thread wakes up periodically to sample an event counter. In this sample there is no correlation of the event samples with what is happening on the GPU. To get some coarse correlation, you can use cuptiDeviceGetTimestamp to collect the GPU timestamp at the time of the sample and also at other interesting points in your application.

1.6. CUPTI Metric API

The CUPTI Metric API allows you to collect application metrics calculated from one or more event values. The following terminology is used by the metric API.

Metric

An characteristic of an application that is calculated from one or more event values.

Metric ID

Each metric is assigned a unique identifier. A named metric will represent the same characteristic on all device types. But the named metric may have different IDs on different device families. Use <code>cuptiMetricGetIdFromName</code> to get the ID for a named metric on a particular device.

Metric Category

Each metric is placed in one of the categories defined by CUpti_MetricCategory. The category indicates the general type of the characteristic measured by the metric.

Metric Property

Each metric is calculated from input values. These input values can be events or properties of the device or system. The available properties are defined by CUpti MetricPropertyID.

Metric Value

Each metric has a value that represents one of the kinds defined by CUpti_MetricValueKind. For each value kind, there is a corresponding member of the CUpti MetricValue union that is used to hold the metric's value.

The tables included in this section list the metrics available for each device, as determined by the device's compute capability. You can also determine the metrics available on a device using the <code>cuptiDeviceEnumMetrics</code> function. The <code>cupti_query</code> sample described on the samples page shows how to use this function. You can also

enumerate all the CUPTI metrics available on any device using the cuptiEnumMetrics function.

CUPTI provides two functions for calculating a metric value. cuptiMetricGetValue2 can be used to calculate a metric value when the device is not available. All required event values and metric properties must be provided by the caller. cuptiMetricGetValue can be used to calculate a metric value when the device is available (as a CUdevice object). All required event values must be provided by the caller but CUPTI will determine the appropriate property values from the CUdevice object.

Configuring and calculating metric values requires the following steps. First, determine the name of the metric that you want to collect, and then use the <code>cuptiMetricGetIdFromName</code> to get the metric ID. Use <code>cuptiMetricEnumEvents</code> to get the events required to calculate the metric and follow instructions in the CUPTI Event API section to create the event groups for those events. When creating event groups in this manner it is important to use the result of <code>cuptiMetricGetRequiredEventGroupSets</code> to properly group together events that must be collected in the same pass to ensure proper metric calculation.

Alternatively, you can use the <code>cuptiMetricCreateEventGroupSets</code> function to automatically create the event <code>group(s)</code> required for metric's events. When using this function events will be grouped as required to most accurately calculate the metric, as a result it is not necessary to use <code>cuptiMetricGetRequiredEventGroupSets</code>.

If you are using cuptiMetricGetValue2 then you must also collect the required metric property values using cuptiMetricEnumProperties.

Collect event counts as described in the CUPTI Event API section, and then use either cuptiMetricGetValue or cuptiMetricGetValue2 to calculate the metric value from the collected event and property values. The **callback_metric** sample described on the samples page shows how to use the functions to calculate event values and calculate a metric using cuptiMetricGetValue. Note that, as shown in the example, you should collect event counts from all domain instances and normalize the counts to get the most accurate metric values. It is necessary to normalize the event counts because the number of event counter instances varies by device and by the event being counted.

For example, a device might have 8 multiprocessors but only have event counters for 4 of the multiprocessors, and might have 3 memory units and only have events counters for one memory unit. When calculating a metric that requires a multiprocessor event and a memory unit event, the 4 multiprocessor counters should be summed and multiplied by 2 to normalize the event count across the entire device. Similarly, the one memory unit counter should be multiplied by 3 to normalize the event count across the entire device. The normalized values can then be passed to <code>cuptiMetricGetValue</code> or <code>cuptiMetricGetValue</code>2 to calculate the metric value.

As described, the normalization assumes the kernel executes a sufficient number of blocks to completely load the device. If the kernel has only a small number of blocks, normalizing across the entire device may skew the result.

Metric Reference - Compute Capability 2.x

Devices with compute capability between 2.0, inclusive, and 3.0 implement the metrics shown in the following table. A scope value of single-context indicates that the metric can only be accurately collected when a single context (CUDA or graphics) is executing on the GPU. A scope value of multi-context indicates that the metric can be accurately collected when multiple contexts are executing on the GPU.

Table 1 Capability 2.x Metrics

Metric Name	Description	Scope
achieved_occupancy	Ratio of the average active warps per active cycle to the maximum number of warps supported on a multiprocessor	Multi-context
alu_fu_utilization	The utilization level of the multiprocessor function units that execute integer and floating-point arithmetic instructions on a scale of 0 to 10	Multi-context
atomic_replay_overhead	Average number of replays due to atomic and reduction bank conflicts for each instruction executed	Multi-context
atomic_throughput	Global memory atomic and reduction throughput	Multi-context
atomic_transactions	Global memory atomic and reduction transactions	Multi-context
atomic_transactions_per_request	Average number of global memory atomic and reduction transactions performed for each atomic and reduction instruction	Multi-context
branch_efficiency	Ratio of non-divergent branches to total branches expressed as percentage	Multi-context
cf_executed	Number of executed control-flow instructions	Multi-context
cf_fu_utilization	The utilization level of the multiprocessor function units that execute control-flow instructions on a scale of 0 to 10	Multi-context
cf_issued	Number of issued control-flow instructions	Multi-context

Metric Name	Description	Scope
dram_read_throughput	Device memory read throughput	Single-context
dram_read_transactions	Device memory read transactions	Single-context
dram_utilization	The utilization level of the device memory relative to the peak utilization on a scale of 0 to 10	Single-context
dram_write_throughput	Device memory write throughput	Single-context
dram_write_transactions	Device memory write transactions	Single-context
ecc_throughput	ECC throughput from L2 to DRAM	Single-context
ecc_transactions	Number of ECC transactions between L2 and DRAM	Single-context
eligible_warps_per_cycle	Average number of warps that are eligible to issue per active cycle	Multi-context
flop_count_dp	Number of double-precision floating-point operations executed by non-predicated threads (add, multiply, multiply-accumulate and special). Each multiply-accumulate operation contributes 2 to the count.	Multi-context
flop_count_dp_add	Number of double-precision floating-point add operations executed by non-predicated threads	Multi-context
flop_count_dp_fma	Number of double-precision floating-point multiply-accumulate operations executed by non-predicated threads. Each multiply-accumulate operation contributes 1 to the count.	Multi-context
flop_count_dp_mul	Number of double-precision floating-point multiply operations executed by non-predicated threads	Multi-context
flop_count_sp	Number of single-precision floating-point operations executed by non-predicated threads (add, multiply, multiply-accumulate and special). Each multiply-accumulate operation contributes 2 to the count.	Multi-context

Metric Name	Description	Scope
flop_count_sp_add	Number of single-precision floating-point add operations executed by non-predicated threads	Multi-context
flop_count_sp_fma	Number of single-precision floating-point multiply-accumulate operations executed by non-predicated threads. Each multiply-accumulate operation contributes 1 to the count.	Multi-context
flop_count_sp_mul	Number of single-precision floating-point multiply operations executed by non-predicated threads	Multi-context
flop_count_sp_special	Number of single-precision floating-point special operations executed by non-predicated threads	Multi-context
flop_dp_efficiency	Ratio of achieved to peak double-precision floating-point operations	Multi-context
flop_sp_efficiency	Ratio of achieved to peak single-precision floating-point operations	Multi-context
gld_efficiency	Ratio of requested global memory load throughput to required global memory load throughput expressed as percentage	Single-context
gld_requested_throughput	Requested global memory load throughput	Multi-context
gld_throughput	Global memory load throughput	Single-context
gld_transactions	Number of global memory load transactions	Single-context
gld_transactions_per_request	Average number of global memory load transactions performed for each global memory load	Single-context
global_cache_replay_overhead	Average number of replays due to global memory cache misses for each instruction executed	Single-context
gst_efficiency	Ratio of requested global memory store throughput to required global memory store throughput expressed as percentage	Single-context
gst_requested_throughput	Requested global memory store throughput	Multi-context
gst_throughput	Global memory store throughput	Single-context

Metric Name	Description	Scope
gst_transactions	Number of global memory store transactions	Single-context
gst_transactions_per_request	Average number of global memory store transactions performed for each global memory store	Single-context
inst_bit_convert	Number of bit-conversion instructions executed by non-predicated threads	Multi-context
inst_compute_ld_st	Number of compute load/store instructions executed by non-predicated threads	Multi-context
inst_control	Number of control-flow instructions executed by non-predicated threads (jump, branch, etc.)	Multi-context
inst_executed	The number of instructions executed	Multi-context
inst_fp_32	Number of single-precision floating-point instructions executed by non-predicated threads (arithmetic, compare, etc.)	Multi-context
inst_fp_64	Number of double-precision floating-point instructions executed by non-predicated threads (arithmetic, compare, etc.)	Multi-context
inst_integer	Number of integer instructions executed by non-predicated threads	Multi-context
inst_inter_thread_communication	Number of inter-thread communication instructions executed by non-predicated threads	Multi-context
inst_issued	The number of instructions issued	Multi-context
inst_misc	Number of miscellaneous instructions executed by non-predicated threads	Multi-context
inst_per_warp	Average number of instructions executed by each warp	Multi-context
inst_replay_overhead	Average number of replays for each instruction executed	Multi-context
ipc	Instructions executed per cycle	Multi-context
ipc_instance	Instructions executed per cycle for a single multiprocessor	Multi-context

Metric Name	Description	Scope
issue_slot_utilization	Percentage of issue slots that issued at least one instruction, averaged across all cycles	Multi-context
issue_slots	The number of issue slots used	Multi-context
issued_ipc	Instructions issued per cycle	Multi-context
l1_cache_global_hit_rate	Hit rate in L1 cache for global loads	Single-context
l1_cache_local_hit_rate	Hit rate in L1 cache for local loads and stores	Single-context
l1_shared_utilization	The utilization level of the L1/shared memory relative to peak utilization on a scale of 0 to 10	Single-context
I2_atomic_throughput	Memory read throughput seen at L2 cache for atomic and reduction requests	Single-context
l2_atomic_transactions	Memory read transactions seen at L2 cache for atomic and reduction requests	Single-context
l2_l1_read_hit_rate	Hit rate at L2 cache for all read requests from L1 cache	Single-context
l2_l1_read_throughput	Memory read throughput seen at L2 cache for read requests from L1 cache	Single-context
l2_l1_read_transactions	Memory read transactions seen at L2 cache for all read requests from L1 cache	Single-context
l2_l1_write_throughput	Memory write throughput seen at L2 cache for write requests from L1 cache	Single-context
I2_l1_write_transactions	Memory write transactions seen at L2 cache for all write requests from L1 cache	Single-context
l2_read_throughput	Memory read throughput seen at L2 cache for all read requests	Single-context
l2_read_transactions	Memory read transactions seen at L2 cache for all read requests	Single-context
l2_tex_read_transactions	Memory read transactions seen at L2 cache for read requests from the texture cache	Single-context
l2_tex_read_hit_rate	Hit rate at L2 cache for all read requests from texture cache	Single-context
l2_tex_read_throughput	Memory read throughput seen at L2 cache for read requests from the texture cache	Single-context

Metric Name	Description	Scope
l2_utilization	The utilization level of the L2 cache relative to the peak utilization on a scale of 0 to 10	Single-context
l2_write_throughput	Memory write throughput seen at L2 cache for all write requests	Single-context
l2_write_transactions	Memory write transactions seen at L2 cache for all write requests	Single-context
ldst_executed	Number of executed load and store instructions	Multi-context
ldst_fu_utilization	The utilization level of the multiprocessor function units that execute global, local and shared memory instructions on a scale of 0 to 10	Multi-context
ldst_issued	Number of issued load and store instructions	Multi-context
local_load_throughput	Local memory load throughput	Single-context
local_load_transactions	Number of local memory load transactions	Single-context
local_load_transactions_per_request	Average number of local memory load transactions performed for each local memory load	Single-context
local_memory_overhead	Ratio of local memory traffic to total memory traffic between the L1 and L2 caches expressed as percentage	Single-context
local_replay_overhead	Average number of replays due to local memory accesses for each instruction executed	Single-context
local_store_throughput	Local memory store throughput	Single-context
local_store_transactions	Number of local memory store transactions	Single-context
local_store_transactions_per_request	Average number of local memory store transactions performed for each local memory store	Single-context
shared_efficiency	Ratio of requested shared memory throughput to required shared memory throughput expressed as percentage	Single-context
shared_load_throughput	Shared memory load throughput	Single-context
shared_load_transactions	Number of shared memory load transactions	Single-context

hared_load_transactions_per_reque	Average number of shared memory load transactions performed for each shared memory load Average number of replays due to shared memory conflicts for each instruction executed	Single-context Single-context
hared_replay_overhead	memory conflicts for each instruction	Single-context
hared_store_throughput	Shared memory store throughput	Single-context
hared_store_transactions	Number of shared memory store transactions	Single-context
hared_store_transactions_per_reque	stAverage number of shared memory store transactions performed for each shared memory store	Single-context
m_efficiency	The percentage of time at least one warp is active on a multiprocessor averaged over all multiprocessors on the GPU	Single-context
m_efficiency_instance	The percentage of time at least one warp is active on a specific multiprocessor	Single-context
tall_data_request	Percentage of stalls occurring because a memory operation cannot be performed due to the required resources not being available or fully utilized, or because too many requests of a given type are outstanding	Multi-context
tall_exec_dependency	Percentage of stalls occurring because an input required by the instruction is not yet available	Multi-context
tall_inst_fetch	Percentage of stalls occurring because the next assembly instruction has not yet been fetched	Multi-context
tall_other	Percentage of stalls occurring due to miscellaneous reasons	Multi-context
tall_sync	Percentage of stalls occurring because the warp is blocked at asyncthreads() call	Multi-context
tall_texture	Percentage of stalls occurring because the texture sub-system is fully utilized or has too many outstanding requests	Multi-context
ysmem_read_throughput	System memory read throughput	Single-context

Metric Name	Description	Scope
sysmem_read_transactions	System memory read transactions	Single-context
sysmem_utilization	The utilization level of the system memory relative to the peak utilization on a scale of 0 to 10	Single-context
sysmem_write_throughput	System memory write throughput	Single-context
sysmem_write_transactions	System memory write transactions	Single-context
tex_cache_hit_rate	Texture cache hit rate	Single-context
tex_cache_throughput	Texture cache throughput	Single-context
tex_cache_transactions	Texture cache read transactions	Single-context
tex_fu_utilization	The utilization level of the multiprocessor function units that execute texture instructions on a scale of 0 to 10	Multi-context
tex_utilization	The utilization level of the texture cache relative to the peak utilization on a scale of 0 to 10	Single-context
warp_execution_efficiency	Ratio of the average active threads per warp to the maximum number of threads per warp supported on a multiprocessor expressed as percentage	Multi-context

Metric Reference - Compute Capability 3.x

Devices with compute capability between 3.0, inclusive, and 4.0 implement the metrics shown in the following table. Starting CUDA Toolkit 7.0 all metrics can be collected accurately when multiple contexts (CUDA and/or graphics) are executing on the GPU.

Table 2 Capability 3.x Metrics

Metric Name	Description	Scope
achieved_occupancy	Ratio of the average active warps per active cycle to the maximum number of warps supported on a multiprocessor	Multi-context
alu_fu_utilization	The utilization level of the multiprocessor function units that execute integer and floating-point arithmetic instructions on a scale of 0 to 10	Multi-context

Metric Name	Description	Scope
atomic_replay_overhead	Average number of replays due to atomic and reduction bank conflicts for each instruction executed	Multi-context
atomic_throughput	Global memory atomic and reduction throughput	Multi-context
atomic_transactions	Global memory atomic and reduction transactions	Multi-context
atomic_transactions_per_request	Average number of global memory atomic and reduction transactions performed for each atomic and reduction instruction	Multi-context
branch_efficiency	Ratio of non-divergent branches to total branches expressed as percentage. This is available for compute capability 3.0.	Multi-context
cf_executed	Number of executed control-flow instructions	Multi-context
cf_fu_utilization	The utilization level of the multiprocessor function units that execute control-flow instructions on a scale of 0 to 10	Multi-context
cf_issued	Number of issued control-flow instructions	Multi-context
dram_read_throughput	Device memory read throughput. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context*
dram_read_transactions	Device memory read transactions. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
dram_utilization	The utilization level of the device memory relative to the peak utilization on a scale of 0 to 10	Multi-context [*]
dram_write_throughput	Device memory write throughput. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
dram_write_transactions	Device memory write transactions. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
ecc_throughput	ECC throughput from L2 to DRAM. This is available for compute capability 3.5 and 3.7.	Multi-context [*]

Metric Name	Description	Scope
ecc_transactions	Number of ECC transactions between L2 and DRAM. This is available for compute capability 3.5 and 3.7.	Multi-context [*]
eligible_warps_per_cycle	Average number of warps that are eligible to issue per active cycle	Multi-context
flop_count_dp	Number of double-precision floating-point operations executed by non-predicated threads (add, multiply, multiply-accumulate and special). Each multiply-accumulate operation contributes 2 to the count.	Multi-context
flop_count_dp_add	Number of double-precision floating-point add operations executed by non-predicated threads	Multi-context
flop_count_dp_fma	Number of double-precision floating-point multiply-accumulate operations executed by non-predicated threads. Each multiply-accumulate operation contributes 1 to the count.	Multi-context
flop_count_dp_mul	Number of double-precision floating-point multiply operations executed by non-predicated threads	Multi-context
flop_count_sp	Number of single-precision floating-point operations executed by non-predicated threads (add, multiply, multiply-accumulate and special). Each multiply-accumulate operation contributes 2 to the count.	Multi-context
flop_count_sp_add	Number of single-precision floating-point add operations executed by non-predicated threads	Multi-context
flop_count_sp_fma	Number of single-precision floating-point multiply-accumulate operations executed by non-predicated threads. Each multiply-accumulate operation contributes 1 to the count.	Multi-context
flop_count_sp_mul	Number of single-precision floating-point multiply operations executed by non-predicated threads	Multi-context

Metric Name	Description	Scope
flop_count_sp_special	Number of single-precision floating-point special operations executed by non-predicated threads	Multi-context
flop_dp_efficiency	Ratio of achieved to peak double-precision floating-point operations	Multi-context
flop_sp_efficiency	Ratio of achieved to peak single-precision floating-point operations	Multi-context
gld_efficiency	Ratio of requested global memory load throughput to required global memory load throughput expressed as percentage	Multi-context*
gld_requested_throughput	Requested global memory load throughput	Multi-context
gld_throughput	Global memory load throughput	Multi-context*
gld_transactions	Number of global memory load transactions expressed as percentage	Multi-context [*]
gld_transactions_per_request	Average number of global memory load transactions performed for each global memory load	Multi-context*
global_cache_replay_overhead	Average number of replays due to global memory cache misses for each instruction executed	Multi-context
global_replay_overhead	Average number of replays due to global memory cache misses	Multi-context
gst_efficiency	Ratio of requested global memory store throughput to required global memory store throughput expressed as percentage	Multi-context [*]
gst_requested_throughput	Requested global memory store throughput	Multi-context
gst_throughput	Global memory store throughput	Multi-context*
gst_transactions	Number of global memory store transactions	Multi-context [*]
gst_transactions_per_request	Average number of global memory store transactions performed for each global memory store	Multi-context [*]
inst_bit_convert	Number of bit-conversion instructions executed by non-predicated threads	Multi-context

Metric Name	Description	Scope
inst_compute_ld_st	Number of compute load/store instructions executed by non-predicated threads	Multi-context
inst_control	Number of control-flow instructions executed by non-predicated threads (jump, branch, etc.)	Multi-context
inst_executed	The number of instructions executed	Multi-context
inst_fp_32	Number of single-precision floating-point instructions executed by non-predicated threads (arithmetic, compare, etc.)	Multi-context
inst_fp_64	Number of double-precision floating-point instructions executed by non-predicated threads (arithmetic, compare, etc.)	Multi-context
inst_integer	Number of integer instructions executed by non-predicated threads	Multi-context
inst_inter_thread_communication	Number of inter-thread communication instructions executed by non-predicated threads	Multi-context
inst_issued	The number of instructions issued	Multi-context
inst_misc	Number of miscellaneous instructions executed by non-predicated threads	Multi-context
inst_per_warp	Average number of instructions executed by each warp	Multi-context
inst_replay_overhead	Average number of replays for each instruction executed	Multi-context
ірс	Instructions executed per cycle	Multi-context
ipc_instance	Instructions executed per cycle for a single multiprocessor	Multi-context
issue_slot_utilization	Percentage of issue slots that issued at least one instruction, averaged across all cycles	Multi-context
issue_slots	The number of issue slots used	Multi-context
issued_ipc	Instructions issued per cycle	Multi-context
l1_cache_global_hit_rate	Hit rate in L1 cache for global loads	Multi-context [*]
l1_cache_local_hit_rate	Hit rate in L1 cache for local loads and stores	Multi-context [*]

Metric Name	Description	Scope
l1_shared_utilization	The utilization level of the L1/shared memory relative to peak utilization on a scale of 0 to 10. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
l2_atomic_throughput	Memory read throughput seen at L2 cache for atomic and reduction requests	Multi-context [*]
l2_atomic_transactions	Memory read transactions seen at L2 cache for atomic and reduction requests	Multi-context [*]
l2_l1_read_hit_rate	Hit rate at L2 cache for all read requests from L1 cache. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
l2_l1_read_throughput	Memory read throughput seen at L2 cache for read requests from L1 cache. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
l2_l1_read_transactions	Memory read transactions seen at L2 cache for all read requests from L1 cache. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
l2_l1_write_throughput	Memory write throughput seen at L2 cache for write requests from L1 cache. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
l2_l1_write_transactions	Memory write transactions seen at L2 cache for all write requests from L1 cache. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
l2_read_throughput	Memory read throughput seen at L2 cache for all read requests	Multi-context [*]
l2_read_transactions	Memory read transactions seen at L2 cache for all read requests	Multi-context [*]
l2_tex_read_transactions	Memory read transactions seen at L2 cache for read requests from the texture cache	Multi-context [*]
l2_tex_read_hit_rate	Hit rate at L2 cache for all read requests from texture cache. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
l2_tex_read_throughput	Memory read throughput seen at L2 cache for read requests from the texture cache	Multi-context [*]

Metric Name	Description	Scope
l2_utilization	The utilization level of the L2 cache relative to the peak utilization on a scale of 0 to 10	Multi-context [*]
l2_write_throughput	Memory write throughput seen at L2 cache for all write requests	Multi-context [*]
l2_write_transactions	Memory write transactions seen at L2 cache for all write requests	Multi-context [*]
ldst_executed	Number of executed load and store instructions	Multi-context
ldst_fu_utilization	The utilization level of the multiprocessor function units that execute global, local and shared memory instructions on a scale of 0 to 10	Multi-context
ldst_issued	Number of issued load and store instructions	Multi-context
local_load_throughput	Local memory load throughput	Multi-context*
local_load_transactions	Number of local memory load transactions	Multi-context*
local_load_transactions_per_request	Average number of local memory load transactions performed for each local memory load	Multi-context*
local_memory_overhead	Ratio of local memory traffic to total memory traffic between the L1 and L2 caches expressed as percentage. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
local_replay_overhead	Average number of replays due to local memory accesses for each instruction executed	Multi-context
local_store_throughput	Local memory store throughput	Multi-context [*]
local_store_transactions	Number of local memory store transactions	Multi-context*
local_store_transactions_per_request	Average number of local memory store transactions performed for each local memory store	Multi-context [*]
nc_cache_global_hit_rate	Hit rate in non coherent cache for global loads	Multi-context [*]
nc_gld_efficiency	Ratio of requested non coherent global memory load throughput to required non	Multi-context [*]

Metric Name	Description	Scope
	coherent global memory load throughput expressed as percentage	
nc_gld_requested_throughput	Requested throughput for global memory loaded via non-coherent cache	Multi-context
nc_gld_throughput	Non coherent global memory load throughput	Multi-context*
nc_l2_read_throughput	Memory read throughput for non coherent global read requests seen at L2 cache	Multi-context [*]
nc_l2_read_transactions	Memory read transactions seen at L2 cache for non coherent global read requests	Multi-context [*]
shared_efficiency	Ratio of requested shared memory throughput to required shared memory throughput expressed as percentage	Multi-context [*]
shared_load_throughput	Shared memory load throughput	Multi-context*
shared_load_transactions	Number of shared memory load transactions	Multi-context*
shared_load_transactions_per_reques	t Average number of shared memory load transactions performed for each shared memory load	Multi-context [*]
shared_replay_overhead	Average number of replays due to shared memory conflicts for each instruction executed	Multi-context
shared_store_throughput	Shared memory store throughput	Multi-context*
shared_store_transactions	Number of shared memory store transactions	Multi-context*
shared_store_transactions_per_reque	tAverage number of shared memory store transactions performed for each shared memory store	Multi-context*
sm_efficiency	The percentage of time at least one warp is active on a multiprocessor averaged over all multiprocessors on the GPU	Multi-context [*]
sm_efficiency_instance	The percentage of time at least one warp is active on a specific multiprocessor	Multi-context [*]
stall_constant_memory_dependency	Percentage of stalls occurring because of immediate constant cache miss. This is available for compute capability 3.2, 3.5 and 3.7.	Multi-context

Metric Name	Description	Scope
stall_exec_dependency	Percentage of stalls occurring because an input required by the instruction is not yet available	Multi-context
stall_inst_fetch	Percentage of stalls occurring because the next assembly instruction has not yet been fetched	Multi-context
stall_memory_dependency	Percentage of stalls occurring because a memory operation cannot be performed due to the required resources not being available or fully utilized, or because too many requests of a given type are outstanding.	Multi-context
stall_memory_throttle	Percentage of stalls occurring because of memory throttle.	Multi-context
stall_not_selected	Percentage of stalls occurring because warp was not selected.	Multi-context
stall_other	Percentage of stalls occurring due to miscellaneous reasons	Multi-context
stall_pipe_busy	Percentage of stalls occurring because a compute operation cannot be performed due to the required resources not being available. This is available for compute capability 3.2, 3.5 and 3.7.	Multi-context
stall_sync	Percentage of stalls occurring because the warp is blocked at asyncthreads() call	Multi-context
stall_texture	Percentage of stalls occurring because the texture sub-system is fully utilized or has too many outstanding requests	Multi-context
sysmem_read_throughput	System memory read throughput. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
sysmem_read_transactions	System memory read transactions. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
sysmem_read_utilization	The read utilization level of the system memory relative to the peak utilization. This	Multi-context

Metric Name	Description	Scope
	is available for compute capability 3.0, 3.5 and 3.7.	
sysmem_utilization	The utilization level of the system memory relative to the peak utilization on a scale of 0 to 10. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
sysmem_write_throughput	System memory write throughput. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
sysmem_write_transactions	System memory write transactions. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context [*]
sysmem_write_utilization	The write utilization level of the system memory relative to the peak utilization. This is available for compute capability 3.0, 3.5 and 3.7.	Multi-context
tex_cache_hit_rate	Texture cache hit rate	Multi-context*
tex_cache_throughput	Texture cache throughput	Multi-context*
tex_cache_transactions	Texture cache read transactions	Multi-context*
tex_fu_utilization	The utilization level of the multiprocessor function units that execute texture instructions on a scale of 0 to 10	Multi-context
tex_utilization	The utilization level of the texture cache relative to the peak utilization on a scale of 0 to 10	Multi-context [*]
warp_execution_efficiency	Ratio of the average active threads per warp to the maximum number of threads per warp supported on a multiprocessor expressed as percentage	Multi-context
warp_nonpred_execution_efficiency	Ratio of the average active threads per warp executing non-predicated instructions to the maximum number of threads per warp supported on a multiprocessor expressed as percentage	Multi-context

Metric Reference - Compute Capability 5.x

Devices with compute capability greater than or equal to 5.0 implement the metrics shown in the following table. A scope value of single-context indicates that the metric can only be accurately collected when a single context (CUDA or graphics) is executing on the GPU. A scope value of multi-context indicates that the metric can be accurately collected when multiple contexts are executing on the GPU. Note that, starting CUDA Toolkit 7.0 all metrics can be collected accurately on the devices with compute capability 5.0 when multiple contexts are executing on the GPU.

Table 3 Capability 5.x Metrics

Metric Name	Description	Scope
achieved_occupancy	Ratio of the average active warps per active cycle to the maximum number of warps supported on a multiprocessor	Multi-context
atomic_transactions	Global memory atomic and reduction transactions	Multi-context
atomic_transactions_per_request	Average number of global memory atomic and reduction transactions performed for each atomic and reduction instruction	Multi-context
branch_efficiency	Ratio of non-divergent branches to total branches expressed as percentage	Multi-context
cf_executed	Number of executed control-flow instructions	Multi-context
cf_fu_utilization	The utilization level of the multiprocessor function units that execute control-flow instructions on a scale of 0 to 10	Multi-context
cf_issued	Number of issued control-flow instructions	Multi-context
double_precision_fu_utilization	The utilization level of the multiprocessor function units that execute double-precision floating-point instructions and integer instructions on a scale of 0 to 10	Multi-context
dram_read_throughput	Device memory read throughput. This is available for compute capability 5.0 and 5.2.	Multi-context*
dram_read_transactions	Device memory read transactions. This is available for compute capability 5.0 and 5.2.	Multi-context*
dram_utilization	The utilization level of the device memory relative to the peak utilization on a scale of 0 to 10	Multi-context [*]

Metric Name	Description	Scope
dram_write_throughput	Device memory write throughput. This is available for compute capability 5.0 and 5.2.	Multi-context [*]
dram_write_transactions	Device memory write transactions. This is available for compute capability 5.0 and 5.2.	Multi-context [*]
ecc_throughput	ECC throughput from L2 to DRAM. This is available for compute capability 5.0 and 5.2.	Multi-context [*]
ecc_transactions	Number of ECC transactions between L2 and DRAM. This is available for compute capability 5.0 and 5.2.	Multi-context [*]
eligible_warps_per_cycle	Average number of warps that are eligible to issue per active cycle	Multi-context
flop_count_dp	Number of double-precision floating-point operations executed by non-predicated threads (add, multiply, multiply-accumulate and special). Each multiply-accumulate operation contributes 2 to the count.	Multi-context
flop_count_dp_add	Number of double-precision floating-point add operations executed by non-predicated threads	Multi-context
flop_count_dp_fma	Number of double-precision floating-point multiply-accumulate operations executed by non-predicated threads. Each multiply-accumulate operation contributes 1 to the count.	Multi-context
flop_count_dp_mul	Number of double-precision floating-point multiply operations executed by non-predicated threads	Multi-context
flop_count_hp	Number of half-precision floating-point operations executed by non-predicated threads (add, multiply, multiply-accumulate and special). Each multiply-accumulate operation contributes 2 to the count. This is available for compute capability 5.3.	Multi-context [*]
flop_count_hp_add	Number of half-precision floating-point add operations executed by non-predicated threads. This is available for compute capability 5.3.	Multi-context [*]

Metric Name	Description	Scope
flop_count_hp_fma	Number of half-precision floating-point multiply-accumulate operations executed by non-predicated threads. Each multiply-accumulate operation contributes 1 to the count. This is available for compute capability 5.3.	Multi-context [*]
flop_count_hp_mul	Number of half-precision floating-point multiply operations executed by non-predicated threads. This is available for compute capability 5.3.	Multi-context*
flop_count_sp	Number of single-precision floating-point operations executed by non-predicated threads (add, multiply, multiply-accumulate and special). Each multiply-accumulate operation contributes 2 to the count.	Multi-context
flop_count_sp_add	Number of single-precision floating-point add operations executed by non-predicated threads	Multi-context
flop_count_sp_fma	Number of single-precision floating-point multiply-accumulate operations executed by non-predicated threads. Each multiply-accumulate operation contributes 1 to the count.	Multi-context
flop_count_sp_mul	Number of single-precision floating-point multiply operations executed by non-predicated threads	Multi-context
flop_count_sp_special	Number of single-precision floating-point special operations executed by non-predicated threads	Multi-context
flop_dp_efficiency	Ratio of achieved to peak double-precision floating-point operations	Multi-context
flop_hp_efficiency	Ratio of achieved to peak half-precision floating-point operations. This is available for compute capability 5.3.	Multi-context [*]
flop_sp_efficiency	Ratio of achieved to peak single-precision floating-point operations	Multi-context

Metric Name	Description	Scope
gld_efficiency	Ratio of requested global memory load throughput to required global memory load throughput expressed as percentage	Multi-context*
gld_requested_throughput	Requested global memory load throughput	Multi-context
gld_throughput	Global memory load throughput	Multi-context*
gld_transactions	Number of global memory load transactions	Multi-context*
gld_transactions_per_request	Average number of global memory load transactions performed for each global memory load	Multi-context [*]
global_hit_rate	Hit rate for global loads	Multi-context*
gst_efficiency	Ratio of requested global memory store throughput to required global memory store throughput expressed as percentage	Multi-context*
gst_requested_throughput	Requested global memory store throughput	Multi-context
gst_throughput	Global memory store throughput	Multi-context*
gst_transactions	Number of global memory store transactions	Multi-context*
gst_transactions_per_request	Average number of global memory store transactions performed for each global memory store	Multi-context*
half_precision_fu_utilization	The utilization level of the multiprocessor function units that execute 16 bit floating-point instructions and integer instructions. This is available for compute capability 5.3.	Multi-context [*]
inst_bit_convert	Number of bit-conversion instructions executed by non-predicated threads	Multi-context
inst_compute_ld_st	Number of compute load/store instructions executed by non-predicated threads	Multi-context
inst_control	Number of control-flow instructions executed by non-predicated threads (jump, branch, etc.)	Multi-context
inst_executed	The number of instructions executed	Multi-context
inst_fp_16	Number of half-precision floating-point instructions executed by non-predicated	Multi-context*

Metric Name	Description	Scope
	threads (arithmetic, compare, etc.) This is available for compute capability 5.3.	
inst_fp_32	Number of single-precision floating-point instructions executed by non-predicated threads (arithmetic, compare, etc.)	Multi-context
inst_fp_64	Number of double-precision floating-point instructions executed by non-predicated threads (arithmetic, compare, etc.)	Multi-context
inst_integer	Number of integer instructions executed by non-predicated threads	Multi-context
inst_inter_thread_communication	Number of inter-thread communication instructions executed by non-predicated threads	Multi-context
inst_issued	The number of instructions issued	Multi-context
inst_misc	Number of miscellaneous instructions executed by non-predicated threads	Multi-context
inst_per_warp	Average number of instructions executed by each warp	Multi-context
inst_replay_overhead	Average number of replays for each instruction executed	Multi-context
ірс	Instructions executed per cycle	Multi-context
issue_slot_utilization	Percentage of issue slots that issued at least one instruction, averaged across all cycles	Multi-context
issue_slots	The number of issue slots used	Multi-context
issued_ipc	Instructions issued per cycle	Multi-context
l2_atomic_throughput	Memory read throughput seen at L2 cache for atomic and reduction requests	Multi-context
l2_atomic_transactions	Memory read transactions seen at L2 cache for atomic and reduction requests	Multi-context [*]
l2_read_throughput	Memory read throughput seen at L2 cache for all read requests	Multi-context [*]
l2_read_transactions	Memory read transactions seen at L2 cache for all read requests	Multi-context [*]

Metric Name	Description	Scope
l2_tex_read_hit_rate	Hit rate at L2 cache for all read requests from texture cache. This is available for compute capability 5.0 and 5.2.	Multi-context [*]
l2_tex_read_throughput	Memory read throughput seen at L2 cache for read requests from the texture cache	Multi-context [*]
I2_tex_read_transactions	Memory read transactions seen at L2 cache for read requests from the texture cache	Multi-context [*]
l2_tex_write_hit_rate	Hit Rate at L2 cache for all write requests from texture cache. This is available for compute capability 5.0 and 5.2.	Multi-context*
l2_tex_write_throughput	Memory write throughput seen at L2 cache for write requests from the texture cache	Multi-context [*]
I2_tex_write_transactions	Memory write transactions seen at L2 cache for write requests from the texture cache	Multi-context [*]
l2_utilization	The utilization level of the L2 cache relative to the peak utilization on a scale of 0 to 10	Multi-context [*]
l2_write_throughput	Memory write throughput seen at L2 cache for all write requests	Multi-context [*]
I2_write_transactions	Memory write transactions seen at L2 cache for all write requests	Multi-context [*]
ldst_executed	Number of executed load and store instructions	Multi-context
ldst_fu_utilization	The utilization level of the multiprocessor function units that execute global, local and shared memory instructions on a scale of 0 to 10	Multi-context
ldst_issued	Number of issued load and store instructions	Multi-context
local_hit_rate	Hit rate for local loads and stores	Multi-context [*]
local_load_throughput	Local memory load throughput	Multi-context*
local_load_transactions	Number of local memory load transactions	Multi-context*
local_load_transactions_per_request	Average number of local memory load transactions performed for each local memory load	Multi-context [*]

Metric Name	Description	Scope
local_memory_overhead	Ratio of local memory traffic to total memory traffic between the L1 and L2 caches expressed as percentage	Multi-context [*]
local_store_throughput	Local memory store throughput	Multi-context*
local_store_transactions	Number of local memory store transactions	Multi-context [*]
local_store_transactions_per_request	Average number of local memory store transactions performed for each local memory store	Multi-context [*]
shared_efficiency	Ratio of requested shared memory throughput to required shared memory throughput expressed as percentage	Multi-context*
shared_load_throughput	Shared memory load throughput	Multi-context*
shared_load_transactions	Number of shared memory load transactions	Multi-context*
shared_load_transactions_per_reques	t Average number of shared memory load transactions performed for each shared memory load	Multi-context [*]
shared_store_throughput	Shared memory store throughput	Multi-context*
shared_store_transactions	Number of shared memory store transactions	Multi-context*
shared_store_transactions_per_reque	tAverage number of shared memory store transactions performed for each shared memory store	Multi-context [*]
shared_utilization	The utilization level of the shared memory relative to peak utilization on a scale of 0 to 10	Multi-context [*]
single_precision_fu_utilization	The utilization level of the multiprocessor function units that execute single-precision floating-point instructions and integer instructions on a scale of 0 to 10	Multi-context
sm_efficiency	The percentage of time at least one warp is active on a multiprocessor	Multi-context [*]
special_fu_utilization	The utilization level of the multiprocessor function units that execute sin, cos, ex2, popc, flo, and similar instructions on a scale of 0 to 10	Multi-context

Metric Name	Description	Scope
stall_constant_memory_dependency	Percentage of stalls occurring because of immediate constant cache miss	Multi-context
stall_exec_dependency	Percentage of stalls occurring because an input required by the instruction is not yet available	Multi-context
stall_inst_fetch	Percentage of stalls occurring because the next assembly instruction has not yet been fetched	Multi-context
stall_memory_dependency	Percentage of stalls occurring because a memory operation cannot be performed due to the required resources not being available or fully utilized, or because too many requests of a given type are outstanding	Multi-context
stall_memory_throttle	Percentage of stalls occurring because of memory throttle	Multi-context
stall_not_selected	Percentage of stalls occurring because warp was not selected	Multi-context
stall_other	Percentage of stalls occurring due to miscellaneous reasons	Multi-context
stall_pipe_busy	Percentage of stalls occurring because a compute operation cannot be performed due to the required resources not being available	Multi-context
stall_sync	Percentage of stalls occurring because the warp is blocked at asyncthreads() call	Multi-context
stall_texture	Percentage of stalls occurring because the texture sub-system is fully utilized or has too many outstanding requests	Multi-context
sysmem_read_throughput	System memory read throughput	Multi-context [*]
sysmem_read_transactions	System memory read transactions	Multi-context [*]
sysmem_read_utilization	The read utilization level of the system memory relative to the peak utilization. This is available for compute capability 5.0 and 5.2.	Multi-context
sysmem_utilization	The utilization level of the system memory relative to the peak utilization on a scale of 0	Multi-context [*]

Metric Name	Description	Scope
	to 10. This is available for compute capability 5.0 and 5.2.	
sysmem_write_throughput	System memory write throughput	Multi-context*
sysmem_write_transactions	System memory write transactions	Multi-context*
sysmem_write_utilization	The write utilization level of the system memory relative to the peak utilization. This is available for compute capability 5.0 and 5.2.	Multi-context
tex_cache_hit_rate	Texture cache hit rate	Multi-context*
tex_cache_throughput	Texture cache throughput	Multi-context*
tex_cache_transactions	Texture cache read transactions	Multi-context*
tex_fu_utilization	The utilization level of the multiprocessor function units that execute texture instructions on a scale of 0 to 10	Multi-context
tex_utilization	The utilization level of the texture cache relative to the peak utilization on a scale of 0 to 10	Multi-context*
warp_execution_efficiency	Ratio of the average active threads per warp to the maximum number of threads per warp supported on a multiprocessor expressed as percentage	Multi-context
warp_nonpred_execution_efficiency	Ratio of the average active threads per warp executing non-predicated instructions to the maximum number of threads per warp supported on a multiprocessor	Multi-context

Metric Reference - Compute Capability 6.x

Devices with compute capability greater than or equal to 6.0 implement the metrics shown in the following table. A scope value of single-context indicates that the metric can only be accurately collected when a single context (CUDA or graphics) is executing on the GPU.

A scope value of multi-context indicates that the metric can be accurately collected when multiple contexts are executing on the GPU.

A scope value of device indicates that the metric will be collected at device level, that is it will include values for all the contexts executing on the GPU. The events for these metrics can be collected at device level using

CUPTI_EVENT_COLLECTION_MODE_CONTINUOUS. When these metrics are collected for a kernel using CUPTI_EVENT_COLLECTION_MODE_KERNEL, they exhibit the behavior of single-context.

Note that, starting CUDA Toolkit 7.0 all metrics can be collected accurately on the devices with compute capability 6.0 or more, when multiple contexts are executing on the GPU, except NVLink metrics in kernel mode.

Table 4 Capability 6.x Metrics

Metric Name	Description	Scope
achieved_occupancy	Ratio of the average active warps per active cycle to the maximum number of warps supported on a multiprocessor	Multi-context
atomic_transactions	Global memory atomic and reduction transactions	Multi-context
atomic_transactions_per_request	Average number of global memory atomic and reduction transactions performed for each atomic and reduction instruction	Multi-context
branch_efficiency	Ratio of non-divergent branches to total branches expressed as percentage	Multi-context
cf_executed	Number of executed control-flow instructions	Multi-context
cf_fu_utilization	The utilization level of the multiprocessor function units that execute control-flow instructions on a scale of 0 to 10	Multi-context
cf_issued	Number of issued control-flow instructions	Multi-context
double_precision_fu_utilization	The utilization level of the multiprocessor function units that execute double-precision floating-point instructions and integer instructions on a scale of 0 to 10	Multi-context
dram_read_throughput	Device memory read throughput. This is available for compute capability 6.0 and 6.1.	Multi-context
dram_read_transactions	Device memory read transactions. This is available for compute capability 6.0 and 6.1.	Multi-context
dram_utilization	The utilization level of the device memory relative to the peak utilization on a scale of 0 to 10	Multi-context

Metric Name	Description	Scope
dram_write_throughput	Device memory write throughput. This is available for compute capability 6.0 and 6.1.	Multi-context
dram_write_transactions	Device memory write transactions. This is available for compute capability 6.0 and 6.1.	Multi-context
ecc_throughput	ECC throughput from L2 to DRAM. This is available for compute capability 6.1.	Multi-context
ecc_transactions	Number of ECC transactions between L2 and DRAM. This is available for compute capability 6.1.	Multi-context
eligible_warps_per_cycle	Average number of warps that are eligible to issue per active cycle	Multi-context
executed_ipc	Instructions executed per cycle	Multi-context
flop_count_dp	Number of double-precision floating-point operations executed by non-predicated threads (add, multiply, multiply-accumulate and special). Each multiply-accumulate operation contributes 2 to the count.	Multi-context
flop_count_dp_add	Number of double-precision floating-point add operations executed by non-predicated threads	Multi-context
flop_count_dp_fma	Number of double-precision floating-point multiply-accumulate operations executed by non-predicated threads. Each multiply-accumulate operation contributes 1 to the count.	Multi-context
flop_count_dp_mul	Number of double-precision floating-point multiply operations executed by non-predicated threads	Multi-context
flop_count_hp	Number of half-precision floating-point operations executed by non-predicated threads (add, multiply, multiply-accumulate and special). Each multiply-accumulate operation contributes 2 to the count.	Multi-context
flop_count_hp_add	Number of half-precision floating-point add operations executed by non-predicated threads	Multi-context

Metric Name	Description	Scope
flop_count_hp_fma	Number of half-precision floating-point multiply-accumulate operations executed by non-predicated threads. Each multiply-accumulate operation contributes 1 to the count.	Multi-context
flop_count_hp_mul	Number of half-precision floating-point multiply operations executed by non-predicated threads	Multi-context
flop_count_sp	Number of single-precision floating-point operations executed by non-predicated threads (add, multiply, multiply-accumulate and special). Each multiply-accumulate operation contributes 2 to the count.	Multi-context
flop_count_sp_add	Number of single-precision floating-point add operations executed by non-predicated threads	Multi-context
flop_count_sp_fma	Number of single-precision floating-point multiply-accumulate operations executed by non-predicated threads. Each multiply-accumulate operation contributes 1 to the count.	Multi-context
flop_count_sp_mul	Number of single-precision floating-point multiply operations executed by non-predicated threads	Multi-context
flop_count_sp_special	Number of single-precision floating-point special operations executed by non-predicated threads	Multi-context
flop_dp_efficiency	Ratio of achieved to peak double-precision floating-point operations	Multi-context
flop_hp_efficiency	Ratio of achieved to peak half-precision floating-point operations	Multi-context
flop_sp_efficiency	Ratio of achieved to peak single-precision floating-point operations	Multi-context
gld_efficiency	Ratio of requested global memory load throughput to required global memory load throughput expressed as percentage	Multi-context

Metric Name	Description	Scope
gld_requested_throughput	Requested global memory load throughput	Multi-context
gld_throughput	Global memory load throughput	Multi-context
gld_transactions	Number of global memory load transactions	Multi-context
gld_transactions_per_request	Average number of global memory load transactions performed for each global memory load	Multi-context
global_hit_rate	Hit rate for global loads	Multi-context
gst_efficiency	Ratio of requested global memory store throughput to required global memory store throughput expressed as percentage	Multi-context
gst_requested_throughput	Requested global memory store throughput	Multi-context
gst_throughput	Global memory store throughput	Multi-context
gst_transactions	Number of global memory store transactions	Multi-context
gst_transactions_per_request	Average number of global memory store transactions performed for each global memory store	Multi-context
half_precision_fu_utilization	The utilization level of the multiprocessor function units that execute 16 bit floating-point instructions and integer instructions	Multi-context
inst_bit_convert	Number of bit-conversion instructions executed by non-predicated threads	Multi-context
inst_compute_ld_st	Number of compute load/store instructions executed by non-predicated threads	Multi-context
inst_control	Number of control-flow instructions executed by non-predicated threads (jump, branch, etc.)	Multi-context
inst_executed	The number of instructions executed	Multi-context
inst_fp_16	Number of half-precision floating-point instructions executed by non-predicated threads (arithmetic, compare, etc.)	Multi-context
inst_fp_32	Number of single-precision floating-point instructions executed by non-predicated threads (arithmetic, compare, etc.)	Multi-context

Metric Name	Description	Scope
inst_fp_64	Number of double-precision floating-point instructions executed by non-predicated threads (arithmetic, compare, etc.)	Multi-context
inst_integer	Number of integer instructions executed by non-predicated threads	Multi-context
inst_inter_thread_communication	Number of inter-thread communication instructions executed by non-predicated threads	Multi-context
inst_issued	The number of instructions issued	Multi-context
inst_misc	Number of miscellaneous instructions executed by non-predicated threads	Multi-context
inst_per_warp	Average number of instructions executed by each warp	Multi-context
inst_replay_overhead	Average number of replays for each instruction executed	Multi-context
issue_slot_utilization	Percentage of issue slots that issued at least one instruction, averaged across all cycles	Multi-context
issue_slots	The number of issue slots used	Multi-context
issued_ipc	Instructions issued per cycle	Multi-context
l2_atomic_throughput	Memory read throughput seen at L2 cache for atomic and reduction requests	Multi-context
l2_atomic_transactions	Memory read transactions seen at L2 cache for atomic and reduction requests	Multi-context
l2_read_throughput	Memory read throughput seen at L2 cache for all read requests	Multi-context
l2_read_transactions	Memory read transactions seen at L2 cache for all read requests	Multi-context
l2_tex_read_hit_rate	Hit rate at L2 cache for all read requests from texture cache. This is available for compute capability 6.0 and 6.1.	Multi-context
l2_tex_read_throughput	Memory read throughput seen at L2 cache for read requests from the texture cache	Multi-context
l2_tex_read_transactions	Memory read transactions seen at L2 cache for read requests from the texture cache	Multi-context

Metric Name	Description	Scope
l2_tex_write_hit_rate	Hit Rate at L2 cache for all write requests from texture cache. This is available for compute capability 6.0 and 6.1.	Multi-context
l2_tex_write_throughput	Memory write throughput seen at L2 cache for write requests from the texture cache	Multi-context
I2_tex_write_transactions	Memory write transactions seen at L2 cache for write requests from the texture cache	Multi-context
l2_utilization	The utilization level of the L2 cache relative to the peak utilization on a scale of 0 to 10	Multi-context
l2_write_throughput	Memory write throughput seen at L2 cache for all write requests	Multi-context
l2_write_transactions	Memory write transactions seen at L2 cache for all write requests	Multi-context
ldst_executed	Number of executed load and store instructions	Multi-context
ldst_fu_utilization	The utilization level of the multiprocessor function units that execute global, local and shared memory instructions on a scale of 0 to 10	Multi-context
ldst_issued	Number of issued load and store instructions	Multi-context
local_hit_rate	Hit rate for local loads and stores	Multi-context
local_load_throughput	Local memory load throughput	Multi-context
local_load_transactions	Number of local memory load transactions	Multi-context
local_load_transactions_per_request	Average number of local memory load transactions performed for each local memory load	Multi-context
local_memory_overhead	Ratio of local memory traffic to total memory traffic between the L1 and L2 caches expressed as percentage	Multi-context
local_store_throughput	Local memory store throughput	Multi-context
local_store_transactions	Number of local memory store transactions	Multi-context
local_store_transactions_per_request	Average number of local memory store transactions performed for each local memory store	Multi-context

Metric Name	Description	Scope
nvlink_overhead_data_received	Overhead data bytes received through NVLinks. This is available for compute capability 6.0.	Device
nvlink_overhead_data_transmitted	Overhead data bytes transmitted through NVLinks. This is available for compute capability 6.0.	Device
nvlink_receive_throughput	Number of bytes received per second through NVLinks. This is available for compute capability 6.0.	Device
nvlink_total_data_received	Total data bytes received through NVLinks including headers. This is available for compute capability 6.0.	Device
nvlink_total_data_transmitted	Total data bytes transmitted through NVLinks including headers. This is available for compute capability 6.0.	Device
nvlink_total_nratom_data_transmitte	dTotal non-reduction atomic data bytes transmitted through NVLinks. This is available for compute capability 6.0.	Device
nvlink_total_ratom_data_transmitted	Total reduction atomic data bytes transmitted through NVLinks This is available for compute capability 6.0.	Device
nvlink_total_response_data_received	Total response data bytes received through NVLink, response data includes data for read requests and result of non-reduction atomic requests. This is available for compute capability 6.0.	Device
nvlink_total_write_data_transmitted	Total write data bytes transmitted through NVLinks. This is available for compute capability 6.0.	Device
nvlink_transmit_throughput	Number of Bytes Transmitted per second through NVLinks. This is available for compute capability 6.0.	Device
nvlink_user_data_received	User data bytes received through NVLinks, doesn't include headers. This is available for compute capability 6.0.	Device

Metric Name	Description	Scope
nvlink_user_data_transmitted	User data bytes transmitted through NVLinks, doesn't include headers. This is available for compute capability 6.0.	Device
nvlink_user_nratom_data_transmitted	Total non-reduction atomic user data bytes transmitted through NVLinks. This is available for compute capability 6.0.	Device
nvlink_user_ratom_data_transmitted	Total reduction atomic user data bytes transmitted through NVLinks. This is available for compute capability 6.0.	Device
nvlink_user_response_data_received	Total user response data bytes received through NVLink, response data includes data for read requests and result of non-reduction atomic requests. This is available for compute capability 6.0.	Device
nvlink_user_write_data_transmitted	User write data bytes transmitted through NVLinks. This is available for compute capability 6.0.	Device
shared_efficiency	Ratio of requested shared memory throughput to required shared memory throughput expressed as percentage	Multi-context
shared_load_throughput	Shared memory load throughput	Multi-context
shared_load_transactions	Number of shared memory load transactions	Multi-context
shared_load_transactions_per_reques	t Average number of shared memory load transactions performed for each shared memory load	Multi-context
shared_store_throughput	Shared memory store throughput	Multi-context
shared_store_transactions	Number of shared memory store transactions	Multi-context
shared_store_transactions_per_reque	tAverage number of shared memory store transactions performed for each shared memory store	Multi-context
shared_utilization	The utilization level of the shared memory relative to peak utilization on a scale of 0 to 10	Multi-context
single_precision_fu_utilization	The utilization level of the multiprocessor function units that execute single-precision	Multi-context

Metric Name	Description	Scope
	floating-point instructions and integer instructions on a scale of 0 to 10	
sm_activity	The percentage of time at least one warp is active on a multiprocessor	Multi-context
special_fu_utilization	The utilization level of the multiprocessor function units that execute sin, cos, ex2, popc, flo, and similar instructions on a scale of 0 to 10	Multi-context
stall_constant_memory_dependency	Percentage of stalls occurring because of immediate constant cache miss	Multi-context
stall_exec_dependency	Percentage of stalls occurring because an input required by the instruction is not yet available	Multi-context
stall_inst_fetch	Percentage of stalls occurring because the next assembly instruction has not yet been fetched	Multi-context
stall_memory_dependency	Percentage of stalls occurring because a memory operation cannot be performed due to the required resources not being available or fully utilized, or because too many requests of a given type are outstanding	Multi-context
stall_memory_throttle	Percentage of stalls occurring because of memory throttle	Multi-context
stall_not_selected	Percentage of stalls occurring because warp was not selected	Multi-context
stall_other	Percentage of stalls occurring due to miscellaneous reasons	Multi-context
stall_pipe_busy	Percentage of stalls occurring because a compute operation cannot be performed due to the required resources not being available	Multi-context
stall_sync	Percentage of stalls occurring because the warp is blocked at asyncthreads() call	Multi-context
stall_texture	Percentage of stalls occurring because the texture sub-system is fully utilized or has too many outstanding requests	Multi-context

Metric Name	Description	Scope
sysmem_read_throughput	System memory read throughput	Multi-context
sysmem_read_transactions	System memory read transactions	Multi-context
sysmem_read_utilization	The read utilization level of the system memory relative to the peak utilization. This is available for compute capability 6.0 and 6.1.	Multi-context
sysmem_utilization	The utilization level of the system memory relative to the peak utilization on a scale of 0 to 10. This is available for compute capability 6.0 and 6.1.	Multi-context
sysmem_write_throughput	System memory write throughput	Multi-context
sysmem_write_transactions	System memory write transactions	Multi-context
sysmem_write_utilization	The write utilization level of the system memory relative to the peak utilization. This is available for compute capability 6.0 and 6.1.	Multi-context
tex_cache_hit_rate	Texture cache hit rate	Multi-context
tex_cache_throughput	Texture cache throughput	Multi-context
tex_cache_transactions	Texture cache read transactions	Multi-context
tex_fu_utilization	The utilization level of the multiprocessor function units that execute texture instructions on a scale of 0 to 10	Multi-context
tex_utilization	The utilization level of the texture cache relative to the peak utilization on a scale of 0 to 10	Multi-context
warp_execution_efficiency	Ratio of the average active threads per warp to the maximum number of threads per warp supported on a multiprocessor expressed as percentage	Multi-context
warp_nonpred_execution_efficiency	Ratio of the average active threads per warp executing non-predicated instructions to the maximum number of threads per warp supported on a multiprocessor	Multi-context

1.7. Samples

The CUPTI installation includes several samples that demonstrate the use of the CUPTI APIs. The samples are:

activity_trace_async

This sample shows how to collect a trace of CPU and GPU activity using the new asynchronous activity buffer APIs.

callback_event

This sample shows how to use both the callback and event APIs to record the events that occur during the execution of a simple kernel. The sample shows the required ordering for synchronization, and for event group enabling, disabling and reading.

callback_metric

This sample shows how to use both the callback and metric APIs to record the metric's events during the execution of a simple kernel, and then use those events to calculate the metric value.

callback_timestamp

This sample shows how to use the callback API to record a trace of API start and stop times.

cupti_query

This sample shows how to query CUDA-enabled devices for their event domains, events, and metrics.

event_sampling

This sample shows how to use the event APIs to sample events using a separate host thread.

event_multi_gpu

This sample shows how to use the CUPTI event and CUDA APIs to sample events on a setup with multiple GPUs. The sample shows the required ordering for synchronization, and for event group enabling, disabling and reading.

sass_source_map

This sample shows how to generate CUpti_ActivityInstructionExecution records and how to map SASS assembly instructions to CUDA C source.

unified_memory

This sample shows how to collect information about page transfers for unified memory.

pc_sampling

This sample shows how to collect PC Sampling profiling information for a kernel.

nvlink_bandwidth

This sample shows how to collect NVLink topology and NVLink throughput metrics in continuous mode.

openacc_trace

This sample shows how to use CUPTI APIs for OpenACC data collection.

Chapter 2. MODULES

Here is a list of all modules:

- CUPTI Version
- CUPTI Result Codes
- ► CUPTI Activity API
- ► CUPTI Callback API
- ► CUPTI Event API
- ► CUPTI Metric API

2.1. CUPTI Version

Function and macro to determine the CUPTI version.

CUptiResult cuptiGetVersion (uint32_t *version)

Get the CUPTI API version.

Parameters

version

Returns the version

Returns

► CUPTI_SUCCESS

on success

► CUPTI_ERROR_INVALID_PARAMETER

if version is NULL

Description

Return the API version in *version.

See also:

CUPTI API VERSION

#define CUPTI_API_VERSION 9

The API version for this implementation of CUPTI.

The API version for this implementation of CUPTI. This define along with cuptiGetVersion can be used to dynamically detect if the version of CUPTI compiled against matches the version of the loaded CUPTI library.

v1 : CUDAToolsSDK 4.0 v2 : CUDAToolsSDK 4.1 v3 : CUDA Toolkit 5.0 v4 : CUDA Toolkit 5.5 v5 : CUDA Toolkit 6.0 v6 : CUDA Toolkit 6.5 v7 : CUDA Toolkit 6.5(with sm_52 support) v8 : CUDA Toolkit 7.0 v9 : CUDA Toolkit 8.0

2.2. CUPTI Result Codes

Error and result codes returned by CUPTI functions.

enum CUptiResult

CUPTI result codes.

Error and result codes returned by CUPTI functions.

Values

 $CUPTI_SUCCESS = 0$

No error.

CUPTI_ERROR_INVALID_PARAMETER = 1

One or more of the parameters is invalid.

CUPTI_ERROR_INVALID_DEVICE = 2

The device does not correspond to a valid CUDA device.

CUPTI_ERROR_INVALID_CONTEXT = 3

The context is NULL or not valid.

CUPTI_ERROR_INVALID_EVENT_DOMAIN_ID = 4

The event domain id is invalid.

CUPTI_ERROR_INVALID_EVENT_ID = 5

The event id is invalid.

CUPTI ERROR INVALID EVENT NAME = 6

The event name is invalid.

CUPTI_ERROR_INVALID_OPERATION = 7

The current operation cannot be performed due to dependency on other factors.

CUPTI_ERROR_OUT_OF_MEMORY = 8

Unable to allocate enough memory to perform the requested operation.

CUPTI_ERROR_HARDWARE = 9

An error occurred on the performance monitoring hardware.

CUPTI_ERROR_PARAMETER_SIZE_NOT_SUFFICIENT = 10

The output buffer size is not sufficient to return all requested data.

CUPTI_ERROR_API_NOT_IMPLEMENTED = 11

API is not implemented.

CUPTI_ERROR_MAX_LIMIT_REACHED = 12

The maximum limit is reached.

CUPTI_ERROR_NOT_READY = 13

The object is not yet ready to perform the requested operation.

CUPTI ERROR NOT COMPATIBLE = 14

The current operation is not compatible with the current state of the object

CUPTI_ERROR_NOT_INITIALIZED = 15

CUPTI is unable to initialize its connection to the CUDA driver.

CUPTI_ERROR_INVALID_METRIC_ID = 16

The metric id is invalid.

CUPTI ERROR INVALID METRIC NAME = 17

The metric name is invalid.

CUPTI_ERROR_QUEUE_EMPTY = 18

The queue is empty.

CUPTI_ERROR_INVALID_HANDLE = 19

Invalid handle (internal?).

CUPTI_ERROR_INVALID_STREAM = 20

Invalid stream.

CUPTI_ERROR_INVALID_KIND = 21

Invalid kind.

CUPTI_ERROR_INVALID_EVENT_VALUE = 22

Invalid event value.

CUPTI ERROR DISABLED = 23

CUPTI is disabled due to conflicts with other enabled profilers

CUPTI_ERROR_INVALID_MODULE = 24

Invalid module.

CUPTI_ERROR_INVALID_METRIC_VALUE = 25

Invalid metric value.

CUPTI_ERROR_HARDWARE_BUSY = 26

The performance monitoring hardware is in use by other client.

CUPTI_ERROR_NOT_SUPPORTED = 27

The attempted operation is not supported on the current system or device.

CUPTI_ERROR_UM_PROFILING_NOT_SUPPORTED = 28

Unified memory profiling is not supported on the system. Potential reason could be unsupported OS or architecture.

CUPTI_ERROR_UM_PROFILING_NOT_SUPPORTED_ON_DEVICE = 29

Unified memory profiling is not supported on the device

CUPTI_ERROR_UM_PROFILING_NOT_SUPPORTED_ON_NON_P2P_DEVICES = 30

Unified memory profiling is not supported on a multi-GPU configuration without P2P support between any pair of devices

CUPTI_ERROR_UM_PROFILING_NOT_SUPPORTED_WITH_MPS = 31

Unified memory profiling is not supported under the Multi-Process Service (MPS) environment. CUDA 7.5 removes this restriction.

CUPTI_ERROR_UNKNOWN = 999

An unknown internal error has occurred.

CUPTI_ERROR_FORCE_INT = 0x7fffffff

CUptiResult cuptiGetResultString (CUptiResult result, const char **str)

Get the descriptive string for a CUptiResult.

Parameters

result

The result to get the string for

str

Returns the string

Returns

CUPTI_SUCCESS

on success

CUPTI_ERROR_INVALID_PARAMETER

if str is NULL or result is not a valid CUptiResult

Description

Return the descriptive string for a CUptiResult in *str.



Thread-safety: this function is thread safe.

2.3. CUPTI Activity API

Functions, types, and enums that implement the CUPTI Activity API.

struct CUpti_Activity

The base activity record.

struct CUpti_ActivityAPI

The activity record for a driver or runtime API invocation.

struct CUpti_ActivityAutoBoostState

Device auto boost state structure.

struct CUpti_ActivityBranch

The activity record for source level result branch. (deprecated).

struct CUpti_ActivityBranch2

The activity record for source level result branch.

struct CUpti_ActivityCdpKernel

The activity record for CDP (CUDA Dynamic Parallelism) kernel.

struct CUpti_ActivityContext

The activity record for a context.

struct CUpti_ActivityCudaEvent

The activity record for CUDA event.

struct CUpti_ActivityDevice

The activity record for a device. (deprecated).

struct CUpti_ActivityDevice2

The activity record for a device. (CUDA 7.0 onwards).

struct CUpti_ActivityDeviceAttribute

The activity record for a device attribute.

struct CUpti_ActivityEnvironment

The activity record for CUPTI environmental data.

struct CUpti_ActivityEvent

The activity record for a CUPTI event.

struct CUpti_ActivityEventInstance

The activity record for a CUPTI event with instance information.

struct CUpti_ActivityExternalCorrelation

The activity record for correlation with external records.

struct CUpti_ActivityFunction

The activity record for global/device functions.

struct CUpti_ActivityGlobalAccess

The activity record for source-level global access. (deprecated).

struct CUpti_ActivityGlobalAccess2

The activity record for source-level global access.

struct CUpti_ActivityInstantaneousEvent

The activity record for an instantaneous CUPTI event.

struct CUpti_ActivityInstantaneousEventInstance

The activity record for an instantaneous CUPTI event with event domain instance information.

struct CUpti_ActivityInstantaneousMetric

The activity record for an instantaneous CUPTI metric.

struct CUpti_ActivityInstantaneousMetricInstance

The instantaneous activity record for a CUPTI metric with instance information.

struct CUpti_ActivityInstructionCorrelation

The activity record for source-level sass/source line-by-line correlation.

struct CUpti_ActivityInstructionExecution

The activity record for source-level instruction execution.

struct CUpti_ActivityKernel

The activity record for kernel. (deprecated).

struct CUpti_ActivityKernel2

The activity record for kernel. (deprecated).

struct CUpti_ActivityKernel3

The activity record for a kernel (CUDA 6.5(with sm_52 support) onwards).

struct CUpti_ActivityMarker

The activity record providing a marker which is an instantaneous point in time. (deprecated in CUDA 8.0).

struct CUpti_ActivityMarker2

The activity record providing a marker which is an instantaneous point in time.

struct CUpti_ActivityMarkerData

The activity record providing detailed information for a marker.

struct CUpti_ActivityMemcpy

The activity record for memory copies.

struct CUpti_ActivityMemcpy2

The activity record for peer-to-peer memory copies.

struct CUpti_ActivityMemset

The activity record for memset.

struct CUpti_ActivityMetric

The activity record for a CUPTI metric.

struct CUpti_ActivityMetricInstance

The activity record for a CUPTI metric with instance information.

struct CUpti_ActivityModule

The activity record for a CUDA module.

struct CUpti_ActivityName

The activity record providing a name.

struct CUpti_ActivityNvLink

NvLink information.

union CUpti_ActivityObjectKindId

Identifiers for object kinds as specified by CUpti_ActivityObjectKind.

struct CUpti_ActivityOpenAcc

The base activity record for OpenAcc records.

struct CUpti_ActivityOpenAccData

The activity record for OpenACC data.

struct CUpti_ActivityOpenAccLaunch

The activity record for OpenACC launch.

struct CUpti_ActivityOpenAccOther

The activity record for OpenACC other.

struct CUpti_ActivityOverhead

The activity record for CUPTI and driver overheads.

struct CUpti_ActivityPCSampling

The activity record for PC sampling. (deprecated in CUDA 8.0).

struct CUpti_ActivityPCSampling2

The activity record for PC sampling.

struct CUpti_ActivityPCSamplingConfig

PC sampling configuration structure.

struct CUpti_ActivityPCSamplingRecordInfo

The activity record for record status for PC sampling.

struct CUpti_ActivityPreemption

The activity record for a preemption of a CDP kernel.

struct CUpti_ActivitySharedAccess

The activity record for source-level shared access.

struct CUpti_ActivitySourceLocator

The activity record for source locator.

struct CUpti_ActivityStream

The activity record for CUDA stream.

struct CUpti_ActivitySynchronization

The activity record for synchronization management.

struct CUpti_ActivityUnifiedMemoryCounter

The activity record for Unified Memory counters (deprecated in CUDA 7.0).

struct CUpti_ActivityUnifiedMemoryCounter2

The activity record for Unified Memory counters (CUDA 7.0 and beyond).

struct CUpti_ActivityUnifiedMemoryCounterConfig

Unified Memory counters configuration structure.

enum CUpti_ActivityAttribute

Activity attributes.

These attributes are used to control the behavior of the activity API.

Values

CUPTI_ACTIVITY_ATTR_DEVICE_BUFFER_SIZE = 0

The device memory size (in bytes) reserved for storing profiling data for non-CDP operations for each buffer on a context. The value is a size_t.Having larger buffer size means less flush operations but consumes more device memory. Having smaller buffer size increases the risk of dropping timestamps for kernel records if too many kernels are launched/replayed at one time. This value only applies to new buffer allocations.Set this value before initializing CUDA or before creating a context to ensure it is considered for the following allocations.The default value is 8388608 (8MB).Note: The actual amount of device memory per buffer reserved by CUPTI might be larger.

CUPTI_ACTIVITY_ATTR_DEVICE_BUFFER_SIZE_CDP = 1

The device memory size (in bytes) reserved for storing profiling data for CDP operations for each buffer on a context. The value is a size_t.Having larger buffer size means less flush operations but consumes more device memory. This value only applies to new allocations.Set this value before initializing CUDA or before creating a context to ensure it is considered for the following allocations.The default value is 8388608 (8MB).Note: The actual amount of device memory per context reserved by CUPTI might be larger.

CUPTI_ACTIVITY_ATTR_DEVICE_BUFFER_POOL_LIMIT = 2

The maximum number of memory buffers per context. The value is a size_t.Buffers can be reused by the context. Increasing this value reduces the times CUPTI needs to flush the buffers. Setting this value will not modify the number of memory buffers

currently stored. Set this value before initializing CUDA to ensure the limit is not exceeded. The default value is 4.

CUPTI_ACTIVITY_ATTR_DEVICE_BUFFER_FORCE_INT = 0x7ffffffff

enum CUpti_ActivityComputeApiKind

The kind of a compute API.

Values

CUPTI_ACTIVITY_COMPUTE_API_UNKNOWN = 0

The compute API is not known.

CUPTI_ACTIVITY_COMPUTE_API_CUDA = 1

The compute APIs are for CUDA.

CUPTI_ACTIVITY_COMPUTE_API_CUDA_MPS = 2

The compute APIs are for CUDA running in MPS (Multi-Process Service) environment.

CUPTI_ACTIVITY_COMPUTE_API_FORCE_INT = 0x7fffffff

enum CUpti_ActivityEnvironmentKind

The kind of environment data. Used to indicate what type of data is being reported by an environment activity record.

Values

CUPTI_ACTIVITY_ENVIRONMENT_UNKNOWN = 0

Unknown data.

CUPTI_ACTIVITY_ENVIRONMENT_SPEED = 1

The environment data is related to speed.

CUPTI_ACTIVITY_ENVIRONMENT_TEMPERATURE = 2

The environment data is related to temperature.

CUPTI_ACTIVITY_ENVIRONMENT_POWER = 3

The environment data is related to power.

CUPTI_ACTIVITY_ENVIRONMENT_COOLING = 4

The environment data is related to cooling.

CUPTI_ACTIVITY_ENVIRONMENT_COUNT

CUPTI_ACTIVITY_ENVIRONMENT_KIND_FORCE_INT = 0x7fffffff

enum CUpti_ActivityFlag

Flags associated with activity records.

Activity record flags. Flags can be combined by bitwise OR to associated multiple flags with an activity record. Each flag is specific to a certain activity kind, as noted below.

Values

CUPTI_ACTIVITY_FLAG_NONE = 0

Indicates the activity record has no flags.

CUPTI ACTIVITY FLAG DEVICE CONCURRENT KERNELS = 1<<0

Indicates the activity represents a device that supports concurrent kernel execution. Valid for CUPTI_ACTIVITY_KIND_DEVICE.

CUPTI_ACTIVITY_FLAG_DEVICE_ATTRIBUTE_CUDEVICE = 1<<0

Indicates if the activity represents a CUdevice_attribute value or a CUpti_DeviceAttribute value. Valid for CUPTI_ACTIVITY_KIND_DEVICE_ATTRIBUTE.

CUPTI_ACTIVITY_FLAG_MEMCPY_ASYNC = 1<<0

Indicates the activity represents an asynchronous memcpy operation. Valid for CUPTI ACTIVITY KIND MEMCPY.

CUPTI_ACTIVITY_FLAG_MARKER_INSTANTANEOUS = 1<<0

Indicates the activity represents an instantaneous marker. Valid for CUPTI_ACTIVITY_KIND_MARKER.

CUPTI_ACTIVITY_FLAG_MARKER_START = 1<<1

Indicates the activity represents a region start marker. Valid for CUPTI_ACTIVITY_KIND_MARKER.

CUPTI_ACTIVITY_FLAG_MARKER_END = 1<<2

Indicates the activity represents a region end marker. Valid for CUPTI_ACTIVITY_KIND_MARKER.

CUPTI_ACTIVITY_FLAG_MARKER_SYNC_ACQUIRE = 1<<3

Indicates the activity represents an attempt to acquire a user defined synchronization object. Valid for CUPTI_ACTIVITY_KIND_MARKER.

CUPTI_ACTIVITY_FLAG_MARKER_SYNC_ACQUIRE_SUCCESS = 1<<4

Indicates the activity represents success in acquiring the user defined synchronization object. Valid for CUPTI_ACTIVITY_KIND_MARKER.

CUPTI_ACTIVITY_FLAG_MARKER_SYNC_ACQUIRE_FAILED = 1<<5

Indicates the activity represents failure in acquiring the user defined synchronization object. Valid for CUPTI_ACTIVITY_KIND_MARKER.

CUPTI_ACTIVITY_FLAG_MARKER_SYNC_RELEASE = 1<<6

Indicates the activity represents releasing a reservation on user defined synchronization object. Valid for CUPTI_ACTIVITY_KIND_MARKER.

CUPTI_ACTIVITY_FLAG_MARKER_COLOR_NONE = 1<<0

Indicates the activity represents a marker that does not specify a color. Valid for CUPTI_ACTIVITY_KIND_MARKER_DATA.

CUPTI_ACTIVITY_FLAG_MARKER_COLOR_ARGB = 1<<1

Indicates the activity represents a marker that specifies a color in alpha-red-green-blue format. Valid for CUPTI_ACTIVITY_KIND_MARKER_DATA.

CUPTI_ACTIVITY_FLAG_GLOBAL_ACCESS_KIND_SIZE_MASK = 0xFF<<0

The number of bytes requested by each thread Valid for CUpti_ActivityGlobalAccess2.

CUPTI ACTIVITY FLAG GLOBAL ACCESS KIND LOAD = 1<<8

If bit in this flag is set, the access was load, else it is a store access. Valid for CUpti_ActivityGlobalAccess2.

CUPTI_ACTIVITY_FLAG_GLOBAL_ACCESS_KIND_CACHED = 1<<9

If this bit in flag is set, the load access was cached else it is uncached. Valid for CUpti_ActivityGlobalAccess2.

CUPTI_ACTIVITY_FLAG_METRIC_OVERFLOWED = 1<<0

If this bit in flag is set, the metric value overflowed. Valid for CUpti_ActivityMetric and CUpti_ActivityMetricInstance.

CUPTI_ACTIVITY_FLAG_METRIC_VALUE_INVALID = 1<<1

If this bit in flag is set, the metric value couldn't be calculated. This occurs when a value(s) required to calculate the metric is missing. Valid for CUpti_ActivityMetric and CUpti_ActivityMetricInstance.

CUPTI ACTIVITY FLAG INSTRUCTION VALUE INVALID = 1<<0

If this bit in flag is set, the source level metric value couldn't be calculated. This occurs when a value(s) required to calculate the source level metric cannot be evaluated. Valid for CUpti_ActivityInstructionExecution.

CUPTI_ACTIVITY_FLAG_INSTRUCTION_CLASS_MASK = 0xFF<<1

The mask for the instruction class, CUpti_ActivityInstructionClass Valid for CUpti_ActivityInstructionExecution and CUpti_ActivityInstructionCorrelation

CUPTI_ACTIVITY_FLAG_FLUSH_FORCED = 1<<0

When calling cuptiActivityFlushAll, this flag can be set to force CUPTI to flush all records in the buffer, whether finished or not

CUPTI_ACTIVITY_FLAG_SHARED_ACCESS_KIND_SIZE_MASK = 0xFF<<0

The number of bytes requested by each thread Valid for CUpti_ActivitySharedAccess.

CUPTI_ACTIVITY_FLAG_SHARED_ACCESS_KIND_LOAD = 1<<8

If bit in this flag is set, the access was load, else it is a store access. Valid for CUpti_ActivitySharedAccess.

CUPTI_ACTIVITY_FLAG_MEMSET_ASYNC = 1<<0

Indicates the activity represents an asynchronous memset operation. Valid for CUPTI_ACTIVITY_KIND_MEMSET.

CUPTI_ACTIVITY_FLAG_FORCE_INT = 0x7fffffff

enum CUpti_ActivityInstructionClass

SASS instruction classification.

The sass instruction are broadly divided into different class. Each enum represents a classification.

Values

CUPTI_ACTIVITY_INSTRUCTION_CLASS_UNKNOWN = 0

The instruction class is not known.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_FP_32 = 1

Represents a 32 bit floating point operation.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_FP_64 = 2

Represents a 64 bit floating point operation.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_INTEGER = 3

Represents an integer operation.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_BIT_CONVERSION = 4

Represents a bit conversion operation.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_CONTROL_FLOW = 5

Represents a control flow instruction.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_GLOBAL = 6

Represents a global load-store instruction.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_SHARED = 7

Represents a shared load-store instruction.

CUPTI ACTIVITY INSTRUCTION CLASS LOCAL = 8

Represents a local load-store instruction.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_GENERIC = 9

Represents a generic load-store instruction.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_SURFACE = 10

Represents a surface load-store instruction.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_CONSTANT = 11

Represents a constant load instruction.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_TEXTURE = 12

Represents a texture load-store instruction.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_GLOBAL_ATOMIC = 13

Represents a global atomic instruction.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_SHARED_ATOMIC = 14

Represents a shared atomic instruction.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_SURFACE_ATOMIC = 15

Represents a surface atomic instruction.

- 16

= 16

Represents a inter-thread communication instruction.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_BARRIER = 17

Represents a barrier instruction.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_MISCELLANEOUS = 18

Represents some miscellaneous instructions which do not fit in the above classification.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_INTER_THREAD_COMMUNICATION

CUPTI_ACTIVITY_INSTRUCTION_CLASS_FP_16 = 19

Represents a 16 bit floating point operation.

CUPTI_ACTIVITY_INSTRUCTION_CLASS_KIND_FORCE_INT = 0x7fffffff

enum CUpti_ActivityKind

The kinds of activity records.

Each activity record kind represents information about a GPU or an activity occurring on a CPU or GPU. Each kind is associated with a activity record structure that holds the information associated with the kind.

See also:

CUpti_Activity

CUpti_ActivityAPI

CUpti_ActivityContext

CUpti_ActivityDevice

CUpti_ActivityDevice2

CUpti_ActivityDeviceAttribute

CUpti_ActivityEvent

CUpti_ActivityEventInstance

CUpti_ActivityKernel

CUpti_ActivityKernel2

CUpti_ActivityKernel3

CUpti_ActivityCdpKernel

CUpti_ActivityPreemption

CUpti_ActivityMemcpy

CUpti_ActivityMemcpy2

CUpti_ActivityMemset

CUpti_ActivityMetric

CUpti_ActivityMetricInstance

CUpti_ActivityName

CUpti_ActivityMarker

CUpti_ActivityMarker2

CUpti_ActivityMarkerData

CUpti_ActivitySourceLocator

CUpti_ActivityGlobalAccess

CUpti_ActivityGlobalAccess2

CUpti_ActivityBranch

CUpti_ActivityBranch2

CUpti_ActivityOverhead

CUpti_ActivityEnvironment

CUpti_ActivityInstructionExecution

CUpti_ActivityUnifiedMemoryCounter

CUpti_ActivityFunction

CUpti_ActivityModule

CUpti_ActivitySharedAccess

CUpti_ActivityPCSampling

CUpti_ActivityPCSampling2

CUpti_ActivityPCSamplingRecordInfo

CUpti_ActivityCudaEvent

CUpti_ActivityStream

CUpti_ActivitySynchronization

CUpti_ActivityInstructionCorrelation

CUpti_ActivityExternalCorrelation

CUpti_ActivityUnifiedMemoryCounter2

CUpti_ActivityOpenAccData

CUpti_ActivityOpenAccLaunch

CUpti_ActivityOpenAccOther

CUpti_ActivityNvLink

Values

CUPTI_ACTIVITY_KIND_INVALID = 0

The activity record is invalid.

CUPTI_ACTIVITY_KIND_MEMCPY = 1

A host<->host, host<->device, or device<->device memory copy. The corresponding activity record structure is CUpti_ActivityMemcpy.

CUPTI_ACTIVITY_KIND_MEMSET = 2

A memory set executing on the GPU. The corresponding activity record structure is CUpti_ActivityMemset.

CUPTI ACTIVITY KIND KERNEL = 3

A kernel executing on the GPU. The corresponding activity record structure is CUpti_ActivityKernel3.

CUPTI_ACTIVITY_KIND_DRIVER = 4

A CUDA driver API function execution. The corresponding activity record structure is CUpti_ActivityAPI.

CUPTI_ACTIVITY_KIND_RUNTIME = 5

A CUDA runtime API function execution. The corresponding activity record structure is CUpti_ActivityAPI.

CUPTI_ACTIVITY_KIND_EVENT = 6

An event value. The corresponding activity record structure is CUpti_ActivityEvent.

CUPTI_ACTIVITY_KIND_METRIC = 7

A metric value. The corresponding activity record structure is CUpti_ActivityMetric.

CUPTI ACTIVITY KIND DEVICE = 8

Information about a device. The corresponding activity record structure is CUpti_ActivityDevice2.

CUPTI_ACTIVITY_KIND_CONTEXT = 9

Information about a context. The corresponding activity record structure is CUpti_ActivityContext.

CUPTI_ACTIVITY_KIND_CONCURRENT_KERNEL = 10

A (potentially concurrent) kernel executing on the GPU. The corresponding activity record structure is CUpti_ActivityKernel3.

CUPTI ACTIVITY KIND NAME = 11

Thread, device, context, etc. name. The corresponding activity record structure is CUpti_ActivityName.

CUPTI_ACTIVITY_KIND_MARKER = 12

Instantaneous, start, or end marker. The corresponding activity record structure is CUpti_ActivityMarker2.

CUPTI_ACTIVITY_KIND_MARKER_DATA = 13

Extended, optional, data about a marker. The corresponding activity record structure is CUpti_ActivityMarkerData.

CUPTI_ACTIVITY_KIND_SOURCE_LOCATOR = 14

Source information about source level result. The corresponding activity record structure is CUpti_ActivitySourceLocator.

CUPTI_ACTIVITY_KIND_GLOBAL_ACCESS = 15

Results for source-level global access. The corresponding activity record structure is CUpti_ActivityGlobalAccess2.

CUPTI_ACTIVITY_KIND_BRANCH = 16

Results for source-level branch. The corresponding activity record structure is CUpti_ActivityBranch2.

CUPTI_ACTIVITY_KIND_OVERHEAD = 17

Overhead activity records. The corresponding activity record structure is CUpti_ActivityOverhead.

CUPTI ACTIVITY KIND CDP KERNEL = 18

A CDP (CUDA Dynamic Parallel) kernel executing on the GPU. The corresponding activity record structure is CUpti_ActivityCdpKernel. This activity can not be directly enabled or disabled. It is enabled and disabled through concurrent kernel activity i.e. _CONCURRENT_KERNEL

CUPTI_ACTIVITY_KIND_PREEMPTION = 19

Preemption activity record indicating a preemption of a CDP (CUDA Dynamic Parallel) kernel executing on the GPU. The corresponding activity record structure is CUpti_ActivityPreemption.

CUPTI_ACTIVITY_KIND_ENVIRONMENT = 20

Environment activity records indicating power, clock, thermal, etc. levels of the GPU. The corresponding activity record structure is CUpti_ActivityEnvironment.

CUPTI_ACTIVITY_KIND_EVENT_INSTANCE = 21

An event value associated with a specific event domain instance. The corresponding activity record structure is CUpti_ActivityEventInstance.

CUPTI_ACTIVITY_KIND_MEMCPY2 = 22

A peer to peer memory copy. The corresponding activity record structure is CUpti_ActivityMemcpy2.

CUPTI_ACTIVITY_KIND_METRIC_INSTANCE = 23

A metric value associated with a specific metric domain instance. The corresponding activity record structure is CUpti_ActivityMetricInstance.

CUPTI_ACTIVITY_KIND_INSTRUCTION_EXECUTION = 24

Results for source-level instruction execution. The corresponding activity record structure is CUpti_ActivityInstructionExecution.

CUPTI_ACTIVITY_KIND_UNIFIED_MEMORY_COUNTER = 25

Unified Memory counter record. The corresponding activity record structure is CUpti_ActivityUnifiedMemoryCounter2.

CUPTI_ACTIVITY_KIND_FUNCTION = 26

Device global/function record. The corresponding activity record structure is CUpti_ActivityFunction.

CUPTI_ACTIVITY_KIND_MODULE = 27

CUDA Module record. The corresponding activity record structure is CUpti ActivityModule.

CUPTI_ACTIVITY_KIND_DEVICE_ATTRIBUTE = 28

A device attribute value. The corresponding activity record structure is CUpti ActivityDeviceAttribute.

CUPTI_ACTIVITY_KIND_SHARED_ACCESS = 29

Results for source-level shared access. The corresponding activity record structure is CUpti_ActivitySharedAccess.

CUPTI_ACTIVITY_KIND_PC_SAMPLING = 30

Enable PC sampling for kernels. This will serialize kernels. The corresponding activity record structure is CUpti ActivityPCSampling2.

CUPTI_ACTIVITY_KIND_PC_SAMPLING_RECORD_INFO = 31

Summary information about PC sampling records. The corresponding activity record structure is CUpti_ActivityPCSamplingRecordInfo.

CUPTI_ACTIVITY_KIND_INSTRUCTION_CORRELATION = 32

SASS/Source line-by-line correlation record. This will generate sass/source correlation for functions that have source level analysis or pc sampling results. The records will be generated only when either of source level analysis or pc sampling activity is enabled. The corresponding activity record structure is CUpti_ActivityInstructionCorrelation.

CUPTI_ACTIVITY_KIND_OPENACC_DATA = 33

OpenACC data events. The corresponding activity record structure is CUpti_ActivityOpenAccData.

CUPTI_ACTIVITY_KIND_OPENACC_LAUNCH = 34

OpenACC launch events. The corresponding activity record structure is CUpti_ActivityOpenAccLaunch.

CUPTI_ACTIVITY_KIND_OPENACC_OTHER = 35

OpenACC other events. The corresponding activity record structure is CUpti_ActivityOpenAccOther.

CUPTI_ACTIVITY_KIND_CUDA_EVENT = 36

Information about a CUDA event. The corresponding activity record structure is CUpti_ActivityCudaEvent.

CUPTI_ACTIVITY_KIND_STREAM = 37

Information about a CUDA stream. The corresponding activity record structure is CUpti ActivityStream.

CUPTI_ACTIVITY_KIND_SYNCHRONIZATION = 38

Records for synchronization management. The corresponding activity record structure is CUpti_ActivitySynchronization.

CUPTI_ACTIVITY_KIND_EXTERNAL_CORRELATION = 39

Records for correlation of different programming APIs. The corresponding activity record structure is CUpti_ActivityExternalCorrelation.

CUPTI_ACTIVITY_KIND_NVLINK = 40

Nvlink information. The corresponding activity record structure is CUpti_ActivityNvLink.

CUPTI_ACTIVITY_KIND_INSTANTANEOUS_EVENT = 41

Instantaneous Event information. The corresponding activity record structure is CUpti_ActivityInstantaneousEvent.

CUPTI_ACTIVITY_KIND_INSTANTANEOUS_EVENT_INSTANCE = 42

Instantaneous Event information for a specific event domain instance. The corresponding activity record structure is CUpti_ActivityInstantaneousEventInstance

CUPTI_ACTIVITY_KIND_INSTANTANEOUS_METRIC = 43

Instantaneous Metric information The corresponding activity record structure is CUpti_ActivityInstantaneousMetric.

CUPTI_ACTIVITY_KIND_INSTANTANEOUS_METRIC_INSTANCE = 44

Instantaneous Metric information for a specific metric domain instance. The corresponding activity record structure is CUpti ActivityInstantaneousMetricInstance.

CUPTI_ACTIVITY_KIND_FORCE_INT = 0x7fffffff

enum CUpti_ActivityMemcpyKind

The kind of a memory copy, indicating the source and destination targets of the copy.

Each kind represents the source and destination targets of a memory copy. Targets are host, device, and array.

Values

CUPTI_ACTIVITY_MEMCPY_KIND_UNKNOWN = 0

The memory copy kind is not known.

CUPTI_ACTIVITY_MEMCPY_KIND_HTOD = 1

A host to device memory copy.

CUPTI_ACTIVITY_MEMCPY_KIND_DTOH = 2

A device to host memory copy.

CUPTI_ACTIVITY_MEMCPY_KIND_HTOA = 3

A host to device array memory copy.

CUPTI_ACTIVITY_MEMCPY_KIND_ATOH = 4

A device array to host memory copy.

CUPTI_ACTIVITY_MEMCPY_KIND_ATOA = 5

A device array to device array memory copy.

CUPTI_ACTIVITY_MEMCPY_KIND_ATOD = 6

A device array to device memory copy.

CUPTI_ACTIVITY_MEMCPY_KIND_DTOA = 7

A device to device array memory copy.

CUPTI_ACTIVITY_MEMCPY_KIND_DTOD = 8

A device to device memory copy on the same device.

CUPTI_ACTIVITY_MEMCPY_KIND_HTOH = 9

A host to host memory copy.

CUPTI_ACTIVITY_MEMCPY_KIND_PTOP = 10

A peer to peer memory copy across different devices.

CUPTI_ACTIVITY_MEMCPY_KIND_FORCE_INT = 0x7fffffff

enum CUpti_ActivityMemoryKind

The kinds of memory accessed by a memory copy.

Each kind represents the type of the memory accessed by a memory copy.

Values

CUPTI_ACTIVITY_MEMORY_KIND_UNKNOWN = 0

The memory kind is unknown.

CUPTI_ACTIVITY_MEMORY_KIND_PAGEABLE = 1

The memory is pageable.

CUPTI_ACTIVITY_MEMORY_KIND_PINNED = 2

The memory is pinned.

CUPTI_ACTIVITY_MEMORY_KIND_DEVICE = 3

The memory is on the device.

CUPTI_ACTIVITY_MEMORY_KIND_ARRAY = 4

The memory is an array.

CUPTI_ACTIVITY_MEMORY_KIND_MANAGED = 5

The memory is managed

CUPTI_ACTIVITY_MEMORY_KIND_FORCE_INT = 0x7fffffff

enum CUpti_ActivityObjectKind

The kinds of activity objects.

See also:

CUpti_ActivityObjectKindId

Values

CUPTI_ACTIVITY_OBJECT_UNKNOWN = 0

The object kind is not known.

CUPTI_ACTIVITY_OBJECT_PROCESS = 1

A process.

CUPTI_ACTIVITY_OBJECT_THREAD = 2

A thread.

CUPTI_ACTIVITY_OBJECT_DEVICE = 3

A device.

CUPTI_ACTIVITY_OBJECT_CONTEXT = 4

A context.

CUPTI_ACTIVITY_OBJECT_STREAM = 5

A stream.

CUPTI_ACTIVITY_OBJECT_FORCE_INT = 0x7fffffff

enum CUpti_ActivityOverheadKind

The kinds of activity overhead.

Values

CUPTI_ACTIVITY_OVERHEAD_UNKNOWN = 0

The overhead kind is not known.

CUPTI_ACTIVITY_OVERHEAD_DRIVER_COMPILER = 1

Compiler(JIT) overhead.

CUPTI_ACTIVITY_OVERHEAD_CUPTI_BUFFER_FLUSH = 1<<16

Activity buffer flush overhead.

CUPTI_ACTIVITY_OVERHEAD_CUPTI_INSTRUMENTATION = 2<<16

CUPTI instrumentation overhead.

CUPTI_ACTIVITY_OVERHEAD_CUPTI_RESOURCE = 3<<16

CUPTI resource creation and destruction overhead.

CUPTI_ACTIVITY_OVERHEAD_FORCE_INT = 0x7fffffff

enum CUpti_ActivityPartitionedGlobalCacheConfig

Partitioned global caching option.

Values

CUPTI_ACTIVITY_PARTITIONED_GLOBAL_CACHE_CONFIG_UNKNOWN = 0

Partitioned global cache config unknown.

CUPTI_ACTIVITY_PARTITIONED_GLOBAL_CACHE_CONFIG_NOT_SUPPORTED = 1

Partitioned global cache not supported.

CUPTI_ACTIVITY_PARTITIONED_GLOBAL_CACHE_CONFIG_OFF = 2

Partitioned global cache config off.

CUPTI_ACTIVITY_PARTITIONED_GLOBAL_CACHE_CONFIG_ON = 3

Partitioned global cache config on.

CUPTI_ACTIVITY_PARTITIONED_GLOBAL_CACHE_CONFIG_FORCE_INT = 0x7fffffff

enum CUpti_ActivityPCSamplingPeriod

Sampling period for PC sampling method Sampling period can be set using /ref cuptiActivityConfigurePCSampling.

Values

CUPTI_ACTIVITY_PC_SAMPLING_PERIOD_INVALID = 0

The PC sampling period is not set.

CUPTI_ACTIVITY_PC_SAMPLING_PERIOD_MIN = 1

Minimum sampling period available on the device.

CUPTI_ACTIVITY_PC_SAMPLING_PERIOD_LOW = 2

Sampling period in lower range.

CUPTI_ACTIVITY_PC_SAMPLING_PERIOD_MID = 3

Medium sampling period.

CUPTI_ACTIVITY_PC_SAMPLING_PERIOD_HIGH = 4

Sampling period in higher range.

CUPTI_ACTIVITY_PC_SAMPLING_PERIOD_MAX = 5

Maximum sampling period available on the device.

CUPTI_ACTIVITY_PC_SAMPLING_PERIOD_FORCE_INT = 0x7fffffff

enum CUpti_ActivityPCSamplingStallReason

The stall reason for PC sampling activity.

Values

CUPTI_ACTIVITY_PC_SAMPLING_STALL_INVALID = 0

Invalid reason

CUPTI_ACTIVITY_PC_SAMPLING_STALL_NONE = 1

No stall, instruction is selected for issue

CUPTI_ACTIVITY_PC_SAMPLING_STALL_INST_FETCH = 2

Warp is blocked because next instruction is not yet available, because of instruction cache miss, or because of branching effects

CUPTI_ACTIVITY_PC_SAMPLING_STALL_EXEC_DEPENDENCY = 3

Instruction is waiting on an arithmatic dependency

CUPTI_ACTIVITY_PC_SAMPLING_STALL_MEMORY_DEPENDENCY = 4

Warp is blocked because it is waiting for a memory access to complete.

CUPTI_ACTIVITY_PC_SAMPLING_STALL_TEXTURE = 5

Texture sub-system is fully utilized or has too many outstanding requests.

CUPTI_ACTIVITY_PC_SAMPLING_STALL_SYNC = 6

Warp is blocked as it is waiting at syncthreads() or at memory barrier.

CUPTI_ACTIVITY_PC_SAMPLING_STALL_CONSTANT_MEMORY_DEPENDENCY = 7

Warp is blocked waiting for __constant__ memory and immediate memory access to complete.

CUPTI_ACTIVITY_PC_SAMPLING_STALL_PIPE_BUSY = 8

Compute operation cannot be performed due to the required resources not being available.

CUPTI_ACTIVITY_PC_SAMPLING_STALL_MEMORY_THROTTLE = 9

Warp is blocked because there are too many pending memory operations. In Kepler architecture it often indicates high number of memory replays.

CUPTI_ACTIVITY_PC_SAMPLING_STALL_NOT_SELECTED = 10

Warp was ready to issue, but some other warp issued instead.

CUPTI_ACTIVITY_PC_SAMPLING_STALL_OTHER = 11

Miscellaneous reasons

CUPTI_ACTIVITY_PC_SAMPLING_STALL_FORCE_INT = 0x7fffffff

enum CUpti_ActivityPreemptionKind

The kind of a preemption activity.

Values

CUPTI_ACTIVITY_PREEMPTION_KIND_UNKNOWN = 0

The preemption kind is not known.

CUPTI_ACTIVITY_PREEMPTION_KIND_SAVE = 1

Preemption to save CDP block.

CUPTI_ACTIVITY_PREEMPTION_KIND_RESTORE = 2

Preemption to restore CDP block.

CUPTI_ACTIVITY_PREEMPTION_KIND_FORCE_INT = 0x7ffffffff

enum CUpti_ActivityStreamFlag

stream type.

The types of stream to be used with CUpti_ActivityStream.

Values

CUPTI_ACTIVITY_STREAM_CREATE_FLAG_UNKNOWN = 0 Unknown data.

CUPTI_ACTIVITY_STREAM_CREATE_FLAG_DEFAULT = 1
Default stream.

CUPTI_ACTIVITY_STREAM_CREATE_FLAG_NON_BLOCKING = 2 Non-blocking stream.

CUPTI_ACTIVITY_STREAM_CREATE_FLAG_NULL = 3
Null stream.

CUPTI_ACTIVITY_STREAM_CREATE_MASK = 0xFFFF
Stream create Mask

CUPTI_ACTIVITY_STREAM_CREATE_FLAG_FORCE_INT = 0x7fffffff

enum CUpti_ActivitySynchronizationType

Synchronization type.

The types of synchronization to be used with CUpti_ActivitySynchronization.

Values

CUPTI_ACTIVITY_SYNCHRONIZATION_TYPE_UNKNOWN = 0 Unknown data.

CUPTI_ACTIVITY_SYNCHRONIZATION_TYPE_EVENT_SYNCHRONIZE = 1 Event synchronize API.

CUPTI_ACTIVITY_SYNCHRONIZATION_TYPE_STREAM_WAIT_EVENT = 2
Stream wait event API.

CUPTI_ACTIVITY_SYNCHRONIZATION_TYPE_STREAM_SYNCHRONIZE = 3
Stream synchronize API.

CUPTI_ACTIVITY_SYNCHRONIZATION_TYPE_CONTEXT_SYNCHRONIZE = 4
Context synchronize API.

CUPTI ACTIVITY SYNCHRONIZATION TYPE FORCE INT = 0x7fffffff

enum CUpti_ActivityThreadIdType

Thread-Id types.

CUPTI uses different methods to obtain the thread-id depending on the support and the underlying platform. This enum documents these methods for each type. APIs cuptiSetThreadIdType and cuptiGetThreadIdType can be used to set and get the thread-id type.

Values

CUPTI_ACTIVITY_THREAD_ID_TYPE_DEFAULT = 0

Default type Windows uses API GetCurrentThreadId() Linux/Mac/Android/QNX use POSIX pthread API pthread_self()

CUPTI_ACTIVITY_THREAD_ID_TYPE_SYSTEM = 1

This type is based on the system API available on the underlying platform and thread-id obtained is supposed to be unique for the process lifetime. Windows uses API GetCurrentThreadId() Linux uses syscall SYS_gettid Mac uses syscall SYS_thread_selfid Android/QNX use gettid()

CUPTI_ACTIVITY_THREAD_ID_TYPE_FORCE_INT = 0x7ffffffff

enum CUpti_ActivityUnifiedMemoryAccessType

Access type of the Unified Memory counter.

This is valid for

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_GPU_PAGE_FAULT

Values

${\bf CUPTI_ACTIVITY_UNIFIED_MEMORY_ACCESS_TYPE_UNKNOWN=0}$

The unified memory access type is not known

CUPTI_ACTIVITY_UNIFIED_MEMORY_ACCESS_TYPE_READ = 1

The unified memory access type is read

CUPTI_ACTIVITY_UNIFIED_MEMORY_ACCESS_TYPE_WRITE = 2

The unified memory access type is write

CUPTI_ACTIVITY_UNIFIED_MEMORY_ACCESS_TYPE_ATOMIC = 3

The unified memory access type is atomic

CUPTI_ACTIVITY_UNIFIED_MEMORY_ACCESS_TYPE_PREFETCH = 4

The unified memory access type is prefetch

enum CUpti_ActivityUnifiedMemoryCounterKind

Kind of the Unified Memory counter.

Many activities are associated with Unified Memory mechanism; among them are transfer from host to device, device to host, page fault at host side.

Values

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_UNKNOWN = 0

The unified memory counter kind is not known.

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_BYTES_TRANSFER_HTOD = 1

Number of bytes transfered from host to device

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_BYTES_TRANSFER_DTOH = 2

Number of bytes transfered from device to host

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_CPU_PAGE_FAULT_COUNT = 3

Number of CPU page faults, this is only supported on 64 bit linux platforms

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_GPU_PAGE_FAULT = 4

Number of GPU page faults, this is only supported on devices with compute capability 6.0 and higher and 64 bit linux platforms

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_COUNT CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_FORCE_INT = 0x7fffffff

enum CUpti_ActivityUnifiedMemoryCounterScope

Scope of the unified memory counter (deprecated in CUDA 7.0).

Values

 ${\bf CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_SCOPE_UNKNOWN=0}$

The unified memory counter scope is not known.

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_SCOPE_PROCESS_SINGLE_DEVICE = 1

Collect unified memory counter for single process on one device

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_SCOPE_PROCESS_ALL_DEVICES = 2

Collect unified memory counter for single process across all devices

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_SCOPE_COUNT CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_SCOPE_FORCE_INT = 0x7fffffff

enum CUpti_ActivityUnifiedMemoryMigrationCause

Migration cause of the Unified Memory counter.

This is valid for

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_BYTES_TRANSFER_HTOD and

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_BYTES_TRANSFER_DTOH

Values

CUPTI_ACTIVITY_UNIFIED_MEMORY_MIGRATION_CAUSE_UNKNOWN = 0
The unified memory migration cause is not known

CUPTI_ACTIVITY_UNIFIED_MEMORY_MIGRATION_CAUSE_USER = 1
The unified memory migration cause is user

CUPTI_ACTIVITY_UNIFIED_MEMORY_MIGRATION_CAUSE_COHERENCE = 2
The unified memory migration cause is coherence

CUPTI_ACTIVITY_UNIFIED_MEMORY_MIGRATION_CAUSE_PREFETCH = 3
The unified memory migration cause is prefetch

CUPTI_ACTIVITY_UNIFIED_MEMORY_MIGRATION_CAUSE_EVICTION = 4
The unified memory migration cause is eviction

enum CUpti_DevType

The device type for device connected to nvLink.

Values

CUPTI_DEV_TYPE_INVALID = 0

CUPTI_DEV_TYPE_GPU = 1

The device type in GPU.

CUPTI_DEV_TYPE_NPU = 2

The device type nvLink processing unit in CPU.

CUPTI_DEV_TYPE_FORCE_INT = 0x7ffffffff

enum CUpti_EnvironmentClocksThrottleReason

Reasons for clock throttling.

The possible reasons that a clock can be throttled. There can be more than one reason that a clock is being throttled so these types can be combined by bitwise OR. These are used in the clocksThrottleReason field in the Environment Activity Record.

Values

CUPTI_CLOCKS_THROTTLE_REASON_GPU_IDLE = 0x00000001

Nothing is running on the GPU and the clocks are dropping to idle state.

CUPTI_CLOCKS_THROTTLE_REASON_USER_DEFINED_CLOCKS = 0x00000002
The GPU clocks are limited by a user specified limit.

CUPTI_CLOCKS_THROTTLE_REASON_SW_POWER_CAP = 0x00000004

A software power scaling algorithm is reducing the clocks below requested clocks.

CUPTI CLOCKS THROTTLE REASON HW SLOWDOWN = 0x00000008

Hardware slowdown to reduce the clock by a factor of two or more is engaged. This is an indicator of one of the following: 1) Temperature is too high, 2) External power brake assertion is being triggered (e.g. by the system power supply), 3) Change in power state.

CUPTI CLOCKS THROTTLE REASON UNKNOWN = 0x80000000

Some unspecified factor is reducing the clocks.

CUPTI_CLOCKS_THROTTLE_REASON_UNSUPPORTED = 0x40000000

Throttle reason is not supported for this GPU.

CUPTI_CLOCKS_THROTTLE_REASON_NONE = 0x00000000

No clock throttling.

CUPTI_CLOCKS_THROTTLE_REASON_FORCE_INT = 0x7ffffffff

enum CUpti_ExternalCorrelationKind

The kind of external APIs supported for correlation.

See also:

CUpti_ActivityExternalCorrelation

Values

CUPTI_EXTERNAL_CORRELATION_KIND_INVALID = 0
CUPTI_EXTERNAL_CORRELATION_KIND_UNKNOWN = 1
CUPTI_EXTERNAL_CORRELATION_KIND_OPENACC = 2
CUPTI_EXTERNAL_CORRELATION_KIND_SIZE
CUPTI_EXTERNAL_CORRELATION_KIND_FORCE_INT = 0x7fffffff

enum CUpti_LinkFlag

Link flags.

Describes link properties, to be used with CUpti_ActivityNvLink.

Values

CUPTI_LINK_FLAG_INVALID = 0

CUPTI_LINK_FLAG_PEER_ACCESS = (1<<1)

Is peer to peer access supported by this link.

CUPTI_LINK_FLAG_SYSMEM_ACCESS = (1<<2)

Is system memory access supported by this link.

CUPTI_LINK_FLAG_PEER_ATOMICS = (1<<3)

Is peer atomic access supported by this link.

CUPTI_LINK_FLAG_SYSMEM_ATOMICS = (1<<4)

Is system memory atomic access supported by this link.

CUPTI_LINK_FLAG_FORCE_INT = 0x7fffffff

enum CUpti_OpenAccConstructKind

The OpenAcc parent construct kind for OpenAcc activity records.

Values

CUPTI_OPENACC_CONSTRUCT_KIND_UNKNOWN = 0 CUPTI_OPENACC_CONSTRUCT_KIND_PARALLEL = 1 CUPTI OPENACC CONSTRUCT KIND KERNELS = 2 CUPTI_OPENACC_CONSTRUCT_KIND_LOOP = 3 CUPTI_OPENACC_CONSTRUCT_KIND_DATA = 4 CUPTI_OPENACC_CONSTRUCT_KIND_ENTER_DATA = 5 CUPTI_OPENACC_CONSTRUCT_KIND_EXIT_DATA = 6 CUPTI_OPENACC_CONSTRUCT_KIND_HOST_DATA = 7 CUPTI OPENACC CONSTRUCT KIND ATOMIC = 8 CUPTI_OPENACC_CONSTRUCT_KIND_DECLARE = 9 CUPTI_OPENACC_CONSTRUCT_KIND_INIT = 10 CUPTI OPENACC CONSTRUCT KIND SHUTDOWN = 11 CUPTI_OPENACC_CONSTRUCT_KIND_SET = 12 CUPTI_OPENACC_CONSTRUCT_KIND_UPDATE = 13 CUPTI OPENACC CONSTRUCT KIND ROUTINE = 14 CUPTI_OPENACC_CONSTRUCT_KIND_WAIT = 15 CUPTI_OPENACC_CONSTRUCT_KIND_RUNTIME_API = 16 CUPTI_OPENACC_CONSTRUCT_KIND_FORCE_INT = 0x7fffffff

enum CUpti_OpenAccEventKind

The OpenAcc event kind for OpenAcc activity records.

See also:

CUpti_ActivityKindOpenAcc

Values

CUPTI_OPENACC_EVENT_KIND_INVALID = 0
CUPTI_OPENACC_EVENT_KIND_DEVICE_INIT = 1
CUPTI_OPENACC_EVENT_KIND_DEVICE_SHUTDOWN = 2
CUPTI_OPENACC_EVENT_KIND_RUNTIME_SHUTDOWN = 3
CUPTI_OPENACC_EVENT_KIND_ENQUEUE_LAUNCH = 4
CUPTI_OPENACC_EVENT_KIND_ENQUEUE_UPLOAD = 5
CUPTI_OPENACC_EVENT_KIND_ENQUEUE_DOWNLOAD = 6
CUPTI_OPENACC_EVENT_KIND_WAIT = 7
CUPTI_OPENACC_EVENT_KIND_IMPLICIT_WAIT = 8
CUPTI_OPENACC_EVENT_KIND_COMPUTE_CONSTRUCT = 9
CUPTI_OPENACC_EVENT_KIND_UPDATE = 10
CUPTI_OPENACC_EVENT_KIND_ENTER_DATA = 11
CUPTI_OPENACC_EVENT_KIND_EXIT_DATA = 12
CUPTI_OPENACC_EVENT_KIND_CREATE = 13
CUPTI_OPENACC_EVENT_KIND_DELETE = 14

CUPTI_OPENACC_EVENT_KIND_ALLOC = 15 CUPTI_OPENACC_EVENT_KIND_FREE = 16 CUPTI_OPENACC_EVENT_KIND_FORCE_INT = 0x7fffffff

typedef (*CUpti_BuffersCallbackCompleteFunc) (CUcontext context, uint32_t streamId, uint8_t* buffer, size_t size, size_t validSize)

Function type for callback used by CUPTI to return a buffer of activity records.

This callback function returns to the CUPTI client a buffer containing activity records. The buffer contains <code>validSize</code> bytes of activity records which should be read using cuptiActivityGetNextRecord. The number of dropped records can be read using cuptiActivityGetNumDroppedRecords. After this call CUPTI relinquished ownership of the buffer and will not use it anymore. The client may return the buffer to CUPTI using the CUpti_BuffersCallbackRequestFunc callback. Note: CUDA 6.0 onwards, all buffers returned by this callback are global buffers i.e. there is no context/stream specific buffer. User needs to parse the global buffer to extract the context/stream specific activity records.

typedef (*CUpti_BuffersCallbackRequestFunc) (uint8_t* *buffer, size_t* size, size_t* maxNumRecords)

Function type for callback used by CUPTI to request an empty buffer for storing activity records.

This callback function signals the CUPTI client that an activity buffer is needed by CUPTI. The activity buffer is used by CUPTI to store activity records. The callback function can decline the request by setting *buffer to NULL. In this case CUPTI may drop activity records.

CUptiResult cuptiActivityConfigurePCSampling (CUcontext ctx, CUpti_ActivityPCSamplingConfig*config)

Set PC sampling configuration.

Parameters

ctx

The context

config

A pointer to CUpti_ActivityPCSamplingConfig structure containing PC sampling configuration.

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_INVALID_OPERATION

if this api is called while some valid event collection method is set.

► CUPTI_ERROR_INVALID_PARAMETER

if config is NULL or any parameter in the config structures is not a valid value

CUPTI_ERROR_NOT_SUPPORTED

Indicates that the system/device does not support the unified memory counters

CUptiResult

cuptiActivityConfigureUnifiedMemoryCounter
(CUpti_ActivityUnifiedMemoryCounterConfig *config,
uint32_t count)

Set Unified Memory Counter configuration.

Parameters

config

A pointer to CUpti_ActivityUnifiedMemoryCounterConfig structures containing Unified Memory counter configuration.

count

Number of Unified Memory counter configuration structures

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_PARAMETER

if config is NULL or any parameter in the config structures is not a valid value

► CUPTI_ERROR_UM_PROFILING_NOT_SUPPORTED

One potential reason is that platform (OS/arch) does not support the unified memory counters

CUPTI_ERROR_UM_PROFILING_NOT_SUPPORTED_ON_DEVICE

Indicates that the device does not support the unified memory counters

► CUPTI_ERROR_UM_PROFILING_NOT_SUPPORTED_ON_NON_P2P_DEVICES

Indicates that multi-GPU configuration without P2P support between any pair of devices does not support the unified memory counters

CUptiResult cuptiActivityDisable (CUpti_ActivityKind kind)

Disable collection of a specific kind of activity record.

Parameters

kind

The kind of activity record to stop collecting

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_KIND

if the activity kind is not supported

Description

Disable collection of a specific kind of activity record. Multiple kinds can be disabled by calling this function multiple times. By default all activity kinds are disabled for collection.

CUptiResult cuptiActivityDisableContext (CUcontext context, CUpti_ActivityKind kind)

Disable collection of a specific kind of activity record for a context.

Parameters

context

The context for which activity is to be disabled

kind

The kind of activity record to stop collecting

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_KIND

if the activity kind is not supported

Description

Disable collection of a specific kind of activity record for a context. This setting done by this API will supersede the global settings for activity records. Multiple kinds can be enabled by calling this function multiple times.

CUptiResult cuptiActivityEnable (CUpti_ActivityKind kind)

Enable collection of a specific kind of activity record.

Parameters

kind

The kind of activity record to collect

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_NOT_COMPATIBLE
 - if the activity kind cannot be enabled
- CUPTI_ERROR_INVALID_KIND

if the activity kind is not supported

Description

Enable collection of a specific kind of activity record. Multiple kinds can be enabled by calling this function multiple times. By default all activity kinds are disabled for collection.

CUptiResult cuptiActivityEnableContext (CUcontext context, CUpti_ActivityKind kind)

Enable collection of a specific kind of activity record for a context.

Parameters

context

The context for which activity is to be enabled

kind

The kind of activity record to collect

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_NOT_COMPATIBLE
 - if the activity kind cannot be enabled
- CUPTI_ERROR_INVALID_KIND
 - if the activity kind is not supported

Description

Enable collection of a specific kind of activity record for a context. This setting done by this API will supersede the global settings for activity records enabled by cuptiActivityEnable. Multiple kinds can be enabled by calling this function multiple times.

CUptiResult cuptiActivityFlush (CUcontext context, uint32_t streamId, uint32_t flag)

Wait for all activity records are delivered via the completion callback.

Parameters

context

A valid CUcontext or NULL.

streamId

The stream ID.

Hag

The flag can be set to indicate a forced flush. See CUpti_ActivityFlag

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- ► CUPTI_ERROR_CUPTI_ERROR_INVALID_OPERATION
 - if not preceded by a successful call to cuptiActivityRegisterCallbacks
- CUPTI_ERROR_UNKNOWN
 - an internal error occurred

Description

This function does not return until all activity records associated with the specified context/stream are returned to the CUPTI client using the callback registered in cuptiActivityRegisterCallbacks. To ensure that all activity records are complete, the requested stream(s), if any, are synchronized.

If context is NULL, the global activity records (i.e. those not associated with a particular stream) are flushed (in this case no streams are synchonized). If context is a valid CUcontext and streamId is 0, the buffers of all streams of this context are flushed. Otherwise, the buffers of the specified stream in this context is flushed.

Before calling this function, the buffer handling callback api must be activated by calling cuptiActivityRegisterCallbacks.

DEPRECATED This method is deprecated CONTEXT and STREAMID will be ignored. Use cuptiActivityFlushAll to flush all data.

CUptiResult cuptiActivityFlushAll (uint32_t flag)

Wait for all activity records are delivered via the completion callback.

Parameters

flag

The flag can be set to indicate a forced flush. See CUpti_ActivityFlag

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_OPERATION

if not preceded by a successful call to cuptiActivityRegisterCallbacks

CUPTI_ERROR_UNKNOWN

an internal error occurred

Description

This function does not return until all activity records associated with all contexts/ streams (and the global buffers not associated with any stream) are returned to the CUPTI client using the callback registered in cuptiActivityRegisterCallbacks. To ensure that all activity records are complete, the requested stream(s), if any, are synchronized.

Before calling this function, the buffer handling callback api must be activated by calling cuptiActivityRegisterCallbacks.

CUptiResult cuptiActivityGetAttribute (CUpti_ActivityAttribute attr, size_t *valueSize, void *value)

Read an activity API attribute.

Parameters

attr

The attribute to read

valueSize

Size of buffer pointed by the value, and returns the number of bytes written to value value

Returns the value of the attribute

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- ► CUPTI_ERROR_INVALID_PARAMETER

if valueSize or value is NULL, or if attr is not an activity attribute

► CUPTI ERROR PARAMETER SIZE NOT SUFFICIENT

Indicates that the value buffer is too small to hold the attribute value.

Description

Read an activity API attribute and return it in *value.

CUptiResult cuptiActivityGetNextRecord (uint8_t *buffer, size_t validBufferSizeBytes, CUpti_Activity **record)

Iterate over the activity records in a buffer.

Parameters

buffer

The buffer containing activity records

validBufferSizeBytes

The number of valid bytes in the buffer.

record

Inputs the previous record returned by cuptiActivityGetNextRecord and returns the next activity record from the buffer. If input value is NULL, returns the first activity record in the buffer. Records of kind CUPTI_ACTIVITY_KIND_CONCURRENT_KERNEL may contain invalid (0) timestamps, indicating that no timing information could be collected for lack of device memory.

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_MAX_LIMIT_REACHED

if no more records in the buffer

CUPTI_ERROR_INVALID_PARAMETER

if buffer is NULL.

Description

This is a helper function to iterate over the activity records in a buffer. A buffer of activity records is typically obtained by receiving a CUpti_BuffersCallbackCompleteFunc callback.

An example of typical usage:

```
CUpti_Activity *record = NULL;
CUptiResult status = CUPTI_SUCCESS;
do {
    status = cuptiActivityGetNextRecord(buffer, validSize, &record);
    if(status == CUPTI_SUCCESS) {
        // Use record here...
}
else if (status == CUPTI_ERROR_MAX_LIMIT_REACHED)
        break;
else {
        goto Error;
}
while (1);
```

CUptiResult cuptiActivityGetNumDroppedRecords (CUcontext context, uint32_t streamId, size_t *dropped)

Get the number of activity records that were dropped of insufficient buffer space.

Parameters

context

The context, or NULL to get dropped count from global queue

streamId

The stream ID

dropped

The number of records that were dropped since the last call to this function.

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_PARAMETER

if dropped is NULL

Description

Get the number of records that were dropped because of insufficient buffer space. The dropped count includes records that could not be recorded because CUPTI did not have activity buffer space available for the record (because the CUpti_BuffersCallbackRequestFunc callback did not return an empty buffer of sufficient size) and also CDP records that could not be record because the device-size buffer was full (size is controlled by the CUPTI_ACTIVITY_ATTR_DEVICE_BUFFER_SIZE_CDP attribute). The dropped count maintained for the queue is reset to zero when this function is called.

CUptiResult cuptiActivityPopExternalCorrelationId (CUpti_ExternalCorrelationKind kind, uint64_t *lastId)

Pop an external correlation id for the calling thread.

Parameters

kind

The kind of external API activities should be correlated with.

lastId

If the function returns successful, contains the last external correlation id for this kind, can be NULL.

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_INVALID_PARAMETER

The external API kind is invalid.

► CUPTI_ERROR_QUEUE_EMPTY

No external id is currently associated with kind.

Description

This function notifies CUPTI that the calling thread is leaving an external API region.

CUptiResult cuptiActivityPushExternalCorrelationId (CUpti_ExternalCorrelationKind kind, uint64_t id)

Push an external correlation id for the calling thread.

Parameters

kind

The kind of external API activities should be correlated with.

id

External correlation id.

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_INVALID_PARAMETER

The external API kind is invalid

Description

This function notifies CUPTI that the calling thread is entering an external API region. When a CUPTI activity API record is created while within an external API region and CUPTI_ACTIVITY_KIND_EXTERNAL_CORRELATION is enabled, the activity API record will be preceded by a CUpti_ActivityExternalCorrelation record for each CUpti_ExternalCorrelationKind.

CUptiResult cuptiActivityRegisterCallbacks (CUpti_BuffersCallbackRequestFunc funcBufferRequested, CUpti_BuffersCallbackCompleteFunc funcBufferCompleted)

Registers callback functions with CUPTI for activity buffer handling.

Parameters

funcBufferRequested

callback which is invoked when an empty buffer is requested by CUPTI

funcBufferCompleted

callback which is invoked when a buffer containing activity records is available from CUPTI

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_INVALID_PARAMETER

if either funcBufferRequested or funcBufferCompleted is NULL

Description

This function registers two callback functions to be used in asynchronous buffer handling. If registered, activity record buffers are handled using asynchronous requested/completed callbacks from CUPTI.

Registering these callbacks prevents the client from using CUPTI's blocking enqueue/dequeue functions.

CUptiResult cuptiActivitySetAttribute (CUpti_ActivityAttribute attr, size_t *valueSize, void *value)

Write an activity API attribute.

Parameters

attr

The attribute to write

valueSize

The size, in bytes, of the value

value

The attribute value to write

Returns

- ► CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_PARAMETER

if valueSize or value is NULL, or if attr is not an activity attribute

► CUPTI_ERROR_PARAMETER_SIZE_NOT_SUFFICIENT

Indicates that the value buffer is too small to hold the attribute value.

Description

Write an activity API attribute.

CUptiResult cuptiComputeCapabilitySupported (int major, int minor, int *support)

Check support for a compute capability.

Parameters

major

The major revision number of the compute capability

minor

The minor revision number of the compute capability

support

Pointer to an integer to return the support status

Returns

- CUPTI_SUCCESS
- CUPTI ERROR INVALID PARAMETER

if support is NULL

Description

This function is used to check the support for a device based on it's compute capability. It sets the support when the compute capability is supported by the current version of CUPTI, and clears it otherwise.

CUptiResult cuptiFinalize (void)

Cleanup CUPTI.

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_API_NOT_IMPLEMENTED

indicates API is not implemented

Description

Explicitly destroys and cleans up all resources associated with CUPTI in the current process. Any subsequent CUPTI API call will reinitialize CUPTI. This API can be called at any time but for the safe use it is suggested that CUPTI client makes sure that required CUDA synchronization is done before calling the API.

CUptiResult cuptiGetAutoBoostState (CUcontext context, CUpti_ActivityAutoBoostState *state)

Get auto boost state.

Parameters

context

A valid CUcontext.

state

A pointer to CUpti_ActivityAutoBoostState structure which contains the current state and the id of the process that has requested the current state

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_INVALID_PARAMETER

if CUcontext or state is NULL

► CUPTI_ERROR_NOT_SUPPORTED

Indicates that the device does not support auto boost

CUPTI_ERROR_UNKNOWN

an internal error occurred

Description

The profiling results can be inconsistent in case auto boost is enabled. CUPTI tries to disable auto boost while profiling. It can fail to disable in cases where user does not have the permissions or CUDA_AUTO_BOOST env variable is set. The function can be used to query whether auto boost is enabled.

CUptiResult cuptiGetContextId (CUcontext context, uint32_t *contextId)

Get the ID of a context.

Parameters

context

The context

contextId

Returns a process-unique ID for the context

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI ERROR INVALID CONTEXT

The context is NULL or not valid.

CUPTI_ERROR_INVALID_PARAMETER

if contextId is NULL

Description

Get the ID of a context.

CUptiResult cuptiGetDeviceId (CUcontext context, uint32_t *deviceId)

Get the ID of a device.

Parameters

context

The context, or NULL to indicate the current context.

deviceId

Returns the ID of the device that is current for the calling thread.

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_DEVICE

if unable to get device ID

CUPTI_ERROR_INVALID_PARAMETER

if deviceId is NULL

Description

If context is NULL, returns the ID of the device that contains the currently active context. If context is non-NULL, returns the ID of the device which contains that context. Operates in a similar manner to cudaGetDevice() or cuCtxGetDevice() but may be called from within callback functions.

CUptiResult cuptiGetLastError (void)

Returns the last error from a cupti call or callback.

Description

Returns the last error that has been produced by any of the cupti api calls or the callback in the same host thread and resets it to CUPTI_SUCCESS.

CUptiResult cuptiGetStreamId (CUcontext context, CUstream stream, uint32_t *streamId)

Get the ID of a stream.

Parameters

context

If non-NULL then the stream is checked to ensure that it belongs to this context. Typically this parameter should be null.

stream

The stream

streamId

Returns a context-unique ID for the stream

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_STREAM

if unable to get stream ID, or if context is non-NULL and stream does not belong to the context

► CUPTI ERROR INVALID PARAMETER

if streamId is NULL

Description

Get the ID of a stream. The stream ID is unique within a context (i.e. all streams within a context will have unique stream IDs).

DEPRECATED This method is deprecated as of CUDA 8.0. Use method cuptiGetStreamIdEx instead.

CUptiResult cuptiGetStreamIdEx (CUcontext context, CUstream stream, uint8_t perThreadStream, uint32_t *streamId)

Get the ID of a stream.

Parameters

context

If non-NULL then the stream is checked to ensure that it belongs to this context. Typically this parameter should be null.

stream

The stream

perThreadStream

Flag to indicate if program is compiled for per-thread streams

streamId

Returns a context-unique ID for the stream

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_STREAM

if unable to get stream ID, or if context is non-NULL and stream does not belong to the context

► CUPTI_ERROR_INVALID_PARAMETER

if streamId is NULL

Description

Get the ID of a stream. The stream ID is unique within a context (i.e. all streams within a context will have unique stream IDs).

CUptiResult cuptiGetThreadIdType (CUpti_ActivityThreadIdType *type)

Get the thread-id type.

Returns

- CUPTI SUCCESS
- CUPTI ERROR INVALID PARAMETER

if type is NULL

Description

Returns the thread-id type used in CUPTI

CUptiResult cuptiGetTimestamp (uint64_t *timestamp)

Get the CUPTI timestamp.

Parameters

timestamp

Returns the CUPTI timestamp

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_INVALID_PARAMETER

if timestamp is NULL

Description

Returns a timestamp normalized to correspond with the start and end timestamps reported in the CUPTI activity records. The timestamp is reported in nanoseconds.

CUptiResult cuptiSetThreadIdType (CUpti_ActivityThreadIdType type)

Set the thread-id type.

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_SUPPORTED

if type is not supported on the platform

Description

CUPTI uses the method corresponding to set type to generate the thread-id. See enum / ref CUpti_ActivityThreadIdType for the list of methods. Activity records having thread-id field contain the same value. Thread id type must not be changed during the profiling session to avoid thread-id value mismatch across activity records.

#define CUPTI_AUTO_BOOST_INVALID_CLIENT_PID 0

An invalid/unknown process id.

#define CUPTI_CORRELATION_ID_UNKNOWN 0

An invalid/unknown correlation ID. A correlation ID of this value indicates that there is no correlation for the activity record.

#define CUPTI_GRID_ID_UNKNOWN 0LL

An invalid/unknown grid ID.

#define CUPTI_NVLINK_INVALID_PORT -1

Invalid/unknown NVlink port number.

#define CUPTI_SOURCE_LOCATOR_ID_UNKNOWN 0

The source-locator ID that indicates an unknown source location. There is not an actual CUpti_ActivitySourceLocator object corresponding to this value.

#define CUPTI SYNCHRONIZATION INVALID VALUE -1

An invalid/unknown value.

#define CUPTI_TIMESTAMP_UNKNOWN OLL

An invalid/unknown timestamp for a start, end, queued, submitted, or completed time.

2.4. CUPTI Callback API

Functions, types, and enums that implement the CUPTI Callback API.

struct CUpti_CallbackData

Data passed into a runtime or driver API callback function.

struct CUpti_ModuleResourceData

Module data passed into a resource callback function.

struct CUpti_NvtxData

Data passed into a NVTX callback function.

struct CUpti_ResourceData

Data passed into a resource callback function.

struct CUpti_SynchronizeData

Data passed into a synchronize callback function.

enum CUpti_ApiCallbackSite

Specifies the point in an API call that a callback is issued.

Specifies the point in an API call that a callback is issued. This value is communicated to the callback function via CUpti_CallbackData::callbackSite.

Values

$CUPTI_API_ENTER = 0$

The callback is at the entry of the API call.

$CUPTI_API_EXIT = 1$

The callback is at the exit of the API call.

CUPTI_API_CBSITE_FORCE_INT = 0x7fffffff

enum CUpti_CallbackDomain

Callback domains.

Callback domains. Each domain represents callback points for a group of related API functions or CUDA driver activity.

Values

CUPTI_CB_DOMAIN_INVALID = 0

Invalid domain.

CUPTI_CB_DOMAIN_DRIVER_API = 1

Domain containing callback points for all driver API functions.

CUPTI_CB_DOMAIN_RUNTIME_API = 2

Domain containing callback points for all runtime API functions.

CUPTI CB DOMAIN RESOURCE = 3

Domain containing callback points for CUDA resource tracking.

CUPTI_CB_DOMAIN_SYNCHRONIZE = 4

Domain containing callback points for CUDA synchronization.

CUPTI_CB_DOMAIN_NVTX = 5

Domain containing callback points for NVTX API functions.

CUPTI_CB_DOMAIN_SIZE = 6

CUPTI_CB_DOMAIN_FORCE_INT = 0x7fffffff

enum CUpti_CallbackIdResource

Callback IDs for resource domain.

Callback IDs for resource domain, CUPTI_CB_DOMAIN_RESOURCE. This value is communicated to the callback function via the cbid parameter.

Values

CUPTI_CBID_RESOURCE_INVALID = 0

Invalid resource callback ID.

CUPTI_CBID_RESOURCE_CONTEXT_CREATED = 1

A new context has been created.

CUPTI_CBID_RESOURCE_CONTEXT_DESTROY_STARTING = 2

A context is about to be destroyed.

CUPTI_CBID_RESOURCE_STREAM_CREATED = 3

A new stream has been created.

CUPTI_CBID_RESOURCE_STREAM_DESTROY_STARTING = 4

A stream is about to be destroyed.

CUPTI_CBID_RESOURCE_CU_INIT_FINISHED = 5

The driver has finished initializing.

CUPTI_CBID_RESOURCE_MODULE_LOADED = 6

A module has been loaded.

CUPTI_CBID_RESOURCE_MODULE_UNLOAD_STARTING = 7

A module is about to be unloaded.

CUPTI CBID RESOURCE MODULE PROFILED = 8

The current module which is being profiled.

CUPTI_CBID_RESOURCE_SIZE

CUPTI CBID RESOURCE FORCE INT = 0x7fffffff

enum CUpti_CallbackIdSync

Callback IDs for synchronization domain.

Callback IDs for synchronization domain, CUPTI_CB_DOMAIN_SYNCHRONIZE. This value is communicated to the callback function via the cbid parameter.

Values

CUPTI_CBID_SYNCHRONIZE_INVALID = 0

Invalid synchronize callback ID.

CUPTI_CBID_SYNCHRONIZE_STREAM_SYNCHRONIZED = 1

Stream synchronization has completed for the stream.

CUPTI_CBID_SYNCHRONIZE_CONTEXT_SYNCHRONIZED = 2

Context synchronization has completed for the context.

CUPTI_CBID_SYNCHRONIZE_SIZE

CUPTI_CBID_SYNCHRONIZE_FORCE_INT = 0x7fffffff

typedef (*CUpti_CallbackFunc) (void* userdata, CUpti_CallbackDomain domain, CUpti_CallbackId cbid, const void* cbdata)

Function type for a callback.

Function type for a callback. The type of the data passed to the callback in cbdata depends on the domain. If domain is CUPTI_CB_DOMAIN_DRIVER_API or CUPTI_CB_DOMAIN_RUNTIME_API the type of cbdata will be CUpti_CallbackData. If domain is CUPTI_CB_DOMAIN_RESOURCE the type of cbdata will be CUpti_ResourceData. If domain is CUPTI_CB_DOMAIN_SYNCHRONIZE the type of cbdata will be CUpti_SynchronizeData. If domain is CUPTI_CB_DOMAIN_NVTX the type of cbdata will be CUpti_NvtxData.

typedef uint32_t CUpti_CallbackId

An ID for a driver API, runtime API, resource or synchronization callback.

An ID for a driver API, runtime API, resource or synchronization callback. Within a driver API callback this should be interpreted as a CUpti_driver_api_trace_cbid value (these values are defined in cupti_driver_cbid.h). Within a runtime API callback this should be interpreted as a CUpti_runtime_api_trace_cbid value (these values are defined in cupti_runtime_cbid.h). Within a resource API callback this should be interpreted as a CUpti_CallbackIdResource value. Within a synchronize API callback this should be interpreted as a CUpti_CallbackIdSync value.

typedef CUpti_DomainTable

Pointer to an array of callback domains.

typedef struct CUpti_Subscriber_st *CUpti_SubscriberHandle

A callback subscriber.

CUptiResult cuptiEnableAllDomains (uint32_t enable, CUpti_SubscriberHandle subscriber)

Enable or disable all callbacks in all domains.

Parameters

enable

New enable state for all callbacks in all domain. Zero disables all callbacks, non-zero enables all callbacks.

subscriber

- Handle to callback subscription

Returns

CUPTI SUCCESS

on success

CUPTI_ERROR_NOT_INITIALIZED

if unable to initialized CUPTI

► CUPTI_ERROR_INVALID_PARAMETER

if subscriber is invalid

Description

Enable or disable all callbacks in all domains.



Thread-safety: a subscriber must serialize access to cuptiGetCallbackState, cuptiEnableCallback, cuptiEnableDomain, and cuptiEnableAllDomains. For example, if cuptiGetCallbackState(sub, d, *) and cuptiEnableAllDomains(sub) are called concurrently, the results are undefined.

CUptiResult cuptiEnableCallback (uint32_t enable, CUpti_SubscriberHandle subscriber, CUpti_CallbackDomain domain, CUpti_CallbackId cbid)

Enable or disabled callbacks for a specific domain and callback ID.

Parameters

enable

New enable state for the callback. Zero disables the callback, non-zero enables the callback.

subscriber

- Handle to callback subscription

domain

The domain of the callback

cbid

The ID of the callback

Returns

CUPTI_SUCCESS

on success

CUPTI_ERROR_NOT_INITIALIZED

if unable to initialized CUPTI

► CUPTI_ERROR_INVALID_PARAMETER

if subscriber, domain or cbid is invalid.

Description

Enable or disabled callbacks for a subscriber for a specific domain and callback ID.



Thread-safety: a subscriber must serialize access to cuptiGetCallbackState, cuptiEnableCallback, cuptiEnableDomain, and cuptiEnableAllDomains. For example, if cuptiGetCallbackState(sub, d, c) and cuptiEnableCallback(sub, d, c) are called concurrently, the results are undefined.

CUptiResult cuptiEnableDomain (uint32_t enable, CUpti_SubscriberHandle subscriber, CUpti_CallbackDomain domain)

Enable or disabled all callbacks for a specific domain.

Parameters

enable

New enable state for all callbacks in the domain. Zero disables all callbacks, non-zero enables all callbacks.

subscriber

- Handle to callback subscription

domain

The domain of the callback

Returns

CUPTI_SUCCESS

on success

CUPTI_ERROR_NOT_INITIALIZED

if unable to initialized CUPTI

► CUPTI_ERROR_INVALID_PARAMETER

if subscriber or domain is invalid

Description

Enable or disabled all callbacks for a specific domain.



Thread-safety: a subscriber must serialize access to cuptiGetCallbackState, cuptiEnableCallback, cuptiEnableDomain, and cuptiEnableAllDomains. For example, if cuptiGetCallbackEnabled(sub, d, *) and cuptiEnableDomain(sub, d) are called concurrently, the results are undefined.

CUptiResult cuptiGetCallbackName (CUpti_CallbackDomain domain, uint32_t cbid, const char **name)

Get the name of a callback for a specific domain and callback ID.

Parameters

domain

The domain of the callback

cbid

The ID of the callback

name

Returns pointer to the name string on success, NULL otherwise

Returns

CUPTI SUCCESS

on success

► CUPTI_ERROR_INVALID_PARAMETER

if name is NULL, or if domain or cbid is invalid.

Description

Returns a pointer to the name c_string in **name.



Names are available only for the DRIVER and RUNTIME domains.

CUptiResult cuptiGetCallbackState (uint32_t *enable, CUpti_SubscriberHandle subscriber, CUpti_CallbackId cbid)

Get the current enabled/disabled state of a callback for a specific domain and function ID.

Parameters

enable

Returns non-zero if callback enabled, zero if not enabled

subscriber

Handle to the initialize subscriber

domain

The domain of the callback

cbid

The ID of the callback

Returns

CUPTI_SUCCESS

on success

CUPTI_ERROR_NOT_INITIALIZED

if unable to initialized CUPTI

► CUPTI_ERROR_INVALID_PARAMETER

if enabled is NULL, or if subscriber, domain or cbid is invalid.

Description

Returns non-zero in *enable if the callback for a domain and callback ID is enabled, and zero if not enabled.



Thread-safety: a subscriber must serialize access to cuptiGetCallbackState, cuptiEnableCallback, cuptiEnableDomain, and cuptiEnableAllDomains. For example, if cuptiGetCallbackState(sub, d, c) and cuptiEnableCallback(sub, d, c) are called concurrently, the results are undefined.

CUptiResult cuptiSubscribe (CUpti_SubscriberHandle *subscriber, CUpti_CallbackFunc callback, void *userdata)

Initialize a callback subscriber with a callback function and user data.

Parameters

subscriber

Returns handle to initialize subscriber

callback

The callback function

userdata

A pointer to user data. This data will be passed to the callback function via the userdata paramater.

Returns

CUPTI_SUCCESS

on success

CUPTI_ERROR_NOT_INITIALIZED

if unable to initialize CUPTI

CUPTI_ERROR_MAX_LIMIT_REACHED

if there is already a CUPTI subscriber

CUPTI_ERROR_INVALID_PARAMETER

if subscriber is NULL

Description

Initializes a callback subscriber with a callback function and (optionally) a pointer to user data. The returned subscriber handle can be used to enable and disable the callback for specific domains and callback IDs.



- Only a single subscriber can be registered at a time.
- This function does not enable any callbacks.
- Thread-safety: this function is thread safe.

CUptiResult cuptiSupportedDomains (size_t *domainCount, CUpti_DomainTable *domainTable)

Get the available callback domains.

Parameters

domainCount

Returns number of callback domains

domainTable

Returns pointer to array of available callback domains

Returns

► CUPTI_SUCCESS

on success

CUPTI_ERROR_NOT_INITIALIZED

if unable to initialize CUPTI

► CUPTI_ERROR_INVALID_PARAMETER

if domainCount or domainTable are NULL

Description

Returns in *domainTable an array of size *domainCount of all the available callback domains.



Thread-safety: this function is thread safe.

CUptiResult cuptiUnsubscribe (CUpti_SubscriberHandle subscriber)

Unregister a callback subscriber.

Parameters

subscriber

Handle to the initialize subscriber

Returns

CUPTI SUCCESS

on success

CUPTI_ERROR_NOT_INITIALIZED

if unable to initialized CUPTI

► CUPTI_ERROR_INVALID_PARAMETER

if subscriber is NULL or not initialized

Description

Removes a callback subscriber so that no future callbacks will be issued to that subscriber.



Thread-safety: this function is thread safe.

2.5. CUPTI Event API

Functions, types, and enums that implement the CUPTI Event API.

struct CUpti_EventGroupSet

A set of event groups.

struct CUpti_EventGroupSets

A set of event group sets.

enum CUpti_DeviceAttribute

Device attributes.

CUPTI device attributes. These attributes can be read using cuptiDeviceGetAttribute.

Values

CUPTI_DEVICE_ATTR_MAX_EVENT_ID = 1

Number of event IDs for a device. Value is a uint32_t.

CUPTI_DEVICE_ATTR_MAX_EVENT_DOMAIN_ID = 2

Number of event domain IDs for a device. Value is a uint32_t.

CUPTI_DEVICE_ATTR_GLOBAL_MEMORY_BANDWIDTH = 3

Get global memory bandwidth in Kbytes/sec. Value is a uint64_t.

CUPTI_DEVICE_ATTR_INSTRUCTION_PER_CYCLE = 4

Get theoretical maximum number of instructions per cycle. Value is a uint32_t.

CUPTI_DEVICE_ATTR_INSTRUCTION_THROUGHPUT_SINGLE_PRECISION = 5

Get theoretical maximum number of single precision instructions that can be executed per second. Value is a uint64_t.

CUPTI_DEVICE_ATTR_MAX_FRAME_BUFFERS = 6

Get number of frame buffers for device. Value is a uint64_t.

CUPTI DEVICE ATTR PCIE LINK RATE = 7

Get PCIE link rate in Mega bits/sec for device. Return 0 if bus-type is non-PCIE. Value is a uint64 t.

CUPTI_DEVICE_ATTR_PCIE_LINK_WIDTH = 8

Get PCIE link width for device. Return 0 if bus-type is non-PCIE. Value is a uint64_t.

CUPTI_DEVICE_ATTR_PCIE_GEN = 9

Get PCIE generation for device. Return 0 if bus-type is non-PCIE. Value is a uint64_t.

CUPTI_DEVICE_ATTR_DEVICE_CLASS = 10

Get the class for the device. Value is a CUpti_DeviceAttributeDeviceClass.

CUPTI_DEVICE_ATTR_FLOP_SP_PER_CYCLE = 11

Get the peak single precision flop per cycle. Value is a uint64_t.

CUPTI_DEVICE_ATTR_FLOP_DP_PER_CYCLE = 12

Get the peak double precision flop per cycle. Value is a uint64_t.

CUPTI DEVICE ATTR MAX L2 UNITS = 13

Get number of L2 units. Value is a uint64_t.

CUPTI_DEVICE_ATTR_MAX_SHARED_MEMORY_CACHE_CONFIG_PREFER_SHARED = 14

Get the maximum shared memory for the CU_FUNC_CACHE_PREFER_SHARED preference. Value is a uint64_t.

CUPTI_DEVICE_ATTR_MAX_SHARED_MEMORY_CACHE_CONFIG_PREFER_L1 = 15

Get the maximum shared memory for the CU_FUNC_CACHE_PREFER_L1 preference. Value is a uint64 t.

CUPTI_DEVICE_ATTR_MAX_SHARED_MEMORY_CACHE_CONFIG_PREFER_EQUAL = 16

Get the maximum shared memory for the CU_FUNC_CACHE_PREFER_EQUAL preference. Value is a uint64_t.

CUPTI_DEVICE_ATTR_FLOP_HP_PER_CYCLE = 17

Get the peak half precision flop per cycle. Value is a uint64_t.

CUPTI_DEVICE_ATTR_NVLINK_PRESENT = 18

Check if Nvlink is connected to device. Returns 1, if at least one Nvlink is connected to the device, returns 0 otherwise. Value is a uint32_t.

CUPTI_DEVICE_ATTR_GPU_CPU_NVLINK_BW = 19

Check if Nvlink is present between GPU and CPU. Returns Bandwidth, in Bytes/sec, if Nvlink is present, returns 0 otherwise. Value is a uint64_t.

CUPTI_DEVICE_ATTR_FORCE_INT = 0x7fffffff

enum CUpti_DeviceAttributeDeviceClass

Device class.

Enumeration of device classes for device attribute CUPTI_DEVICE_ATTR_DEVICE_CLASS.

Values

CUPTI_DEVICE_ATTR_DEVICE_CLASS_TESLA = 0 CUPTI_DEVICE_ATTR_DEVICE_CLASS_QUADRO = 1 CUPTI_DEVICE_ATTR_DEVICE_CLASS_GEFORCE = 2 CUPTI_DEVICE_ATTR_DEVICE_CLASS_TEGRA = 3

enum CUpti_EventAttribute

Event attributes.

Event attributes. These attributes can be read using cuptiEventGetAttribute.

Values

$CUPTI_EVENT_ATTR_NAME = 0$

Event name. Value is a null terminated const c-string.

CUPTI_EVENT_ATTR_SHORT_DESCRIPTION = 1

Short description of event. Value is a null terminated const c-string.

CUPTI_EVENT_ATTR_LONG_DESCRIPTION = 2

Long description of event. Value is a null terminated const c-string.

CUPTI_EVENT_ATTR_CATEGORY = 3

Category of event. Value is CUpti_EventCategory.

CUPTI_EVENT_ATTR_FORCE_INT = 0x7fffffff

enum CUpti_EventCategory

An event category.

Each event is assigned to a category that represents the general type of the event. A event's category is accessed using cuptiEventGetAttribute and the CUPTI_EVENT_ATTR_CATEGORY attribute.

Values

CUPTI_EVENT_CATEGORY_INSTRUCTION = 0

An instruction related event.

CUPTI_EVENT_CATEGORY_MEMORY = 1

A memory related event.

CUPTI_EVENT_CATEGORY_CACHE = 2

A cache related event.

CUPTI_EVENT_CATEGORY_PROFILE_TRIGGER = 3

A profile-trigger event.

CUPTI_EVENT_CATEGORY_FORCE_INT = 0x7fffffff

enum CUpti_EventCollectionMethod

The collection method used for an event.

The collection method indicates how an event is collected.

Values

CUPTI_EVENT_COLLECTION_METHOD_PM = 0

Event is collected using a hardware global performance monitor.

CUPTI_EVENT_COLLECTION_METHOD_SM = 1

Event is collected using a hardware SM performance monitor.

CUPTI_EVENT_COLLECTION_METHOD_INSTRUMENTED = 2

Event is collected using software instrumentation.

CUPTI_EVENT_COLLECTION_METHOD_NVLINK_TC = 3

Event is collected using NvLink throughput counter method.

CUPTI_EVENT_COLLECTION_METHOD_FORCE_INT = 0x7ffffffff

enum CUpti_EventCollectionMode

Event collection modes.

The event collection mode determines the period over which the events within the enabled event groups will be collected.

Values

CUPTI_EVENT_COLLECTION_MODE_CONTINUOUS = 0

Events are collected for the entire duration between the cuptiEventGroupEnable and cuptiEventGroupDisable calls. For devices with compute capability less than 2.0, event values are reset when a kernel is launched. For all other devices event values are only reset when the events are read. For CUDA toolkit v6.0 and older this was the default mode. From CUDA toolkit v6.5 this mode is supported on Tesla devices only.

CUPTI_EVENT_COLLECTION_MODE_KERNEL = 1

Events are collected only for the durations of kernel executions that occur between the cuptiEventGroupEnable and cuptiEventGroupDisable calls. Event collection begins when a kernel execution begins, and stops when kernel execution completes. Event values are reset to zero when each kernel execution begins. If multiple kernel executions occur between the cuptiEventGroupEnable and cuptiEventGroupDisable calls then the event values must be read after each kernel launch if those events need to be associated with the specific kernel launch. This is the default mode from CUDA toolkit v6.5, and it is the only supported mode for non-Tesla (Quadro, GeForce etc.) devices.

CUPTI_EVENT_COLLECTION_MODE_FORCE_INT = 0x7fffffff

enum CUpti_EventDomainAttribute

Event domain attributes.

Event domain attributes. Except where noted, all the attributes can be read using either cuptiDeviceGetEventDomainAttribute or cuptiEventDomainGetAttribute.

Values

CUPTI_EVENT_DOMAIN_ATTR_NAME = 0

Event domain name. Value is a null terminated const c-string.

CUPTI_EVENT_DOMAIN_ATTR_INSTANCE_COUNT = 1

Number of instances of the domain for which event counts will be collected. The domain may have additional instances that cannot be profiled (see CUPTI_EVENT_DOMAIN_ATTR_TOTAL_INSTANCE_COUNT). Can be read only with cuptiDeviceGetEventDomainAttribute. Value is a uint32_t.

CUPTI_EVENT_DOMAIN_ATTR_TOTAL_INSTANCE_COUNT = 3

Total number of instances of the domain, including instances that cannot be profiled. Use CUPTI_EVENT_DOMAIN_ATTR_INSTANCE_COUNT to get the number of instances that can be profiled. Can be read only with cuptiDeviceGetEventDomainAttribute. Value is a uint32_t.

CUPTI_EVENT_DOMAIN_ATTR_COLLECTION_METHOD = 4

Collection method used for events contained in the event domain. Value is a CUpti EventCollectionMethod.

CUPTI_EVENT_DOMAIN_ATTR_FORCE_INT = 0x7fffffff

enum CUpti_EventGroupAttribute

Event group attributes.

Event group attributes. These attributes can be read using cuptiEventGroupGetAttribute. Attributes marked [rw] can also be written using cuptiEventGroupSetAttribute.

Values

CUPTI_EVENT_GROUP_ATTR_EVENT_DOMAIN_ID = 0

The domain to which the event group is bound. This attribute is set when the first event is added to the group. Value is a CUpti_EventDomainID.

CUPTI_EVENT_GROUP_ATTR_PROFILE_ALL_DOMAIN_INSTANCES = 1

[rw] Profile all the instances of the domain for this eventgroup. This feature can be used to get load balancing across all instances of a domain. Value is an integer.

CUPTI_EVENT_GROUP_ATTR_USER_DATA = 2

[rw] Reserved for user data.

CUPTI_EVENT_GROUP_ATTR_NUM_EVENTS = 3

Number of events in the group. Value is a uint32 t.

CUPTI EVENT GROUP ATTR EVENTS = 4

Enumerates events in the group. Value is a pointer to buffer of size sizeof(CUpti_EventID) * num_of_events in the eventgroup. num_of_events can be queried using CUPTI_EVENT_GROUP_ATTR_NUM_EVENTS.

CUPTI_EVENT_GROUP_ATTR_INSTANCE_COUNT = 5

Number of instances of the domain bound to this event group that will be counted. Value is a uint32 t.

CUPTI_EVENT_GROUP_ATTR_FORCE_INT = 0x7fffffff

enum CUpti_ReadEventFlags

Flags for cuptiEventGroupReadEvent an cuptiEventGroupReadAllEvents.

Flags for cuptiEventGroupReadEvent an cuptiEventGroupReadAllEvents.

Values

CUPTI_EVENT_READ_FLAG_NONE = 0
No flags.
CUPTI_EVENT_READ_FLAG_FORCE_INT = 0x7fffffff

typedef uint32_t CUpti_EventDomainID

ID for an event domain.

ID for an event domain. An event domain represents a group of related events. A device may have multiple instances of a domain, indicating that the device can simultaneously record multiple instances of each event within that domain.

typedef void *CUpti_EventGroup

A group of events.

An event group is a collection of events that are managed together. All events in an event group must belong to the same domain.

typedef uint32_t CUpti_EventID

ID for an event.

An event represents a countable activity, action, or occurrence on the device.

typedef (*CUpti_KernelReplayUpdateFunc) (const char* kernelName, int numReplaysDone, void* customData)

Function type for getting updates on kernel replay.

CUptiResult cuptiDeviceEnumEventDomains (CUdevice device, size_t *arraySizeBytes, CUpti_EventDomainID *domainArray)

Get the event domains for a device.

Parameters

device

The CUDA device

arraySizeBytes

The size of domainArray in bytes, and returns the number of bytes written to domainArray

domainArray

Returns the IDs of the event domains for the device

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_DEVICE
- CUPTI ERROR INVALID PARAMETER

if arraySizeBytes or domainArray are NULL

Description

Returns the event domains IDs in domainArray for a device. The size of the domainArray buffer is given by *arraySizeBytes. The size of the domainArray buffer must be at least numdomains * sizeof(CUpti_EventDomainID) or else all domains will not be returned. The value returned in *arraySizeBytes contains the number of bytes returned in domainArray.



Thread-safety: this function is thread safe.

CUptiResult cuptiDeviceGetAttribute (CUdevice device, CUpti_DeviceAttribute attrib, size_t *valueSize, void *value)

Read a device attribute.

Parameters

device

The CUDA device

attrib

The attribute to read

valueSize

Size of buffer pointed by the value, and returns the number of bytes written to value value

Returns the value of the attribute

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI ERROR INVALID DEVICE
- CUPTI_ERROR_INVALID_PARAMETER

if valueSize or value is NULL, or if attrib is not a device attribute

► CUPTI_ERROR_PARAMETER_SIZE_NOT_SUFFICIENT

For non-c-string attribute values, indicates that the value buffer is too small to hold the attribute value.

Description

Read a device attribute and return it in *value.



Thread-safety: this function is thread safe.

CUptiResult cuptiDeviceGetEventDomainAttribute (CUdevice device, CUpti_EventDomainID eventDomain,

CUpti_EventDomainAttribute attrib, size_t *valueSize, void *value)

Read an event domain attribute.

Parameters

device

The CUDA device

eventDomain

ID of the event domain

attrib

The event domain attribute to read

valueSize

The size of the value buffer in bytes, and returns the number of bytes written to value

value

Returns the attribute's value

Returns

- ► CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_DEVICE
- CUPTI_ERROR_INVALID_EVENT_DOMAIN_ID
- CUPTI ERROR INVALID PARAMETER

if valueSize or value is NULL, or if attrib is not an event domain attribute

► CUPTI ERROR PARAMETER SIZE NOT SUFFICIENT

For non-c-string attribute values, indicates that the value buffer is too small to hold the attribute value.

Description

Returns an event domain attribute in *value. The size of the value buffer is given by *valueSize. The value returned in *valueSize contains the number of bytes returned in value.

If the attribute value is a c-string that is longer than *valueSize, then only the first *valueSize characters will be returned and there will be no terminating null byte.



Thread-safety: this function is thread safe.

CUptiResult cuptiDeviceGetNumEventDomains (CUdevice device, uint32_t *numDomains)

Get the number of domains for a device.

Parameters

device

The CUDA device

numDomains

Returns the number of domains

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_DEVICE
- ► CUPTI_ERROR_INVALID_PARAMETER

if numDomains is NULL

Description

Returns the number of domains in numDomains for a device.



Thread-safety: this function is thread safe.

CUptiResult cuptiDeviceGetTimestamp (CUcontext context, uint64_t *timestamp)

Read a device timestamp.

Parameters

context

A context on the device from which to get the timestamp

timestamp

Returns the device timestamp

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED

- CUPTI_ERROR_INVALID_CONTEXT
- CUPTI_ERROR_INVALID_PARAMETERis timestamp is NULL

Description

Returns the device timestamp in *timestamp. The timestamp is reported in nanoseconds and indicates the time since the device was last reset.



Thread-safety: this function is thread safe.

CUptiResult cuptiDisableKernelReplayMode (CUcontext context)

Disable kernel replay mode.

Parameters

context

The context

Returns

► CUPTI_SUCCESS

Description

Set profiling mode for the context to non-replay (default) mode. Event collection mode will be set to CUPTI_EVENT_COLLECTION_MODE_KERNEL. All previously enabled event groups and event group sets will be disabled.



Thread-safety: this function is thread safe.

CUptiResult cuptiEnableKernelReplayMode (CUcontext context)

Enable kernel replay mode.

Parameters

context

The context

Returns

CUPTI_SUCCESS

Description

Set profiling mode for the context to replay mode. In this mode, any number of events can be collected in one run of the kernel. The event collection mode will automatically switch to CUPTI_EVENT_COLLECTION_MODE_KERNEL. In this mode, cuptiSetEventCollectionMode will return CUPTI_ERROR_INVALID_OPERATION.



- Kernels might take longer to run if many events are enabled.
- ▶ Thread-safety: this function is thread safe.

CUptiResult cuptiEnumEventDomains (size_t *arraySizeBytes, CUpti_EventDomainID *domainArray)

Get the event domains available on any device.

Parameters

arraySizeBytes

The size of domainArray in bytes, and returns the number of bytes written to domainArray

domainArray

Returns all the event domains

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_INVALID_PARAMETER

if arraySizeBytes or domainArray are NULL

Description

Returns all the event domains available on any CUDA-capable device. Event domain IDs are returned in domainArray. The size of the domainArray buffer is given by *arraySizeBytes. The size of the domainArray buffer must be at least numDomains * sizeof(CUpti_EventDomainID) or all domains will not be returned. The value returned in *arraySizeBytes contains the number of bytes returned in domainArray.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventDomainEnumEvents (CUpti_EventDomainID eventDomain, size_t *arraySizeBytes, CUpti_EventID *eventArray)

Get the events in a domain.

Parameters

eventDomain

ID of the event domain

arraySizeBytes

The size of eventArray in bytes, and returns the number of bytes written to eventArray

eventArray

Returns the IDs of the events in the domain

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_EVENT_DOMAIN_ID
- CUPTI ERROR INVALID PARAMETER

if arraySizeBytes or eventArray are NULL

Description

Returns the event IDs in eventArray for a domain. The size of the eventArray buffer is given by *arraySizeBytes. The size of the eventArray buffer must be at least numdomainevents * sizeof(CUpti_EventID) or else all events will not be returned. The value returned in *arraySizeBytes contains the number of bytes returned in eventArray.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventDomainGetAttribute (CUpti_EventDomainID eventDomain,

CUpti_EventDomainAttribute attrib, size_t *valueSize, void *value)

Read an event domain attribute.

Parameters

eventDomain

ID of the event domain

attrib

The event domain attribute to read

valueSize

The size of the value buffer in bytes, and returns the number of bytes written to value

value

Returns the attribute's value

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_EVENT_DOMAIN_ID
- CUPTI_ERROR_INVALID_PARAMETER

if valueSize or value is NULL, or if attrib is not an event domain attribute

► CUPTI_ERROR_PARAMETER_SIZE_NOT_SUFFICIENT

For non-c-string attribute values, indicates that the value buffer is too small to hold the attribute value.

Description

Returns an event domain attribute in *value. The size of the value buffer is given by *valueSize. The value returned in *valueSize contains the number of bytes returned in value.

If the attribute value is a c-string that is longer than *valueSize, then only the first *valueSize characters will be returned and there will be no terminating null byte.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventDomainGetNumEvents (CUpti_EventDomainID eventDomain, uint32_t *numEvents)

Get number of events in a domain.

Parameters

eventDomain

ID of the event domain

numEvents

Returns the number of events in the domain

Returns

- ► CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_EVENT_DOMAIN_ID
- ► CUPTI ERROR INVALID PARAMETER

if numEvents is NULL

Description

Returns the number of events in numEvents for a domain.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventGetAttribute (CUpti_EventID event, CUpti_EventAttribute attrib, size_t *valueSize, void *value)

Get an event attribute.

Parameters

event

ID of the event

attrib

The event attribute to read

valueSize

The size of the value buffer in bytes, and returns the number of bytes written to value

value

Returns the attribute's value

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI ERROR INVALID EVENT ID
- CUPTI_ERROR_INVALID_PARAMETER

if valueSize or value is NULL, or if attrib is not an event attribute

► CUPTI_ERROR_PARAMETER_SIZE_NOT_SUFFICIENT

For non-c-string attribute values, indicates that the value buffer is too small to hold the attribute value.

Description

Returns an event attribute in *value. The size of the value buffer is given by *valueSize. The value returned in *valueSize contains the number of bytes returned in value.

If the attribute value is a c-string that is longer than *valueSize, then only the first *valueSize characters will be returned and there will be no terminating null byte.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventGetIdFromName (CUdevice device, const char *eventName, CUpti_EventID *event)

Find an event by name.

Parameters

device

The CUDA device

eventName

The name of the event to find

event

Returns the ID of the found event or undefined if unable to find the event

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_DEVICE
- ► CUPTI_ERROR_INVALID_EVENT_NAME

if unable to find an event with name eventName. In this case *event is undefined

CUPTI ERROR INVALID PARAMETER

if eventName or event are NULL

Description

Find an event by name and return the event ID in *event.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventGroupAddEvent (CUpti_EventGroup eventGroup, CUpti_EventID event)

Add an event to an event group.

Parameters

eventGroup

The event group

event

The event to add to the group

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_EVENT_ID
- CUPTI_ERROR_OUT_OF_MEMORY
- CUPTI_ERROR_INVALID_OPERATION
 - if eventGroup is enabled
- ► CUPTI_ERROR_NOT_COMPATIBLE

if event belongs to a different event domain than the events already in eventGroup, or if a device limitation prevents event from being collected at the same time as the events already in eventGroup

CUPTI_ERROR_MAX_LIMIT_REACHED

if eventGroup is full

CUPTI_ERROR_INVALID_PARAMETER

if eventGroup is NULL

Description

Add an event to an event group. The event add can fail for a number of reasons:

- ▶ The event group is enabled
- ► The event does not belong to the same event domain as the events that are already in the event group
- Device limitations on the events that can belong to the same group
- The event group is full



Thread-safety: this function is thread safe.

CUptiResult cuptiEventGroupCreate (CUcontext context, CUpti_EventGroup *eventGroup, uint32_t flags)

Create a new event group for a context.

Parameters

context

The context for the event group

eventGroup

Returns the new event group

flags

Reserved - must be zero

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI ERROR INVALID CONTEXT
- CUPTI_ERROR_OUT_OF_MEMORY
- CUPTI_ERROR_INVALID_PARAMETER

if eventGroup is NULL

Description

Creates a new event group for context and returns the new group in *eventGroup.



- flags are reserved for future use and should be set to zero.
- Thread-safety: this function is thread safe.

CUptiResult cuptiEventGroupDestroy (CUpti_EventGroup eventGroup)

Destroy an event group.

Parameters

eventGroup

The event group to destroy

Returns

- ► CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_OPERATION
 - if the event group is enabled
- ► CUPTI_ERROR_INVALID_PARAMETER

if eventGroup is NULL

Description

Destroy an eventGroup and free its resources. An event group cannot be destroyed if it is enabled.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventGroupDisable (CUpti_EventGroup eventGroup)

Disable an event group.

Parameters

eventGroup

The event group

Returns

- ► CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- ► CUPTI_ERROR_HARDWARE
- ► CUPTI_ERROR_INVALID_PARAMETER

if eventGroup is NULL

Description

Disable an event group. Disabling an event group stops collection of events contained in the group.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventGroupEnable (CUpti_EventGroup eventGroup)

Enable an event group.

Parameters

eventGroup

The event group

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_HARDWARE
- CUPTI_ERROR_NOT_READY

if eventGroup does not contain any events

► CUPTI_ERROR_NOT_COMPATIBLE

if eventGroup cannot be enabled due to other already enabled event groups

► CUPTI_ERROR_INVALID_PARAMETER

if eventGroup is NULL

CUPTI_ERROR_HARDWARE_BUSY

if another client is profiling and hardware is busy

Description

Enable an event group. Enabling an event group zeros the value of all the events in the group and then starts collection of those events.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventGroupGetAttribute (CUpti_EventGroup eventGroup, CUpti_EventGroupAttribute attrib, size_t *valueSize, void *value)

Read an event group attribute.

Parameters

eventGroup

The event group

attrib

The attribute to read

valueSize

Size of buffer pointed by the value, and returns the number of bytes written to value value

Returns the value of the attribute

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_PARAMETER

if valueSize or value is NULL, or if attrib is not an eventgroup attribute

CUPTI_ERROR_PARAMETER_SIZE_NOT_SUFFICIENT

For non-c-string attribute values, indicates that the value buffer is too small to hold the attribute value.

Description

Read an event group attribute and return it in *value.



Thread-safety: this function is thread safe but client must guard against simultaneous destruction or modification of eventGroup (for example, client must guard against simultaneous calls to cuptiEventGroupDestroy, cuptiEventGroupAddEvent, etc.), and must guard against simultaneous destruction of the context in which eventGroup was created (for example, client must guard against simultaneous calls to cudaDeviceReset, cuCtxDestroy, etc.).

CUptiResult cuptiEventGroupReadAllEvents
(CUpti_EventGroup eventGroup, CUpti_ReadEventFlags
flags, size_t *eventValueBufferSizeBytes, uint64_t
*eventValueBuffer, size_t *eventIdArraySizeBytes,
CUpti_EventID *eventIdArray, size_t *numEventIdsRead)

Read the values for all the events in an event group.

Parameters

eventGroup

The event group

flags

Flags controlling the reading mode

eventValueBufferSizeBytes

The size of eventValueBuffer in bytes, and returns the number of bytes written to eventValueBuffer

eventValueBuffer

Returns the event values

eventIdArraySizeBytes

The size of eventIdArray in bytes, and returns the number of bytes written to eventIdArray

eventIdArray

Returns the IDs of the events in the same order as the values return in eventValueBuffer.

numEventIdsRead

Returns the number of event IDs returned in eventIdArray

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- ► CUPTI_ERROR_HARDWARE
- CUPTI_ERROR_INVALID_OPERATION
 - if eventGroup is disabled
- CUPTI ERROR INVALID PARAMETER

if eventGroup, eventValueBufferSizeBytes, eventValueBuffer, eventIdArraySizeBytes, eventIdArray or numEventIdsRead is NULL

Description

Read the values for all the events in an event group. The event values are returned in the eventValueBuffer buffer. eventValueBufferSizeBytes indicates the size of eventValueBuffer. The buffer must be at least (sizeof(uint64) * number of events in group) if CUPTI_EVENT_GROUP_ATTR_PROFILE_ALL_DOMAIN_INSTANCES is not set on the group containing the events. The buffer must be at least (sizeof(uint64) * number of domain instances * number of events in group) if CUPTI_EVENT_GROUP_ATTR_PROFILE_ALL_DOMAIN_INSTANCES is set on the group.

The data format returned in eventValueBuffer is:

- domain instance 0: event0 event1 ... eventN
- domain instance 1: event0 event1 ... eventN
- •
- domain instance M: event0 event1 ... eventN

The event order in eventValueBuffer is returned in eventIdArray. The size of eventIdArray is specified in eventIdArraySizeBytes. The size should be at least (sizeof(CUpti_EventID) * number of events in group).

If any instance of any event counter overflows, the value returned for that event instance will be CUPTI_EVENT_OVERFLOW.

The only allowed value for flags is CUPTI_EVENT_READ_FLAG_NONE.

Reading events from a disabled event group is not allowed. After being read, an event's value is reset to zero.



Thread-safety: this function is thread safe but client must guard against simultaneous destruction or modification of eventGroup (for example, client must guard against simultaneous calls to cuptiEventGroupDestroy, cuptiEventGroupAddEvent, etc.), and must guard against simultaneous destruction of the context in which



eventGroup was created (for example, client must guard against simultaneous calls to cudaDeviceReset, cuCtxDestroy, etc.). If cuptiEventGroupResetAllEvents is called simultaneously with this function, then returned event values are undefined.

CUptiResult cuptiEventGroupReadEvent (CUpti_EventGroup eventGroup, CUpti_ReadEventFlags flags, CUpti_EventID event, size_t *eventValueBufferSizeBytes, uint64_t *eventValueBuffer)

Read the value for an event in an event group.

Parameters

eventGroup

The event group

flags

Flags controlling the reading mode

event

The event to read

eventValueBufferSizeBytes

The size of eventValueBuffer in bytes, and returns the number of bytes written to eventValueBuffer

eventValueBuffer

Returns the event value(s)

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_EVENT_ID
- CUPTI_ERROR_HARDWARE
- ► CUPTI_ERROR_INVALID_OPERATION

if eventGroup is disabled

► CUPTI_ERROR_INVALID_PARAMETER

 $if\ event \ Group,\ event \ Value \ Buffer \ Size Bytes\ or\ event \ Value \ Buffer\ is\ NULL$

Description

Read the value for an event in an event group. The event value is returned in the eventValueBuffer buffer. eventValueBufferSizeBytes indicates the size of the eventValueBuffer buffer. The buffer must be at least sizeof(uint64) if CUPTI_EVENT_GROUP_ATTR_PROFILE_ALL_DOMAIN_INSTANCES is not set on the group containing the event. The buffer must be at least (sizeof(uint64) * number of domain instances) if CUPTI_EVENT_GROUP_ATTR_PROFILE_ALL_DOMAIN_INSTANCES is set on the group.

If any instance of an event counter overflows, the value returned for that event instance will be CUPTI_EVENT_OVERFLOW.

The only allowed value for flags is CUPTI_EVENT_READ_FLAG_NONE.

Reading an event from a disabled event group is not allowed. After being read, an event's value is reset to zero.



Thread-safety: this function is thread safe but client must guard against simultaneous destruction or modification of eventGroup (for example, client must guard against simultaneous calls to cuptiEventGroupDestroy, cuptiEventGroupAddEvent, etc.), and must guard against simultaneous destruction of the context in which eventGroup was created (for example, client must guard against simultaneous calls to cudaDeviceReset, cuCtxDestroy, etc.). If cuptiEventGroupResetAllEvents is called simultaneously with this function, then returned event values are undefined.

CUptiResult cuptiEventGroupRemoveAllEvents (CUpti_EventGroup eventGroup)

Remove all events from an event group.

Parameters

eventGroup

The event group

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_OPERATION if eventGroup is enabled
- CUPTI_ERROR_INVALID_PARAMETER

if eventGroup is NULL

Description

Remove all events from an event group. Events cannot be removed if the event group is enabled



Thread-safety: this function is thread safe.

CUptiResult cuptiEventGroupRemoveEvent (CUpti_EventGroup eventGroup, CUpti_EventID event)

Remove an event from an event group.

Parameters

eventGroup

The event group

event

The event to remove from the group

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_EVENT_ID
- CUPTI_ERROR_INVALID_OPERATION

if eventGroup is enabled

► CUPTI_ERROR_INVALID_PARAMETER

if eventGroup is NULL

Description

Remove event from the an event group. The event cannot be removed if the event group is enabled.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventGroupResetAllEvents (CUpti_EventGroup eventGroup)

Zero all the event counts in an event group.

Parameters

eventGroup

The event group

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_HARDWARE
- CUPTI_ERROR_INVALID_PARAMETER

if eventGroup is NULL

Description

Zero all the event counts in an event group.



Thread-safety: this function is thread safe but client must guard against simultaneous destruction or modification of eventGroup (for example, client must guard against simultaneous calls to cuptiEventGroupDestroy, cuptiEventGroupAddEvent, etc.), and must guard against simultaneous destruction of the context in which eventGroup was created (for example, client must guard against simultaneous calls to cudaDeviceReset, cuCtxDestroy, etc.).

CUptiResult cuptiEventGroupSetAttribute (CUpti_EventGroup eventGroup, CUpti_EventGroupAttribute attrib, size_t valueSize, void *value)

Write an event group attribute.

Parameters

eventGroup

The event group

attrib

The attribute to write

valueSize

The size, in bytes, of the value

value

The attribute value to write

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_PARAMETER

if valueSize or value is NULL, or if attrib is not an event group attribute, or if attrib is not a writable attribute

► CUPTI ERROR PARAMETER SIZE NOT SUFFICIENT

Indicates that the value buffer is too small to hold the attribute value.

Description

Write an event group attribute.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventGroupSetDisable (CUpti_EventGroupSet *eventGroupSet)

Disable an event group set.

Parameters

eventGroupSet

The pointer to the event group set

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_HARDWARE
- ► CUPTI_ERROR_INVALID_PARAMETER

if eventGroupSet is NULL

Description

Disable a set of event groups. Disabling a set of event groups stops collection of events contained in the groups.



- Thread-safety: this function is thread safe.
- If this call fails, some of the event groups in the set may be disabled and other event groups may remain enabled.

CUptiResult cuptiEventGroupSetEnable (CUpti_EventGroupSet *eventGroupSet)

Enable an event group set.

Parameters

eventGroupSet

The pointer to the event group set

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_HARDWARE
- CUPTI_ERROR_NOT_READY

if eventGroup does not contain any events

► CUPTI_ERROR_NOT_COMPATIBLE

if eventGroup cannot be enabled due to other already enabled event groups

CUPTI_ERROR_INVALID_PARAMETER

if eventGroupSet is NULL

CUPTI_ERROR_HARDWARE_BUSY

if other client is profiling and hardware is busy

Description

Enable a set of event groups. Enabling a set of event groups zeros the value of all the events in all the groups and then starts collection of those events.



Thread-safety: this function is thread safe.

CUptiResult cuptiEventGroupSetsCreate (CUcontext context, size_t eventIdArraySizeBytes, CUpti_EventID *eventIdArray, CUpti_EventGroupSets **eventGroupPasses)

For a set of events, get the grouping that indicates the number of passes and the event groups necessary to collect the events.

Parameters

context

The context for event collection

eventIdArraySizeBytes

Size of eventIdArray in bytes

eventIdArray

Array of event IDs that need to be grouped

eventGroupPasses

Returns a CUpti_EventGroupSets object that indicates the number of passes required to collect the events and the events to collect on each pass

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_CONTEXT
- CUPTI_ERROR_INVALID_EVENT_ID
- CUPTI_ERROR_INVALID_PARAMETER

if eventIdArray or eventGroupPasses is NULL

Description

The number of events that can be collected simultaneously varies by device and by the type of the events. When events can be collected simultaneously, they may need to be grouped into multiple event groups because they are from different event domains. This function takes a set of events and determines how many passes are required to collect all those events, and which events can be collected simultaneously in each pass.

The CUpti_EventGroupSets returned in eventGroupPasses indicates how many passes are required to collect the events with the numSets field. Within each event

group set, the sets array indicates the event groups that should be collected on each pass.



Thread-safety: this function is thread safe, but client must guard against another thread simultaneously destroying context.

CUptiResult cuptiEventGroupSetsDestroy (CUpti_EventGroupSets *eventGroupSets)

Destroy a CUpti_EventGroupSets object.

Parameters

eventGroupSets

The object to destroy

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_OPERATION
 if any of the event groups contained in the sets is enabled
- CUPTI_ERROR_INVALID_PARAMETER

if eventGroupSets is NULL

Description

Destroy a CUpti_EventGroupSets object.



Thread-safety: this function is thread safe.

CUptiResult cuptiGetNumEventDomains (uint32_t *numDomains)

Get the number of event domains available on any device.

Parameters

numDomains

Returns the number of domains

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_INVALID_PARAMETER

if numDomains is NULL

Description

Returns the total number of event domains available on any CUDA-capable device.



Thread-safety: this function is thread safe.

CUptiResult cuptiKernelReplaySubscribeUpdate (CUpti_KernelReplayUpdateFunc updateFunc, void *customData)

Subscribe to kernel replay updates.

Parameters

updateFunc

The update function pointer

customData

Pointer to any custom data

Returns

CUPTI_SUCCESS

Description

When subscribed, the function pointer passed in will be called each time a kernel run is finished during kernel replay. Previously subscribed function pointer will be replaced. Pass in NULL as the function pointer unsubscribes the update.

CUptiResult cuptiSetEventCollectionMode (CUcontext context, CUpti_EventCollectionMode mode)

Set the event collection mode.

Parameters

context

The context

mode

The event collection mode

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_CONTEXT
- CUPTI_ERROR_INVALID_OPERATION
 if called when replay mode is enabled
- ► CUPTI_ERROR_NOT_SUPPORTED if mode is not supported on the device

Description

Set the event collection mode for a context. The mode controls the event collection behavior of all events in event groups created in the context. This API is invalid in kernel replay mode.



Thread-safety: this function is thread safe.

#define CUPTI_EVENT_INVALID ((uint64_t)0xFFFFFFFFFFFFFFEULL)

The value that indicates the event value is invalid.

#define CUPTI_EVENT_OVERFLOW ((uint64_t)0xFFFFFFFFFFFFFFULL)

The overflow value for a CUPTI event.

The CUPTI event value that indicates an overflow.

2.6. CUPTI Metric API

Functions, types, and enums that implement the CUPTI Metric API.

union CUpti_MetricValue

A metric value.

enum CUpti_MetricAttribute

Metric attributes.

Metric attributes describe properties of a metric. These attributes can be read using cuptiMetricGetAttribute.

Values

CUPTI_METRIC_ATTR_NAME = 0

Metric name. Value is a null terminated const c-string.

CUPTI_METRIC_ATTR_SHORT_DESCRIPTION = 1

Short description of metric. Value is a null terminated const c-string.

CUPTI_METRIC_ATTR_LONG_DESCRIPTION = 2

Long description of metric. Value is a null terminated const c-string.

CUPTI_METRIC_ATTR_CATEGORY = 3

Category of the metric. Value is of type CUpti_MetricCategory.

CUPTI_METRIC_ATTR_VALUE_KIND = 4

Value type of the metric. Value is of type CUpti_MetricValueKind.

CUPTI_METRIC_ATTR_EVALUATION_MODE = 5

Metric evaluation mode. Value is of type CUpti_MetricEvaluationMode.

CUPTI_METRIC_ATTR_FORCE_INT = 0x7fffffff

enum CUpti_MetricCategory

A metric category.

Each metric is assigned to a category that represents the general type of the metric. A metric's category is accessed using cuptiMetricGetAttribute and the CUPTI_METRIC_ATTR_CATEGORY attribute.

Values

CUPTI_METRIC_CATEGORY_MEMORY = 0

A memory related metric.

CUPTI_METRIC_CATEGORY_INSTRUCTION = 1

An instruction related metric.

CUPTI_METRIC_CATEGORY_MULTIPROCESSOR = 2

A multiprocessor related metric.

CUPTI_METRIC_CATEGORY_CACHE = 3

A cache related metric.

CUPTI_METRIC_CATEGORY_TEXTURE = 4

A texture related metric.

CUPTI METRIC CATEGORY NVLINK = 5

A Nvlink related metric.

CUPTI_METRIC_CATEGORY_FORCE_INT = 0x7fffffff

enum CUpti_MetricEvaluationMode

A metric evaluation mode.

A metric can be evaluated per hardware instance to know the load balancing across instances of a domain or the metric can be evaluated in aggregate mode when the events involved in metric evaluation are from different event domains. It might be possible to evaluate some metrics in both modes for convenience. A metric's evaluation mode is accessed using CUpti_MetricEvaluationMode and the CUPTI_METRIC_ATTR_EVALUATION_MODE attribute.

Values

CUPTI_METRIC_EVALUATION_MODE_PER_INSTANCE = 1

If this bit is set, the metric can be profiled for each instance of the domain. The event values passed to cuptiMetricGetValue can contain values for one instance of the domain. And cuptiMetricGetValue can be called for each instance.

CUPTI_METRIC_EVALUATION_MODE_AGGREGATE = 1<<1

If this bit is set, the metric can be profiled over all instances. The event values passed to cuptiMetricGetValue can be aggregated values of events for all instances of the domain.

CUPTI_METRIC_EVALUATION_MODE_FORCE_INT = 0x7fffffff

enum CUpti_MetricPropertyDeviceClass

Device class.

Enumeration of device classes for metric property CUPTI_METRIC_PROPERTY_DEVICE_CLASS.

Values

CUPTI_METRIC_PROPERTY_DEVICE_CLASS_TESLA = 0 CUPTI_METRIC_PROPERTY_DEVICE_CLASS_QUADRO = 1 CUPTI_METRIC_PROPERTY_DEVICE_CLASS_GEFORCE = 2 CUPTI_METRIC_PROPERTY_DEVICE_CLASS_TEGRA = 3

enum CUpti_MetricPropertyID

Metric device properties.

Metric device properties describe device properties which are needed for a metric. Some of these properties can be collected using cuDeviceGetAttribute.

Values

CUPTI_METRIC_PROPERTY_MULTIPROCESSOR_COUNT

CUPTI_METRIC_PROPERTY_WARPS_PER_MULTIPROCESSOR

CUPTI METRIC PROPERTY KERNEL GPU TIME

CUPTI_METRIC_PROPERTY_CLOCK_RATE

CUPTI_METRIC_PROPERTY_FRAME_BUFFER_COUNT

CUPTI_METRIC_PROPERTY_GLOBAL_MEMORY_BANDWIDTH

CUPTI_METRIC_PROPERTY_PCIE_LINK_RATE

CUPTI_METRIC_PROPERTY_PCIE_LINK_WIDTH

CUPTI_METRIC_PROPERTY_PCIE_GEN

CUPTI_METRIC_PROPERTY_DEVICE_CLASS

CUPTI_METRIC_PROPERTY_FLOP_SP_PER_CYCLE

CUPTI_METRIC_PROPERTY_FLOP_DP_PER_CYCLE

CUPTI_METRIC_PROPERTY_L2_UNITS

CUPTI_METRIC_PROPERTY_ECC_ENABLED

CUPTI METRIC PROPERTY FLOP HP PER CYCLE

CUPTI_METRIC_PROPERTY_GPU_CPU_NVLINK_BANDWIDTH

enum CUpti_MetricValueKind

Kinds of metric values.

Metric values can be one of several different kinds. Corresponding to each kind is a member of the CUpti_MetricValue union. The metric value returned by cuptiMetricGetValue should be accessed using the appropriate member of that union based on its value kind.

Values

CUPTI_METRIC_VALUE_KIND_DOUBLE = 0

The metric value is a 64-bit double.

CUPTI_METRIC_VALUE_KIND_UINT64 = 1

The metric value is a 64-bit unsigned integer.

CUPTI_METRIC_VALUE_KIND_PERCENT = 2

The metric value is a percentage represented by a 64-bit double. For example, 57.5% is represented by the value 57.5.

CUPTI_METRIC_VALUE_KIND_THROUGHPUT = 3

The metric value is a throughput represented by a 64-bit integer. The unit for throughput values is bytes/second.

CUPTI_METRIC_VALUE_KIND_INT64 = 4

The metric value is a 64-bit signed integer.

CUPTI_METRIC_VALUE_KIND_UTILIZATION_LEVEL = 5

The metric value is a utilization level, as represented by

CUpti_MetricValueUtilizationLevel.

CUPTI_METRIC_VALUE_KIND_FORCE_INT = 0x7fffffff

enum CUpti_MetricValueUtilizationLevel

Enumeration of utilization levels for metrics values of kind CUPTI_METRIC_VALUE_KIND_UTILIZATION_LEVEL. Utilization values can vary from IDLE (0) to MAX (10) but the enumeration only provides specific names for a few values.

Values

CUPTI_METRIC_VALUE_UTILIZATION_IDLE = 0

CUPTI_METRIC_VALUE_UTILIZATION_LOW = 2

CUPTI_METRIC_VALUE_UTILIZATION_MID = 5

CUPTI_METRIC_VALUE_UTILIZATION_HIGH = 8

CUPTI_METRIC_VALUE_UTILIZATION_MAX = 10

CUPTI_METRIC_VALUE_UTILIZATION_FORCE_INT = 0x7fffffff

typedef uint32_t CUpti_MetricID

ID for a metric.

A metric provides a measure of some aspect of the device.

CUptiResult cuptiDeviceEnumMetrics (CUdevice device, size_t *arraySizeBytes, CUpti_MetricID *metricArray)

Get the metrics for a device.

Parameters

device

The CUDA device

arraySizeBytes

The size of metricArray in bytes, and returns the number of bytes written to metricArray

metricArray

Returns the IDs of the metrics for the device

Returns

- CUPTI_SUCCESS
- CUPTI ERROR NOT INITIALIZED
- CUPTI_ERROR_INVALID_DEVICE
- CUPTI ERROR INVALID PARAMETER

if arraySizeBytes or metricArray are NULL

Description

Returns the metric IDs in metricArray for a device. The size of the metricArray buffer is given by *arraySizeBytes. The size of the metricArray buffer must be at least numMetrics * sizeof(CUpti_MetricID) or else all metric IDs will not be returned. The value returned in *arraySizeBytes contains the number of bytes returned in metricArray.

CUptiResult cuptiDeviceGetNumMetrics (CUdevice device, uint32_t *numMetrics)

Get the number of metrics for a device.

Parameters

device

The CUDA device

numMetrics

Returns the number of metrics available for the device

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_DEVICE
- CUPTI_ERROR_INVALID_PARAMETER

if numMetrics is NULL

Description

Returns the number of metrics available for a device.

CUptiResult cuptiEnumMetrics (size_t *arraySizeBytes, CUpti_MetricID *metricArray)

Get all the metrics available on any device.

Parameters

arraySizeBytes

The size of metricArray in bytes, and returns the number of bytes written to metricArray

metricArray

Returns the IDs of the metrics

Returns

- CUPTI_SUCCESS
- ► CUPTI_ERROR_INVALID_PARAMETER

if arraySizeBytes or metricArray are NULL

Description

Returns the metric IDs in metricArray for all CUDA-capable devices. The size of the metricArray buffer is given by *arraySizeBytes. The size of the metricArray buffer must be at least numMetrics * sizeof(CUpti_MetricID) or all metric IDs will not be returned. The value returned in *arraySizeBytes contains the number of bytes returned in metricArray.

CUptiResult cuptiGetNumMetrics (uint32_t *numMetrics)

Get the total number of metrics available on any device.

Parameters

numMetrics

Returns the number of metrics

Returns

- CUPTI_SUCCESS
- CUPTI ERROR INVALID PARAMETER

if numMetrics is NULL

Description

Returns the total number of metrics available on any CUDA-capable devices.

CUptiResult cuptiMetricCreateEventGroupSets (CUcontext context, size_t metricIdArraySizeBytes, CUpti_MetricID *metricIdArray, CUpti_EventGroupSets **eventGroupPasses)

For a set of metrics, get the grouping that indicates the number of passes and the event groups necessary to collect the events required for those metrics.

Parameters

context

The context for event collection

metricIdArraySizeBytes

Size of the metricIdArray in bytes

metricIdArray

Array of metric IDs

eventGroupPasses

Returns a CUpti_EventGroupSets object that indicates the number of passes required to collect the events and the events to collect on each pass

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_CONTEXT
- CUPTI_ERROR_INVALID_METRIC_ID
- CUPTI_ERROR_INVALID_PARAMETER

if metricIdArray or eventGroupPasses is NULL

Description

For a set of metrics, get the grouping that indicates the number of passes and the event groups necessary to collect the events required for those metrics.

See also:

cuptiEventGroupSetsCreate for details on event group set creation.

CUptiResult cuptiMetricEnumEvents (CUpti_MetricID metric, size_t *eventIdArraySizeBytes, CUpti_EventID *eventIdArray)

Get the events required to calculating a metric.

Parameters

metric

ID of the metric

eventIdArraySizeBytes

The size of eventIdArray in bytes, and returns the number of bytes written to eventIdArray

eventIdArray

Returns the IDs of the events required to calculate metric

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_METRIC_ID
- CUPTI_ERROR_INVALID_PARAMETER

if eventIdArraySizeBytes or eventIdArray are NULL.

Description

Gets the event IDs in eventIdArray required to calculate a metric. The size of the eventIdArray buffer is given by *eventIdArraySizeBytes and must be at least numEvents *sizeof(CUpti_EventID) or all events will not be returned. The value returned in *eventIdArraySizeBytes contains the number of bytes returned in eventIdArray.

CUptiResult cuptiMetricEnumProperties (CUpti_MetricID metric, size_t *propIdArraySizeBytes, CUpti_MetricPropertyID *propIdArray)

Get the properties required to calculating a metric.

Parameters

metric

ID of the metric

propIdArraySizeBytes

The size of propIdArray in bytes, and returns the number of bytes written to propIdArray

propIdArray

Returns the IDs of the properties required to calculate metric

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_METRIC_ID
- CUPTI_ERROR_INVALID_PARAMETER

if propIdArraySizeBytes or propIdArray are NULL.

Description

Gets the property IDs in propidArray required to calculate a metric. The size of the propidArray buffer is given by *propidArraySizeBytes and must be at least numProp * sizeof(CUpti_DeviceAttribute) or all properties will not be returned. The value returned in *propidArraySizeBytes contains the number of bytes returned in propidArray.

CUptiResult cuptiMetricGetAttribute (CUpti_MetricID metric, CUpti_MetricAttribute attrib, size_t *valueSize, void *value)

Get a metric attribute.

Parameters

metric

ID of the metric

attrib

The metric attribute to read

valueSize

The size of the value buffer in bytes, and returns the number of bytes written to value

value

Returns the attribute's value

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_METRIC_ID
- ► CUPTI_ERROR_INVALID_PARAMETER

if valueSize or value is NULL, or if attrib is not a metric attribute

► CUPTI_ERROR_PARAMETER_SIZE_NOT_SUFFICIENT

For non-c-string attribute values, indicates that the value buffer is too small to hold the attribute value.

Description

Returns a metric attribute in *value. The size of the value buffer is given by *valueSize. The value returned in *valueSize contains the number of bytes returned in value.

If the attribute value is a c-string that is longer than *valueSize, then only the first *valueSize characters will be returned and there will be no terminating null byte.

CUptiResult cuptiMetricGetIdFromName (CUdevice device, const char *metricName, CUpti_MetricID *metric)

Find an metric by name.

Parameters

device

The CUDA device

metricName

The name of metric to find

metric

Returns the ID of the found metric or undefined if unable to find the metric

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_DEVICE
- ► CUPTI_ERROR_INVALID_METRIC_NAME

if unable to find a metric with name metricName. In this case *metric is undefined

CUPTI ERROR INVALID PARAMETER

if metricName or metric are NULL.

Description

Find a metric by name and return the metric ID in *metric.

CUptiResult cuptiMetricGetNumEvents (CUpti_MetricID metric, uint32_t *numEvents)

Get number of events required to calculate a metric.

Parameters

metric

ID of the metric

numEvents

Returns the number of events required for the metric

Returns

- ► CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_METRIC_ID
- ► CUPTI_ERROR_INVALID_PARAMETER

if numEvents is NULL

Description

Returns the number of events in numEvents that are required to calculate a metric.

CUptiResult cuptiMetricGetNumProperties (CUpti_MetricID metric, uint32_t *numProp)

Get number of properties required to calculate a metric.

Parameters

metric

ID of the metric

numProp

Returns the number of properties required for the metric

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI_ERROR_INVALID_METRIC_ID
- CUPTI_ERROR_INVALID_PARAMETER
 if numProp is NULL

Description

Returns the number of properties in numProp that are required to calculate a metric.

CUptiResult cuptiMetricGetRequiredEventGroupSets (CUcontext context, CUpti_MetricID metric, CUpti_EventGroupSets **eventGroupSets)

For a metric get the groups of events that must be collected in the same pass.

Parameters

context

The context for event collection

metric

The metric ID

eventGroupSets

Returns a CUpti_EventGroupSets object that indicates the events that must be collected in the same pass to ensure the metric is calculated correctly. Returns NULL if no grouping is required for metric

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI ERROR INVALID METRIC ID

Description

For a metric get the groups of events that must be collected in the same pass to ensure that the metric is calculated correctly. If the events are not collected as specified then the metric value may be inaccurate.

The function returns NULL if a metric does not have any required event group. In this case the events needed for the metric can be grouped in any manner for collection.

CUptiResult cuptiMetricGetValue (CUdevice device, CUpti_MetricID metric, size_t eventIdArraySizeBytes, CUpti_EventID *eventIdArray, size_t eventValueArraySizeBytes, uint64_t

*eventValueArray, uint64_t timeDuration, CUpti_MetricValue *metricValue)

Calculate the value for a metric.

Parameters

device

The CUDA device that the metric is being calculated for

metric

The metric ID

eventIdArraySizeBytes

The size of eventIdArray in bytes

eventIdArray

The event IDs required to calculate metric

eventValueArraySizeBytes

The size of eventValueArray in bytes

eventValueArray

The normalized event values required to calculate metric. The values must be order to match the order of events in eventIdArray

timeDuration

The duration over which the events were collected, in ns

metricValue

Returns the value for the metric

Returns

- CUPTI_SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI ERROR INVALID METRIC ID
- CUPTI_ERROR_INVALID_OPERATION
- ► CUPTI_ERROR_PARAMETER_SIZE_NOT_SUFFICIENT

if the eventIdArray does not contain all the events needed for metric

CUPTI ERROR INVALID EVENT VALUE

if any of the event values required for the metric is CUPTI_EVENT_OVERFLOW

CUPTI_ERROR_INVALID_METRIC_VALUE

if the computed metric value cannot be represented in the metric's value type. For example, if the metric value type is unsigned and the computed metric value is negative

CUPTI_ERROR_INVALID_PARAMETER

if metricValue, eventIdArray or eventValueArray is NULL

Description

Use the events collected for a metric to calculate the metric value. Metric value evaluation depends on the evaluation mode CUpti_MetricEvaluationMode that the metric supports. If a metric has evaluation mode as CUPTI_METRIC_EVALUATION_MODE_PER_INSTANCE, then it assumes that the input event value is for one domain instance. If a metric has evaluation mode as CUPTI_METRIC_EVALUATION_MODE_AGGREGATE, it assumes that input event values are normalized to represent all domain instances on a device. For the most accurate metric collection, the events required for the metric should be collected for all profiled domain instances. For example, to collect all instances of an event, set the CUPTI_EVENT_GROUP_ATTR_PROFILE_ALL_DOMAIN_INSTANCES attribute on the group containing the event to 1. The normalized value for the event is then: (sum event values * totalInstanceCount) / instanceCount, where sum event values is the summation of the event values across all profiled domain instances, totalInstanceCount is obtained from querying CUPTI_EVENT_DOMAIN_ATTR_TOTAL_INSTANCE_COUNT and instanceCount is obtained from querying CUPTI_EVENT_GROUP_ATTR_INSTANCE_COUNT (or CUPTI_EVENT_DOMAIN_ATTR_INSTANCE_COUNT).

CUptiResult cuptiMetricGetValue2 (CUpti_MetricID metric, size_t eventIdArraySizeBytes, CUpti_EventID *eventIdArray, size_t eventValueArraySizeBytes, uint64_t *eventValueArray, size_t propIdArraySizeBytes, CUpti_MetricPropertyID *propIdArray, size_t propValueArraySizeBytes, uint64_t *propValueArray, CUpti_MetricValue *metricValue)

Calculate the value for a metric.

Parameters

metric

The metric ID

eventIdArraySizeBytes

The size of eventIdArray in bytes

eventIdArray

The event IDs required to calculate metric

eventValueArraySizeBytes

The size of eventValueArray in bytes

eventValueArray

The normalized event values required to calculate metric. The values must be order to match the order of events in eventIdArray

propIdArraySizeBytes

The size of propIdArray in bytes

propIdArray

The metric property IDs required to calculate metric

propValueArraySizeBytes

The size of propValueArray in bytes

propValueArray

The metric property values required to calculate metric. The values must be order to match the order of metric properties in propldArray

metricValue

Returns the value for the metric

Returns

- CUPTI SUCCESS
- CUPTI_ERROR_NOT_INITIALIZED
- CUPTI ERROR INVALID METRIC ID
- CUPTI_ERROR_INVALID_OPERATION
- CUPTI_ERROR_PARAMETER_SIZE_NOT_SUFFICIENT

if the eventIdArray does not contain all the events needed for metric

CUPTI_ERROR_INVALID_EVENT_VALUE

if any of the event values required for the metric is CUPTI_EVENT_OVERFLOW

► CUPTI_ERROR_NOT_COMPATIBLE

if the computed metric value cannot be represented in the metric's value type. For example, if the metric value type is unsigned and the computed metric value is negative

CUPTI_ERROR_INVALID_PARAMETER

if metricValue, eventIdArray or eventValueArray is NULL

Description

Use the events and properties collected for a metric to calculate the metric value. Metric value evaluation depends on the evaluation mode CUpti_MetricEvaluationMode that the metric supports. If a metric has evaluation mode as CUPTI_METRIC_EVALUATION_MODE_PER_INSTANCE, then it assumes that the input event value is for one domain instance. If a metric has evaluation mode as CUPTI_METRIC_EVALUATION_MODE_AGGREGATE, it assumes that input event values are normalized to represent all domain instances on a device. For the most accurate metric collection, the events required for the metric should be collected for all profiled domain instances. For example, to collect all instances of an event,

set the CUPTI_EVENT_GROUP_ATTR_PROFILE_ALL_DOMAIN_INSTANCES attribute on the group containing the event to 1. The normalized value for the event is then: (sum_event_values * totalInstanceCount) / instanceCount, where sum_event_values is the summation of the event values across all profiled domain instances, totalInstanceCount is obtained from querying CUPTI_EVENT_DOMAIN_ATTR_TOTAL_INSTANCE_COUNT and instanceCount is obtained from querying CUPTI_EVENT_GROUP_ATTR_INSTANCE_COUNT (or CUPTI_EVENT_DOMAIN_ATTR_INSTANCE_COUNT).

Chapter 3. DATA STRUCTURES

Here are the data structures with brief descriptions:

CUpti_Activity

The base activity record

CUpti_ActivityAPI

The activity record for a driver or runtime API invocation

CUpti_ActivityAutoBoostState

Device auto boost state structure

CUpti_ActivityBranch

The activity record for source level result branch. (deprecated)

CUpti_ActivityBranch2

The activity record for source level result branch

CUpti_ActivityCdpKernel

The activity record for CDP (CUDA Dynamic Parallelism) kernel

CUpti_ActivityContext

The activity record for a context

CUpti_ActivityCudaEvent

The activity record for CUDA event

CUpti_ActivityDevice

The activity record for a device. (deprecated)

CUpti_ActivityDevice2

The activity record for a device. (CUDA 7.0 onwards)

CUpti_ActivityDeviceAttribute

The activity record for a device attribute

CUpti_ActivityEnvironment

The activity record for CUPTI environmental data

CUpti_ActivityEvent

The activity record for a CUPTI event

CUpti_ActivityEventInstance

The activity record for a CUPTI event with instance information

CUpti_ActivityExternalCorrelation

The activity record for correlation with external records

CUpti_ActivityFunction

The activity record for global/device functions

CUpti_ActivityGlobalAccess

The activity record for source-level global access. (deprecated)

CUpti_ActivityGlobalAccess2

The activity record for source-level global access

CUpti_ActivityInstantaneousEvent

The activity record for an instantaneous CUPTI event

CUpti_ActivityInstantaneousEventInstance

The activity record for an instantaneous CUPTI event with event domain instance information

CUpti ActivityInstantaneousMetric

The activity record for an instantaneous CUPTI metric

CUpti_ActivityInstantaneousMetricInstance

The instantaneous activity record for a CUPTI metric with instance information

CUpti_ActivityInstructionCorrelation

The activity record for source-level sass/source line-by-line correlation

CUpti_ActivityInstructionExecution

The activity record for source-level instruction execution

CUpti_ActivityKernel

The activity record for kernel. (deprecated)

CUpti_ActivityKernel2

The activity record for kernel. (deprecated)

CUpti_ActivityKernel3

The activity record for a kernel (CUDA 6.5(with sm_52 support) onwards)

CUpti_ActivityMarker

The activity record providing a marker which is an instantaneous point in time. (deprecated in CUDA 8.0)

CUpti_ActivityMarker2

The activity record providing a marker which is an instantaneous point in time

CUpti_ActivityMarkerData

The activity record providing detailed information for a marker

CUpti_ActivityMemcpy

The activity record for memory copies

CUpti_ActivityMemcpy2

The activity record for peer-to-peer memory copies

CUpti_ActivityMemset

The activity record for memset

CUpti_ActivityMetric

The activity record for a CUPTI metric

CUpti_ActivityMetricInstance

The activity record for a CUPTI metric with instance information

CUpti_ActivityModule

The activity record for a CUDA module

CUpti_ActivityName

The activity record providing a name

CUpti_ActivityNvLink

NvLink information

CUpti_ActivityObjectKindId

Identifiers for object kinds as specified by CUpti_ActivityObjectKind

CUpti_ActivityOpenAcc

The base activity record for OpenAcc records

CUpti_ActivityOpenAccData

The activity record for OpenACC data

CUpti_ActivityOpenAccLaunch

The activity record for OpenACC launch

CUpti_ActivityOpenAccOther

The activity record for OpenACC other

CUpti_ActivityOverhead

The activity record for CUPTI and driver overheads

CUpti_ActivityPCSampling

The activity record for PC sampling. (deprecated in CUDA 8.0)

CUpti_ActivityPCSampling2

The activity record for PC sampling

CUpti_ActivityPCSamplingConfig

PC sampling configuration structure

CUpti_ActivityPCSamplingRecordInfo

The activity record for record status for PC sampling

CUpti_ActivityPreemption

The activity record for a preemption of a CDP kernel

CUpti_ActivitySharedAccess

The activity record for source-level shared access

CUpti_ActivitySourceLocator

The activity record for source locator

CUpti_ActivityStream

The activity record for CUDA stream

CUpti_ActivitySynchronization

The activity record for synchronization management

CUpti_ActivityUnifiedMemoryCounter

The activity record for Unified Memory counters (deprecated in CUDA 7.0)

CUpti_ActivityUnifiedMemoryCounter2

The activity record for Unified Memory counters (CUDA 7.0 and beyond)

CUpti_ActivityUnifiedMemoryCounterConfig

Unified Memory counters configuration structure

CUpti_CallbackData

Data passed into a runtime or driver API callback function

CUpti_EventGroupSet

A set of event groups

CUpti_EventGroupSets

A set of event group sets

CUpti_MetricValue

A metric value

CUpti_ModuleResourceData

Module data passed into a resource callback function

CUpti_NvtxData

Data passed into a NVTX callback function

CUpti_ResourceData

Data passed into a resource callback function

CUpti_SynchronizeData

Data passed into a synchronize callback function

3.1. CUpti_Activity Struct Reference

The base activity record.

The activity API uses a CUpti_Activity as a generic representation for any activity. The 'kind' field is used to determine the specific activity kind, and from that the CUpti_Activity object can be cast to the specific activity record type appropriate for that kind.

Note that all activity record types are padded and aligned to ensure that each member of the record is naturally aligned.

See also:

CUpti_ActivityKind

CUpti_ActivityKind CUpti_Activity::kind

The kind of this activity.

3.2. CUpti_ActivityAPI Struct Reference

The activity record for a driver or runtime API invocation.

This activity record represents an invocation of a driver or runtime API (CUPTI_ACTIVITY_KIND_DRIVER and CUPTI_ACTIVITY_KIND_RUNTIME).

CUpti_CallbackId CUpti_ActivityAPI::cbid

The ID of the driver or runtime function.

uint32_t CUpti_ActivityAPI::correlationId

The correlation ID of the driver or runtime CUDA function. Each function invocation is assigned a unique correlation ID that is identical to the correlation ID in the memcpy, memset, or kernel activity record that is associated with this function.

uint64_t CUpti_ActivityAPI::end

The end timestamp for the function, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the function.

CUpti_ActivityKind CUpti_ActivityAPI::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_DRIVER or CUPTI_ACTIVITY_KIND_RUNTIME.

uint32_t CUpti_ActivityAPI::processId

The ID of the process where the driver or runtime CUDA function is executing.

uint32_t CUpti_ActivityAPI::returnValue

The return value for the function. For a CUDA driver function with will be a CUresult value, and for a CUDA runtime function this will be a cudaError_t value.

uint64_t CUpti_ActivityAPI::start

The start timestamp for the function, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the function.

uint32_t CUpti_ActivityAPI::threadId

The ID of the thread where the driver or runtime CUDA function is executing.

3.3. CUpti_ActivityAutoBoostState Struct Reference

Device auto boost state structure.

This structure defines auto boost state for a device. See function /ref cuptiGetAutoBoostState

uint32_t CUpti_ActivityAutoBoostState::enabled

Returned auto boost state. 1 is returned in case auto boost is enabled, 0 otherwise

uint32_t CUpti_ActivityAutoBoostState::pid

Id of process that has set the current boost state. The value will be CUPTI_AUTO_BOOST_INVALID_CLIENT_PID if the user does not have the permission to query process ids or there is an error in querying the process id.

3.4. CUpti_ActivityBranch Struct Reference

The activity record for source level result branch. (deprecated).

This activity record the locations of the branches in the source (CUPTI_ACTIVITY_KIND_BRANCH). Branch activities are now reported using the CUpti_ActivityBranch2 activity record.

uint32_t CUpti_ActivityBranch::correlationId

The correlation ID of the kernel to which this result is associated.

uint32_t CUpti_ActivityBranch::diverged

Number of times this branch diverged

uint32_t CUpti_ActivityBranch::executed

The number of times this branch was executed

CUpti_ActivityKind CUpti_ActivityBranch::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_BRANCH.

uint32_t CUpti_ActivityBranch::pcOffset

The pc offset for the branch.

uint32_t CUpti_ActivityBranch::sourceLocatorId

The ID for source locator.

uint64_t CUpti_ActivityBranch::threadsExecuted

This increments each time when this instruction is executed by number of threads that executed this instruction

3.5. CUpti_ActivityBranch2 Struct Reference

The activity record for source level result branch.

This activity record the locations of the branches in the source (CUPTI_ACTIVITY_KIND_BRANCH).

uint32_t CUpti_ActivityBranch2::correlationId

The correlation ID of the kernel to which this result is associated.

uint32_t CUpti_ActivityBranch2::diverged

Number of times this branch diverged

uint32_t CUpti_ActivityBranch2::executed

The number of times this branch was executed

uint32_t CUpti_ActivityBranch2::functionId

Correlation ID with global/device function name

CUpti_ActivityKind CUpti_ActivityBranch2::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_BRANCH.

uint32_t CUpti_ActivityBranch2::pad

Undefined. Reserved for internal use.

uint32_t CUpti_ActivityBranch2::pcOffset

The pc offset for the branch.

uint32_t CUpti_ActivityBranch2::sourceLocatorId

The ID for source locator.

uint64_t CUpti_ActivityBranch2::threadsExecuted

This increments each time when this instruction is executed by number of threads that executed this instruction

3.6. CUpti_ActivityCdpKernel Struct Reference

The activity record for CDP (CUDA Dynamic Parallelism) kernel.

This activity record represents a CDP kernel execution.

int32_t CUpti_ActivityCdpKernel::blockX

The X-dimension block size for the kernel.

int32_t CUpti_ActivityCdpKernel::blockY

The Y-dimension block size for the kernel.

int32_t CUpti_ActivityCdpKernel::blockZ

The Z-dimension grid size for the kernel.

uint64_t CUpti_ActivityCdpKernel::completed

The timestamp when kernel is marked as completed, in ns. A value of CUPTI_TIMESTAMP_UNKNOWN indicates that the completion time is unknown.

uint32_t CUpti_ActivityCdpKernel::contextId

The ID of the context where the kernel is executing.

uint32_t CUpti_ActivityCdpKernel::correlationId

The correlation ID of the kernel. Each kernel execution is assigned a unique correlation ID that is identical to the correlation ID in the driver API activity record that launched the kernel.

uint32_t CUpti_ActivityCdpKernel::deviceId

The ID of the device where the kernel is executing.

int32_t

CUpti_ActivityCdpKernel::dynamicSharedMemory

The dynamic shared memory reserved for the kernel, in bytes.

uint64_t CUpti_ActivityCdpKernel::end

The end timestamp for the kernel execution, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the kernel.

uint8_t CUpti_ActivityCdpKernel::executed

The cache configuration used for the kernel. The value is one of the CUfunc_cache enumeration values from cuda.h.

int64_t CUpti_ActivityCdpKernel::gridId

The grid ID of the kernel. Each kernel execution is assigned a unique grid ID.

int32_t CUpti_ActivityCdpKernel::gridX

The X-dimension grid size for the kernel.

int32_t CUpti_ActivityCdpKernel::gridY

The Y-dimension grid size for the kernel.

int32_t CUpti_ActivityCdpKernel::gridZ

The Z-dimension grid size for the kernel.

CUpti_ActivityKind CUpti_ActivityCdpKernel::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_CDP_KERNEL

uint32 t

CUpti_ActivityCdpKernel::localMemoryPerThread

The amount of local memory reserved for each thread, in bytes.

uint32_t CUpti_ActivityCdpKernel::localMemoryTotal

The total amount of local memory reserved for the kernel, in bytes.

const char *CUpti_ActivityCdpKernel::name

The name of the kernel. This name is shared across all activity records representing the same kernel, and so should not be modified.

uint32_t CUpti_ActivityCdpKernel::parentBlockX

The X-dimension of the parent block.

uint32_t CUpti_ActivityCdpKernel::parentBlockY

The Y-dimension of the parent block.

uint32_t CUpti_ActivityCdpKernel::parentBlockZ

The Z-dimension of the parent block.

int64_t CUpti_ActivityCdpKernel::parentGridId

The grid ID of the parent kernel.

uint64_t CUpti_ActivityCdpKernel::queued

The timestamp when kernel is queued up, in ns. A value of CUPTI_TIMESTAMP_UNKNOWN indicates that the queued time is unknown.

uint16_t CUpti_ActivityCdpKernel::registersPerThread

The number of registers required for each thread executing the kernel.

uint8_t CUpti_ActivityCdpKernel::requested

The cache configuration requested by the kernel. The value is one of the CUfunc_cache enumeration values from cuda.h.

uint8_t CUpti_ActivityCdpKernel::sharedMemoryConfig

The shared memory configuration used for the kernel. The value is one of the CUsharedconfig enumeration values from cuda.h.

uint64_t CUpti_ActivityCdpKernel::start

The start timestamp for the kernel execution, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the kernel.

int32_t CUpti_ActivityCdpKernel::staticSharedMemory

The static shared memory allocated for the kernel, in bytes.

uint32_t CUpti_ActivityCdpKernel::streamId

The ID of the stream where the kernel is executing.

uint64_t CUpti_ActivityCdpKernel::submitted

The timestamp when kernel is submitted to the gpu, in ns. A value of CUPTI_TIMESTAMP_UNKNOWN indicates that the submission time is unknown.

3.7. CUpti_ActivityContext Struct Reference

The activity record for a context.

This activity record represents information about a context (CUPTI_ACTIVITY_KIND_CONTEXT).

uint16_t CUpti_ActivityContext::computeApiKind

The compute API kind.

See also:

CUpti_ActivityComputeApiKind

uint32_t CUpti_ActivityContext::contextId

The context ID.

uint32_t CUpti_ActivityContext::deviceId

The device ID.

CUpti_ActivityKind CUpti_ActivityContext::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_CONTEXT.

uint16_t CUpti_ActivityContext::nullStreamId

The ID for the NULL stream in this context

3.8. CUpti_ActivityCudaEvent Struct Reference

The activity record for CUDA event.

This activity is used to track recorded events. (CUPTI_ACTIVITY_KIND_CUDA_EVENT).

uint32_t CUpti_ActivityCudaEvent::contextId

The ID of the context where the event was recorded.

uint32_t CUpti_ActivityCudaEvent::correlationId

The correlation ID of the API to which this result is associated.

uint32_t CUpti_ActivityCudaEvent::eventId

A unique event ID to identify the event record.

CUpti_ActivityKind CUpti_ActivityCudaEvent::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_CUDA_EVENT.

uint32_t CUpti_ActivityCudaEvent::pad

Undefined. Reserved for internal use.

uint32_t CUpti_ActivityCudaEvent::streamId

The compute stream where the event was recorded.

3.9. CUpti_ActivityDevice Struct Reference

The activity record for a device. (deprecated).

This activity record represents information about a GPU device (CUPTI_ACTIVITY_KIND_DEVICE). Device activity is now reported using the CUpti_ActivityDevice2 activity record.

uint32_t CUpti_ActivityDevice::computeCapabilityMajor

Compute capability for the device, major number.

uint32_t CUpti_ActivityDevice::computeCapabilityMinor

Compute capability for the device, minor number.

uint32_t CUpti_ActivityDevice::constantMemorySize

The amount of constant memory on the device, in bytes.

uint32_t CUpti_ActivityDevice::coreClockRate

The core clock rate of the device, in kHz.

CUpti_ActivityFlag CUpti_ActivityDevice::flags

The flags associated with the device.

See also:

CUpti_ActivityFlag

uint64_t CUpti_ActivityDevice::globalMemoryBandwidth

The global memory bandwidth available on the device, in kBytes/sec.

uint64_t CUpti_ActivityDevice::globalMemorySize

The amount of global memory on the device, in bytes.

uint32 t CUpti ActivityDevice::id

The device ID.

CUpti_ActivityKind CUpti_ActivityDevice::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_DEVICE.

uint32_t CUpti_ActivityDevice::l2CacheSize

The size of the L2 cache on the device, in bytes.

uint32_t CUpti_ActivityDevice::maxBlockDimX

Maximum allowed X dimension for a block.

uint32_t CUpti_ActivityDevice::maxBlockDimY

Maximum allowed Y dimension for a block.

uint32_t CUpti_ActivityDevice::maxBlockDimZ

Maximum allowed Z dimension for a block.

uint32_t

CUpti_ActivityDevice::maxBlocksPerMultiprocessor

Maximum number of blocks that can be present on a multiprocessor at any given time.

uint32_t CUpti_ActivityDevice::maxGridDimX

Maximum allowed X dimension for a grid.

uint32_t CUpti_ActivityDevice::maxGridDimY

Maximum allowed Y dimension for a grid.

uint32_t CUpti_ActivityDevice::maxGridDimZ

Maximum allowed Z dimension for a grid.

uint32_t CUpti_ActivityDevice::maxIPC

The maximum "instructions per cycle" possible on each device multiprocessor.

uint32_t CUpti_ActivityDevice::maxRegistersPerBlock

Maximum number of registers that can be allocated to a block.

uint32_t

CUpti_ActivityDevice::maxSharedMemoryPerBlock

Maximum amount of shared memory that can be assigned to a block, in bytes.

uint32_t CUpti_ActivityDevice::maxThreadsPerBlock

Maximum number of threads allowed in a block.

uint32_t

CUpti_ActivityDevice::maxWarpsPerMultiprocessor

Maximum number of warps that can be present on a multiprocessor at any given time.

const char *CUpti_ActivityDevice::name

The device name. This name is shared across all activity records representing instances of the device, and so should not be modified.

uint32_t CUpti_ActivityDevice::numMemcpyEngines

Number of memory copy engines on the device.

uint32_t CUpti_ActivityDevice::numMultiprocessors

Number of multiprocessors on the device.

uint32 t CUpti ActivityDevice::numThreadsPerWarp

The number of threads per warp on the device.

3.10. CUpti_ActivityDevice2 Struct Reference

The activity record for a device. (CUDA 7.0 onwards).

This activity record represents information about a GPU device (CUPTI_ACTIVITY_KIND_DEVICE).

uint32 t

CUpti_ActivityDevice2::computeCapabilityMajor

Compute capability for the device, major number.

uint32_t

CUpti_ActivityDevice2::computeCapabilityMinor

Compute capability for the device, minor number.

uint32_t CUpti_ActivityDevice2::constantMemorySize

The amount of constant memory on the device, in bytes.

uint32_t CUpti_ActivityDevice2::coreClockRate

The core clock rate of the device, in kHz.

uint32_t CUpti_ActivityDevice2::eccEnabled

ECC enabled flag for device

CUpti_ActivityFlag CUpti_ActivityDevice2::flags

The flags associated with the device.

See also:

CUpti_ActivityFlag

uint64_t

CUpti_ActivityDevice2::globalMemoryBandwidth

The global memory bandwidth available on the device, in kBytes/sec.

uint64_t CUpti_ActivityDevice2::globalMemorySize

The amount of global memory on the device, in bytes.

uint32_t CUpti_ActivityDevice2::id

The device ID.

CUpti_ActivityKind CUpti_ActivityDevice2::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_DEVICE.

uint32_t CUpti_ActivityDevice2::l2CacheSize

The size of the L2 cache on the device, in bytes.

uint32_t CUpti_ActivityDevice2::maxBlockDimX

Maximum allowed X dimension for a block.

uint32_t CUpti_ActivityDevice2::maxBlockDimY

Maximum allowed Y dimension for a block.

uint32_t CUpti_ActivityDevice2::maxBlockDimZ

Maximum allowed Z dimension for a block.

uint32_t

CUpti_ActivityDevice2::maxBlocksPerMultiprocessor

Maximum number of blocks that can be present on a multiprocessor at any given time.

uint32_t CUpti_ActivityDevice2::maxGridDimX

Maximum allowed X dimension for a grid.

uint32_t CUpti_ActivityDevice2::maxGridDimY

Maximum allowed Y dimension for a grid.

uint32_t CUpti_ActivityDevice2::maxGridDimZ

Maximum allowed Z dimension for a grid.

uint32_t CUpti_ActivityDevice2::maxIPC

The maximum "instructions per cycle" possible on each device multiprocessor.

uint32_t CUpti_ActivityDevice2::maxRegistersPerBlock

Maximum number of registers that can be allocated to a block.

uint32_t

CUpti_ActivityDevice2::maxRegistersPerMultiprocessor

Maximum number of 32-bit registers available per multiprocessor.

uint32_t

CUpti_ActivityDevice2::maxSharedMemoryPerBlock

Maximum amount of shared memory that can be assigned to a block, in bytes.

uint32_t

CUpti_ActivityDevice2::maxSharedMemoryPerMultiprocessor

Maximum amount of shared memory available per multiprocessor, in bytes.

uint32_t CUpti_ActivityDevice2::maxThreadsPerBlock

Maximum number of threads allowed in a block.

uint32_t

CUpti_ActivityDevice2::maxWarpsPerMultiprocessor

Maximum number of warps that can be present on a multiprocessor at any given time.

const char *CUpti_ActivityDevice2::name

The device name. This name is shared across all activity records representing instances of the device, and so should not be modified.

uint32_t CUpti_ActivityDevice2::numMemcpyEngines

Number of memory copy engines on the device.

uint32_t CUpti_ActivityDevice2::numMultiprocessors

Number of multiprocessors on the device.

uint32_t CUpti_ActivityDevice2::numThreadsPerWarp

The number of threads per warp on the device.

uint32_t CUpti_ActivityDevice2::pad

Undefined. Reserved for internal use.

CUuuid CUpti_ActivityDevice2::uuid

The device UUID. This value is the globally unique immutable alphanumeric identifier of the device.

3.11. CUpti_ActivityDeviceAttribute Struct Reference

The activity record for a device attribute.

This activity record represents information about a GPU device: either a CUpti_DeviceAttribute or CUdevice_attribute value (CUPTI_ACTIVITY_KIND_DEVICE_ATTRIBUTE).

CUpti_ActivityDeviceAttribute::@8 CUpti_ActivityDeviceAttribute::attribute

The attribute, either a CUpti_DeviceAttribute or CUdevice_attribute. Flag CUPTI_ACTIVITY_FLAG_DEVICE_ATTRIBUTE_CUDEVICE is used to indicate what kind of attribute this is. If CUPTI_ACTIVITY_FLAG_DEVICE_ATTRIBUTE_CUDEVICE is 1 then CUdevice_attribute field is value, otherwise CUpti_DeviceAttribute field is valid.

uint32_t CUpti_ActivityDeviceAttribute::deviceId

The ID of the device that this attribute applies to.

CUpti ActivityFlag CUpti ActivityDeviceAttribute::flags

The flags associated with the device.

See also:

CUpti_ActivityFlag

CUpti_ActivityKind CUpti_ActivityDeviceAttribute::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_DEVICE_ATTRIBUTE.

CUpti_ActivityDeviceAttribute::@9 CUpti_ActivityDeviceAttribute::value

The value for the attribute. See CUpti_DeviceAttribute and CUdevice_attribute for the type of the value for a given attribute.

3.12. CUpti_ActivityEnvironment Struct Reference

The activity record for CUPTI environmental data.

This activity record provides CUPTI environmental data, include power, clocks, and thermals. This information is sampled at various rates and returned in this activity record. The consumer of the record needs to check the environmentKind field to figure out what kind of environmental record this is.

CUpti_EnvironmentClocksThrottleReason CUpti_ActivityEnvironment::clocksThrottleReasons

The clocks throttle reasons.

CUpti_ActivityEnvironment::@10::@14 CUpti_ActivityEnvironment::cooling

Data returned for CUPTI_ACTIVITY_ENVIRONMENT_COOLING environment kind.

uint32_t CUpti_ActivityEnvironment::deviceId

The ID of the device

CUpti_ActivityEnvironmentKind CUpti_ActivityEnvironment::environmentKind

The kind of data reported in this record.

uint32_t CUpti_ActivityEnvironment::fanSpeed

The fan speed as percentage of maximum.

uint32_t CUpti_ActivityEnvironment::gpuTemperature

The GPU temperature in degrees C.

CUpti_ActivityKind CUpti_ActivityEnvironment::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_ENVIRONMENT.

uint32_t CUpti_ActivityEnvironment::memoryClock

The memory frequency in MHz

uint32_t CUpti_ActivityEnvironment::pcieLinkGen

The PCIe link generation.

uint32_t CUpti_ActivityEnvironment::pcieLinkWidth

The PCIe link width.

CUpti_ActivityEnvironment::@10::@13 CUpti_ActivityEnvironment::power

Data returned for CUPTI_ACTIVITY_ENVIRONMENT_POWER environment kind.

uint32_t CUpti_ActivityEnvironment::power

The power in milliwatts consumed by GPU and associated circuitry.

uint32_t CUpti_ActivityEnvironment::powerLimit

The power in milliwatts that will trigger power management algorithm.

uint32_t CUpti_ActivityEnvironment::smClock

The SM frequency in MHz

CUpti_ActivityEnvironment::@10::@11 CUpti_ActivityEnvironment::speed

Data returned for CUPTI_ACTIVITY_ENVIRONMENT_SPEED environment kind.

CUpti_ActivityEnvironment::@10::@12 CUpti_ActivityEnvironment::temperature

Data returned for CUPTI_ACTIVITY_ENVIRONMENT_TEMPERATURE environment kind.

uint64_t CUpti_ActivityEnvironment::timestamp

The timestamp when this sample was retrieved, in ns. A value of 0 indicates that timestamp information could not be collected for the marker.

3.13. CUpti_ActivityEvent Struct Reference

The activity record for a CUPTI event.

This activity record represents a CUPTI event value (CUPTI_ACTIVITY_KIND_EVENT). This activity record kind is not produced by the activity API but is included for completeness and ease-of-use. Profile frameworks built on top of CUPTI that collect event data may choose to use this type to store the collected event data.

uint32_t CUpti_ActivityEvent::correlationId

The correlation ID of the event. Use of this ID is user-defined, but typically this ID value will equal the correlation ID of the kernel for which the event was gathered.

CUpti_EventDomainID CUpti_ActivityEvent::domain

The event domain ID.

CUpti_EventID CUpti_ActivityEvent::id

The event ID.

CUpti_ActivityKind CUpti_ActivityEvent::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_ EVENT.

uint64_t CUpti_ActivityEvent::value

The event value.

3.14. CUpti_ActivityEventInstance Struct Reference

The activity record for a CUPTI event with instance information.

This activity record represents the a CUPTI event value for a specific event domain instance (CUPTI_ACTIVITY_KIND_EVENT_INSTANCE). This activity record kind is not produced by the activity API but is included for completeness and ease-of-use. Profile frameworks built on top of CUPTI that collect event data may choose to use this type to store the collected event data. This activity record should be used when event domain instance information needs to be associated with the event.

uint32_t CUpti_ActivityEventInstance::correlationId

The correlation ID of the event. Use of this ID is user-defined, but typically this ID value will equal the correlation ID of the kernel for which the event was gathered.

CUpti_EventDomainID CUpti_ActivityEventInstance::domain

The event domain ID.

CUpti_EventID CUpti_ActivityEventInstance::id

The event ID.

uint32_t CUpti_ActivityEventInstance::instance

The event domain instance.

CUpti_ActivityKind CUpti_ActivityEventInstance::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_EVENT_INSTANCE.

uint32_t CUpti_ActivityEventInstance::pad

Undefined. Reserved for internal use.

uint64_t CUpti_ActivityEventInstance::value

The event value.

3.15. CUpti_ActivityExternalCorrelation Struct Reference

The activity record for correlation with external records.

This activity record correlates native CUDA records (e.g. CUDA Driver API, kernels, memcpys, ...) with records from external APIs such as OpenACC. (CUPTI_ACTIVITY_KIND_EXTERNAL_CORRELATION).

See also:

CUpti_ActivityKind

uint32_t

CUpti_ActivityExternalCorrelation::correlationId

The correlation ID of the associated CUDA driver or runtime API record.

uint64_t CUpti_ActivityExternalCorrelation::externalId

The correlation ID of the associated non-CUDA API record. The exact field in the associated external record depends on that record's activity kind (

See also:

externalKind).

CUpti_ExternalCorrelationKind CUpti_ActivityExternalCorrelation::externalKind

The kind of external API this record correlated to.

CUpti_ActivityKind CUpti_ActivityExternalCorrelation::kind

The kind of this activity.

uint32_t CUpti_ActivityExternalCorrelation::reserved

Undefined. Reserved for internal use.

3.16. CUpti_ActivityFunction Struct Reference

The activity record for global/device functions.

This activity records function name and corresponding module information. (CUPTI_ACTIVITY_KIND_FUNCTION).

uint32_t CUpti_ActivityFunction::contextId

The ID of the context where the function is launched.

uint32_t CUpti_ActivityFunction::functionIndex

The function's unique symbol index in the module.

uint32_t CUpti_ActivityFunction::id

ID to uniquely identify the record

CUpti_ActivityKind CUpti_ActivityFunction::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_FUNCTION.

uint32_t CUpti_ActivityFunction::moduleId

The module ID in which this global/device function is present.

const char *CUpti_ActivityFunction::name

The name of the function. This name is shared across all activity records representing the same kernel, and so should not be modified.

3.17. CUpti_ActivityGlobalAccess Struct Reference

The activity record for source-level global access. (deprecated).

This activity records the locations of the global accesses in the source (CUPTI_ACTIVITY_KIND_GLOBAL_ACCESS). Global access activities are now reported using the CUpti_ActivityGlobalAccess2 activity record.

uint32_t CUpti_ActivityGlobalAccess::correlationId

The correlation ID of the kernel to which this result is associated.

uint32_t CUpti_ActivityGlobalAccess::executed

The number of times this instruction was executed

CUpti_ActivityFlag CUpti_ActivityGlobalAccess::flags

The properties of this global access.

CUpti_ActivityKind CUpti_ActivityGlobalAccess::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_GLOBAL_ACCESS.

uint64_t CUpti_ActivityGlobalAccess::l2_transactions

The total number of 32 bytes transactions to L2 cache generated by this access

uint32_t CUpti_ActivityGlobalAccess::pcOffset

The pc offset for the access.

uint32_t CUpti_ActivityGlobalAccess::sourceLocatorId

The ID for source locator.

uint64_t CUpti_ActivityGlobalAccess::threadsExecuted

This increments each time when this instruction is executed by number of threads that executed this instruction with predicate and condition code evaluating to true.

3.18. CUpti_ActivityGlobalAccess2 Struct Reference

The activity record for source-level global access.

This activity records the locations of the global accesses in the source (CUPTI_ACTIVITY_KIND_GLOBAL_ACCESS).

uint32_t CUpti_ActivityGlobalAccess2::correlationId

The correlation ID of the kernel to which this result is associated.

uint32_t CUpti_ActivityGlobalAccess2::executed

The number of times this instruction was executed

CUpti_ActivityFlag CUpti_ActivityGlobalAccess2::flags

The properties of this global access.

uint32_t CUpti_ActivityGlobalAccess2::functionId

Correlation ID with global/device function name

CUpti_ActivityKind CUpti_ActivityGlobalAccess2::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_GLOBAL_ACCESS.

uint64_t CUpti_ActivityGlobalAccess2::l2_transactions

The total number of 32 bytes transactions to L2 cache generated by this access

uint32_t CUpti_ActivityGlobalAccess2::pad

Undefined. Reserved for internal use.

uint32_t CUpti_ActivityGlobalAccess2::pcOffset

The pc offset for the access.

uint32_t CUpti_ActivityGlobalAccess2::sourceLocatorId

The ID for source locator.

uint64_t

CUpti_ActivityGlobalAccess2::theoreticalL2Transactions

The minimum number of L2 transactions possible based on the access pattern.

uint64_t CUpti_ActivityGlobalAccess2::threadsExecuted

This increments each time when this instruction is executed by number of threads that executed this instruction with predicate and condition code evaluating to true.

3.19. CUpti_ActivityInstantaneousEvent Struct Reference

The activity record for an instantaneous CUPTI event.

This activity record represents a CUPTI event value (CUPTI_ACTIVITY_KIND_EVENT) sampled at a particular instant. This activity record kind is not produced by the activity API but is included for completeness and ease-of-use. Profiler frameworks built on top of CUPTI that collect event data at a particular time may choose to use this type to store the collected event data.

uint32_t CUpti_ActivityInstantaneousEvent::deviceId

The device id

CUpti_EventID CUpti_ActivityInstantaneousEvent::id

The event ID.

CUpti_ActivityKind CUpti_ActivityInstantaneousEvent::kind

The activity record kind, must be CUPTI ACTIVITY KIND INSTANTANEOUS EVENT.

uint32_t CUpti_ActivityInstantaneousEvent::reserved

Undefined. reserved for internal use

uint64_t CUpti_ActivityInstantaneousEvent::timestamp

The timestamp at which event is sampled

uint64_t CUpti_ActivityInstantaneousEvent::value

The event value.

3.20. CUpti_ActivityInstantaneousEventInstance Struct Reference

The activity record for an instantaneous CUPTI event with event domain instance information.

This activity record represents the a CUPTI event value for a specific event domain instance (CUPTI_ACTIVITY_KIND_EVENT_INSTANCE) sampled at a particular instant. This activity record kind is not produced by the activity API but is included for completeness and ease-of-use. Profiler frameworks built on top of CUPTI that collect event data may choose to use this type to store the collected event data. This activity record should be used when event domain instance information needs to be associated with the event.

uint32_t

CUpti_ActivityInstantaneousEventInstance::deviceId

The device id

CUpti_EventID CUpti_ActivityInstantaneousEventInstance::id

The event ID.

uint8_t

CUpti_ActivityInstantaneousEventInstance::instance

The event domain instance

CUpti_ActivityKind CUpti_ActivityInstantaneousEventInstance::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_INSTANTANEOUS_EVENT_INSTANCE.

uint8_t CUpti_ActivityInstantaneousEventInstance::pad

Undefined. reserved for internal use

uint64_t

CUpti_ActivityInstantaneousEventInstance::timestamp

The timestamp at which event is sampled

uint64_t

CUpti_ActivityInstantaneousEventInstance::value

The event value.

3.21. CUpti_ActivityInstantaneousMetric Struct Reference

The activity record for an instantaneous CUPTI metric.

This activity record represents the collection of a CUPTI metric value (CUPTI_ACTIVITY_KIND_METRIC) at a particular instance. This activity record kind is not produced by the activity API but is included for completeness and ease-of-use. Profiler frameworks built on top of CUPTI that collect metric data may choose to use this type to store the collected metric data.

uint32_t CUpti_ActivityInstantaneousMetric::deviceId

The device id

uint8_t CUpti_ActivityInstantaneousMetric::flags

The properties of this metric.

See also:

CUpti_ActivityFlag

CUpti_MetricID CUpti_ActivityInstantaneousMetric::id

The metric ID.

CUpti_ActivityKind CUpti_ActivityInstantaneousMetric::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_INSTANTANEOUS_METRIC.

uint8_t CUpti_ActivityInstantaneousMetric::pad

Undefined. reserved for internal use

uint64_t CUpti_ActivityInstantaneousMetric::timestamp

The timestamp at which metric is sampled

CUpti_ActivityInstantaneousMetric::value

The metric value.

3.22. CUpti_ActivityInstantaneousMetricInstance Struct Reference

The instantaneous activity record for a CUPTI metric with instance information.

This activity record represents a CUPTI metric value for a specific metric domain instance (CUPTI_ACTIVITY_KIND_METRIC_INSTANCE) sampled at a particular time. This activity record kind is not produced by the activity API but is included for completeness and ease-of-use. Profiler frameworks built on top of CUPTI that collect metric data may choose to use this type to store the collected metric data. This activity record should be used when metric domain instance information needs to be associated with the metric.

uint32_t

CUpti_ActivityInstantaneousMetricInstance::deviceId

The device id

uint8_t

CUpti_ActivityInstantaneousMetricInstance::flags

The properties of this metric.

See also:

CUpti_ActivityFlag

CUpti_MetricID

CUpti_ActivityInstantaneousMetricInstance::id

The metric ID.

uint8_t

CUpti_ActivityInstantaneousMetricInstance::instance

The metric domain instance

CUpti_ActivityKind

CUpti_ActivityInstantaneousMetricInstance::kind

The activity record kind, must be

CUPTI_ACTIVITY_KIND_INSTANTANEOUS_METRIC_INSTANCE.

uint8_t CUpti_ActivityInstantaneousMetricInstance::pad

Undefined, reserved for internal use

uint64_t

CUpti_ActivityInstantaneousMetricInstance::timestamp

The timestamp at which metric is sampled

CUpti_ActivityInstantaneousMetricInstance::value

The metric value.

3.23. CUpti_ActivityInstructionCorrelation Struct Reference

The activity record for source-level sass/source line-by-line correlation.

This activity records source level sass/source correlation information. (CUPTI_ACTIVITY_KIND_INSTRUCTION_CORRELATION).

CUpti_ActivityFlag CUpti_ActivityInstructionCorrelation::flags

The properties of this instruction.

uint32_t CUpti_ActivityInstructionCorrelation::functionId

Correlation ID with global/device function name

CUpti_ActivityKind CUpti_ActivityInstructionCorrelation::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_INSTRUCTION_CORRELATION.

uint32_t CUpti_ActivityInstructionCorrelation::pad

Undefined. Reserved for internal use.

uint32_t CUpti_ActivityInstructionCorrelation::pcOffset

The pc offset for the instruction.

uint32_t

CUpti_ActivityInstructionCorrelation::sourceLocatorId

The ID for source locator.

3.24. CUpti_ActivityInstructionExecution Struct Reference

The activity record for source-level instruction execution.

This activity records result for source level instruction execution. (CUPTI_ACTIVITY_KIND_INSTRUCTION_EXECUTION).

uint32_t

CUpti_ActivityInstructionExecution::correlationId

The correlation ID of the kernel to which this result is associated.

uint32_t CUpti_ActivityInstructionExecution::executed

The number of times this instruction was executed.

CUpti_ActivityFlag CUpti_ActivityInstructionExecution::flags

The properties of this instruction execution.

uint32_t CUpti_ActivityInstructionExecution::functionId

Correlation ID with global/device function name

CUpti_ActivityKind CUpti_ActivityInstructionExecution::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_INSTRUCTION_EXECUTION.

uint64_t

CUpti_ActivityInstructionExecution::notPredOffThreadsExecuted

This increments each time when this instruction is executed by number of threads that executed this instruction with predicate and condition code evaluating to true.

uint32_t CUpti_ActivityInstructionExecution::pad

Undefined. Reserved for internal use.

uint32_t CUpti_ActivityInstructionExecution::pcOffset

The pc offset for the instruction.

uint32_t

CUpti_ActivityInstructionExecution::sourceLocatorId

The ID for source locator.

uint64_t

CUpti_ActivityInstructionExecution::threadsExecuted

This increments each time when this instruction is executed by number of threads that executed this instruction, regardless of predicate or condition code.

3.25. CUpti_ActivityKernel Struct Reference

The activity record for kernel. (deprecated).

This activity record represents a kernel execution (CUPTI_ACTIVITY_KIND_KERNEL and CUPTI_ACTIVITY_KIND_CONCURRENT_KERNEL) but is no longer generated by CUPTI. Kernel activities are now reported using the CUpti_ActivityKernel3 activity record.

int32_t CUpti_ActivityKernel::blockX

The X-dimension block size for the kernel.

int32_t CUpti_ActivityKernel::blockY

The Y-dimension block size for the kernel.

int32_t CUpti_ActivityKernel::blockZ

The Z-dimension grid size for the kernel.

uint8_t CUpti_ActivityKernel::cacheConfigExecuted

The cache configuration used for the kernel. The value is one of the CUfunc_cache enumeration values from cuda.h.

uint8_t CUpti_ActivityKernel::cacheConfigRequested

The cache configuration requested by the kernel. The value is one of the CUfunc_cache enumeration values from cuda.h.

uint32_t CUpti_ActivityKernel::contextId

The ID of the context where the kernel is executing.

uint32_t CUpti_ActivityKernel::correlationId

The correlation ID of the kernel. Each kernel execution is assigned a unique correlation ID that is identical to the correlation ID in the driver API activity record that launched the kernel.

uint32_t CUpti_ActivityKernel::deviceId

The ID of the device where the kernel is executing.

int32_t CUpti_ActivityKernel::dynamicSharedMemory

The dynamic shared memory reserved for the kernel, in bytes.

uint64_t CUpti_ActivityKernel::end

The end timestamp for the kernel execution, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the kernel.

int32_t CUpti_ActivityKernel::gridX

The X-dimension grid size for the kernel.

int32_t CUpti_ActivityKernel::gridY

The Y-dimension grid size for the kernel.

int32_t CUpti_ActivityKernel::gridZ

The Z-dimension grid size for the kernel.

CUpti_ActivityKind CUpti_ActivityKernel::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_KERNEL or CUPTI_ACTIVITY_KIND_CONCURRENT_KERNEL.

uint32_t CUpti_ActivityKernel::localMemoryPerThread

The amount of local memory reserved for each thread, in bytes.

uint32_t CUpti_ActivityKernel::localMemoryTotal

The total amount of local memory reserved for the kernel, in bytes.

const char *CUpti_ActivityKernel::name

The name of the kernel. This name is shared across all activity records representing the same kernel, and so should not be modified.

uint32_t CUpti_ActivityKernel::pad

Undefined. Reserved for internal use.

uint16_t CUpti_ActivityKernel::registersPerThread

The number of registers required for each thread executing the kernel.

void *CUpti_ActivityKernel::reserved0

Undefined. Reserved for internal use.

uint32_t CUpti_ActivityKernel::runtimeCorrelationId

The runtime correlation ID of the kernel. Each kernel execution is assigned a unique runtime correlation ID that is identical to the correlation ID in the runtime API activity record that launched the kernel.

uint64_t CUpti_ActivityKernel::start

The start timestamp for the kernel execution, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the kernel.

int32_t CUpti_ActivityKernel::staticSharedMemory

The static shared memory allocated for the kernel, in bytes.

uint32_t CUpti_ActivityKernel::streamId

The ID of the stream where the kernel is executing.

3.26. CUpti_ActivityKernel2 Struct Reference

The activity record for kernel. (deprecated).

This activity record represents a kernel execution (CUPTI_ACTIVITY_KIND_KERNEL and CUPTI_ACTIVITY_KIND_CONCURRENT_KERNEL) but is no longer generated by CUPTI. Kernel activities are now reported using the CUpti_ActivityKernel3 activity record.

int32_t CUpti_ActivityKernel2::blockX

The X-dimension block size for the kernel.

int32_t CUpti_ActivityKernel2::blockY

The Y-dimension block size for the kernel.

int32_t CUpti_ActivityKernel2::blockZ

The Z-dimension grid size for the kernel.

uint64_t CUpti_ActivityKernel2::completed

The completed timestamp for the kernel execution, in ns. It represents the completion of all it's child kernels and the kernel itself. A value of CUPTI_TIMESTAMP_UNKNOWN indicates that the completion time is unknown.

uint32_t CUpti_ActivityKernel2::contextId

The ID of the context where the kernel is executing.

uint32_t CUpti_ActivityKernel2::correlationId

The correlation ID of the kernel. Each kernel execution is assigned a unique correlation ID that is identical to the correlation ID in the driver or runtime API activity record that launched the kernel.

uint32_t CUpti_ActivityKernel2::deviceId

The ID of the device where the kernel is executing.

int32_t CUpti_ActivityKernel2::dynamicSharedMemory

The dynamic shared memory reserved for the kernel, in bytes.

uint64_t CUpti_ActivityKernel2::end

The end timestamp for the kernel execution, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the kernel.

uint8_t CUpti_ActivityKernel2::executed

The cache configuration used for the kernel. The value is one of the CUfunc_cache enumeration values from cuda.h.

int64_t CUpti_ActivityKernel2::gridId

The grid ID of the kernel. Each kernel is assigned a unique grid ID at runtime.

int32_t CUpti_ActivityKernel2::gridX

The X-dimension grid size for the kernel.

int32_t CUpti_ActivityKernel2::gridY

The Y-dimension grid size for the kernel.

int32_t CUpti_ActivityKernel2::gridZ

The Z-dimension grid size for the kernel.

CUpti_ActivityKind CUpti_ActivityKernel2::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_KERNEL or CUPTI_ACTIVITY_KIND_CONCURRENT_KERNEL.

uint32_t CUpti_ActivityKernel2::localMemoryPerThread

The amount of local memory reserved for each thread, in bytes.

uint32_t CUpti_ActivityKernel2::localMemoryTotal

The total amount of local memory reserved for the kernel, in bytes.

const char *CUpti_ActivityKernel2::name

The name of the kernel. This name is shared across all activity records representing the same kernel, and so should not be modified.

uint16_t CUpti_ActivityKernel2::registersPerThread

The number of registers required for each thread executing the kernel.

uint8_t CUpti_ActivityKernel2::requested

The cache configuration requested by the kernel. The value is one of the CUfunc_cache enumeration values from cuda.h.

void *CUpti_ActivityKernel2::reserved0

Undefined. Reserved for internal use.

uint8_t CUpti_ActivityKernel2::sharedMemoryConfig

The shared memory configuration used for the kernel. The value is one of the CUshared configuration values from cuda.h.

uint64_t CUpti_ActivityKernel2::start

The start timestamp for the kernel execution, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the kernel.

int32_t CUpti_ActivityKernel2::staticSharedMemory

The static shared memory allocated for the kernel, in bytes.

uint32_t CUpti_ActivityKernel2::streamId

The ID of the stream where the kernel is executing.

3.27. CUpti_ActivityKernel3 Struct Reference

The activity record for a kernel (CUDA 6.5(with sm_52 support) onwards).

This activity record represents a kernel execution (CUPTI_ACTIVITY_KIND_KERNEL and CUPTI_ACTIVITY_KIND_CONCURRENT_KERNEL).

int32_t CUpti_ActivityKernel3::blockX

The X-dimension block size for the kernel.

int32_t CUpti_ActivityKernel3::blockY

The Y-dimension block size for the kernel.

int32_t CUpti_ActivityKernel3::blockZ

The Z-dimension grid size for the kernel.

uint64_t CUpti_ActivityKernel3::completed

The completed timestamp for the kernel execution, in ns. It represents the completion of all it's child kernels and the kernel itself. A value of CUPTI_TIMESTAMP_UNKNOWN indicates that the completion time is unknown.

uint32_t CUpti_ActivityKernel3::contextId

The ID of the context where the kernel is executing.

uint32_t CUpti_ActivityKernel3::correlationId

The correlation ID of the kernel. Each kernel execution is assigned a unique correlation ID that is identical to the correlation ID in the driver or runtime API activity record that launched the kernel.

uint32_t CUpti_ActivityKernel3::deviceId

The ID of the device where the kernel is executing.

int32_t CUpti_ActivityKernel3::dynamicSharedMemory

The dynamic shared memory reserved for the kernel, in bytes.

uint64_t CUpti_ActivityKernel3::end

The end timestamp for the kernel execution, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the kernel.

uint8_t CUpti_ActivityKernel3::executed

The cache configuration used for the kernel. The value is one of the CUfunc_cache enumeration values from cuda.h.

int64_t CUpti_ActivityKernel3::gridId

The grid ID of the kernel. Each kernel is assigned a unique grid ID at runtime.

int32_t CUpti_ActivityKernel3::gridX

The X-dimension grid size for the kernel.

int32_t CUpti_ActivityKernel3::gridY

The Y-dimension grid size for the kernel.

int32_t CUpti_ActivityKernel3::gridZ

The Z-dimension grid size for the kernel.

CUpti_ActivityKind CUpti_ActivityKernel3::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_KERNEL or CUPTI_ACTIVITY_KIND_CONCURRENT_KERNEL.

uint32_t CUpti_ActivityKernel3::localMemoryPerThread

The amount of local memory reserved for each thread, in bytes.

uint32_t CUpti_ActivityKernel3::localMemoryTotal

The total amount of local memory reserved for the kernel, in bytes.

const char *CUpti_ActivityKernel3::name

The name of the kernel. This name is shared across all activity records representing the same kernel, and so should not be modified.

CUpti_ActivityPartitionedGlobalCacheConfig CUpti_ActivityKernel3::partitionedGlobalCacheExecuted

The partitioned global caching executed for the kernel. Partitioned global caching is required to enable caching on certain chips, such as devices with compute capability 5.2. Partitioned global caching can be automatically disabled if the occupancy requirement of the launch cannot support caching.

CUpti_ActivityPartitionedGlobalCacheConfig CUpti_ActivityKernel3::partitionedGlobalCacheRequested

The partitioned global caching requested for the kernel. Partitioned global caching is required to enable caching on certain chips, such as devices with compute capability 5.2.

uint16_t CUpti_ActivityKernel3::registersPerThread

The number of registers required for each thread executing the kernel.

uint8_t CUpti_ActivityKernel3::requested

The cache configuration requested by the kernel. The value is one of the CUfunc_cache enumeration values from cuda.h.

void *CUpti_ActivityKernel3::reserved0

Undefined. Reserved for internal use.

uint8_t CUpti_ActivityKernel3::sharedMemoryConfig

The shared memory configuration used for the kernel. The value is one of the CUshared configuration values from cuda.h.

uint64_t CUpti_ActivityKernel3::start

The start timestamp for the kernel execution, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the kernel.

int32_t CUpti_ActivityKernel3::staticSharedMemory

The static shared memory allocated for the kernel, in bytes.

uint32_t CUpti_ActivityKernel3::streamId

The ID of the stream where the kernel is executing.

3.28. CUpti_ActivityMarker Struct Reference

The activity record providing a marker which is an instantaneous point in time. (deprecated in CUDA 8.0).

The marker is specified with a descriptive name and unique id (CUPTI_ACTIVITY_KIND_MARKER). Marker activity is now reported using the CUpti_ActivityMarker2 activity record.

CUpti_ActivityFlag CUpti_ActivityMarker::flags

The flags associated with the marker.

See also:

CUpti_ActivityFlag

uint32_t CUpti_ActivityMarker::id

The marker ID.

CUpti_ActivityKind CUpti_ActivityMarker::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_MARKER.

const char *CUpti_ActivityMarker::name

The marker name for an instantaneous or start marker. This will be NULL for an end marker.

CUpti_ActivityMarker::objectId

The identifier for the activity object associated with this marker. 'objectKind' indicates which ID is valid for this record.

CUpti_ActivityObjectKind CUpti_ActivityMarker::objectKind

The kind of activity object associated with this marker.

uint64_t CUpti_ActivityMarker::timestamp

The timestamp for the marker, in ns. A value of 0 indicates that timestamp information could not be collected for the marker.

3.29. CUpti_ActivityMarker2 Struct Reference

The activity record providing a marker which is an instantaneous point in time.

The marker is specified with a descriptive name and unique id (CUPTI_ACTIVITY_KIND_MARKER).

const char *CUpti_ActivityMarker2::domain

The name of the domain to which this marker belongs to. This will be NULL for default domain.

CUpti_ActivityFlag CUpti_ActivityMarker2::flags

The flags associated with the marker.

See also:

CUpti_ActivityFlag

uint32_t CUpti_ActivityMarker2::id

The marker ID.

CUpti_ActivityKind CUpti_ActivityMarker2::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_MARKER.

const char *CUpti_ActivityMarker2::name

The marker name for an instantaneous or start marker. This will be NULL for an end marker.

CUpti_ActivityMarker2::objectId

The identifier for the activity object associated with this marker. 'objectKind' indicates which ID is valid for this record.

CUpti_ActivityObjectKind CUpti_ActivityMarker2::objectKind

The kind of activity object associated with this marker.

uint32_t CUpti_ActivityMarker2::pad

Undefined. Reserved for internal use.

uint64_t CUpti_ActivityMarker2::timestamp

The timestamp for the marker, in ns. A value of 0 indicates that timestamp information could not be collected for the marker.

3.30. CUpti_ActivityMarkerData Struct Reference

The activity record providing detailed information for a marker.

The marker data contains color, payload, and category. (CUPTI_ACTIVITY_KIND_MARKER_DATA).

uint32_t CUpti_ActivityMarkerData::category

The category for the marker.

uint32_t CUpti_ActivityMarkerData::color

The color for the marker.

CUpti_ActivityFlag CUpti_ActivityMarkerData::flags

The flags associated with the marker.

See also:

CUpti_ActivityFlag

uint32_t CUpti_ActivityMarkerData::id

The marker ID.

CUpti_ActivityKind CUpti_ActivityMarkerData::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_MARKER_DATA.

CUpti_ActivityMarkerData::payload

The payload value.

CUpti_MetricValueKind CUpti_ActivityMarkerData::payloadKind

Defines the payload format for the value associated with the marker.

3.31. CUpti_ActivityMemcpy Struct Reference

The activity record for memory copies.

This activity record represents a memory copy (CUPTI_ACTIVITY_KIND_MEMCPY).

uint64_t CUpti_ActivityMemcpy::bytes

The number of bytes transferred by the memory copy.

uint32_t CUpti_ActivityMemcpy::contextId

The ID of the context where the memory copy is occurring.

uint8_t CUpti_ActivityMemcpy::copyKind

The kind of the memory copy, stored as a byte to reduce record size.

See also:

CUpti_ActivityMemcpyKind

uint32_t CUpti_ActivityMemcpy::correlationId

The correlation ID of the memory copy. Each memory copy is assigned a unique correlation ID that is identical to the correlation ID in the driver API activity record that launched the memory copy.

uint32_t CUpti_ActivityMemcpy::deviceId

The ID of the device where the memory copy is occurring.

uint8_t CUpti_ActivityMemcpy::dstKind

The destination memory kind read by the memory copy, stored as a byte to reduce record size.

See also:

CUpti_ActivityMemoryKind

uint64_t CUpti_ActivityMemcpy::end

The end timestamp for the memory copy, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the memory copy.

uint8_t CUpti_ActivityMemcpy::flags

The flags associated with the memory copy.

See also:

CUpti_ActivityFlag

CUpti_ActivityKind CUpti_ActivityMemcpy::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_MEMCPY.

void *CUpti_ActivityMemcpy::reserved0

Undefined. Reserved for internal use.

uint32_t CUpti_ActivityMemcpy::runtimeCorrelationId

The runtime correlation ID of the memory copy. Each memory copy is assigned a unique runtime correlation ID that is identical to the correlation ID in the runtime API activity record that launched the memory copy.

uint8_t CUpti_ActivityMemcpy::srcKind

The source memory kind read by the memory copy, stored as a byte to reduce record size.

See also:

CUpti_ActivityMemoryKind

uint64_t CUpti_ActivityMemcpy::start

The start timestamp for the memory copy, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the memory copy.

uint32_t CUpti_ActivityMemcpy::streamId

The ID of the stream where the memory copy is occurring.

3.32. CUpti_ActivityMemcpy2 Struct Reference

The activity record for peer-to-peer memory copies.

This activity record represents a peer-to-peer memory copy (CUPTI_ACTIVITY_KIND_MEMCPY2).

uint64_t CUpti_ActivityMemcpy2::bytes

The number of bytes transferred by the memory copy.

uint32_t CUpti_ActivityMemcpy2::contextId

The ID of the context where the memory copy is occurring.

uint8_t CUpti_ActivityMemcpy2::copyKind

The kind of the memory copy, stored as a byte to reduce record size.

See also:

CUpti_ActivityMemcpyKind

uint32_t CUpti_ActivityMemcpy2::correlationId

The correlation ID of the memory copy. Each memory copy is assigned a unique correlation ID that is identical to the correlation ID in the driver and runtime API activity record that launched the memory copy.

uint32_t CUpti_ActivityMemcpy2::deviceId

The ID of the device where the memory copy is occurring.

uint32_t CUpti_ActivityMemcpy2::dstContextId

The ID of the context owning the memory being copied to.

uint32_t CUpti_ActivityMemcpy2::dstDeviceId

The ID of the device where memory is being copied to.

uint8_t CUpti_ActivityMemcpy2::dstKind

The destination memory kind read by the memory copy, stored as a byte to reduce record size.

See also:

CUpti_ActivityMemoryKind

uint64_t CUpti_ActivityMemcpy2::end

The end timestamp for the memory copy, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the memory copy.

uint8_t CUpti_ActivityMemcpy2::flags

The flags associated with the memory copy.

See also:

CUpti_ActivityFlag

CUpti_ActivityKind CUpti_ActivityMemcpy2::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_MEMCPY2.

uint32_t CUpti_ActivityMemcpy2::pad

Undefined. Reserved for internal use.

void *CUpti_ActivityMemcpy2::reserved0

Undefined. Reserved for internal use.

uint32_t CUpti_ActivityMemcpy2::srcContextId

The ID of the context owning the memory being copied from.

uint32_t CUpti_ActivityMemcpy2::srcDeviceId

The ID of the device where memory is being copied from.

uint8_t CUpti_ActivityMemcpy2::srcKind

The source memory kind read by the memory copy, stored as a byte to reduce record size.

See also:

CUpti_ActivityMemoryKind

uint64_t CUpti_ActivityMemcpy2::start

The start timestamp for the memory copy, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the memory copy.

uint32_t CUpti_ActivityMemcpy2::streamId

The ID of the stream where the memory copy is occurring.

3.33. CUpti_ActivityMemset Struct Reference

The activity record for memset.

This activity record represents a memory set operation (CUPTI_ACTIVITY_KIND_MEMSET).

uint64_t CUpti_ActivityMemset::bytes

The number of bytes being set by the memory set.

uint32_t CUpti_ActivityMemset::contextId

The ID of the context where the memory set is occurring.

uint32_t CUpti_ActivityMemset::correlationId

The correlation ID of the memory set. Each memory set is assigned a unique correlation ID that is identical to the correlation ID in the driver API activity record that launched the memory set.

uint32_t CUpti_ActivityMemset::deviceId

The ID of the device where the memory set is occurring.

uint64_t CUpti_ActivityMemset::end

The end timestamp for the memory set, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the memory set.

uint16_t CUpti_ActivityMemset::flags

The flags associated with the memset.

See also:

CUpti_ActivityFlag

CUpti_ActivityKind CUpti_ActivityMemset::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_MEMSET.

uint16_t CUpti_ActivityMemset::memoryKind

The memory kind of the memory set

See also:

CUpti_ActivityMemoryKind

void *CUpti_ActivityMemset::reserved0

Undefined. Reserved for internal use.

uint64_t CUpti_ActivityMemset::start

The start timestamp for the memory set, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the memory set.

uint32_t CUpti_ActivityMemset::streamId

The ID of the stream where the memory set is occurring.

uint32_t CUpti_ActivityMemset::value

The value being assigned to memory by the memory set.

3.34. CUpti_ActivityMetric Struct Reference

The activity record for a CUPTI metric.

This activity record represents the collection of a CUPTI metric value (CUPTI_ACTIVITY_KIND_METRIC). This activity record kind is not produced by the activity API but is included for completeness and ease-of-use. Profile frameworks built on top of CUPTI that collect metric data may choose to use this type to store the collected metric data.

uint32_t CUpti_ActivityMetric::correlationId

The correlation ID of the metric. Use of this ID is user-defined, but typically this ID value will equal the correlation ID of the kernel for which the metric was gathered.

uint8_t CUpti_ActivityMetric::flags

The properties of this metric.

See also:

CUpti_ActivityFlag

CUpti_MetricID CUpti_ActivityMetric::id

The metric ID.

CUpti_ActivityKind CUpti_ActivityMetric::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_METRIC.

uint8_t CUpti_ActivityMetric::pad

Undefined. Reserved for internal use.

CUpti_ActivityMetric::value

The metric value.

3.35. CUpti_ActivityMetricInstance Struct Reference

The activity record for a CUPTI metric with instance information.

This activity record represents a CUPTI metric value for a specific metric domain instance (CUPTI_ACTIVITY_KIND_METRIC_INSTANCE). This activity record kind is not produced by the activity API but is included for completeness and ease-of-use. Profile frameworks built on top of CUPTI that collect metric data may choose to use this type to store the collected metric data. This activity record should be used when metric domain instance information needs to be associated with the metric.

uint32_t CUpti_ActivityMetricInstance::correlationId

The correlation ID of the metric. Use of this ID is user-defined, but typically this ID value will equal the correlation ID of the kernel for which the metric was gathered.

uint8_t CUpti_ActivityMetricInstance::flags

The properties of this metric.

See also:

CUpti_ActivityFlag

CUpti_MetricID CUpti_ActivityMetricInstance::id

The metric ID.

uint32_t CUpti_ActivityMetricInstance::instance

The metric domain instance.

CUpti_ActivityKind CUpti_ActivityMetricInstance::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_METRIC_INSTANCE.

uint8_t CUpti_ActivityMetricInstance::pad

Undefined. Reserved for internal use.

CUpti_ActivityMetricInstance::value

The metric value.

3.36. CUpti_ActivityModule Struct Reference

The activity record for a CUDA module.

This activity record represents a CUDA module (CUPTI_ACTIVITY_KIND_MODULE). This activity record kind is not produced by the activity API but is included for completeness and ease-of-use. Profile frameworks built on top of CUPTI that collect module data from the module callback may choose to use this type to store the collected module data.

uint32_t CUpti_ActivityModule::contextId

The ID of the context where the module is loaded.

const void *CUpti_ActivityModule::cubin

The pointer to cubin.

uint32_t CUpti_ActivityModule::cubinSize

The cubin size.

uint32_t CUpti_ActivityModule::id

The module ID.

CUpti_ActivityKind CUpti_ActivityModule::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_MODULE.

uint32_t CUpti_ActivityModule::pad

Undefined. Reserved for internal use.

3.37. CUpti_ActivityName Struct Reference

The activity record providing a name.

This activity record provides a name for a device, context, thread, etc. (CUPTI_ACTIVITY_KIND_NAME).

CUpti_ActivityKind CUpti_ActivityName::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_NAME.

const char *CUpti_ActivityName::name

The name.

CUpti_ActivityName::objectId

The identifier for the activity object. 'objectKind' indicates which ID is valid for this record.

CUpti_ActivityObjectKind CUpti_ActivityName::objectKind

The kind of activity object being named.

3.38. CUpti_ActivityNvLink Struct Reference

NvLink information.

This structure gives capabilities of each logical nvlink connection between two devices, gpu<->gpu or gpu<->CPU which can be used to understand the topology.

uint64_t CUpti_ActivityNvLink::bandwidth

Banwidth of NvLink in kbytes/sec

uint32_t CUpti_ActivityNvLink::domainId

Domain ID of NPU. On Linux, this can be queried using lspci.

uint32_t CUpti_ActivityNvLink::flag

Flag gives capabilities of the link

See also:

CUpti_LinkFlag

CUpti_ActivityNvLink::@15 CUpti_ActivityNvLink::idDev0

If typeDev0 is CUPTI_DEV_TYPE_GPU, UUID for device 0. CUpti_ActivityDevice2. If typeDev0 is CUPTI_DEV_TYPE_NPU, struct npu for NPU.

CUpti_ActivityNvLink::@16 CUpti_ActivityNvLink::idDev1

If typeDev1 is CUPTI_DEV_TYPE_GPU, UUID for device 1. CUpti_ActivityDevice2. If typeDev1 is CUPTI_DEV_TYPE_NPU, struct npu for NPU.

uint32_t CUpti_ActivityNvLink::index

Index of the NPU. First index will always be zero.

CUpti_ActivityKind CUpti_ActivityNvLink::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_NVLINK.

uint32_t CUpti_ActivityNvLink::nvlinkVersion

NvLink version.

uint32_t CUpti_ActivityNvLink::physicalNvLinkCount

Number of physical nvlinks present between two devices.

int8_t CUpti_ActivityNvLink::portDev0

Port numbers for maximum 4 nvlinks connected to device 0. If typeDev0 is CUPTI_DEV_TYPE_NPU, ignore this field. In case of invalid/unknown port number, this field will be set to value CUPTI_NVLINK_INVALID_PORT. This will be used to correlate the metric values to individual physical link and attribute traffic to the logical nvlink in the topology.

int8_t CUpti_ActivityNvLink::portDev1

Port numbers for maximum 4 nvlinks connected to device 1. If typeDev1 is CUPTI_DEV_TYPE_NPU, ignore this field. In case of invalid/unknown port number, this field will be set to value CUPTI_NVLINK_INVALID_PORT. This will be used to correlate the metric values to individual physical link and attribute traffic to the logical nvlink in the topology.

CUpti_DevType CUpti_ActivityNvLink::typeDev0

Type of device 0 CUpti_DevType

CUpti_DevType CUpti_ActivityNvLink::typeDev1

Type of device 1 CUpti_DevType

3.39. CUpti_ActivityObjectKindId Union Reference

Identifiers for object kinds as specified by CUpti_ActivityObjectKind.

See also:

CUpti_ActivityObjectKind

CUpti_ActivityObjectKindId::@1 CUpti_ActivityObjectKindId::dcs

A device object requires that we identify the device ID. A context object requires that we identify both the device and context ID. A stream object requires that we identify device, context, and stream ID.

CUpti_ActivityObjectKindId::@0 CUpti_ActivityObjectKindId::pt

A process object requires that we identify the process ID. A thread object requires that we identify both the process and thread ID.

3.40. CUpti_ActivityOpenAcc Struct Reference

The base activity record for OpenAcc records.

The OpenACC activity API part uses a CUpti_ActivityOpenAcc as a generic representation for any OpenACC activity. The 'kind' field is used to determine the

specific activity kind, and from that the CUpti_ActivityOpenAcc object can be cast to the specific OpenACC activity record type appropriate for that kind.

Note that all OpenACC activity record types are padded and aligned to ensure that each member of the record is naturally aligned.

See also:

CUpti_ActivityKind

uint32_t CUpti_ActivityOpenAcc::cuContextId

CUDA context id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAcc::cuDeviceId

CUDA device id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAcc::cuProcessId

The ID of the process where the OpenACC activity is executing.

uint32_t CUpti_ActivityOpenAcc::cuStreamId

CUDA stream id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAcc::cuThreadId

The ID of the thread where the OpenACC activity is executing.

uint64_t CUpti_ActivityOpenAcc::end

CUPTI end timestamp

CUpti_OpenAccEventKind CUpti_ActivityOpenAcc::eventKind

CUPTI OpenACC event kind (

See also:

CUpti_OpenAccEventKind)

uint32_t CUpti_ActivityOpenAcc::externalId

The OpenACC correlation ID. Valid only if deviceType is acc_device_nvidia. If not 0, it uniquely identifies this record. It is identical to the externalId in the preceding external correlation record of type CUPTI_EXTERNAL_CORRELATION_KIND_OPENACC.

CUpti_ActivityKind CUpti_ActivityOpenAcc::kind

The kind of this activity.

CUpti_OpenAccConstructKind CUpti_ActivityOpenAcc::parentConstruct

CUPTI OpenACC parent construct kind (

See also:

CUpti_OpenAccConstructKind)

Note that for applications using PGI OpenACC runtime < 16.1, this will always be CUPTI_OPENACC_CONSTRUCT_KIND_UNKNOWN.

uint64_t CUpti_ActivityOpenAcc::start

CUPTI start timestamp

uint32_t CUpti_ActivityOpenAcc::threadId

ThreadId

3.41. CUpti_ActivityOpenAccData Struct Reference

The activity record for OpenACC data.

(CUPTI_ACTIVITY_KIND_OPENACC_DATA).

uint64_t CUpti_ActivityOpenAccData::bytes

Number of bytes

uint32_t CUpti_ActivityOpenAccData::cuContextId

CUDA context id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAccData::cuDeviceId

CUDA device id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAccData::cuProcessId

The ID of the process where the OpenACC activity is executing.

uint32_t CUpti_ActivityOpenAccData::cuStreamId

CUDA stream id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAccData::cuThreadId

The ID of the thread where the OpenACC activity is executing.

uint64_t CUpti_ActivityOpenAccData::devicePtr

Device pointer if available

uint64_t CUpti_ActivityOpenAccData::end

CUPTI end timestamp

CUpti_OpenAccEventKind CUpti_ActivityOpenAccData::eventKind

CUPTI OpenACC event kind (

See also:

CUpti_OpenAccEventKind)

uint32_t CUpti_ActivityOpenAccData::externalId

The OpenACC correlation ID. Valid only if deviceType is acc_device_nvidia. If not 0, it uniquely identifies this record. It is identical to the externalId in the preceding external correlation record of type CUPTI_EXTERNAL_CORRELATION_KIND_OPENACC.

uint64_t CUpti_ActivityOpenAccData::hostPtr

Host pointer if available

CUpti_ActivityKind CUpti_ActivityOpenAccData::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_OPENACC_DATA.

uint32_t CUpti_ActivityOpenAccData::pad1

Undefined. Reserved for internal use.

uint64_t CUpti_ActivityOpenAccData::start

CUPTI start timestamp

uint32_t CUpti_ActivityOpenAccData::threadId

ThreadId

3.42. CUpti_ActivityOpenAccLaunch Struct Reference

The activity record for OpenACC launch.

(CUPTI_ACTIVITY_KIND_OPENACC_LAUNCH).

uint32_t CUpti_ActivityOpenAccLaunch::cuContextId

CUDA context id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAccLaunch::cuDeviceId

CUDA device id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAccLaunch::cuProcessId

The ID of the process where the OpenACC activity is executing.

uint32_t CUpti_ActivityOpenAccLaunch::cuStreamId

CUDA stream id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAccLaunch::cuThreadId

The ID of the thread where the OpenACC activity is executing.

uint64_t CUpti_ActivityOpenAccLaunch::end

CUPTI end timestamp

CUpti_OpenAccEventKind CUpti_ActivityOpenAccLaunch::eventKind

CUPTI OpenACC event kind (

See also:

CUpti_OpenAccEventKind)

uint32_t CUpti_ActivityOpenAccLaunch::externalId

The OpenACC correlation ID. Valid only if deviceType is acc_device_nvidia. If not 0, it uniquely identifies this record. It is identical to the externalId in the preceding external correlation record of type CUPTI_EXTERNAL_CORRELATION_KIND_OPENACC.

CUpti_ActivityKind CUpti_ActivityOpenAccLaunch::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_OPENACC_LAUNCH.

uint64_t CUpti_ActivityOpenAccLaunch::numGangs

The number of gangs created for this kernel launch

uint64_t CUpti_ActivityOpenAccLaunch::numWorkers

The number of workers created for this kernel launch

uint32_t CUpti_ActivityOpenAccLaunch::pad1

Undefined. Reserved for internal use.

uint64_t CUpti_ActivityOpenAccLaunch::start

CUPTI start timestamp

uint32_t CUpti_ActivityOpenAccLaunch::threadId

ThreadId

uint64_t CUpti_ActivityOpenAccLaunch::vectorLength

The number of vector lanes created for this kernel launch

3.43. CUpti_ActivityOpenAccOther Struct Reference

The activity record for OpenACC other.

(CUPTI_ACTIVITY_KIND_OPENACC_OTHER).

uint32_t CUpti_ActivityOpenAccOther::cuContextId

CUDA context id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAccOther::cuDeviceId

CUDA device id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAccOther::cuProcessId

The ID of the process where the OpenACC activity is executing.

uint32_t CUpti_ActivityOpenAccOther::cuStreamId

CUDA stream id Valid only if deviceType is acc_device_nvidia.

uint32_t CUpti_ActivityOpenAccOther::cuThreadId

The ID of the thread where the OpenACC activity is executing.

uint64_t CUpti_ActivityOpenAccOther::end

CUPTI end timestamp

CUpti_OpenAccEventKind
CUpti_ActivityOpenAccOther::eventKind

CUPTI OpenACC event kind (

See also:

CUpti_OpenAccEventKind)

uint32_t CUpti_ActivityOpenAccOther::externalId

The OpenACC correlation ID. Valid only if deviceType is acc_device_nvidia. If not 0, it uniquely identifies this record. It is identical to the externalId in the preceding external correlation record of type CUPTI_EXTERNAL_CORRELATION_KIND_OPENACC.

CUpti_ActivityKind CUpti_ActivityOpenAccOther::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_OPENACC_OTHER.

uint64_t CUpti_ActivityOpenAccOther::start

CUPTI start timestamp

uint32_t CUpti_ActivityOpenAccOther::threadId

ThreadId

3.44. CUpti_ActivityOverhead Struct Reference

The activity record for CUPTI and driver overheads.

This activity record provides CUPTI and driver overhead information (CUPTI_ACTIVITY_OVERHEAD).

uint64_t CUpti_ActivityOverhead::end

The end timestamp for the overhead, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the overhead.

CUpti_ActivityKind CUpti_ActivityOverhead::kind

The activity record kind, must be CUPTI_ACTIVITY_OVERHEAD.

CUpti_ActivityOverhead::objectId

The identifier for the activity object. 'objectKind' indicates which ID is valid for this record.

CUpti_ActivityObjectKind CUpti_ActivityOverhead::objectKind

The kind of activity object that the overhead is associated with.

CUpti_ActivityOverheadKind CUpti_ActivityOverhead::overheadKind

The kind of overhead, CUPTI, DRIVER, COMPILER etc.

uint64_t CUpti_ActivityOverhead::start

The start timestamp for the overhead, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the overhead.

3.45. CUpti_ActivityPCSampling Struct Reference

The activity record for PC sampling. (deprecated in CUDA 8.0).

This activity records information obtained by sampling PC (CUPTI_ACTIVITY_KIND_PC_SAMPLING). PC sampling activities are now reported using the CUpti_ActivityPCSampling2 activity record.

uint32_t CUpti_ActivityPCSampling::correlationId

The correlation ID of the kernel to which this result is associated.

CUpti_ActivityFlag CUpti_ActivityPCSampling::flags

The properties of this instruction.

uint32_t CUpti_ActivityPCSampling::functionId

Correlation ID with global/device function name

CUpti_ActivityKind CUpti_ActivityPCSampling::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_PC_SAMPLING.

uint32_t CUpti_ActivityPCSampling::pcOffset

The pc offset for the instruction.

uint32_t CUpti_ActivityPCSampling::samples

Number of times the PC was sampled with the stallReason in the record. The same PC can be sampled with different stall reasons.

uint32_t CUpti_ActivityPCSampling::sourceLocatorId

The ID for source locator.

CUpti_ActivityPCSamplingStallReason CUpti_ActivityPCSampling::stallReason

Current stall reason. Includes one of the reasons from CUpti_ActivityPCSamplingStallReason

3.46. CUpti_ActivityPCSampling2 Struct Reference

The activity record for PC sampling.

This activity records information obtained by sampling PC (CUPTI_ACTIVITY_KIND_PC_SAMPLING).

uint32_t CUpti_ActivityPCSampling2::correlationId

The correlation ID of the kernel to which this result is associated.

CUpti_ActivityFlag CUpti_ActivityPCSampling2::flags

The properties of this instruction.

uint32_t CUpti_ActivityPCSampling2::functionId

Correlation ID with global/device function name

CUpti_ActivityKind CUpti_ActivityPCSampling2::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_PC_SAMPLING.

uint32_t CUpti_ActivityPCSampling2::latencySamples

Number of times the PC was sampled with the stallReason in the record. These samples indicate that no instruction was issued in that cycle from the warp scheduler from where the warp was sampled. Field is valid for devices with compute capability 6.0 and higher

uint32_t CUpti_ActivityPCSampling2::pcOffset

The pc offset for the instruction.

uint32_t CUpti_ActivityPCSampling2::samples

Number of times the PC was sampled with the stallReason in the record. The same PC can be sampled with different stall reasons. The count includes latencySamples.

uint32_t CUpti_ActivityPCSampling2::sourceLocatorId

The ID for source locator.

CUpti_ActivityPCSamplingStallReason CUpti_ActivityPCSampling2::stallReason

Current stall reason. Includes one of the reasons from CUpti_ActivityPCSamplingStallReason

3.47. CUpti_ActivityPCSamplingConfig Struct Reference

PC sampling configuration structure.

This structure defines the pc sampling configuration.

See function /ref cuptiActivityConfigurePCSampling

CUpti_ActivityPCSamplingPeriod CUpti_ActivityPCSamplingConfig::samplingPeriod

There are 5 level provided for sampling period. The level internally maps to a period in terms of cycles. Same level can map to different number of cycles on different gpus. No of cycles will be chosen to minimize information loss. The period chosen will be given by samplingPeriodInCycles in /ref CUpti_ActivityPCSamplingRecordInfo for each kernel instance.

uint32_t CUpti_ActivityPCSamplingConfig::size

Size of configuration structure. Should be used to check if required parameters are available in the structure.

3.48. CUpti_ActivityPCSamplingRecordInfo Struct Reference

The activity record for record status for PC sampling.

This activity records information obtained by sampling PC (CUPTI_ACTIVITY_KIND_PC_SAMPLING_RECORD_INFO).

uint32_t

CUpti_ActivityPCSamplingRecordInfo::correlationId

The correlation ID of the kernel to which this result is associated.

uint64_t

CUpti_ActivityPCSamplingRecordInfo::droppedSamples

Number of samples that were dropped by hardware due to backpressure/overflow.

CUpti_ActivityKind CUpti_ActivityPCSamplingRecordInfo::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_PC_SAMPLING_RECORD_INFO.

uint64 t

CUpti_ActivityPCSamplingRecordInfo::samplingPeriodInCycles

Sampling period in terms of number of cycles.

uint64_t

CUpti_ActivityPCSamplingRecordInfo::totalSamples

Number of times the PC was sampled for this kernel instance including all dropped samples.

3.49. CUpti_ActivityPreemption Struct Reference

The activity record for a preemption of a CDP kernel.

This activity record represents a preemption of a CDP kernel.

uint32_t CUpti_ActivityPreemption::blockX

The X-dimension of the block that is preempted

uint32_t CUpti_ActivityPreemption::blockY

The Y-dimension of the block that is preempted

uint32_t CUpti_ActivityPreemption::blockZ

The Z-dimension of the block that is preempted

int64_t CUpti_ActivityPreemption::gridId

The grid-id of the block that is preempted

CUpti_ActivityKind CUpti_ActivityPreemption::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_PREEMPTION

uint32_t CUpti_ActivityPreemption::pad

Undefined. Reserved for internal use.

CUpti_ActivityPreemptionKind CUpti_ActivityPreemption::preemptionKind

kind of the preemption

uint64_t CUpti_ActivityPreemption::timestamp

The timestamp of the preemption, in ns. A value of 0 indicates that timestamp information could not be collected for the preemption.

3.50. CUpti_ActivitySharedAccess Struct Reference

The activity record for source-level shared access.

This activity records the locations of the shared accesses in the source (CUPTI_ACTIVITY_KIND_SHARED_ACCESS).

uint32_t CUpti_ActivitySharedAccess::correlationId

The correlation ID of the kernel to which this result is associated.

uint32_t CUpti_ActivitySharedAccess::executed

The number of times this instruction was executed

CUpti_ActivityFlag CUpti_ActivitySharedAccess::flags

The properties of this shared access.

uint32_t CUpti_ActivitySharedAccess::functionId

Correlation ID with global/device function name

CUpti_ActivityKind CUpti_ActivitySharedAccess::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_SHARED_ACCESS.

uint32_t CUpti_ActivitySharedAccess::pad

Undefined. Reserved for internal use.

uint32_t CUpti_ActivitySharedAccess::pcOffset

The pc offset for the access.

uint64 t

CUpti_ActivitySharedAccess::sharedTransactions

The total number of shared memory transactions generated by this access

uint32_t CUpti_ActivitySharedAccess::sourceLocatorId

The ID for source locator.

uint64_t

CUpti_ActivitySharedAccess::theoreticalSharedTransactions

The minimum number of shared memory transactions possible based on the access pattern.

uint64_t CUpti_ActivitySharedAccess::threadsExecuted

This increments each time when this instruction is executed by number of threads that executed this instruction with predicate and condition code evaluating to true.

3.51. CUpti_ActivitySourceLocator Struct Reference

The activity record for source locator.

This activity record represents a source locator (CUPTI_ACTIVITY_KIND_SOURCE_LOCATOR).

const char *CUpti_ActivitySourceLocator::fileName

The path for the file.

uint32_t CUpti_ActivitySourceLocator::id

The ID for the source path, will be used in all the source level results.

CUpti_ActivityKind CUpti_ActivitySourceLocator::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_SOURCE_LOCATOR.

uint32_t CUpti_ActivitySourceLocator::lineNumber

The line number in the source.

3.52. CUpti_ActivityStream Struct Reference

The activity record for CUDA stream.

This activity is used to track created streams. (CUPTI_ACTIVITY_KIND_STREAM).

uint32_t CUpti_ActivityStream::contextId

The ID of the context where the stream was created.

CUpti_ActivityStreamFlag CUpti_ActivityStream::flag

Flags associated with the stream.

CUpti_ActivityKind CUpti_ActivityStream::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_STREAM.

uint32_t CUpti_ActivityStream::pad

Undefined. Reserved for internal use.

uint32_t CUpti_ActivityStream::priority

The clamped priority for the stream.

uint32_t CUpti_ActivityStream::streamId

A unique stream ID to identify the stream.

3.53. CUpti_ActivitySynchronization Struct Reference

The activity record for synchronization management.

This activity is used to track various CUDA synchronization APIs. (CUPTI_ACTIVITY_KIND_SYNCHRONIZATION).

uint32_t CUpti_ActivitySynchronization::contextId

The ID of the context for which the synchronization API is called. In case of context synchronization API it is the context id for which the API is called. In case of stream/ event synchronization it is the ID of the context where the stream/event was created.

uint32_t CUpti_ActivitySynchronization::correlationId

The correlation ID of the API to which this result is associated.

uint32_t CUpti_ActivitySynchronization::cudaEventId

The event ID for which the synchronization API is called. A CUPTI_SYNCHRONIZATION_INVALID_VALUE value indicate the field is not applicable for this record. Not valid for cuCtxSynchronize, cuStreamSynchronize.

uint64_t CUpti_ActivitySynchronization::end

The end timestamp for the function, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the function.

CUpti_ActivityKind CUpti_ActivitySynchronization::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_SYNCHRONIZATION.

uint64_t CUpti_ActivitySynchronization::start

The start timestamp for the function, in ns. A value of 0 for both the start and end timestamps indicates that timestamp information could not be collected for the function.

uint32_t CUpti_ActivitySynchronization::streamId

The compute stream for which the synchronization API is called. A CUPTI_SYNCHRONIZATION_INVALID_VALUE value indicate the field is not applicable for this record. Not valid for cuCtxSynchronize, cuEventSynchronize.

CUpti_ActivitySynchronizationType CUpti_ActivitySynchronization::type

The type of record.

3.54. CUpti_ActivityUnifiedMemoryCounter Struct Reference

The activity record for Unified Memory counters (deprecated in CUDA 7.0).

This activity record represents a Unified Memory counter (CUPTI_ACTIVITY_KIND_UNIFIED_MEMORY_COUNTER).

CUpti_ActivityUnifiedMemoryCounterKind CUpti_ActivityUnifiedMemoryCounter::counterKind

The Unified Memory counter kind. See /ref CUpti ActivityUnifiedMemoryCounterKind

uint32_t CUpti_ActivityUnifiedMemoryCounter::deviceId

The ID of the device involved in the memory transfer operation. It is not relevant if the scope of the counter is global (all devices).

CUpti_ActivityKind CUpti_ActivityUnifiedMemoryCounter::kind

The activity record kind, must be CUPTI ACTIVITY KIND UNIFIED MEMORY COUNTER

uint32_t CUpti_ActivityUnifiedMemoryCounter::pad

Undefined. Reserved for internal use.

uint32_t CUpti_ActivityUnifiedMemoryCounter::processId

The ID of the process to which this record belongs to. In case of global scope, processId is undefined.

CUpti_ActivityUnifiedMemoryCounterScope CUpti_ActivityUnifiedMemoryCounter::scope

Scope of the Unified Memory counter. See /ref CUpti_ActivityUnifiedMemoryCounterScope

uint64_t CUpti_ActivityUnifiedMemoryCounter::timestamp

The timestamp when this sample was retrieved, in ns. A value of 0 indicates that timestamp information could not be collected

uint64_t CUpti_ActivityUnifiedMemoryCounter::value

Value of the counter

3.55. CUpti_ActivityUnifiedMemoryCounter2 Struct Reference

The activity record for Unified Memory counters (CUDA 7.0 and beyond).

This activity record represents a Unified Memory counter (CUPTI_ACTIVITY_KIND_UNIFIED_MEMORY_COUNTER).

uint64_t CUpti_ActivityUnifiedMemoryCounter2::address

This is the virtual base address of the page/s being transferred. For cpu and gpu faults, the virtual address for the page that faulted.

CUpti_ActivityUnifiedMemoryCounterKind CUpti_ActivityUnifiedMemoryCounter2::counterKind

The Unified Memory counter kind

uint32_t CUpti_ActivityUnifiedMemoryCounter2::dstld

The ID of the destination CPU/device involved in the memory transfer operation. Ignore this field if counterKind is CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_GPU_PAGE_FAULT or CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_CPU_PAGE_FAULT_COUNT

uint64_t CUpti_ActivityUnifiedMemoryCounter2::end

The end timestamp of the counter, in ns. Ignore this field if counterKind is CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_CPU_PAGE_FAULT_COUNT. For counterKind

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_BYTES_TRANSFER_HTOD and

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_BYTES_TRANSFER_DTOH, timestamp is captured when activity finishes on GPU. For counterKind CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_GPU_PAGE_FAULT, timestamp is captured when CUDA driver queues the replay of faulting memory accesses on the GPU

uint32_t CUpti_ActivityUnifiedMemoryCounter2::flags

The flags associated with this record. See enums

CUpti_ActivityUnifiedMemoryAccessType if counterKind is

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_GPU_PAGE_FAULT

and CUpti_ActivityUnifiedMemoryMigrationCause if counterKind is

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_BYTES_TRANSFER_HTOD

or

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_BYTES_TRANSFER_HTOD

CUpti_ActivityKind CUpti_ActivityUnifiedMemoryCounter2::kind

The activity record kind, must be CUPTI_ACTIVITY_KIND_UNIFIED_MEMORY_COUNTER

uint32_t CUpti_ActivityUnifiedMemoryCounter2::pad

Undefined. Reserved for internal use.

uint32_t

CUpti_ActivityUnifiedMemoryCounter2::processId

The ID of the process to which this record belongs to.

uint32_t CUpti_ActivityUnifiedMemoryCounter2::srcld

The ID of the source CPU/device involved in the memory transfer or page fault operation. Ignore this field if counterKind is CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_CPU_PAGE_FAULT_COUNT

uint64_t CUpti_ActivityUnifiedMemoryCounter2::start

The start timestamp of the counter, in ns. For counterKind CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_BYTES_TRANSFER_HTOD and

CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_BYTES_TRANSFER_DTOH, timestamp is captured when activity starts on GPU. For counterKind CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_GPU_PAGE_FAULT and CUPTI_ACTIVITY_UNIFIED_MEMORY_COUNTER_KIND_CPU_PAGE_FAULT_COUNT, timestamp is captured when CUDA driver started processing the fault.

uint32_t CUpti_ActivityUnifiedMemoryCounter2::streamId

The ID of the stream causing the transfer. This value of this field is invalid.

uint64_t CUpti_ActivityUnifiedMemoryCounter2::value

Value of the counter

3.56. CUpti_ActivityUnifiedMemoryCounterConfig Struct Reference

Unified Memory counters configuration structure.

This structure controls the enable/disable of the various Unified Memory counters consisting of scope, kind and other parameters. See function /ref cuptiActivityConfigureUnifiedMemoryCounter

uint32_t CUpti_ActivityUnifiedMemoryCounterConfig::deviceId

Device id of the traget device. This is relevant only for single device scopes. (deprecated in CUDA 7.0)

uint32_t CUpti_ActivityUnifiedMemoryCounterConfig::enable

Control to enable/disable the counter. To enable the counter set it to non-zero value while disable is indicated by zero.

CUpti_ActivityUnifiedMemoryCounterKind CUpti_ActivityUnifiedMemoryCounterConfig::kind

Unified Memory counter Counter kind

CUpti_ActivityUnifiedMemoryCounterScope CUpti_ActivityUnifiedMemoryCounterConfig::scope

Unified Memory counter Counter scope. (deprecated in CUDA 7.0)

3.57. CUpti_CallbackData Struct Reference

Data passed into a runtime or driver API callback function.

Data passed into a runtime or driver API callback function as the cbdata argument to CUpti_CallbackFunc. The cbdata will be this type for domain equal to CUPTI_CB_DOMAIN_DRIVER_API or CUPTI_CB_DOMAIN_RUNTIME_API. The callback data is valid only within the invocation of the callback function that is passed the data. If you need to retain some data for use outside of the callback, you must make a copy of that data. For example, if you make a shallow copy of CUpti_CallbackData within a callback, you cannot dereference functionParams outside of that callback to

access the function parameters. functionName is an exception: the string pointed to by functionName is a global constant and so may be accessed outside of the callback.

CUpti_ApiCallbackSite CUpti_CallbackData::callbackSite

Point in the runtime or driver function from where the callback was issued.

CUcontext CUpti_CallbackData::context

Driver context current to the thread, or null if no context is current. This value can change from the entry to exit callback of a runtime API function if the runtime initializes a context.

uint32_t CUpti_CallbackData::contextUid

Unique ID for the CUDA context associated with the thread. The UIDs are assigned sequentially as contexts are created and are unique within a process.

uint64_t *CUpti_CallbackData::correlationData

Pointer to data shared between the entry and exit callbacks of a given runtime or drive API function invocation. This field can be used to pass 64-bit values from the entry callback to the corresponding exit callback.

uint32_t CUpti_CallbackData::correlationId

The activity record correlation ID for this callback. For a driver domain callback (i.e. domain CUPTI_CB_DOMAIN_DRIVER_API) this ID will equal the correlation ID in the CUpti_ActivityAPI record corresponding to the CUDA driver function call. For a runtime domain callback (i.e. domain CUPTI_CB_DOMAIN_RUNTIME_API) this ID will equal the correlation ID in the CUpti_ActivityAPI record corresponding to the CUDA runtime function call. Within the callback, this ID can be recorded to correlate user data with the activity record. This field is new in 4.1.

const char *CUpti_CallbackData::functionName

Name of the runtime or driver API function which issued the callback. This string is a global constant and so may be accessed outside of the callback.

const void *CUpti_CallbackData::functionParams

Pointer to the arguments passed to the runtime or driver API call. See generated_cuda_runtime_api_meta.h and generated_cuda_meta.h for structure definitions for the parameters for each runtime and driver API function.

void *CUpti_CallbackData::functionReturnValue

Pointer to the return value of the runtime or driver API call. This field is only valid within the exit::CUPTI_API_EXIT callback. For a runtime API functionReturnValue points to a cudaError_t. For a driver API functionReturnValue points to a CUresult.

const char *CUpti_CallbackData::symbolName

Name of the symbol operated on by the runtime or driver API function which issued the callback. This entry is valid only for driver and runtime launch callbacks, where it returns the name of the kernel.

3.58. CUpti_EventGroupSet Struct Reference

A set of event groups.

A set of event groups. When returned by cuptiEventGroupSetsCreate and cuptiMetricCreateEventGroupSets a set indicates that event groups that can be enabled at the same time (i.e. all the events in the set can be collected simultaneously).

CUpti_EventGroup *CUpti_EventGroupSet::eventGroups

An array of numEventGroups event groups.

uint32_t CUpti_EventGroupSet::numEventGroups

The number of event groups in the set.

3.59. CUpti_EventGroupSets Struct Reference

A set of event group sets.

A set of event group sets. When returned by cuptiEventGroupSetsCreate and cuptiMetricCreateEventGroupSets a CUpti_EventGroupSets indicates the number of passes required to collect all the events, and the event groups that should be collected during each pass.

uint32_t CUpti_EventGroupSets::numSets

Number of event group sets.

CUpti_EventGroupSet *CUpti_EventGroupSets::sets

An array of numSets event group sets.

3.60. CUpti_MetricValue Union Reference

A metric value.

Metric values can be one of several different kinds. Corresponding to each kind is a member of the CUpti_MetricValue union. The metric value returned by cuptiMetricGetValue should be accessed using the appropriate member of that union based on its value kind.

3.61. CUpti_ModuleResourceData Struct Reference

Module data passed into a resource callback function.

CUDA module data passed into a resource callback function as the <code>cbdata</code> argument to CUpti_CallbackFunc. The <code>cbdata</code> will be this type for <code>domain</code> equal to CUPTI_CB_DOMAIN_RESOURCE. The module data is valid only within the invocation of the callback function that is passed the data. If you need to retain some data for use outside of the callback, you must make a copy of that data.

size_t CUpti_ModuleResourceData::cubinSize

The size of the cubin.

uint32_t CUpti_ModuleResourceData::moduleId

Identifier to associate with the CUDA module.

const char *CUpti_ModuleResourceData::pCubin

Pointer to the associated cubin.

3.62. CUpti_NvtxData Struct Reference

Data passed into a NVTX callback function.

Data passed into a NVTX callback function as the cbdata argument to CUpti_CallbackFunc. The cbdata will be this type for domain equal to CUPTI_CB_DOMAIN_NVTX. Unless otherwise notes, the callback data is valid only within the invocation of the callback function that is passed the data. If you need to retain some data for use outside of the callback, you must make a copy of that data.

const char *CUpti_NvtxData::functionName

Name of the NVTX API function which issued the callback. This string is a global constant and so may be accessed outside of the callback.

const void *CUpti_NvtxData::functionParams

Pointer to the arguments passed to the NVTX API call. See generated_nvtx_meta.h for structure definitions for the parameters for each NVTX API function.

3.63. CUpti_ResourceData Struct Reference

Data passed into a resource callback function.

Data passed into a resource callback function as the cbdata argument to CUpti_CallbackFunc. The cbdata will be this type for domain equal to CUPTI_CB_DOMAIN_RESOURCE. The callback data is valid only within the invocation of the callback function that is passed the data. If you need to retain some data for use outside of the callback, you must make a copy of that data.

CUcontext CUpti_ResourceData::context

For CUPTI_CBID_RESOURCE_CONTEXT_CREATED and CUPTI_CBID_RESOURCE_CONTEXT_DESTROY_STARTING, the context being created or destroyed. For CUPTI_CBID_RESOURCE_STREAM_CREATED and CUPTI_CBID_RESOURCE_STREAM_DESTROY_STARTING, the context containing the stream being created or destroyed.

void *CUpti_ResourceData::resourceDescriptor

Reserved for future use.

CUstream CUpti_ResourceData::stream

For CUPTI_CBID_RESOURCE_STREAM_CREATED and CUPTI_CBID_RESOURCE_STREAM_DESTROY_STARTING, the stream being created or destroyed.

3.64. CUpti_SynchronizeData Struct Reference

Data passed into a synchronize callback function.

Data passed into a synchronize callback function as the cbdata argument to CUpti_CallbackFunc. The cbdata will be this type for domain equal to

CUPTI_CB_DOMAIN_SYNCHRONIZE. The callback data is valid only within the invocation of the callback function that is passed the data. If you need to retain some data for use outside of the callback, you must make a copy of that data.

CUcontext CUpti_SynchronizeData::context

The context of the stream being synchronized.

CUstream CUpti_SynchronizeData::stream

The stream being synchronized.

Chapter 4. DATA FIELDS

Here is a list of all documented struct and union fields with links to the struct/union documentation for each field:

```
Α
address
  CUpti_ActivityUnifiedMemoryCounter2
attribute
  CUpti_ActivityDeviceAttribute
В
bandwidth
  CUpti_ActivityNvLink
blockX
  CUpti_ActivityKernel
  CUpti_ActivityKernel3
  CUpti_ActivityCdpKernel
  CUpti_ActivityKernel2
  CUpti_ActivityPreemption
blockY
  CUpti_ActivityKernel2
  CUpti_ActivityKernel3
  CUpti_ActivityCdpKernel
  CUpti_ActivityPreemption
  CUpti_ActivityKernel
blockZ
  CUpti_ActivityCdpKernel
  CUpti_ActivityPreemption
  CUpti_ActivityKernel2
  CUpti_ActivityKernel3
  CUpti_ActivityKernel
```

```
bytes
  CUpti_ActivityMemcpy2
  CUpti_ActivityMemset
  CUpti_ActivityOpenAccData
  CUpti_ActivityMemcpy
C
cacheConfigExecuted
  CUpti_ActivityKernel
cacheConfigRequested
  CUpti_ActivityKernel
callbackSite
  CUpti_CallbackData
category
  CUpti_ActivityMarkerData
cbid
  CUpti_ActivityAPI
clocksThrottleReasons
  CUpti_ActivityEnvironment
color
  CUpti_ActivityMarkerData
completed
  CUpti_ActivityKernel2
  CUpti_ActivityKernel3
  CUpti_ActivityCdpKernel
computeApiKind
  CUpti_ActivityContext
computeCapabilityMajor
  CUpti_ActivityDevice
  CUpti_ActivityDevice2
computeCapabilityMinor
  CUpti_ActivityDevice
  CUpti ActivityDevice2
constantMemorySize
  CUpti_ActivityDevice
  CUpti_ActivityDevice2
context
  CUpti_CallbackData
  CUpti_ResourceData
  CUpti_SynchronizeData
contextId
  CUpti_ActivityStream
  CUpti_ActivitySynchronization
```

CUpti_ActivityMemcpy

CUpti_ActivityMemcpy2

CUpti_ActivityMemset

CUpti_ActivityKernel

CUpti_ActivityKernel2

CUpti_ActivityKernel3

CUpti_ActivityCdpKernel

CUpti_ActivityContext

CUpti_ActivityFunction

CUpti_ActivityModule

CUpti_ActivityCudaEvent

contextUid

CUpti_CallbackData

cooling

CUpti_ActivityEnvironment

copyKind

CUpti_ActivityMemcpy

CUpti_ActivityMemcpy2

coreClockRate

CUpti_ActivityDevice

CUpti_ActivityDevice2

correlationData

CUpti_CallbackData

correlationId

CUpti_ActivityBranch

CUpti_ActivityExternalCorrelation

CUpti_CallbackData

CUpti_ActivityPCSampling2

CUpti_ActivityMemcpy

CUpti_ActivityCdpKernel

CUpti_ActivityMemcpy2

CUpti_ActivityMemset

CUpti ActivityKernel

CUpti_ActivityKernel2

CUpti_ActivityKernel3

CUpti_ActivityAPI

CUpti_ActivityEvent

CUpti_ActivityEventInstance

CUpti_ActivityMetric

CUpti_ActivityMetricInstance

CUpti_ActivityGlobalAccess

CUpti_ActivityGlobalAccess2

CUpti_ActivitySharedAccess

CUpti_ActivityBranch2

 $CUpti_ActivityInstructionExecution\\$

CUpti_ActivitySynchronization

CUpti_ActivityPCSampling

CUpti_ActivityCudaEvent

CUpti_ActivityPCSamplingRecordInfo

counterKind

 $CUpti_ActivityUnifiedMemoryCounter\\$

CUpti_ActivityUnifiedMemoryCounter2

cubin

CUpti_ActivityModule

cubinSize

CUpti_ActivityModule

CUpti ModuleResourceData

cuContextId

CUpti_ActivityOpenAccData

CUpti_ActivityOpenAccOther

CUpti_ActivityOpenAcc

CUpti_ActivityOpenAccLaunch

cudaEventId

CUpti_ActivitySynchronization

cuDeviceId

CUpti_ActivityOpenAccData

CUpti_ActivityOpenAcc

CUpti_ActivityOpenAccLaunch

CUpti_ActivityOpenAccOther

cuProcessId

CUpti_ActivityOpenAcc

CUpti_ActivityOpenAccOther

CUpti_ActivityOpenAccLaunch

CUpti_ActivityOpenAccData

cuStreamId

CUpti ActivityOpenAccData

CUpti_ActivityOpenAccOther

CUpti_ActivityOpenAcc

CUpti_ActivityOpenAccLaunch

cuThreadId

CUpti_ActivityOpenAccLaunch

CUpti_ActivityOpenAccOther

CUpti_ActivityOpenAccData

CUpti_ActivityOpenAcc

```
D
dcs
  CUpti_ActivityObjectKindId
deviceId
  CUpti_ActivityUnifiedMemoryCounterConfig
  CUpti_ActivityMemcpy2
  CUpti_ActivityKernel3
  CUpti_ActivityInstantaneousMetric
  CUpti_ActivityInstantaneousMetricInstance
  CUpti_ActivityCdpKernel
  CUpti_ActivityMemset
  CUpti_ActivityDeviceAttribute
  CUpti_ActivityContext
  CUpti_ActivityMemcpy
  CUpti_ActivityKernel
  CUpti_ActivityEnvironment
  CUpti_ActivityUnifiedMemoryCounter
  CUpti_ActivityKernel2
  CUpti_ActivityInstantaneousEvent
  CUpti ActivityInstantaneousEventInstance
devicePtr
  CUpti_ActivityOpenAccData
diverged
  CUpti_ActivityBranch
  CUpti_ActivityBranch2
domain
  CUpti_ActivityEvent
  CUpti_ActivityEventInstance
  CUpti_ActivityMarker2
domainId
  CUpti_ActivityNvLink
droppedSamples
  CUpti_ActivityPCSamplingRecordInfo
dstContextId
  CUpti_ActivityMemcpy2
dstDeviceId
  CUpti_ActivityMemcpy2
dstId
  CUpti\_ActivityUnifiedMemoryCounter2\\
dstKind
  CUpti_ActivityMemcpy
  CUpti_ActivityMemcpy2
```

```
dynamicSharedMemory
  CUpti_ActivityKernel2
  CUpti_ActivityKernel3
  CUpti_ActivityKernel
  CUpti_ActivityCdpKernel
Ε
eccEnabled
  CUpti_ActivityDevice2
enable
  CUpti_ActivityUnifiedMemoryCounterConfig
enabled
  CUpti_ActivityAutoBoostState
end
  CUpti_ActivityMemcpy
  CUpti_ActivityKernel2
  CUpti_ActivityOpenAccData
  CUpti_ActivityOpenAccLaunch
  CUpti_ActivityKernel3
  CUpti_ActivityOpenAccOther
  CUpti_ActivityMemcpy2
  CUpti_ActivityCdpKernel
  CUpti_ActivityAPI
  CUpti_ActivityMemset
  CUpti_ActivityOverhead
  CUpti_ActivityUnifiedMemoryCounter2
  CUpti_ActivityKernel
  CUpti_ActivitySynchronization
  CUpti_ActivityOpenAcc
environmentKind
  CUpti_ActivityEnvironment
eventGroups
  CUpti_EventGroupSet
eventId
  CUpti_ActivityCudaEvent
eventKind
  CUpti_ActivityOpenAccData
  CUpti_ActivityOpenAcc
  CUpti_ActivityOpenAccLaunch
  CUpti_ActivityOpenAccOther
executed
  CUpti_ActivityGlobalAccess2
  CUpti_ActivityKernel2
```

CUpti_ActivityKernel3 CUpti_ActivityBranch2 CUpti_ActivityInstructionExecution CUpti_ActivityBranch CUpti_ActivitySharedAccess $CUpti_ActivityGlobalAccess$ CUpti_ActivityCdpKernel externalId CUpti_ActivityOpenAccOther CUpti_ActivityOpenAccData CUpti ActivityExternalCorrelation CUpti_ActivityOpenAcc CUpti_ActivityOpenAccLaunch externalKind CUpti_ActivityExternalCorrelation F fanSpeed CUpti_ActivityEnvironment fileName CUpti_ActivitySourceLocator flag CUpti_ActivityNvLink CUpti_ActivityStream flags CUpti_ActivityMetric CUpti_ActivityMarker2 CUpti_ActivityMarkerData CUpti_ActivityMetricInstance CUpti_ActivityInstructionExecution CUpti_ActivityPCSampling CUpti_ActivityMemcpy CUpti ActivityGlobalAccess CUpti_ActivityPCSampling2 CUpti_ActivityUnifiedMemoryCounter2 CUpti_ActivityInstantaneousMetricInstance CUpti_ActivityGlobalAccess2 CUpti_ActivitySharedAccess CUpti_ActivityInstructionCorrelation CUpti_ActivityMemcpy2 CUpti_ActivityDevice CUpti_ActivityInstantaneousMetric CUpti_ActivityDevice2

```
CUpti_ActivityMemset
  CUpti_ActivityDeviceAttribute
  CUpti_ActivityMarker
functionId
  CUpti_ActivitySharedAccess
  CUpti_ActivityInstructionCorrelation
  CUpti_ActivityGlobalAccess2
  CUpti_ActivityInstructionExecution
  CUpti_ActivityBranch2
  CUpti_ActivityPCSampling
  CUpti_ActivityPCSampling2
functionIndex
  CUpti_ActivityFunction
functionName
  CUpti_NvtxData
  CUpti_CallbackData
functionParams
  CUpti_NvtxData
  CUpti_CallbackData
functionReturnValue
  CUpti_CallbackData
G
globalMemoryBandwidth
  CUpti_ActivityDevice
  CUpti_ActivityDevice2
globalMemorySize
  CUpti_ActivityDevice2
  CUpti_ActivityDevice
gpuTemperature
  CUpti_ActivityEnvironment
gridId
  CUpti_ActivityCdpKernel
  CUpti_ActivityPreemption
  CUpti_ActivityKernel2
  CUpti_ActivityKernel3
gridX
  CUpti_ActivityKernel
  CUpti_ActivityKernel2
  CUpti_ActivityKernel3
  CUpti_ActivityCdpKernel
gridY
  CUpti_ActivityCdpKernel
```

```
CUpti_ActivityKernel3
  CUpti_ActivityKernel
  CUpti_ActivityKernel2
gridZ
  CUpti_ActivityKernel2
  CUpti_ActivityKernel
  CUpti_ActivityCdpKernel
  CUpti_ActivityKernel3
Н
hostPtr
  CUpti_ActivityOpenAccData
ı
id
  CUpti_ActivityEvent
  CUpti_ActivityEventInstance
  CUpti_ActivityMetricInstance
  CUpti_ActivityMarker
  CUpti_ActivityInstantaneousMetricInstance
  CUpti_ActivityMarker2
  CUpti_ActivitySourceLocator
  CUpti_ActivityMarkerData
  CUpti_ActivityFunction
  CUpti_ActivityInstantaneousMetric
  CUpti_ActivityInstantaneousEventInstance
  CUpti_ActivityInstantaneousEvent
  CUpti_ActivityModule
  CUpti_ActivityMetric
  CUpti_ActivityDevice
  CUpti_ActivityDevice2
idDev0
  CUpti_ActivityNvLink
idDev1
  CUpti_ActivityNvLink
index
  CUpti_ActivityNvLink
instance
  CUpti_ActivityInstantaneousEventInstance
  CUpti_ActivityEventInstance
  CUpti_ActivityInstantaneousMetricInstance
  CUpti_ActivityMetricInstance
```

K

kind

CUpti_ActivityUnifiedMemoryCounterConfig

CUpti_ActivityInstantaneousMetricInstance

CUpti_ActivityInstantaneousMetric

CUpti_ActivityInstantaneousEventInstance

CUpti_ActivityInstantaneousEvent

CUpti_ActivityNvLink

CUpti_ActivityExternalCorrelation

CUpti_ActivityOpenAccOther

CUpti_ActivityOpenAccLaunch

CUpti_ActivityOpenAccData

CUpti_ActivityOpenAcc

CUpti_ActivityInstructionCorrelation

CUpti_ActivitySynchronization

CUpti_ActivityStream

CUpti_ActivityCudaEvent

CUpti_ActivitySharedAccess

CUpti_ActivityModule

CUpti_ActivityFunction

CUpti_ActivityUnifiedMemoryCounter2

CUpti_ActivityUnifiedMemoryCounter

CUpti ActivityPCSamplingRecordInfo

CUpti_ActivityPCSampling2

CUpti_ActivityPCSampling

CUpti_ActivityInstructionExecution

CUpti_ActivityEnvironment

CUpti_ActivityOverhead

CUpti_ActivityMarkerData

CUpti ActivityMarker2

CUpti_ActivityMarker

CUpti_ActivityName

CUpti ActivityContext

CUpti_ActivityDeviceAttribute

CUpti_ActivityDevice2

CUpti ActivityDevice

CUpti_ActivityBranch2

CUpti_ActivityBranch

CUpti_ActivityGlobalAccess2

CUpti_ActivityGlobalAccess

CUpti_ActivitySourceLocator

CUpti_ActivityMetricInstance

CUpti_ActivityMetric

CUpti_ActivityEventInstance CUpti_ActivityEvent CUpti_ActivityAPI CUpti_ActivityPreemption CUpti_ActivityCdpKernel CUpti_ActivityKernel3 CUpti_ActivityKernel2 CUpti_ActivityKernel CUpti_ActivityMemset CUpti_ActivityMemcpy2 CUpti_ActivityMemcpy CUpti_Activity L 12_transactions CUpti_ActivityGlobalAccess CUpti_ActivityGlobalAccess2 12CacheSize CUpti_ActivityDevice2 CUpti_ActivityDevice latencySamples CUpti_ActivityPCSampling2 lineNumber CUpti_ActivitySourceLocator local Memory Per ThreadCUpti_ActivityKernel2 CUpti_ActivityKernel3 CUpti_ActivityCdpKernel CUpti_ActivityKernel localMemoryTotal CUpti_ActivityCdpKernel CUpti_ActivityKernel CUpti_ActivityKernel2 CUpti_ActivityKernel3 M maxBlockDimX CUpti_ActivityDevice CUpti_ActivityDevice2 maxBlockDimY CUpti_ActivityDevice2

CUpti_ActivityDevice

maxBlockDimZ

CUpti_ActivityDevice

CUpti_ActivityDevice2

max Blocks Per Multiprocessor

CUpti_ActivityDevice2

CUpti_ActivityDevice

maxGridDimX

CUpti_ActivityDevice

CUpti_ActivityDevice2

maxGridDimY

CUpti_ActivityDevice

CUpti_ActivityDevice2

maxGridDimZ

CUpti ActivityDevice

CUpti_ActivityDevice2

maxIPC

CUpti_ActivityDevice2

CUpti_ActivityDevice

maxRegistersPerBlock

CUpti_ActivityDevice

CUpti_ActivityDevice2

max Registers Per Multiprocessor

CUpti_ActivityDevice2

maxSharedMemoryPerBlock

CUpti_ActivityDevice

CUpti_ActivityDevice2

max Shared Memory Per Multiprocessor

CUpti_ActivityDevice2

maxThreadsPerBlock

CUpti_ActivityDevice

CUpti_ActivityDevice2

maxWarpsPerMultiprocessor

CUpti ActivityDevice

CUpti_ActivityDevice2

memoryClock

CUpti_ActivityEnvironment

memoryKind

CUpti_ActivityMemset

moduleId

CUpti_ModuleResourceData

CUpti_ActivityFunction

N name CUpti_ActivityKernel CUpti_ActivityKernel2 CUpti_ActivityCdpKernel CUpti_ActivityMarker CUpti_ActivityMarker2 CUpti_ActivityDevice CUpti_ActivityFunction CUpti_ActivityKernel3 CUpti_ActivityDevice2 CUpti_ActivityName not PredOff Threads ExecutedCUpti_ActivityInstructionExecution nullStreamId CUpti_ActivityContext numEventGroups CUpti_EventGroupSet numGangs CUpti_ActivityOpenAccLaunch numMemcpyEngines CUpti_ActivityDevice2 CUpti_ActivityDevice numMultiprocessors CUpti_ActivityDevice CUpti_ActivityDevice2 numSets CUpti_EventGroupSets numThreadsPerWarp CUpti_ActivityDevice2 CUpti_ActivityDevice numWorkers CUpti_ActivityOpenAccLaunch nvlinkVersion CUpti_ActivityNvLink 0 objectId CUpti_ActivityName CUpti_ActivityMarker CUpti_ActivityOverhead CUpti_ActivityMarker2

CUpti_ActivityMarker CUpti_ActivityName CUpti_ActivityOverhead CUpti_ActivityMarker2 overheadKind CUpti_ActivityOverhead Ρ pad CUpti_ActivityMemcpy2 CUpti_ActivityKernel CUpti_ActivityEventInstance CUpti_ActivityBranch2 CUpti_ActivityCudaEvent CUpti_ActivityStream CUpti_ActivityDevice2 CUpti_ActivityInstructionCorrelation CUpti_ActivityInstantaneousEventInstance CUpti_ActivityMetric CUpti_ActivityMarker2 CUpti_ActivityInstantaneousMetric CUpti_ActivityInstantaneousMetricInstance CUpti_ActivityInstructionExecution CUpti_ActivityPreemption CUpti_ActivityMetricInstance CUpti_ActivityUnifiedMemoryCounter CUpti_ActivityUnifiedMemoryCounter2 CUpti_ActivityGlobalAccess2 CUpti_ActivityModule CUpti_ActivitySharedAccess pad1 CUpti_ActivityOpenAccData CUpti_ActivityOpenAccLaunch parentBlockX CUpti_ActivityCdpKernel parentBlockY CUpti_ActivityCdpKernel parentBlockZ CUpti_ActivityCdpKernel parentConstruct CUpti_ActivityOpenAcc

objectKind

parentGridId CUpti_ActivityCdpKernel partitionedGlobalCacheExecuted CUpti_ActivityKernel3 partitionedGlobalCacheRequested CUpti_ActivityKernel3 payload CUpti_ActivityMarkerData payloadKind CUpti_ActivityMarkerData pcieLinkGen CUpti_ActivityEnvironment pcieLinkWidth CUpti_ActivityEnvironment pcOffset CUpti_ActivityGlobalAccess CUpti_ActivityGlobalAccess2 CUpti_ActivityBranch CUpti_ActivitySharedAccess CUpti_ActivityBranch2 CUpti_ActivityPCSampling CUpti_ActivityPCSampling2 CUpti_ActivityInstructionCorrelation CUpti_ActivityInstructionExecution pCubin CUpti_ModuleResourceData physicalNvLinkCount CUpti_ActivityNvLink pid CUpti_ActivityAutoBoostState portDev0 CUpti_ActivityNvLink portDev1 CUpti_ActivityNvLink power CUpti_ActivityEnvironment powerLimit CUpti_ActivityEnvironment preemptionKind CUpti_ActivityPreemption priority CUpti_ActivityStream

```
processId
  CUpti\_ActivityUnifiedMemoryCounter2\\
  CUpti_ActivityUnifiedMemoryCounter
  CUpti_ActivityAPI
pt
  CUpti_ActivityObjectKindId
Q
queued
  CUpti_ActivityCdpKernel
R
registersPerThread
  CUpti_ActivityKernel
  CUpti_ActivityKernel2
  CUpti_ActivityCdpKernel
  CUpti_ActivityKernel3
requested
  CUpti_ActivityKernel2
  CUpti_ActivityKernel3
  CUpti_ActivityCdpKernel
reserved
  CUpti_ActivityExternalCorrelation
  CUpti_ActivityInstantaneousEvent
reserved0
  CUpti_ActivityMemcpy2
  CUpti_ActivityKernel
  CUpti_ActivityMemcpy
  CUpti_ActivityKernel2
  CUpti_ActivityKernel3
  CUpti_ActivityMemset
resourceDescriptor
  CUpti_ResourceData
returnValue
  CUpti_ActivityAPI
runtimeCorrelationId
  CUpti_ActivityKernel
  CUpti_ActivityMemcpy
S
samples
  CUpti_ActivityPCSampling
  CUpti_ActivityPCSampling2
```

```
samplingPeriod
  CUpti_ActivityPCSamplingConfig
samplingPeriodInCycles
  CUpti_ActivityPCSamplingRecordInfo
scope
  CUpti_ActivityUnifiedMemoryCounterConfig
  CUpti_ActivityUnifiedMemoryCounter
sets
  CUpti_EventGroupSets
sharedMemoryConfig
  CUpti_ActivityKernel2
  CUpti_ActivityKernel3
  CUpti_ActivityCdpKernel
sharedTransactions
  CUpti_ActivitySharedAccess
size
  CUpti_ActivityPCSamplingConfig
smClock
  CUpti_ActivityEnvironment
sourceLocatorId
  CUpti_ActivityBranch
  CUpti_ActivityBranch2
  CUpti_ActivityInstructionExecution
  CUpti_ActivityPCSampling
  CUpti_ActivityPCSampling2
  CUpti_ActivitySharedAccess
  CUpti_ActivityInstructionCorrelation
  CUpti_ActivityGlobalAccess
  CUpti_ActivityGlobalAccess2
speed
  CUpti_ActivityEnvironment
srcContextId
  CUpti ActivityMemcpy2
srcDeviceId
  CUpti_ActivityMemcpy2
srcId
  CUpti\_ActivityUnifiedMemoryCounter2\\
srcKind
  CUpti_ActivityMemcpy
  CUpti_ActivityMemcpy2
stallReason
  CUpti_ActivityPCSampling
  CUpti_ActivityPCSampling2
```

start

CUpti_ActivityKernel2

CUpti_ActivityOpenAccData

CUpti_ActivityMemcpy2

CUpti_ActivityMemset

CUpti_ActivityKernel

CUpti_ActivityKernel3

CUpti_ActivityCdpKernel

CUpti_ActivityAPI

CUpti_ActivityUnifiedMemoryCounter2

CUpti_ActivitySynchronization

CUpti_ActivityOpenAcc

CUpti_ActivityOpenAccLaunch

CUpti_ActivityOpenAccOther

CUpti_ActivityOverhead

CUpti_ActivityMemcpy

staticSharedMemory

CUpti_ActivityCdpKernel

CUpti_ActivityKernel

CUpti_ActivityKernel3

CUpti_ActivityKernel2

stream

CUpti_SynchronizeData

CUpti_ResourceData

streamId

CUpti_ActivityMemset

CUpti_ActivityUnifiedMemoryCounter2

CUpti_ActivityMemcpy

CUpti_ActivitySynchronization

CUpti_ActivityKernel3

CUpti_ActivityKernel

CUpti_ActivityMemcpy2

CUpti ActivityStream

CUpti_ActivityCudaEvent

CUpti_ActivityKernel2

CUpti_ActivityCdpKernel

submitted

CUpti_ActivityCdpKernel

symbolName

CUpti_CallbackData

```
Т
temperature
  CUpti_ActivityEnvironment
theoreticalL2Transactions
  CUpti_ActivityGlobalAccess2
theoreticalSharedTransactions
  CUpti_ActivitySharedAccess
threadId
  CUpti_ActivityAPI
  CUpti_ActivityOpenAccOther
  CUpti_ActivityOpenAcc
  CUpti_ActivityOpenAccData
  CUpti_ActivityOpenAccLaunch
threadsExecuted
  CUpti_ActivityGlobalAccess
  CUpti_ActivityGlobalAccess2
  CUpti_ActivityBranch
  CUpti_ActivityBranch2
  CUpti_ActivityInstructionExecution
  CUpti_ActivitySharedAccess
timestamp
  CUpti_ActivityInstantaneousMetricInstance
  CUpti_ActivityMarker
  CUpti_ActivityMarker2
  CUpti_ActivityEnvironment
  CUpti_ActivityUnifiedMemoryCounter
  CUpti_ActivityInstantaneousEvent
  CUpti_ActivityPreemption
  CUpti_ActivityInstantaneousMetric
  CUpti_ActivityInstantaneousEventInstance
totalSamples
  CUpti_ActivityPCSamplingRecordInfo
type
  CUpti_ActivitySynchronization
typeDev0
  CUpti_ActivityNvLink
typeDev1
  CUpti_ActivityNvLink
U
uuid
  CUpti_ActivityDevice2
```

٧

value

CUpti_ActivityMemset

CUpti_ActivityEvent

CUpti_ActivityInstantaneousMetricInstance

 $CUpti_ActivityInstantaneousMetric\\$

CUpti_ActivityInstantaneousEventInstance

 $CUpti_ActivityInstantaneousEvent\\$

CUpti_ActivityMetric

 $CUpti_ActivityUnifiedMemoryCounter\\$

CUpti_ActivityDeviceAttribute

CUpti_ActivityMetricInstance

 $CUpti_ActivityUnifiedMemoryCounter2$

CUpti_ActivityEventInstance

vectorLength

CUpti_ActivityOpenAccLaunch

Chapter 5. LIMITATIONS

The following are known issues with the current release.

- ► The Continuous event collection mode

 CUPTI_EVENT_COLLECTION_MODE_CONTINUOUS is supported only on Tesla
 devices.
- Profiling results might be inconsistent when auto boost is enabled. Profiler tries to disable auto boost by default. But it might fail to do so in some conditions and profiling will continue and results will be inconsistent. API cuptiGetAutoBoostState() can be used to query the auto boost state of the device. This API returns error CUPTI_ERROR_NOT_SUPPORTED on devices that don't support auto boost. Note that auto boost is supported only on certain Tesla devices with compute capability 3.0 and higher.
- CUPTI doesn't populate the activity structures which are deprecated, instead the newer version of the activity structure is filled with the information.
- ▶ While collecting events in continuous mode, event reporting may be delayed i.e. event values may be returned by a later call to readEvent(s) API and the event values for the last readEvent(s) API may get lost.
- ▶ When profiling events, it is possible that the domain instance that gets profiled gives event value 0 due to absence of workload on the domain instance since CUPTI profiles one instance of the domain by default. To profile all instances of the domain, user can set event group attribute CUPTI_EVENT_GROUP_ATTR_PROFILE_ALL_DOMAIN_INSTANCES through API cuptiEventGroupSetAttribute().

Chapter 6. CHANGELOG

CUPTI changes in CUDA 7.5

List of changes done as part of the CUDA Toolkit 7.5 release.

- ▶ Device-wide sampling of the program counter (PC) is enabled by default. This was a preview feature in the CUDA Toolkit 7.0 release and it was not enabled by default.
- Ability to collect all events and metrics accurately in presence of multiple contexts on the GPU is extended for devices with compute capability 5.x.
- API cuptiGetLastError is introduced to return the last error that has been produced by any of the CUPTI API calls or the callbacks in the same host thread.
- Unified memory profiling is supported with MPS (Multi-Process Service)
- Callback is provided to collect replay information after every kernel run during kernel replay. See API cuptiKernelReplaySubscribeUpdate and callback type CUpti KernelReplayUpdateFunc.
- Added new attributes in enum CUpti_DeviceAttribute to query maximum shared memory size for different cache preferences for a device function.

CUPTI changes in CUDA 7.0

List of changes done as part of the CUDA Toolkit 7.0 release.

- ► CUPTI supports device-wide sampling of the program counter (PC). Program counters along with the stall reasons from all active warps are sampled at a fixed frequency in the round robin order. Activity record CUpti_ActivityPCSampling enabled using activity kind CUPTI_ACTIVITY_KIND_PC_SAMPLING outputs stall reason along with PC and other related information.

 Enum CUpti_ActivityPCSamplingStallReason lists all the stall reasons. Sampling period is configurable and can be tuned using API cuptiActivityConfigurePCSampling. This feature is available on devices with compute capability 5.2.
- Added new activity record CUpti_ActivityInstructionCorrelation which can be used to dump source locator records for all the PCs of the function.

- ▶ All events and metrics for devices with compute capability 3.x and 5.0 can be collected accurately in presence of multiple contexts on the GPU. In previous releases only some events and metrics could be collected accurately when multiple contexts were executing on the GPU.
- ▶ Unified memory profiling is enhanced by providing fine grain data transfers to and from the GPU, coupled with more accurate timestamps with each transfer. This information is provided through new activity record CUpti_ActivityUnifiedMemoryCounter2, deprecating old record CUpti_ActivityUnifiedMemoryCounter.
- ▶ MPS tracing and profiling support is extended on multi-gpu setups.
- Activity record CUpti_ActivityDevice for device information has been deprecated and replaced by new activity record CUpti_ActivityDevice2. New record adds device UUID which can be used to uniquely identify the device across profiler runs.
- Activity record CUpti_ActivityKernel2 for kernel execution has been deprecated and replaced by new activity record CUpti_ActivityKernel3. New record gives information about Global Partitioned Cache Configuration requested and executed. Partitioned global caching has an impact on occupancy calculation. If it is ON, then a CTA can only use a half SM, and thus a half of the registers available per SM. The new fields apply for devices with compute capability 5.2 and higher. Note that this change was done in CUDA 6.5 release with support for compute capability 5.2.

CUPTI changes in CUDA 6.5

List of changes done as part of the CUDA Toolkit 6.5 release.

- ► Instruction classification is done for source-correlated Instruction Execution activity CUpti_ActivityInstructionExecution. See CUpti ActivityInstructionClass for instruction classes.
- ► Two new device attributes are added to the activity CUpti DeviceAttribute:
 - ► CUPTI_DEVICE_ATTR_FLOP_SP_PER_CYCLE gives peak single precision flop per cycle for the GPU.
 - ► CUPTI_DEVICE_ATTR_FLOP_DP_PER_CYCLE gives peak double precision flop per cycle for the GPU.
- Two new metric properties are added:
 - ► CUPTI_METRIC_PROPERTY_FLOP_SP_PER_CYCLE gives peak single precision flop per cycle for the GPU.
 - ► CUPTI_METRIC_PROPERTY_FLOP_DP_PER_CYCLE gives peak double precision flop per cycle for the GPU.
- Activity record CUpti_ActivityGlobalAccess for source level global access information has been deprecated and replaced by new activity record CUpti_ActivityGlobalAccess2. New record additionally gives information

- needed to map SASS assembly instructions to CUDA C source code. And it also provides ideal L2 transactions count based on the access pattern.
- Activity record CUpti_ActivityBranch for source level branch information has been deprecated and replaced by new activity record CUpti_ActivityBranch2. New record additionally gives information needed to map SASS assembly instructions to CUDA C source code.
- ▶ Sample sass_source_map is added to demonstrate the mapping of SASS assembly instructions to CUDA C source code.
- ► Default event collection mode is changed to Kernel (CUPTI_EVENT_COLLECTION_MODE_KERNEL) from Continuous (CUPTI_EVENT_COLLECTION_MODE_CONTINUOUS). Also Continuous mode is now supported only on Tesla devices.
- Profiling results might be inconsistent when auto boost is enabled. Profiler tries to disable auto boost by default, it might fail to do so in some conditions, but profiling will continue. A new API cuptiGetAutoBoostState is added to query the auto boost state of the device. This API returns error CUPTI_ERROR_NOT_SUPPORTED on devices that don't support auto boost. Note that auto boost is supported only on certain Tesla devices from the Kepler+ family.
- Activity record CUpti_ActivityKernel2 for kernel execution has been deprecated and replaced by new activity record CUpti_ActivityKernel3. New record additionally gives information about Global Partitioned Cache Configuration requested and executed. The new fields apply for devices with 5.2 Compute Capability.

CUPTI changes in CUDA 6.0

List of changes done as part of the CUDA Toolkit 6.0 release.

- Two new CUPTI activity kinds have been introduced to enable two new types of source-correlated data collection. The Instruction Execution kind collects SASS-level instruction execution counts, divergence data, and predication data. The Shared Access kind collects source correlated data indication inefficient shared memory accesses.
- ► CUPTI now provides support for CUDA applications using Unified Memory. A new activity record reports Unified Memory activity such as transfers to and from a GPU and the number of Unified Memory related page faults.
- CUPTI now recognized and reports the special MPS context that is used by CUDA applications running on a system with MPS enabled.
- ► The CUpti_ActivityContext activity record CUpti_ActivityContext has been updated to introduce a new field into the structure in a backwards compatible manner. The 32-bit computeApiKind field was replaced with two 16 bit fields, computeApiKind and defaultStreamId. Because all valid computeApiKind values fit within 16 bits, and because all supported CUDA platforms are little-endian, persisted context record data read with the new structure

- will have the correct value for computeApiKind and have a value of zero for defaultStreamId. The CUPTI client is responsible for versioning the persisted context data to recognize when the defaultStreamId field is valid.
- To ensure that metric values are calculated as accurately as possible, a new metric API is introduced. Function <code>cuptiMetricGetRequiredEventGroupSets</code> can be used to get the groups of events that should be collected at the same time.
- Execution overheads introduced by CUPTI have been dramatically decreased.
- ▶ The new activity buffer API introduced in CUDA Toolkit 5.5 is now required. The legacy cuptiActivityEnqueueBuffer and cuptiActivityDequeueBuffer functions have been removed.

CUPTI changes in CUDA 5.5

List of changes done as part of CUDA Toolkit 5.5 release.

- ► Applications that use CUDA Dynamic Parallelism can now be profiled using CUPTI. Device-side kernel launches are reported using a new activity kind.
- ▶ Device attributes such as power usage, clocks, thermals, etc. are now reported via a new activity kind.
- A new activity buffer API uses callbacks to request and return buffers of activity records. The existing cuptiActivityEnqueueBuffer and cuptiActivityDequeueBuffer functions are still supported but are deprecated and will be removed in a future release.
- ► The Event API supports kernel replay so that any number of events can be collected during a single run of the application.
- A new metric API cuptiMetricGetValue2 allows metric values to be calculated for any device, even if that device is not available on the system.
- ► CUDA peer-to-peer memory copies are reported explicitly via the activity API. In previous releases these memory copies were only partially reported.

Notice

ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NONINFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE.

Information furnished is believed to be accurate and reliable. However, NVIDIA Corporation assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use. No license is granted by implication of otherwise under any patent rights of NVIDIA Corporation. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all other information previously supplied. NVIDIA Corporation products are not authorized as critical components in life support devices or systems without express written approval of NVIDIA Corporation.

Trademarks

NVIDIA and the NVIDIA logo are trademarks or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated.

Copyright

© 2007-2016 NVIDIA Corporation. All rights reserved.

