







Wall Length (300mm Cavity)		
	Standard External Insulated Cavity Wall - 0.24W/m ² K 102.5mm facing brickwork 100mm cavity filled with blown mineral fibre insulation* 100mm aerated concrete block, K-value 0.11W/m ² K, min strength 2.9N/mm ² 12.5mm gypsum board on adhesive dabs	
	Mid Strength External Insulated Cavity Wall - 0.25W/m ² K 102.5mm facing brickwork 100mm cavity filled with blown mineral fibre insulation* 100mm aerated concrete block, K-value 0.15W/m ² K, min strength 3.6N/mm ² 12.5mm gypsum board on adhesive dabs	
	High Strength External Insulated Cavity Wall - 0.26W/m ² K 102.5mm facing brickwork 100mm cavity filled with blown mineral fibre insulation* 100mm aerated concrete block, K-value 0.19W/m ² K, min strength 7.3N/mm ² 12.5mm gypsum board on adhesive dabs	
	External Uninsulated Cavity Wall (to garage, cold roof space etc.) 102.5mm facing brickwork 100mm air cavity 100mm aerated concrete block min strength 2.9N/mm ²	
	Party Wall 100mm aerated concrete block, with density range between 600-800kg/m 100mm Party Wall blown glass mineral wool insulation 100mm aerated concrete block, with density range between 600-800kg/m 12.5mm gypsum board on adhesive dabs	3
	Internal Blockwork Partition Between Dwelling and Garage 100mm aerated concrete block min strength 2.9N/mm ² 63mm British Gypsum Thermaline PIR Plasterboard on adhesive dabs	3
	Internal Blockwork Partition 12.5mm gypsum board on adhesive dabs 100mm aerated concrete block min strength 2.9N/mm ² 12.5mm gypsum board on adhesive dabs	
	Structural Stud Partition 12.5mm gypsum board 12.5mm OSB2 sheathing 63 x 38mm timber studs (studs and noggings rotated through 90°) 12.5mm gypsum board 12.5mm OSB2 sheathing	
	Non-Load Bearing Stud Partition 12.5mm gypsum board 63 x 38mm timber studs 12.5mm gypsum board	
	Stud Partition with Acoustic Insulation 12.5mm gypsum board 63 x 38mm timber studs, with 50mm thick Isover APR 1200 acoustic insulation packed between 12.5mm gypsum board	
Note:- all blockwork drawn blue to be 7.3N/mm ² as per Structural Engineers comments. Refer to relevant Construction Specification for either 2013 and 2021 Build regs for further details For Country Type (CT), Country Weatherboard (CW) and Town Type (TT), external skin to be 3.6N/mm ² lightweight aggregate blocks to areas which are to receive alternative external treatment only. This drawing must be read in conjunction with 25 series drawings.		
* For Welsh Properties, substitute blown mineral fibre with 0.022W/mK 90mm thick PIR board.		

CONSTRUCTION

Bellway

www.bellway.co.uk

Bellway Homes (Eastern Counties)

Building 2030, Cambourne Business Park,

Cambridgeshire CB23 6DW

Tel: 01480 425 200

Project

Somersham

St Ives Road

Working Drawings

Drawing Title


The Fuller Life

FRL-3B-2S-AT

1053 ft² | 3b Det (Corner Turner) | All Traditional Variants

First Floor Setting Out Plan

Drawing Created By	First Issue Date	Scale(s)
Group	April '25	1 : 50
Project No	Drg Status	Revision
BI01	Construction	C1
Drawing No.	BI01/1053FRL/10/AT/02	



Plots 20, 23 (OPP)

[illegible]