

Revision Schedule			
Rev	Date	Description	Drn By
C1	02.12.25	Construction Issue	C1

Substructure Wall Legend (100mm Cavity)

	Standard External Insulated Cavity Wall (Below Ground) 100mm blocks (3.6N/mm²) upto 150mm below external ground level, then class B engineering brickwork (102.5mm) to DPC level 100mm cavity with expanded polystyrene board (thermal conductivity 0.038 W/m²/K) 100mm aerated concrete block / coursing bricks (3.6N/mm²)
	External Uninsulated Cavity Wall (To Garage etc - Below Ground) 100mm blocks (3.6N/mm²) upto 150mm below external ground level, then class B engineering brickwork (102.5mm) to DPC level 100mm cavity 100mm aerated concrete block / coursing bricks (3.6N/mm²)
	Party Wall (Below Ground) 100mm aircrete block (3.6N/mm²) 100mm cavity with expanded polystyrene board (thermal conductivity 0.038 W/m²/K) 100mm aircrete block (3.6N/mm²)
	Internal Blockwork Partition (Below Ground) 100mm aerated concrete block (3.6N/mm²) (Suspended ground floor beam manufacturer's coursing blocks / bricks as required)
	Sleeper Wall 100mm aerated concrete block (3.6N/mm²) to underside of suspended ground floor beams

Refer to current Construction Specification for further details

NB. FOR RWP LOCATIONS REFER TO CIVIL ENGINEER'S DRAWINGS.



TENDER

www.bellway.co.uk

Bellway Homes Limited (Eastern Counties)

Building 2030, Cambourne Business Park
Cambourne, Cambridgeshire, CB23 6DW

Tel: 01480 425200

Project

Somersham

St Ives Road

Working Drawings

Drawing Title

The Halstead

630 ft² | 1b Semi-Det | Country Brick

Substructure Plan

Drawing Created By	First Issue Date	Scale(s)
FDL	28.03.25	1 : 50
Project No	Drq Status	Revision
BI01		C1
Drawing No.	BI01 /630 HA / 30 / 01	

Do not scale - if in doubt, ask

1 Substructure Plan
1 : 50