AirTutor: Adaptive Pedagogical Decision System

Comprehensive Project Research, Implementation & Evaluation Report

Authoritative Spec: docs/research_roadmap_v2.md | **Runtime:** Python 3.11+, CPU-Only (8 GB RAM) | **Test Suite:** 86/86 Passed (100%)
Date: September 2026 | **Architecture:** Tabular Q-Learning (Research Core) + Decoupled LLM Delivery Layer

1. Executive Summary & Core Research Identity

AirTutor is an academic research artifact investigating whether **Reinforcement Learning (RL)** can learn an optimal pedagogical intervention policy under partial observability. In contemporary AI tutoring systems, LLMs are frequently tasked with making pedagogical choices implicitly via unstructured prompts, leading to inconsistent instructional strategies, lack of transparent policy control, and reward-hacking. AirTutor enforces a strict architectural paradigm: **the RL policy is the sole pedagogical decision-maker**, while a completely decoupled **Large Language Model (LLM) serves strictly as a delivery layer**.

The Core Research Invariant: The RL policy conditions *strictly* on a 5-feature observable state vector (320 discrete states) derived from interaction history. The agent never observes the student's true latent parameters ($\theta = [\alpha, \beta, \gamma, h, \tau, \sigma]$) or simulator-internal ground-truth mastery. If the student's behavior changes, the RL policy switches its pedagogical action (EXPLAIN, EXAMPLE, HINT, PRACTICE, REVIEW_PREREQUISITE), and only then does an LLM render that action into structured educational dialogue.

2. Original Implementation Plan vs. Delivered Reality

The project specification is defined in **docs/research_roadmap_v2.md** (43 sections). It phased the development into 7 milestone stages (Stage 0 to Stage 6). **Are we completely developed? YES. 100% of Stages 0 through 6 are fully developed, verified, tested, and benchmarked**. All 86 unit, integration, POMDP barrier, and UI tests pass cleanly, and all publication-grade experiment outputs have been generated.

Stage	Milestone & Scope	Key Deliverables Implemented	Status
Stage 0	Repo Scaffold & Mechanical RL Loop	Toy MDP chain, Tabular Q-learning agent, Bellman updates, git repo, tests.	**100% Complete** (3 tests)
Stage 1	Curriculum, Learner Model & Simulator	GATE CS curriculum schema, 6-trait learner population (θ), smooth dynamics, 5 automated sanity checks.	**100% Complete** (16 tests)
Stage 2	Observable State, Baselines & Metrics	5-feature state encoder (320 states), Random/Fixed/Rule baseline teachers, 6 core evaluation metrics.	**100% Complete** (16 tests)
Stage 3	Tabular Q-Agent & Held-Out Benchmark	Reward v1, tabular training loop across 5 seeds, disjoint held-out evaluation (100 learners), statistical tests.	**100% Complete** (6 tests)
Stage 4	Reward v2/v3, Robustness & Ablations	Reward v2/v3 formulations, 12-axis parameter sensitivity sweep, state/reward/population ablations, 5 publication plots.	**100% Complete** (8 tests)
Stage 5	Flexible LLM Layer & Extensibility	Provider-agnostic LLM interface (Gemini, OpenAI, Offline fallback), schema validation, Add Material notes ingestion.	**100% Complete** (19 tests)
Stage 6	Streamlit UI, Packaging & Documentation	4-tab interactive Streamlit UI (Tutoring, Policy Inspection, Benchmarks, Add Material), README, methodology, logs.	**100% Complete** (3 UI tests)

3. Deep System Architecture & Theoretical Formalism

AirTutor operates as a **Partially Observable Markov Decision Process (POMDP)**. To ensure strict scientific validity and hardware efficiency (running on CPU with 8 GB RAM), the POMDP is solved via tabular Q-learning over a discretized observable feature space:

3.1 Observable State Space (|S| = 320):

The state encoder maps student interaction history to a 5-tuple: (b_m, c_last, acc_3, s_err, h):
• **b_m (Estimated Mastery Bucket):** 5 intervals ([0.0, 0.2), ..., [0.8, 1.0]) computed by observable learner model.
• **c_last (Last Response Correctness):** Binary ({0, 1}).
• **acc_3 (Recent Accuracy):** Correct answers across last 3 attempts ({0, 1, 2, 3}).
• **s_err (Error Streak):** Consecutive incorrect responses capped at 3+ ({0, 1, 2, 3+}).
• **h (Hint Used on Prior Step):** Binary indicator ({0, 1}).
Total state count: **5 × 2 × 4 × 4 × 2 = 320 discrete states**.

3.2 Pedagogical Action Space (|A| = 5):

• EXPLAIN: Conceptual exposition introducing underlying principles.
• EXAMPLE: Worked code example demonstrating concrete application.
• HINT: Scaffolding clue targeted at the active assessment item.
• PRACTICE: Formative assessment question (MCQ, short-answer, or code completion).
• REVIEW_PREREQUISITE: Remedial revision of foundational prerequisite concept.

3.3 Reward Evolution Across Stages:

• **Reward v1 (Mastery Delta):** r_t = M_hat(c, t+1) - M_hat(c, t). Optimizes immediate gains but risks over-explaining.
• **Reward v2 (Retention & Cost Aware):** Adds retention signals across unpracticed concepts and penalizes step costs.
• **Reward v3 (Transfer & Balanced Penalties):** Incorporates prerequisite transfer credit and explicit penalties for excessive hints and wasted steps.

3.4 Behavioral Verification of the POMDP Information Barrier:

The implemented information barrier is behaviorally tested for the verified execution paths, with dedicated tests preventing latent-state leakage into the tabular RL policy. In tests/test_pomdp_barrier.py, simulated learners with vastly different true latent mastery and divergent latent parameter vectors θ are subjected to identical observable interaction sequences. The tests verify that the observable state encoder, teacher observation, discrete state indices, and policy action selections remain strictly identical. Dedicated tests likewise verify identical 14-D states and policy selections for the optional continuous DQN agent, ensuring that latent learner traits never leak into the decision layer.

4. What We Have in Our Output: Benchmark Findings & Empirical Results

All experimental benchmarks were conducted on **N = 100 held-out simulated learners** sampled from seed range [10000, 10100), which is **strictly disjoint** from the training cohort (seeds [0, 300)). The standing research rule was enforced: baseline strength and simulator parameters were never modified post-hoc.

4.1 Primary Benchmark: RL vs. Baseline Pedagogical Teachers (Stage 3)

Pedagogical Teacher	Observable Gain (ΔM_hat)	True Latent Gain (ΔM)	Intervention Efficiency	Hint Rate	Action Entropy
Random (Uniform exploration)	+0.0194 ± 0.0546	+0.0842 ± 0.1103	0.0006	21.8%	2.23 bits
Fixed (Explain → Practice)	-0.0566 ± 0.0345	+0.0686 ± 0.1308	-0.0019	0.0%	1.00 bits
Rule Baseline (Adaptive Scaffolding)	+0.0520 ± 0.1041	+0.2632 ± 0.1823	0.0017	6.3%	1.08 bits
RL Agent (Tabular Q)	**+0.1146 ± 0.0766**	**+0.2276 ± 0.1714**	**0.0038**	**13.3%**	**1.51 bits**

Statistical Analysis & POMDP Trade-Off: The RL policy achieves more than double the observable learning gain of the Rule baseline (**+0.1146 vs +0.0520**, $p < 10^{-15}$) and **2.2× higher** intervention efficiency (0.0038 vs 0.0017). On true latent gain, the Rule teacher achieves +0.2632 vs RL's +0.2276, reflecting the POMDP information barrier where the agent optimizes observable progress without access to the student's true latent parameters θ.

Figure 1: Held-Out Learning Gain Comparison Across Pedagogical Teachers (with ±1σ error bars)





Figure 2: RL Training Convergence Across 5 Independent Random Seeds (±1σ shaded error band)



4.2 Reward & State Ablations: Qualitative & Quantitative Discoveries

• **Reward Formulation Shifts:** Under Reward v1 (pure delta), the policy relies almost exclusively on EXPLAIN (61.4%) and EXAMPLE (26.1%), with negligible PRACTICE (1.7%). Under Reward v2/v3, incorporating intervention costs and retention signals increases PRACTICE frequency to **10.8%** and HINT to **6.2%**, creating a balanced pedagogical curriculum.
• **Recent Accuracy is Load-Bearing:** Removing recent accuracy drops observable gain by **-0.023** and efficiency from 0.0030 to 0.0022.
• **Hint Awareness Prevents False Optimism:** Ablating hint awareness causes apparent observable gain to falsely rise (+0.102) while true latent gain drops (-0.025). The agent overestimates student independence when hint flags are hidden.
• **Population Diversity:** Training on narrow θ bounds (±10%) drops held-out generalization by **-0.021** true gain.

Figure 3: Reward Formulation Ablation (Learning Gains vs. Action Selection Distribution Shifts)






Figure 4: State Feature Ablation Δ vs. Full State Representation (320 States)



4.3 12-Axis Sensitivity Sweep: Empirical Robustness & Boundary Conditions

To test Hypothesis H3 (investigating whether the RL advantage is an artifact of narrow simulator tuning), we conducted a 12-axis parameter perturbation sweep (α ±20%, β ±20%, noise σ ±50%, intervention power ±20%, high hint dependence skew, curriculum difficulty ±1.0). **Result: The RL advantage holds across 11 of 12 axes (Δ ≥ +0.051). Under the Harder Curriculum condition (+1.0 difficulty offset), the advantage vanishes (Δ = -0.0075, status: Vanishes)**, identifying an important regime where severe student struggle constraints give the heuristic rule baseline parity or slight advantage.

Figure 5: 12-Axis Robustness & Sensitivity Sweep (RL Advantage Δ over Rule Baseline across ±20% Parameter Shifts)



5. What We Can Do With the Output: Operational Capabilities

The deliverables produced by AirTutor enable multiple immediate practical, operational, and research applications:

Capability Area	Operational Workflow & Practical Utility
1. Interactive AI Tutoring Session (Streamlit Tab 1)	Students or evaluators interact in real time with an adaptive tutor. When a student answers incorrectly, the learner model decrements mastery, the state encoder recalculates the 320-state index, the RL policy selects the optimal pedagogical intervention, and the LLM renders targeted feedback, hints, or code examples.
2. Transparent Policy Inspection (Streamlit Tab 2)	Unlike opaque end-to-end LLM tutors, AirTutor provides 100% white-box transparency. Evaluators can inspect the exact Q-values $Q(s, a)$ for all 5 actions, read the policy rationale, and use the interactive 'What-If' state explorer to simulate any student behavioral condition.
3. Curriculum Extensibility (Streamlit Tab 4)	Educators can paste unstructured lecture notes or syllabus outlines. The system invokes an LLM schema transformation pipeline with automated validation (DAG acyclicity, MCQ syntax, code stubs) to generate brand-new JSON curriculum modules that instantly plug into the RL environment.
4. Academic Publishing & Benchmarking (Evaluation Suite)	Provides turnkey generation of publication-grade figures, LaTeX statistical comparison tables, bootstrap 95% CIs, and complete reproducibility packages (commit hash, seeds, configs) under experiments/.
5. Zero-Cost Offline Deployment (Delivery Layer)	Without configured API credentials, the application uses the offline template adapter by default; live external LLM calls were not part of this verification. Pre-written pedagogical templates ensure reproducible, headless benchmarking and demonstration with zero external API dependencies.

6. Critical Analysis: Drawbacks, Limitations & Honest Accounting

Per Section 37 and 39 of the research roadmap, maintaining rigorous scientific integrity requires an explicit, honest accounting of project limitations and threats to validity:

1. **Synthetic Simulator Realism (The Sim-to-Real Gap):** The learner population is generated via a 6-parameter vector ($\theta = [\alpha, \beta, \gamma, h, \tau, \sigma]$) governed by logistic response probability curves. While continuous, smooth, and validated through 5 monotonic sanity checks, real human learning entails complex cognitive phenomena (fatigue, frustration, spaced repetition consolidation, and metacognitive biases) not fully captured by synthetic distributions.
2. **Tabular State-Space Discretization Boundary:** To ensure CPU-only execution and high interpretability, the state space is discretized into 320 states. While optimal for single-module mastery, tabular Q-learning cannot generalize across unseen continuous states without function approximation. Expanding to full degree curricula will require moving to Deep Q-Networks (DQN) or Actor-Critic methods.
3. **Population-Average vs. Individualized Policy:** The policy learns an optimal strategy for the *average population* of learners. It does not perform in-session personalized meta-learning (e.g., dynamically estimating a specific student's learning rate α and tailoring action selection to that individual's unique cognitive profile).
4. **LLM Generation Variability & Hallucination:** Although the LLM has zero decision-making power, the delivery layer is subject to the stochastic nature of generative models. In online mode, different LLM providers (Gemini vs. OpenAI vs. local models) may render explanations with varying pedagogical tone, verbosity, or occasional code inaccuracies.
5. **Ethical Deployment Constraint:** AirTutor is a **research prototype** providing *preliminary simulated evidence*. Under no circumstance should this system be deployed in high-stakes accredited educational settings without human oversight and institutional review (IRB).

7. Future Research Horizons (Levels 2–6)

Roadmap Section 40 designates the following progressive research horizons beyond Stage 6:

Level	Research Extension	Target Scientific Breakthrough
Level 2	**Knowledge Tracing**	Replace the heuristic learner model (η=0.20, δ=0.01) with Bayesian Knowledge Tracing (BKT) or Deep Knowledge Tracing (DKT).
Level 3	**Personalized Policies**	Incorporate estimated learner traits into the state space to learn individualized pedagogical policies.
Level 4	**Unseen-Learner Adaptation**	Meta-learning and contextual bandits for rapid in-session adaptation to outlier learner profiles within 5–10 steps.
Level 5	**Counterfactual Evaluation**	Off-policy evaluation (OPE) via doubly robust estimators on logged student interaction trajectories.
Level 6	**Real-User Pilot Study**	IRB-approved randomized controlled trial with human engineering students comparing AirTutor against standard LMS platforms.

8. Final Verdict & Academic Checklist

AirTutor successfully completes all 16 items of the authoritative Research Checklist (Roadmap Sec. 43). The project delivers a fully working, reproducible, lightweight, and empirically evaluated adaptive tutoring prototype. The codebase is modular, clean, and ready for academic inspection, demonstration, and future extension.

Final Assessment:

- **Implementation Plan Completion:** 100% of Stages 0–6 fully delivered.
- **Empirical Hypothesis H1:** Supported (RL beats Rule baseline with $p < 10^{-15}$, Cohen's $d = 1.396$).
- **Empirical Hypothesis H2:** Supported (Reward v2/v3 prevents over-explaining and restores formative practice).
- **Empirical Hypothesis H3:** Supported across 11 of 12 parameter axes with $\Delta \geq +0.052$; under Harder Curriculum, the advantage vanishes ($\Delta = -0.0075$, status: Vanishes).
- **Software Artifacts:** Streamlit GUI, 86 passing pytest tests, 5 publication figures, and decoupled LLM layer.