```
In [123]:
.....
ISYE6501: US Army optimization problem with PuLP Modeller
Author: Guillermo de la Hera Casado
Optimization Model Specs:
Variables: amount of servings for each food type.
Constraints: there will be a min and max intake value for each property (cals, fat, sodium...,
across all the foods selected in the diet.
Objective Function: minimize the total cost of the diet, defined as the serving cost of each food
involved in the diet * cost per
serving on that particular food.
Code and solution as per below:
# Import pulp and pandas
from pulp import
import pandas as pd
import csv
import pprint
foodData = pd.read excel("diet.xls")
foodData = foodData[0:64]
foodData = foodData.values.tolist()
foods = [x[0] for x in foodData]
#create a dictionary for the cost of the foods
cost = dict([(x[0], float(x[1])) for x in foodData])
cals = dict([(x[0], float(x[3])) for x in foodData])
cho = dict([(x[0], float(x[4])) for x in foodData])
fat = dict([(x[0], float(x[5])) for x in foodData])
sodium = dict([(x[0], float(x[6])) for x in foodData])
carbo = dict([(x[0], float(x[7])) for x in foodData])
fiber = dict([(x[0], float(x[8])) for x in foodData])
protein = dict([(x[0], float(x[9])) for x in foodData])
vitA = dict([(x[0], float(x[10])) for x in foodData])
vitC = dict([(x[0], float(x[11])) for x in foodData])
calcium = dict([(x[0], float(x[12])) for x in foodData])
iron = dict([(x[0], float(x[13])) for x in foodData])
#we define the optimization problem by giving it a name and letting it know we are minimizing
problem = LpProblem("Diet Problem", LpMinimize)
#we define our primary variables (the amount of each food in the diet)
amountVars = LpVariable.dicts("Amounts", foods, 0)
#we add the objective function to the problem, inner product of cost and amountVars
problem += lpSum([cost[i] * amountVars[i] for i in foods]), "total cost"
#next, we hard core all the constraints
problem += lpSum([cals[i] * amountVars[i] for i in foods]) >=1500, 'min cals'
problem += lpSum([cals[i] * amountVars[i] for i in foods]) <=2500, 'max cals'</pre>
problem += lpSum([cho[i] * amountVars[i] for i in foods]) >=30, 'min cho'
problem += lpSum([cho[i] * amountVars[i] for i in foods]) <=240, 'max cho'</pre>
problem += lpSum([fat[i] * amountVars[i] for i in foods]) >=20, 'min fat'
problem += lpSum([fat[i] * amountVars[i] for i in foods]) <=70, 'max fat'</pre>
problem += lpSum([sodium[i] * amountVars[i] for i in foods]) >=800, 'min sodium'
problem += lpSum([sodium[i] * amountVars[i] for i in foods]) <=2000, 'max sodium'</pre>
problem += lpSum([carbo[i] * amountVars[i] for i in foods]) >=130, 'min carbo'
problem += lpSum([carbo[i] * amountVars[i] for i in foods]) <=450, 'max carbo'</pre>
problem += lpSum([fiber[i] * amountVars[i] for i in foods]) >=125, 'min fiber'
```

```
problem += lpSum([fiber[i] * amountVars[i] for i in foods]) <=250, 'max fiber'</pre>
problem += lpSum([protein[i] * amountVars[i] for i in foods]) >=60, 'min protein'
problem += lpSum([protein[i] * amountVars[i] for i in foods]) <=100, 'max protein'</pre>
problem += lpSum([vitA[i] * amountVars[i] for i in foods]) >=1000, 'min vitA'
problem += lpSum([vitA[i] * amountVars[i] for i in foods]) <=10000, 'max vitA'</pre>
problem += lpSum([vitC[i] * amountVars[i] for i in foods]) >=400, 'min vitC'
problem += lpSum([vitC[i] * amountVars[i] for i in foods]) <=5000, 'max vitC'</pre>
problem += lpSum([calcium[i] * amountVars[i] for i in foods]) >=700, 'min calcium'
problem += lpSum([calcium[i] * amountVars[i] for i in foods]) <=1500, 'max calcium'</pre>
problem += lpSum([iron[i] * amountVars[i] for i in foods]) >=10, 'min iron'
problem += lpSum([iron[i] * amountVars[i] for i in foods]) <=40, 'max iron'</pre>
#we solve the problem
problem.solve()
#print out amount values from optimal solution
varsDictionary = {}
for v in problem.variables():
    if v.varValue>0:
       varsDictionary[v.name] = v.varValue
#print(varsDictionary)
pprint.pprint(varsDictionary)
{'Amounts Celery, Raw': 52.64371,
 'Amounts Frozen Broccoli': 0.25960653,
 'Amounts_Lettuce, Iceberg, Raw': 63.988506,
 'Amounts Oranges': 2.2929389,
 'Amounts Poached Eggs': 0.14184397,
 'Amounts Popcorn, Air Popped': 13.869322}
```

In [70]:

```
2a) adding the constraint for minimum 1/10 serving when a food is selected
#we define the optimization problem by giving it a name and letting it know we are minimizing
problem = LpProblem("Diet Problem", LpMinimize)
#we define our primary variables (the amount of each food in the diet)
amountVars = LpVariable.dicts("Amounts", foods, 0)
binaryVars = LpVariable.dicts("InorOut", foods, 0, 1, LpBinary)
#we add the objective function to the problem, inner product of cost and amountVars
problem += lpSum([cost[i] * amountVars[i] for i in foods]), "total cost"
#next, we hard core all the constraints
problem += lpSum([cals[i] * amountVars[i] for i in foods]) >=1500, 'min cals'
problem += lpSum([cals[i] * amountVars[i] for i in foods]) <=2500, 'max cals'</pre>
problem += lpSum([cho[i] * amountVars[i] for i in foods]) >=30, 'min cho'
problem += lpSum([cho[i] * amountVars[i] for i in foods]) <=240, 'max cho'</pre>
problem += lpSum([fat[i] * amountVars[i] for i in foods]) >=20, 'min fat'
problem += lpSum([fat[i] * amountVars[i] for i in foods]) <=70, 'max fat'</pre>
problem += lpSum([sodium[i] * amountVars[i] for i in foods]) >=800, 'min sodium'
problem += lpSum([sodium[i] * amountVars[i] for i in foods]) <=2000, 'max sodium'</pre>
problem += lpSum([carbo[i] * amountVars[i] for i in foods]) >=130, 'min carbo'
problem += lpSum([carbo[i] * amountVars[i] for i in foods]) <=450, 'max carbo'</pre>
problem += lpSum([fiber[i] * amountVars[i] for i in foods]) >=125, 'min fiber'
problem += lpSum([fiber[i] * amountVars[i] for i in foods]) <=250, 'max fiber'</pre>
problem += lpSum([protein[i] * amountVars[i] for i in foods]) >=60, 'min protein'
```

```
problem += ipsum([protein[i] * amountvars[i] for 1 in ioods]) <=iUU, 'max protein'</pre>
problem += lpSum([vitA[i] * amountVars[i] for i in foods]) >=1000, 'min vitA'
problem += lpSum([vitA[i] * amountVars[i] for i in foods]) <=10000, 'max vitA'</pre>
problem += lpSum([vitC[i] * amountVars[i] for i in foods]) >=400, 'min vitC'
problem += lpSum([vitC[i] * amountVars[i] for i in foods]) <=5000, 'max vitC'</pre>
problem += lpSum([calcium[i] * amountVars[i] for i in foods]) >=700, 'min calcium'
problem += lpSum([calcium[i] * amountVars[i] for i in foods]) <=1500, 'max calcium'</pre>
problem += lpSum([iron[i] * amountVars[i] for i in foods]) >=10, 'min iron'
problem += lpSum([iron[i] * amountVars[i] for i in foods]) <=40, 'max iron'</pre>
for i in foods:
    problem += amountVars[i]>= binaryVars[i]*0.1
    problem += amountVars[i] <= binaryVars[i] *1e5</pre>
    problem += amountVars[i] >= 1/10*binaryVars[i]
#we solve the problem
problem.solve()
#print out amount values from optimal solution
varsDictionary = {}
for v in problem.variables():
     if v.varValue>0:
        varsDictionary[v.name] = v.varValue
#print(varsDictionary)
pprint.pprint(varsDictionary)
{'Amounts Celery, Raw': 52.64371,
 'Amounts Frozen Broccoli': 0.25960653,
 'Amounts Lettuce, Iceberg, Raw': 63.988506,
 'Amounts Oranges': 2.2929389,
 'Amounts_Poached_Eggs': 0.14184397,
 'Amounts Popcorn, Air Popped': 13.869322,
 'InorOut_Celery,_Raw': 1.0,
 'InorOut Frozen Broccoli': 1.0,
 'InorOut Lettuce, Iceberg, Raw': 1.0,
 'InorOut_Oranges': 1.0,
 'InorOut Poached Eggs': 1.0,
 'InorOut_Popcorn,Air_Popped': 1.0}
In [79]:
2b) Many people dislike brocoli and celery. At most one, but not both can be selected
#we define the optimization problem by giving it a name and letting it know we are minimizing
problem = LpProblem("Diet Problem", LpMinimize)
#we define our primary variables (the amount of each food in the diet)
amountVars = LpVariable.dicts("Amounts", foods, 0)
binaryVars = LpVariable.dicts("InorOut", foods, 0, 1, LpBinary)
#we add the objective function to the problem, inner product of cost and amountVars
problem += lpSum([cost[i] * amountVars[i] for i in foods]), "total cost"
#next, we hard core all the constraints
problem += lpSum([cals[i] * amountVars[i] for i in foods]) >=1500, 'min cals'
problem += lpSum([cals[i] * amountVars[i] for i in foods]) <=2500, 'max cals'</pre>
problem += lpSum([cho[i] * amountVars[i] for i in foods]) >=30, 'min cho'
problem += lpSum([cho[i] * amountVars[i] for i in foods]) <=240, 'max cho'</pre>
problem += lpSum([fat[i] * amountVars[i] for i in foods]) >=20, 'min fat'
problem += lpSum([fat[i] * amountVars[i] for i in foods]) <=70, 'max fat'</pre>
problem += lpSum([sodium[i] * amountVars[i] for i in foods]) >=800, 'min sodium'
problem += lpSum([sodium[i] * amountVars[i] for i in foods]) <=2000, 'max sodium'</pre>
problem += lpSum([carbo[i] * amountVars[i] for i in foods]) >=130, 'min carbo'
problem += lpSum([carbo[i] * amountVars[i] for i in foods]) <=450, 'max carbo'</pre>
```

```
problem += lpSum([fiber[i] * amountVars[i] for i in foods]) >=125, 'min fiber'
problem += lpSum([fiber[i] * amountVars[i] for i in foods]) <=250, 'max fiber'</pre>
problem += lpSum([protein[i] * amountVars[i] for i in foods]) >=60, 'min protein'
problem += lpSum([protein[i] * amountVars[i] for i in foods]) <=100, 'max protein'</pre>
problem += lpSum([vitA[i] * amountVars[i] for i in foods]) >=1000, 'min vitA'
problem += lpSum([vitA[i] * amountVars[i] for i in foods]) <=10000, 'max vitA'</pre>
problem += lpSum([vitC[i] * amountVars[i] for i in foods]) >=400, 'min vitC'
problem += lpSum([vitC[i] * amountVars[i] for i in foods]) <=5000, 'max vitC'</pre>
problem += lpSum([calcium[i] * amountVars[i] for i in foods]) >=700, 'min calcium'
problem += lpSum([calcium[i] * amountVars[i] for i in foods]) <=1500, 'max calcium'</pre>
problem += lpSum([iron[i] * amountVars[i] for i in foods]) >=10, 'min iron'
problem += lpSum([iron[i] * amountVars[i] for i in foods]) <=40, 'max iron'</pre>
for i in foods:
    problem += amountVars[i]>= binaryVars[i]*0.1
    problem += amountVars[i] <= binaryVars[i] *1e5</pre>
problem += binaryVars['Frozen Broccoli'] + binaryVars['Celery, Raw'] <=1</pre>
#we solve the problem
problem.solve()
#print out amount values from optimal solution
varsDictionary = {}
for v in problem.variables():
     if v.varValue>0:
        varsDictionary[v.name] = v.varValue
#print(varsDictionary)
pprint.pprint(varsDictionary)
{'Amounts_Celery,_Raw': 43.154119,
 'Amounts Lettuce, Iceberg, Raw': 80.919121,
 'Amounts Oranges': 3.0765161,
 'Amounts Peanut Butter': 2.0464575,
 'Amounts Poached Eggs': 0.14184397,
 'Amounts_Popcorn, Air_Popped': 13.181772,
 'InorOut_Celery,_Raw': 1.0,
 'InorOut Lettuce, Iceberg, Raw': 1.0,
 'InorOut_Oranges': 1.0,
 'InorOut Peanut Butter': 1.0,
 'InorOut_Poached_Eggs': 1.0,
 'InorOut_Popcorn,Air_Popped': 1.0}
In [90]:
.....
2c) at least 3 kinds of meat/poultry/fish/eggs must be selected
#we define the optimization problem by giving it a name and letting it know we are minimizing
problem = LpProblem("Diet Problem", LpMinimize)
#we define our primary variables (the amount of each food in the diet)
amountVars = LpVariable.dicts("Amounts", foods, 0)
selectionVars = LpVariable.dicts("InorOut", foods, 0, 1, LpBinary)
isProtein = dict([(x[0], 0) for x in foodData])
#we add the objective function to the problem, inner product of cost and amountVars
problem += lpSum([cost[i] * amountVars[i] for i in foods]), "total cost"
#next, we hard core all the constraints
problem += lpSum([cals[i] * amountVars[i] for i in foods]) >=1500, 'min cals'
problem += lpSum([cals[i] * amountVars[i] for i in foods]) <=2500, 'max cals'</pre>
problem += lpSum([cho[i] * amountVars[i] for i in foods]) >=30, 'min cho'
problem += lpSum([cho[i] * amountVars[i] for i in foods]) <=240, 'max cho'</pre>
problem += lpSum([fat[i] * amountVars[i] for i in foods]) >=20, 'min fat'
```

```
problem += lpSum([fat[i] * amountVars[i] for i in foods]) <=70, 'max fat'</pre>
problem += lpSum([sodium[i] * amountVars[i] for i in foods]) >=800, 'min sodium'
problem += lpSum([sodium[i] * amountVars[i] for i in foods]) <=2000, 'max sodium'</pre>
problem += lpSum([carbo[i] * amountVars[i] for i in foods]) >=130, 'min carbo'
problem += lpSum([carbo[i] * amountVars[i] for i in foods]) <=450, 'max carbo'</pre>
problem += lpSum([fiber[i] * amountVars[i] for i in foods]) >=125, 'min fiber'
problem += lpSum([fiber[i] * amountVars[i] for i in foods]) <=250, 'max fiber'</pre>
problem += lpSum([protein[i] * amountVars[i] for i in foods]) >=60, 'min protein'
problem += lpSum([protein[i] * amountVars[i] for i in foods]) <=100, 'max protein'</pre>
problem += lpSum([vitA[i] * amountVars[i] for i in foods]) >=1000, 'min vitA'
problem += lpSum([vitA[i] * amountVars[i] for i in foods]) <=10000, 'max vitA'</pre>
problem += lpSum([vitC[i] * amountVars[i] for i in foods]) >=400, 'min vitC'
problem += lpSum([vitC[i] * amountVars[i] for i in foods]) <=5000, 'max vitC'</pre>
problem += lpSum([calcium[i] * amountVars[i] for i in foods]) >=700, 'min calcium'
problem += lpSum([calcium[i] * amountVars[i] for i in foods]) <=1500, 'max calcium'</pre>
problem += lpSum([iron[i] * amountVars[i] for i in foods]) >=10, 'min iron'
problem += lpSum([iron[i] * amountVars[i] for i in foods]) <=40, 'max iron'</pre>
for i in foods:
    problem += amountVars[i]>= selectionVars[i]*0.1
    problem += amountVars[i] <= selectionVars[i] *1e5</pre>
isProtein['Roasted Chicken'] = 1
isProtein['Roasted Chicken'] = 1
isProtein['Poached Eggs'] = 1
isProtein['Scrambled Eggs'] = 1
isProtein['Bologna, Turkey'] = 1
isProtein['Frankfurter, Beef'] = 1
isProtein['Ham, Sliced, Extralean'] = 1
isProtein['Kielbasa, Prk'] = 1
isProtein['Pork'] = 1
isProtein['Sardines in Oil'] = 1
isProtein['White Tuna in Water'] = 1
problem += lpSum([isProtein[i] * selectionVars[i] for i in foods]) >=3, 'min proteins'
#we solve the problem
problem.solve()
#print out amount values from optimal solution
varsDictionary = {}
for v in problem.variables():
     if v.varValue>0:
        varsDictionary[v.name] = v.varValue
#print(varsDictionary)
pprint.pprint(varsDictionary)
{'Amounts Bologna, Turkey': 0.1,
 'Amounts Celery, Raw': 51.522935,
 'Amounts Frozen Broccoli': 0.22815709,
 'Amounts Lettuce, Iceberg, Raw': 66.955456,
'Amounts_Oranges': 2.3760495,
 'Amounts_Poached_Eggs': 0.1,
 'Amounts_Popcorn, Air_Popped': 13.847028,
 'Amounts Scrambled_Eggs': 0.1,
 'InorOut Bologna, Turkey': 1.0,
 'InorOut_Celery,_Raw': 1.0,
 'InorOut_Frozen_Broccoli': 1.0,
 'InorOut_Lettuce, Iceberg, Raw': 1.0,
 'InorOut Oranges': 1.0,
 'InorOut Poached Eggs': 1.0,
 'InorOut Popcorn, Air Popped': 1.0,
'InorOut Scrambled Eggs': 1.0}
```

```
Long diet problem
.....
import math
foodData = pd.read excel("diet large.xls")
foodData = foodData[1:7147]
foodData = foodData.values.tolist()
foods = [x[0] for x in foodData]
protein = dict([(x[0], float(0.0) if math.isnan(x[1]) else float(x[1])) for x in foodData])
calcium = dict([(x[0], float(0.0) if math.isnan(x[6]) else float(x[6])) for x in foodData])
selectionVars = LpVariable.dicts("InorOut", foods, 0, 1, LpBinary)
#create a dictionary for the cholesterol cost of the foods
 \verb|cho| cost = dict([(x[0], float(0.0) | \textbf{if} | math.isnan(x[28])) | \textbf{else} | float(x[28])) | \textbf{for} | x | \textbf{in} | float(0.0) | flo
#we define the optimization problem by giving it a name and letting it know we are minimizing
problem = LpProblem("Diet Large Problem", LpMinimize)
#we define our primary variables (the amount of each food in the diet)
amountVars = LpVariable.dicts("Amounts", foods, 0)
#we add the objective function to the problem, inner product of cholesterol cost and amountVars
problem += lpSum([cho cost[i] * amountVars[i] for i in foods]), "total cholesterol cost"
#we create some constraints in proteins, so that there is a minimum amount of proteins required in
the diet - otherwise
\#the solver would not provide any food - minimizing cholesterol to 0
problem += lpSum([protein[i] * amountVars[i] for i in foods]) >=60, 'min protein'
problem += lpSum([protein[i] * amountVars[i] for i in foods]) <=100, 'max protein'</pre>
problem += lpSum([calcium[i] * amountVars[i] for i in foods]) >=100, 'min calcium'
problem += lpSum([calcium[i] * amountVars[i] for i in foods]) <=500, 'max calcium'</pre>
for i in foods:
      problem += amountVars[i]>= selectionVars[i]*0.1
       problem += amountVars[i] <= selectionVars[i] *100</pre>
#we solve the problem
try:
      problem.solve()
        #print out amount values from optimal solution
      varsDictionary = {}
       for v in problem.variables():
             if v.varValue>0:
                    varsDictionary[v.name] = v.varValue
                    pprint.pprint(varsDictionary)
except Exception:
       print('Problem infeasible')
{'Amounts_Fish,_herring,_Pacific,_meat_packed_in_oil,_air_dried_(Alaska_N': 1.2949118}
{'Amounts_Fish,_herring,_Pacific,_meat_packed_in_oil,_air_dried_(Alaska_N': 1.2949118,
 'Amounts_Infant_formula,_NESTLE,_GOOD_START_ESSENTIALS__SOY,__with_iron,': 0.19011407}
{'Amounts_Fish,_herring,_Pacific,_meat_packed_in_oil,_air_dried_(Alaska_N': 1.2949118,
 'Amounts_Infant_formula,_NESTLE,_GOOD_START_ESSENTIALS__SOY,__with_iron,': 0.19011407,
  'InorOut_Fish,_herring,_Pacific,_meat_packed_in_oil,_air_dried_(Alaska_N': 1.0}
{'Amounts_Fish,_herring,_Pacific,_meat_packed_in_oil,_air_dried_(Alaska_N': 1.2949118,
  'Amounts Infant formula, NESTLE, GOOD START ESSENTIALS SOY, with iron,': 0.19011407,
 'InorOut_Fish,_herring,_Pacific,_meat_packed_in_oil,_air_dried_(Alaska_N': 1.0,
 'InorOut Infant formula, NESTLE, GOOD START ESSENTIALS SOY, with iron,': 1.0}
In [ ]:
```

11 11 11