

5.4 Defect Report

Defect 1: Timeout during property update response

- **Unique Defect ID:** DEF-001
 - **Title:** Test timeout waiting for API response during owner property update.
 - **Description:** The automated test times out after 30,000ms while waiting for the network response after submitting a property update. Given the manual UI works, the test's `page.waitForResponse` regex or URL matcher might be misaligned with the actual network request dispatched by Axios.
 - **Steps to Reproduce:**
 1. Run the E2E test suite for `update-property.spec.ts`.
 2. Execute test case `TC-FUNC-EDIT-001`.
 3. Observe the test execution log.
 - **Expected Behaviour:** The test should intercept a successful `200 OK` network response from the update endpoint within the 30-second timeout.
 - **Actual Behaviour:** `page.waitForResponse` exceeds the 30,000ms timeout limit.
 - **Severity:** High (Blocks the happy-path automation test)
 - **Priority:** High
 - **Status:** Open
 - **Related Test Case ID:** TC-FUNC-EDIT-001
 - **Evidence:** `update-defect.png`
-

Defect 2: Incorrect HTTP status code for unauthorized update

- **Unique Defect ID:** DEF-002
 - **Title:** Server returns 400 Bad Request instead of 403 Forbidden on unauthorized edit.
 - **Description:** When a user attempts to update a property they do not own, the backend controller rejects the request with a **400 Bad Request** instead of the standard **403 Forbidden** status code.
 - **Steps to Reproduce:**
 1. Authenticate as User A.
 2. Attempt to send a PUT/PATCH request to `/api/property/:id` for a property owned by User B.
 3. Check the HTTP response status code.
 - **Expected Behaviour:** The server should return a **403 Forbidden** status code to indicate the user lacks permission for this specific resource.
 - **Actual Behaviour:** The server returns a **400 Bad Request** status code (Received: 400, Expected: 403).
 - **Severity:** Medium (The action is correctly blocked, but violates REST API status code conventions)
 - **Priority:** Medium
 - **Status:** Open
 - **Related Test Case ID:** TC-FUNC-EDIT-002
 - **Evidence:** [update-defect2.png](#)
-

Defect 3: Incorrect HTTP status code for non-existent property

- **Unique Defect ID:** DEF-003
 - **Title:** Server returns 400 Bad Request instead of 404 Not Found for missing property.
 - **Description:** When sending an update request for a property ID that does not exist in the database, the server responds with a 400 status instead of a 404. This suggests the controller might be treating the empty database result as a generic bad request rather than a "Not Found" error.
 - **Steps to Reproduce:**
 1. Send a property update request to a validly formatted but non-existent property ID (e.g., `/api/property/999999`).
 2. Observe the HTTP response status code.
 - **Expected Behaviour:** The server should return a 404 Not Found status.
 - **Actual Behaviour:** The server returns a 400 Bad Request status code (Received: 400, Expected: 404).
 - **Severity:** Low (Does not impact core functionality, but affects API contract consistency)
 - **Priority:** Low
 - **Status:** Open
 - **Related Test Case ID:** TC-FUNC-EDIT-003
 - **Evidence:** `update-defect3.png`
-

Defect 4: Missing "Scanning..." UI state during AI generation

- **Unique Defect ID:** DEF-004
- **Title:** AI description loading button text locator fails.
- **Description:** The UI test attempts to locate a button displaying the text "Scanning..." while waiting for the Gemini API response. The locator times out after 5,000ms. If the AI generation works manually, the actual application is likely using different loading text (e.g., "Generating...", "Loading...") or a spinner without text, causing the strict text assertion to fail.
- **Steps to Reproduce:**
 1. Run test case [TC-FUNC-MP-004](#).
 2. The test triggers the AI description generation.
 3. The test attempts to assert visibility on `locator('button').filter({ hasText: 'Scanning...' })`.
- **Expected Behaviour:** A button with the exact text "Scanning..." becomes visible in the DOM during the API call.
- **Actual Behaviour:** The element is not found within the 5,000ms timeout period.
- **Severity:** Low (Test script failure rather than an application failure)
- **Priority:** Medium (Update the Playwright script to match the actual React component's state)
- **Status:** Open
- **Related Test Case ID:** TC-FUNC-MP-004
- **Evidence:** [ai-description-defect.png](#)

Defect 5: Missing "Invalid credentials" text on failed login

- **Unique Defect ID:** DEF-005
 - **Title:** Login error message locator fails on incorrect password attempt.
 - **Description:** The automated test attempts to verify that the system gracefully handles incorrect passwords by looking for an element containing the exact text "Invalid credentials". The locator times out after 5,000ms. If the application handles this correctly during manual testing, the UI is likely rendering a different error string (e.g., "Incorrect password," "Login failed") or displaying the error inside a toast notification that the current locator cannot target.
 - **Steps to Reproduce:**
 1. Run the E2E test suite for login.spec.ts.
 2. Execute test case TC-LOG-002.
 3. The script submits the login form with an incorrect password.
 4. The script attempts to assert visibility on locator('text=Invalid credentials').
 - **Expected Behaviour:** An element displaying the exact text "Invalid credentials" becomes visible in the DOM.
 - **Actual Behaviour:** The element is not found within the 5,000ms timeout period.
 - **Severity:** Low (Test script assertion failure rather than an application crash)
 - **Priority:** Medium (Update the Playwright script to match the actual React error state string)
 - **Status:** Open
 - **Related Test Case ID:** TC-LOG-002
 - **Evidence:** login-defect.png
-

Defect 6: Missing "Email already in use" text on duplicate registration

- **Unique Defect ID:** DEF-006
- **Title:** Registration error message locator fails for duplicate emails.
- **Description:** The test verifies that a user cannot register with an email that already exists in the database. The script expects the frontend to display the exact text "Email already in use". The locator times out after 5,000ms. Since the manual application correctly prevents the registration, the React frontend is likely displaying a slightly different error message (e.g., "User already exists," "This email is taken") that causes the strict text assertion to fail.
- **Steps to Reproduce:**
 1. Run the E2E test suite for register.spec.ts.
 2. Execute test case TC-REG-002.
 3. The script submits the registration form using an email already present in the database.
 4. The script attempts to assert visibility on locator('text=Email already in use').
- **Expected Behaviour:** An element displaying the exact text "Email already in use" becomes visible in the DOM.
- **Actual Behaviour:** The element is not found within the 5,000ms timeout period.
- **Severity:** Low (Test script assertion failure rather than an application crash)
- **Priority:** Medium (Update the Playwright script to match the actual React error state string)
- **Status:** Open
- **Related Test Case ID:** TC-REG-002
- **Evidence:** register-defect.png

TC-FUNC-EDIT-001: Owner can successfully update their own property

properties/update-property.spec.ts:69

30.0s

chromium

Run

Errors

Test timeout of 30000ms exceeded.

Copy prompt

Error: page.waitForResponse: Test timeout of 30000ms exceeded.

```
90 | // We use a regex for the URL to be safe against trailing slashes
91 | const [response] = await Promise.all([
> 92 |   page.waitForResponse(
      ^
93 |     (res) =>
94 |       res
95 |         .url()
    at /home/vona50/0kul/3-2/Verification/reliabuy/tests/e2e/properties/update-property.spec.ts:92:12
```

TC-FUNC-EDIT-002: Server rejects update if user does not own the property (403 Forbidden)

properties/update-property.spec.ts:114

246ms

chromium

Run

Errors

Error: expect(received).toBe(expected) // Object.is equality

Copy prompt

Expected: 403

Received: 400

```
132 |
133 | // Check that the custom middleware/controller caught the mismatch
> 134 | expect(apiResponse.status()).toBe(403);
      ^
135 | const apiBody = await apiResponse.json();
136 | expect(apiBody.message).toBe(
137 |   "Unauthorized: You can only edit your own properties.",
    at /home/vona50/0kul/3-2/Verification/reliabuy/tests/e2e/properties/update-property.spec.ts:134:34
```

TC-LOG-002: Verify login gracefully handles incorrect passwords

auth/login.spec.ts:59

5.4s

chromium

✗ Run

Errors

Error: expect(locator).toBeVisible() failed

Locator: locator('text=Invalid credentials')

Expected: visible

Timeout: 5000ms

Error: element(s) not found

Call log:

- Expect "toBeVisible" with timeout 5000ms
- waiting for locator('text=Invalid credentials')

```
79 | // EXPECTED RESULT 2: Frontend displays error without crashing [cite: 158]
80 | const errorMessage = page.locator("text=Invalid credentials"); // Adjust text based on your exact U
> 81 | await expect(errorMessage).toBeVisible();
    |                               ^
82 |
83 | // EXPECTED RESULT 3: No token in localStorage [cite: 158]
84 | const token = await page.evaluate(() => localStorage.getItem("token"));
    at /home/vona50/0kul/3-2/Verification/reliabuy/tests/e2e/auth/login.spec.ts:81:32
```

TC-REG-002: Verify registration fails when using an email that is already registered

auth/register.spec.ts:84

5.5s

chromium

✗ Run

Errors

Error: expect(locator).toBeVisible() failed

Locator: locator('text=Email already in use')

Expected: visible

Timeout: 5000ms

Error: element(s) not found

Call log:

- Expect "toBeVisible" with timeout 5000ms
- waiting for locator('text=Email already in use')

```
111 | // EXPECTED RESULT 2: The app does not crash, and a user-friendly error is displayed
112 | const errorMessage = page.locator("text=Email already in use");
> 113 | await expect(errorMessage).toBeVisible();
    |                               ^
114 |
115 | // Verify the user was NOT added a second time
116 | const dbResult = await pool.query("SELECT * FROM users WHERE email = $1", [
    at /home/vona50/0kul/3-2/Verification/reliabuy/tests/e2e/auth/register.spec.ts:113:32
```


TC-FUNC-EDIT-003: Server returns 404 when updating non-existent property

properties/update-property.spec.ts:148

236ms

chromium

✖ Run

Errors

Error: expect(received).toBe(expected) // Object.is equality

Copy prompt

Expected: 404
Received: 400

```
164 |     );  
165 |  
> 166 |     expect(apiResponse.status()).toBe(404);  
    |                                     ^  
167 |  
168 |   });  
169 |   test("TC-FUNC-EDIT-004: Server rejects invalid ID string formats (400 Bad Request)", async ({  
    |   at /home/vona50/Okul/3-2/Verification/reliabuy/tests/e2e/properties/update-property.spec.ts:166:34
```

TC-FUNC-MP-004: Verify AI description generation successfully populates the description field

properties/ai-description.spec.ts:38

5.

chromium

Run

Errors

Error: expect(locator).toBeVisible() failed

Copy prompt

Locator: locator('button').filter({ hasText: 'Scanning...' })

Expected: visible

Timeout: 5000ms

Error: element(s) not found

Call log:

- Expect "toBeVisible" with timeout 5000ms

- waiting for locator('button').filter({ hasText: 'Scanning...' })

77 | // Verify UI changes to loading state

78 | const loadingBtn = page.locator("button", { hasText: "Scanning..." });

> 79 | await expect(loadingBtn).toBeVisible();

80 |

81 |

82 | // PROCEDURE 4: Wait for the backend/Gemini response

const apiResponse = await aiResponsePromise;

at /home/vona50/0kul/3-2/Verification/reliabuy/tests/e2e/properties/ai-description.spec.ts:79:30

Test Steps

Q Filter steps

>	✓ Before Hooks	265ms
>	✓ Navigate to "/" — properties/ai-description.spec.ts:42	111ms
>	✓ Evaluate — properties/ai-description.spec.ts:43	46ms
>	✓ Navigate to "/publish" — properties/ai-description.spec.ts:46	39ms
>	✓ Set input files locator("input[type="file"]") — properties/ai-description.spec.ts:53	52ms
>	✓ Wait for event "response" — properties/ai-description.spec.ts:57	4.2s
>	✓ Expect "not toBeDisabled" locator("button").filter({ hasText: 'Auto-Write with AI' }) — properties/ai-description.spec.ts:74	10ms
>	✓ Click locator("button").filter({ hasText: 'Auto-Write with AI' }) — properties/ai-description.spec.ts:75	41ms
>	✗ Expect "toBeVisible" locator("button").filter({ hasText: 'Scanning...' }) — properties/ai-description.spec.ts:79	5.0s
>	✓ After Hooks	44ms
>	✓ Worker Cleanup	16ms