



Vidyavardhini's College of Engineering and Technology
Department of Artificial Intelligence & Data Science

Experiment No.5
Perform simple queries, string manipulation operations and aggregate functions.
Date of Performance:
Date of Submission:



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Aim :- Write simple query to manipulate string operations and perform aggregate functions like (MIN, MAX, SUM, AVERAGE, COUNT).

Objective :- To apply aggregate functions and string manipulation functions to perform simple queries in the database system

Theory:

Simple Queries in SQL:

In SQL, a simple query is a request for data from a database table or tables. It allows users to retrieve specific information by specifying the columns they want to retrieve and any conditions for filtering rows based on certain criteria. Simple queries are the backbone of interacting with databases, enabling users to extract the data they need for analysis, reporting, or further processing.

String Manipulation Operations:

String manipulation operations in SQL involve modifying or transforming string values stored in database columns. These operations are crucial for tasks such as formatting data, combining strings, converting case, or extracting substrings. By using string functions and operators, users can manipulate text data to suit their requirements, whether it's for display purposes or for further analysis.

Aggregate Functions:

Aggregate functions in SQL are used to perform calculations on sets of values and return a single result. These functions allow users to summarize data across multiple rows, providing insights into the overall characteristics of the dataset. Common aggregate functions include calculating counts, sums, averages, minimums, and maximums of numerical values. They are essential tools for data analysis, enabling users to derive meaningful insights from large datasets.

Benefits of Understanding These Concepts:

- **Data Retrieval:** Simple queries allow users to fetch specific data from databases, facilitating data retrieval for various purposes.
- **Data Transformation:** String manipulation operations enable users to format and transform text data according to their needs, improving data consistency and readability.
- **Data Analysis:** Aggregate functions help users summarize and analyze large datasets, providing valuable insights into trends, patterns, and statistical measures.



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Implementation:

Navigator: Query 1 x

SCHEMAS

Filter objects

farm_database

- Tables
- Views
- Stored Procedures
- Functions

sys

yashkerkar

Administration Schemas Information

Schema: farm_database

```
74
75 • UPDATE FMS F_NAME SET F_NAME = "Mr. @" WHERE F_ID = 10;
76
77 • SELECT COUNT(*) AS TOTALFARMERS FROM FMS;
78
79 • SELECT SUM(AGE) AS TOTALAGE FROM FMS;
80
81 • SELECT AVG(AGE) AS AVERAGEAGE FROM FMS;
82
83 • SELECT MAX(AGE) AS MAXAGE FROM FMS;
84
85 • SELECT MIN(AGE) AS MINAGE FROM FMS;
86
87 • SELECT * FROM FMS
88   WHERE F_NAME LIKE 'Y%';
89
90 • SELECT * FROM FMS
91   WHERE F_NAME LIKE '%t';
92
93 • SELECT * FROM FMS
94   WHERE F_NAME LIKE '%k%';
95
96 • SELECT * FROM FMS
97   WHERE F_NAME LIKE '%h%';
98
99 • SELECT * FROM FMS
100  WHERE COUNTRY IS NULL;
101
102 • SELECT * FROM FMS
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Navigator

SCHEMAS

Filter objects

▼ farm_database

- Tables
- Views
- Stored Procedures
- Functions

► sys

► yashkerkar

Administration Schemas

Information

Schema: farm_database

Query 1

Limit to 1000 rows

```
81 • SELECT AVG(AGE) AS AVERAGEAGE FROM FMS;
82
83 • SELECT MAX(AGE) AS MAXAGE FROM FMS;
84
85 • SELECT MIN(AGE) AS MINAGE FROM FMS;
86
87 • SELECT * FROM FMS
88   WHERE F_NAME LIKE 'Y%';
89
90 • SELECT * FROM FMS
91   WHERE F_NAME LIKE '%t';
92
93 • SELECT * FROM FMS
94   WHERE F_NAME LIKE '%k%';
95
96 • SELECT * FROM FMS
97   WHERE F_NAME LIKE '%h%';
98
99 • SELECT * FROM FMS
100  WHERE COUNTRY IS NULL;
101
102 • SELECT * FROM FMS
103  WHERE COUNTRY IS NOT NULL;
104
105 • SELECT * FROM FMS
106  ORDER BY LOAN;
107
108 • SELECT * FROM FMS
109  ORDER BY LOAN DESC;
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Output:


Result Grid		Filter Rows:	Export:	Wrap Cell Content:
TOTALFARMERS	2			

Result Grid		Filter Rows:	Export:	Wrap Cell Content:
TOTALAGE	39			

Result Grid		Filter Rows:	Export:	Wrap Cell Content:
AVERAGEAGE	19.5000			

Result Grid		Filter Rows:	Export:	Wrap Cell Content:
MAXAGE	20			

Result Grid		Filter Rows:	Export:	Wrap Cell Content:
MINAGE	19			

[illegible]



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

F_ID	F_NAME	L_NAME	AGE	MOB_NO	PLACE	LOAN
10	Mr. @	Bari	20	787000098	Dahanu	9500
20	Yash	Kerkar	19	457495550	Nallasopara	9000
NULL	NULL	NULL	NULL	NULL	NULL	NULL

Conclusion:

Through this practical exercise, we have successfully demonstrated the proficiency in performing various queries, string manipulation operations, and aggregate functions in a database management system. These operations are fundamental in managing and extracting meaningful insights from data stored within databases.

1. Write syntax and explanation for each of the five aggregate functions

1. Ans. COUNT():

- Syntax: **COUNT(expression)**
- Explanation: This function counts the number of rows in a specified column or all rows in a table if no column is specified. It ignores NULL values unless the expression is **COUNT(*)**, which counts all rows regardless of NULL values.

2. SUM():

- Syntax: **SUM(expression)**
- Explanation: This function calculates the sum of all non-NULL values in a specified column. It is commonly used with numeric data types such as integers, decimals, or floating-point numbers.

3. AVG():

- Syntax: **AVG(expression)**
- Explanation: This function calculates the average (mean) of all non-NULL values in a specified column. It is useful for finding the typical value within a dataset.



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

4. MAX():

- Syntax: **MAX(expression)**
- Explanation: This function returns the largest (maximum) value in a specified column. Similar to MIN(), it is applicable to numeric, string, or date/time data types and is used to find the highest value within a dataset.

2. Show results of operations performed.

Ans. **COUNT()**:

```
SELECT COUNT(*) AS total_farmers FROM fms;  
total_farmers
```

50

SUM():

```
SELECT SUM(loan) AS total_loans FROM FMS;  
total_loans
```

12500

AVG():

```
SELECT AVG(loan) AS average_loan FROM FMS;  
average_salary
```

55000

MIN():

```
SELECT MIN(age) AS lowest_age FROM FMS;  
lowest_age
```

19

MAX():

```
SELECT MAX(age) AS highest_age_date FROM FMS;  
lowest_age
```
