

Lecture 35: IL for Arrays

One-dimensional Arrays

- How do we process retrieval from and assignment to $x[i]$, for an array x ?
- We assume that all items of the array have fixed size— S bytes—and are arranged sequentially in memory (the usual representation).
- Easy to see that the address of $x[i]$ must be

$$\&x + S \cdot i,$$

where $\&x$ is intended to denote the address of the beginning of x .

- Generically, we call such formulae for getting an element of a data structure *access algorithms*.
- The IL might look like this:

```
cgen(&A[E], t0):  
  cgen(&A, t1)  
  cgen(E, t2)  
  ⇒ t3 := t2 * S  
  ⇒ t0 := t1 + t3
```

Multi-dimensional Arrays

- A 2D array is a 1D array of 1D arrays.
- Java uses arrays of pointers to arrays for >1D arrays.
- But if row size constant, for faster access and compactness, may prefer to represent an $M \times N$ array as a 1D array of M 1D rows of length N (not pointers to rows): *row-major order*...
- Or, as in FORTRAN, a 1D array of N 1D columns of length M : *column-major order*.
- So apply the formula for 1D arrays repeatedly—first to compute the beginning of a row and then to compute the column within that row:

$$\&A[i][j] = \&A + i \cdot S \cdot N + j \cdot S$$

for an M -row by N -column array, where S , again, is the size of an individual element.

IL for $M \times N$ 2D array

```
cgen(&e1[e2,e3], t):  
  # Compute e1, e2, e3, and N:  
  cgen(e1, t1);  
  cgen(e2,t2);  
  cgen(e3,t3)  
  cgen(N, t4) # (N need not be constant)  
  ⇒ t5 := t4 * t2  
  ⇒ t6 := t5 + t3  
  ⇒ t7 := t6 * S  
  ⇒ t := t7 + t1
```

Array Descriptors

- Calculation of element address $\&e1[e2, e3]$ has the form

$$VO + S1 \times e2 + S2 \times e3$$

, where

- $VO(\&e1[0, 0])$ is the *virtual origin*.
 - $S1$ and $S2$ are *strides*.
 - All three of these are constant throughout the lifetime of the array (assuming arrays of constant size).
- Therefore, we can package these up into an *array descriptor*, which can be passed in lieu of the array itself, as a kind of “*fat pointer*” to the array:

$\&e1[0][0]$	$S \times N$	S
--------------	--------------	-----

Array Descriptors (II)

- Assuming that `e1` now evaluates to the address of a 2D array descriptor, the IL code becomes:

```
cgen(&e1[e2,e3], t):  
    cgen(e1, t1);      # Yields a pointer to a descriptor.  
    cgen(e2,t2);  
    cgen(e3,t3)  
⇒ t4 := *t1;          # The V0  
⇒ t5 := *(t1+4)        # Stride #1  
⇒ t6 := *(t1+8)        # Stride #2  
⇒ t7 := t5 * t2  
⇒ t8 := t6 * t3  
⇒ t9 := t4 + t7  
⇒ t10:= t9 + t8
```

(Here, we assume 32-bit quantities. Adjust the constants appropriately for 64-bit pointers and/or integers.)

Array Descriptors (III)

- By judicious choice of descriptor values, can make the same formula work for different kinds of array.
- For example, if lower bounds of indices are 1 rather than 0, must compute address

$$\&e[1,1] + S1 \times (e2-1) + S2 \times (e3-1)$$

- But some algebra puts this into the form

$$V0' + S1 \times e2 + S2 \times e3$$

where

$$V0' = \&e[1,1] - S1 - S2 = \&e[0,0] \text{ (if it existed).}$$

- So with the descriptor

$V0'$	$S \times N$	S
-------	--------------	-----

we can use the same code as on the last slide.

- By passing descriptors as array parameters, we can have functions that adapt to many different array layouts automatically.

Other Uses for Descriptors

- No reason to stop with strides and virtual origins: can include other data.
- By adding upper and lower index bounds to a descriptor, can easily implement bounds checking.
- This also allows for runtime queries of array sizes and bounds.
- Descriptors also allow *views* of arrays: nothing prevents multiple descriptors from pointing to the same data.
- This allows effects such as slicing, array reversal, or array transposition without copying data.

Examples

- Consider a simple base array (in C):

```
int data[12] = { 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12 };
```

and descriptor types (including lengths):

```
struct Desc1 { int* V0, int S1, int len1 };
```

```
struct Desc2 { int* V0, int S1, int len1, int S2, int len2 };
```

- Here are some views:

```
Desc1 v0 = { data, 4, 12 }; /* All of data. */
```

```
Desc1 v1 = { &data[3], 4, 3 }; /* data[3:6]: [4, 5, 6]. */
```

```
/* Every other element of data: [1, 3, ...] */
```

```
Desc1 v2 = { data, 8, 6 };
```

```
Desc1 v3 = { &data[11], -4, 12 }; /* Reversed: [12, 11, ...] */
```

```
/* As a 2D 4x3 array: [ [ 1, 2, 3 ], [ 4, 5, 6 ], ... ] */
```

```
Desc2 v4 = { data, 12, 4, 4, 3 };
```

```
/* As row 2 of v4: [7, 8, 9] */
```

```
Desc1 v5 = { &data[6], 4, 3 }
```