

# Lecture 9: General and Bottom-Up Parsing

## A Little Notation

Here and in lectures to follow, we'll often have to refer to general productions or derivations. In these, we'll use various alphabets to mean various things:

- Capital roman letters are nonterminals ( $A, B, \dots$ ).
- Lower-case roman letters are terminals (or tokens, characters, etc.)
- Lower-case greek letters are sequences of zero or more terminal and nonterminal symbols, such as appear in sentential forms or on the right sides of productions ( $\alpha, \beta, \dots$ ).
- Subscripts on lower-case greek letters indicate individual symbols within them, so  $\alpha = \alpha_1 \alpha_2 \dots \alpha_n$  and each  $\alpha_i$  is a single terminal or nonterminal.

So  $A : \alpha$  might describe the production  $e \Rightarrow e '+' t$ ,

...and  $B \Rightarrow \alpha A \gamma \Rightarrow \alpha \beta \gamma$  might describe the derivation steps

$$e \Rightarrow e '+' t \Rightarrow e '+' ID$$

( $\alpha$  is  $e '+'$ ;  $A$  is  $t$ ;  $B$  is  $e$ ; and  $\gamma$  is empty.)

# Fixing Recursive Descent

- First, let's define an impractical but simple implementation of a top-down parsing routine.
- For nonterminal  $A$  and string  $S = c_1 c_2 \dots c_n$ , we'll define  $\text{parse}(A, S)$  to return the length of a valid prefix of  $S$  derivable from  $A$ .
- That is,  $\text{parse}(A, c_1 c_2 \dots c_n) = k$ , where

$$\underbrace{c_1 c_2 \dots c_k}_{A \xRightarrow{*}} c_{k+1} c_{k+2} \dots c_n$$

## Abstract body of parse(A,S)

- Can formulate top-down parsing analogously to NFAs.

```
parse (A, S):  
    """Assuming A is a nonterminal and S =  $c_1c_2\dots c_n$  is a string, return  
       integer  $k$  such that A can derive the prefix string  $c_1\dots c_k$  of S."""  
    Choose production 'A:  $\alpha_1\alpha_2\dots\alpha_m$ ' for A (nondeterministically)  
    k = 0  
    for x in  $\alpha_1, \alpha_2, \dots, \alpha_m$ :  
        if x is a terminal:  
            if x ==  $c_{k+1}$ :  
                k += 1  
            else:  
                GIVE UP  
        else:  
            k += parse (x,  $c_{k+1}\dots c_n$ )  
    return k
```

- Let the start symbol be  $p$  with exactly one production:  $p: \gamma \vdash$ .
- We'll say that a call to parse returns a value if some set of choices for productions (the blue step) would return a value (just like NFA).
- Then if parse( $p, S$ ) returns a value,  $S$  must be in the language.

# Example

Consider parsing  $S = \text{"ID*ID}\vdash\text{"}$  with a grammar from last time:

```
p : e '⊢'
e : t
  | e '/' t
  | e '*' t
t : ID
```

# Example

Consider parsing  $S = \text{"ID*ID}\mid\text{"}$  with a grammar from last time:

$p : e \mid \mid$   
 $e : t$   
     $\mid e \mid / \mid t$   
     $\mid e \mid * \mid t$   
 $t : \text{ID}$

A failing path through the program:

```
parse(p, S):
  Choose p : e '⊢':
    parse(e, S):
      Choose e : t:
        parse(t, S):
          choose t : ID:
            check S[1] == ID; OK, so  $k_3 += 1$ ;
            return 1      (=  $k_3$ ; added to  $k_2$ )
          return 1 (and add to  $k_1$ )
    Check S[2] == S[ $k_1+1$ ] == '⊢': GIVE UP (S[2] == '*')
```

$k_i$  means "the variable  $k$  in the call to parse that is nested  $i$  deep." Outermost  $k$  is  $k_1$ .

# Example

Consider parsing  $S = \text{"ID*ID-"}$  with a grammar from last time:

```
p : e '−'
e : t
  | e '/' t
  | e '*' t
t : ID
```

A successful path through the program:

```
parse(p, S):
  Choose p : e '−':
    parse(e, S):
      Choose e : e '*' t:
        parse(e, S):
          choose e : t:
            parse(t, S):
              choose t : ID:
                check S[1] == ID; OK, so return 1
              return 1 (so k2 += 1)
            check S[k2] == '*'; OK, k2 += 1
          parse(t, S3): # S3 == "ID −"
            choose t : ID:
              check S3[k3+1] == S3[1] == ID; OK
              k3 += 1; return 1 (so k2 += 1)
            return 3
          Check S[k1+1] == S[4] == '−': OK
          k1 += 1; return 4
```

$k_i$  means "the variable  $k$  in the call to parse that is nested  $i$  deep." Outermost  $k$  is  $k_1$ . Likewise for  $S_i$ .

# Making a Deterministic Algorithm

- If we had an infinite supply of processors, could just spawn new ones at each "Choose" line.
- Some would give up, some loop forever, but on correct programs, at least one processor would get through.
- To do this for real (say with one processor), need to keep track of all possibilities systematically.
- This is the idea behind Earley's algorithm:
  - Handles any context-free grammar.
  - Finds all parses of any string.
  - Can recognize or reject strings in  $O(N^3)$  time for ambiguous grammars,  $O(N^2)$  time for "nondeterministic grammars", or  $O(N)$  time for deterministic grammars (such as accepted by Bison).



# Earley's Algorithm: I

- First, reformulate to use recursion instead of looping. Assume the string  $S = c_1 \cdots c_n$  is fixed.
- Redefine **parse**:

`parse (A:  $\alpha \bullet \beta$ , s, k):`

`"""Assumes A:  $\alpha\beta$  is a production in the grammar,`

`0 <= s <= k <= n, and  $\alpha$  can produce the string  $c_{s+1} \cdots c_k$ .`

`Returns integer j such that  $\beta$  can produce  $c_{k+1} \cdots c_j$ ."""`

- Or diagrammatically, **parse** returns an integer **j** such that:

$$c_1 \cdots c_s \underbrace{c_{s+1} \cdots c_k}_{\alpha \xRightarrow{*}} \underbrace{c_{k+1} \cdots c_j}_{\beta \xRightarrow{*}} c_{j+1} \cdots c_n$$

# Earley's Algorithm: II

```
parse (A:  $\alpha \bullet \beta$ , s, k):  
    """Assumes A:  $\alpha\beta$  is a production in the grammar,  
       0 <= s <= k <= n, and  $\alpha$  can produce the string  $c_{s+1} \cdots c_k$ .  
       Returns integer j such that  $\beta$  can produce  $c_{k+1} \cdots c_j$ ."""  
    if  $\beta$  is empty:  
        return k  
    Assume  $\beta$  has the form  $x\delta$   
    if x is a terminal:  
        if  $x == c_{k+1}$ :  
            return parse(A:  $\alpha x \bullet \delta$ , s, k+1)  
        else:  
            GIVE UP  
    else:  
        Choose production ' $x: \kappa$ ' for x (nondeterministically)  
        j = parse(x:  $\bullet \kappa$ , k, k)  
        return parse (A:  $\alpha x \bullet \delta$ , s, j)
```

- Now do all possible choices that result in such a way as to avoid redundant work ("nondeterministic memoization").
- That is, if parse is called with the same three arguments as a previous call, just use the result(s) of the previous call.

# Chart Parsing

- Idea is to build up a table (known as a *chart*) of all calls to parse that have been made.
- Only one entry in chart for each distinct triple of arguments ( $A: \alpha \bullet \beta, s, k$ ).
- We'll organize table in columns numbered by the  $k$  parameter, so that column  $k$  represents all calls that are looking at  $c_{k+1}$  in the input.
- Each column contains entries with the other two parameters:  $[A: \alpha \bullet \beta, s]$ , which are called *items*.
- The columns, therefore, are *item sets*.

# Example

## Grammar

$p : e \text{ '}' \neg \text{'}$   
 $e : s \ I \mid e \text{ '}' + \text{' } e$   
 $s : \text{' - ' } \mid$

## Input String

$- \ I \ + \ I \ \neg$

**Chart.** Headings are values of  $k$  and  $c_{k+1}$  (raised symbols). Item labels (a-f) trace the "ancestry" of each item.

0	-	1	I	2	+	3	I
a.p: $\bullet e \text{ '}' \neg \text{'}, 0$		d.s: $\text{' - ' } \bullet, 0$		c.e: $s \ I \bullet, 0$		b.e: $e \text{ '}' + \text{' } \bullet e, 0$	
b.e: $\bullet e \text{ '}' + \text{' } e, 0$		c.e: $s \bullet I, 0$		b.e: $e \bullet \text{'}' + \text{' } e, 0$		e.e: $\bullet s \ I, 3$	
c.e: $\bullet s \ I, 0$						f.s: $\bullet, 3$	
d.s: $\bullet \text{' - ' }, 0$						e.e: $s \bullet I, 3$	
4	$\neg$	5					
e.e: $s \ I \bullet, 3$		a.p: $e \text{ '}' \neg \text{' } \bullet, 0$					
b.e: $e \text{ '}' + \text{' } e \bullet, 0$							
a.p: $e \bullet \text{'}' \neg \text{'}, 0$							

# Example, completed

- Last slide showed only those items that survive and get used. Algorithm actually computes dead ends as well (in red).

0	-	1	I	2	+	3	I
<i>a.p</i> : ● <i>e</i> '−', 0 <i>b.e</i> : ● <i>e</i> '+' <i>e</i> , 0 <i>c.e</i> : ● <i>s</i> <i>I</i> , 0 <i>d.s</i> : ● '−', 0 <i>g.s</i> : ●, 0 <i>h.e</i> : <i>s</i> ● <i>I</i> , 0		<i>d.s</i> : '−' ●, 0 <i>c.e</i> : <i>s</i> ● <i>I</i> , 0		<i>c.e</i> : <i>s</i> <i>I</i> ●, 0 <i>b.e</i> : <i>e</i> ● '+' <i>e</i> , 0 <i>a.p</i> : <i>e</i> ● '−', 0		<i>b.e</i> : <i>e</i> '+' ● <i>e</i> , 0 <i>e.e</i> : ● <i>s</i> <i>I</i> , 3 <i>f.s</i> : ●, 3 <i>e.e</i> : <i>s</i> ● <i>I</i> , 3 <i>i.s</i> : ● '−', 3 <i>j.e</i> : ● <i>e</i> '+' <i>e</i> , 3	
4	−	5					
<i>e.e</i> : <i>s</i> <i>I</i> ●, 3 <i>b.e</i> : <i>e</i> '+' <i>e</i> ●, 0 <i>a.p</i> : <i>e</i> ● '−', 0 <i>j.e</i> : <i>e</i> ● '+' <i>e</i> , 3		<i>a.p</i> : <i>e</i> '−' ●, 0					

# Ambiguous Example

## Grammar

$p : e \text{ '}' \neg \text{'}$   
 $e : I \mid e \text{ '}' + \text{' } e$

## Input String

$I + I + I \neg$

**Chart.** Only useful items shown.

0			1			2			3		
$a.p: \bullet e \text{ '}' \neg \text{'}, 0$			$c.e: I \bullet, 0$			$b.e: e \text{ '}' + \text{' } \bullet e, 0$			$d.e: I \bullet, 2$		
$b.e: \bullet e \text{ '}' + \text{' } e, 0$			$b.e: e \bullet \text{ '}' + \text{' } e, 0$			$d.e: \bullet I, 2$			$b.e: e \text{ '}' + \text{' } e \bullet, 0$		
$c.e: \bullet I, 0$						$e.e: \bullet e \text{ '}' + \text{' } e, 2$			$e.e: e \bullet \text{ '}' + \text{' } e, 2$		
									$b.e: e \bullet \text{ '}' + \text{' } e, 0$		
4			5			6					
$b.e: e \text{ '}' + \text{' } \bullet e, 0$			$f.e: I \bullet, 4$			$a.p: e \neg \bullet, 0$					
$e.e: e \text{ '}' + \text{' } \bullet e, 2$			$b.e: e \text{ '}' + \text{' } e \bullet, 0$								
$f.p: \bullet I, 4$			$e.e: e \text{ '}' + \text{' } e \bullet, 2$								
			$a.p: e \bullet \neg, 0$								

# Adding Semantic Actions

- Using syntax-directed translation to get semantic values is pretty much like recursive descent.
- The call  $\text{parse}(A: \alpha \bullet \beta, s, k)$  can return, in addition to  $j$ , the semantic value of the  $A$  that matches symbols  $c_{s+1} \cdots c_j$ .
- The value is computed during calls of the form  $\text{parse}(A: \alpha' \bullet, s, k)$  (i.e., where the  $\beta$  part is empty). For terminal symbols,  $v$  is provided by the lexer.
- On a chart, when we see an item  $A: \alpha \bullet, s$  in column  $k$ , it tells us to
  - Perform the semantic action corresponding to the production  $A: \alpha$ , getting a result  $v$ .
  - For each item  $B: \beta \bullet A\gamma, t$  in column  $s$  of the chart, when adding the item  $B: \beta A \bullet \gamma, t$  to column  $k$ , also attach value  $v$  to that instance of  $A$  in the new item.
  - For all items derived from  $B: \beta \bullet A\gamma, t$  as its dot is shifted, also attach  $v$  to the same instance of  $A$ .

This step is what provides the values of nonterminals needed to compute  $v$  values (in Bison notation:  $\$1, \$2$ , etc.)

# Example with Semantic Values

## Grammar

$p : e \rightarrow \neg$       { \$\$ = \$1; }  
 $e : t$       { \$\$ = \$1; }  
 $e : e \rightarrow + t$       { \$\$ = \$1 + \$3; }  
 $t : I$       { \$\$ = \$1; }  
 $t : t \rightarrow * I$       { \$\$ = \$1 \* \$3; }

## Input String

(I's are integer literals).

1 + 3 \* 2  $\neg$

**Chart.** Only useful items shown. Semantic values are subscripts; red items show where they are computed.

0	I <sub>1</sub>	1	+	2	I <sub>3</sub>	3	*
a. p: •e '¬', 0	d. t <sub>1</sub> : I <sub>1</sub> •, 0	b. e: e <sub>1</sub> '•+' t, 0	e. t: •I, 2	f. t: •t '•*' I, 2	e. t <sub>3</sub> : I <sub>3</sub> •, 2	f. t: t <sub>3</sub> •'•*' I, 2	
b. e: •e '•+' t, 0	c. e <sub>1</sub> : t <sub>1</sub> •, 0						
c. e: •t, 0	b. e: e <sub>1</sub> •'•+' t, 0						
d. t: •I, 0							
4	I <sub>2</sub>	5	¬	6			
f. t: t <sub>3</sub> '•*' •I, 2	f. t <sub>6</sub> : t <sub>3</sub> '•*' I <sub>2</sub> •, 2	a. p <sub>7</sub> : e <sub>7</sub> ¬•, 0					
	b. e <sub>7</sub> : e <sub>1</sub> '•+' t <sub>6</sub> •, 0						
	a. p: e <sub>7</sub> •¬, 0						



# Handling Ambiguity in Semantics (Sketch)

- Ambiguity really only important here when computing semantic actions.
- Rather than being satisfied with a single path through the chart, we look at *all* paths.
- The call `parse(A:  $\alpha \bullet \beta$ , s, k)` can return a *set* of semantic values.
- Accordingly, we attach sets of semantic values to nonterminals.