

IonHive DC Charger

60kW

CCS2 | Single Gun | Dual Gun |
DLM 4 Wheeler | Commercial EV



	Specification	60KW
Power Output	Output Rating	200-1000 V DC
	Charging Interface	Max. Output Current: 125 A, Max. Output Power: 60 kW, Output Plug: CCS2, No.coof Outputs: 2, Efficiency: >95% for 50% loads 100% at Nominal IP Voltage
Power Input	Charging Interface	Input Voltage: 415 VAC, 3-Phase/L1, L2, L3, N, PE, No of I/P Phase: 3, Input Voltage Range: 320 VAC-520 VAC, Input Frequency: 50/60 Hz, Power Factor: > 0.98
Protection fault & safety	Protection	Over Current, Under Voltage, Over Voltage, Residual Current, Surge Protection, Short Circuit, Over Temperature Ground Fault, Insulation Fault, Emergency Stop
Other Specification	Display	7" LCD Touch Screen
	Emergency Swtich	Available (Mushroom Red Switch)
	Charger Configuration	Water Resistance: IP54 Rated, Connectivity: Ethernet (Standard); 3G/4G (Optional) Communication: OCPP v1.6J, Support Language: English, Dimensions: 1,850 650 510 mm (Excluding Pedestal), Weight: 10-12 kg, Charging Operation: Standalone, Visual Indication: Presence of Supply, State of Charging, Error, User Authentication: RFID, QR Code, Plug & Charge, Mobile App