

"Unlock Your Potential: Master RHCSA Certification with Our Dynamic eBook!"



Q ≡ Menu

How to Install and Configure an Ansible Control Node – Part 2

Ravi Saive | Last Updated: October 15, 2019 | Read Time: 3 mins | [Ansible](#) | [1 Comment](#)

In the previous topic, you learn about [basic Ansible terminologies and basic concepts](#). In this topic (Part 2 of [Ansible series](#)), we will demonstrate how you can install and configure an Ansible control node on RHEL 8.

In our setup, we are going to use 1 Ansible server and 2 remote Linux nodes:

Control Node 1: RHEL 8 Server	IP: 192.168.0.108	Ansible Server
Managed Host 1: Debian 10	IP: 192.168.0.15	Webserver
Managed Host 2: CentOS 8	IP: 192.168.0.200	Database Server

What is an Ansible Control Node?

A control node is a Linux server that has Ansible installed on it and is used for managing remote hosts or nodes. These remote systems are known as **Managed Hosts** or **Managed nodes**.

In the setup above, the control node is the RHEL 8 server on which Ansible will be installed and Debian 10 & CentOS 8 are the managed hosts.

NOTE: Ansible is only installed on the control node and not the managed hosts.

Step 1: Installing Python 3

By default, RHEL 8 comes with Python 3 and you can verify the version of Python installed on your server by running.

```
# python3 -V
```

```
[root@rhel-ansible:~]# python3 -V
Python 3.6.8
[root@rhel-ansible:~]# _
```

Check Python Version

If for whatever reason Python3 is not installed, install it using the following [dnf command](#).

```
# dnf install python3
```

```
[root@rhel-ansible:~]# dnf install python3
Updating Subscription Management repositories.
Last metadata expiration check: 0:04:21 ago on Tuesday 15 October 2019 12:08:59 PM IST.
Package python36-3.6.8-2.module+el8.0.0+2975+e0f02136.x86_64 is already installed.
Dependencies resolved.
Nothing to do.
Complete!
[root@rhel-ansible:~]# _
```

Install Python3 on RHEL 8

If multiple versions of Python exist on your RHEL 8 system, you can set Python 3 as the default Python version by running.

```
# alternatives --set python /usr/bin/python3
```

```
[root@rhel-ansible:~]# alternatives --set python /usr/bin/python3
[root@rhel-ansible:~]# python3 -V
Python 3.6.8
[root@rhel-ansible:~]# _
```

Set Default Python Version

Step 2: Enable Official RedHat Repository

After installing Python3, make sure that you have enabled RedHat's official repository for Ansible as shown below.

```
# subscription-manager repos --enable ansible-2.8-for-rhel-8-x86_64-rpms
```

```
(root@rhel-ansible:~) # subscription-manager repos --enable ansible-2.8-for-rhel-8-x86_64-rpms
Repository 'ansible-2.8-for-rhel-8-x86_64-rpms' is enabled for this system.
(root@rhel-ansible:~) # _
```

Enable RedHat Ansible Repository

NOTE: For the above command to work, ensure that you have [registered your RHEL 8 for RedHat subscription](#).

Step 3: Install Ansible on RHEL 8

To install Ansible on the Control node which is our RHEL 8 system, run the command.

```
# dnf install ansible -y
```

```
(root@rhel-ansible:~) # dnf install ansible -y
Updating Subscription Management repositories.
Last metadata expiration check: 0:15:50 ago on Tuesday 15 October 2019 12:16:59 PM IST.
Dependencies resolved.
=====
Package                                Arch                                Version
=====
Installing:
ansible                                noarch                              2.8.5-2.el8ae
Installing dependencies:
sshpas                                 x86_64                              1.06-9.el8
python3-pytz                           noarch                              2017.2-9.el8
python3-babel                           noarch                              2.5.1-3.el8
python3-markupsafe                     x86_64                              0.23-19.el8
python3-jinja2                         noarch                              2.10.1-2.el8_0
python3-pyyaml                         x86_64                              3.12-12.el8
Installing weak dependencies:
python3-jmespath                       noarch                              0.9.0-11.el8
Transaction Summary
=====
Install  8 Packages

Total size: 20 M
Installed size: 102 M
Downloading Packages:
[SKIPPED] sshpas-1.06-9.el8.x86_64.rpm: Already downloaded
[SKIPPED] ansible-2.8.5-2.el8ae.noarch.rpm: Already downloaded
[SKIPPED] python3-jmespath-0.9.0-11.el8.noarch.rpm: Already downloaded
[SKIPPED] python3-pytz-2017.2-9.el8.noarch.rpm: Already downloaded
[SKIPPED] python3-babel-2.5.1-3.el8.noarch.rpm: Already downloaded
[SKIPPED] python3-markupsafe-0.23-19.el8.x86_64.rpm: Already downloaded
[SKIPPED] python3-jinja2-2.10.1-2.el8_0.noarch.rpm: Already downloaded
[SKIPPED] python3-pyyaml-3.12-12.el8.x86_64.rpm: Already downloaded
Running transaction check
Transaction check succeeded.
```

Install Ansible in RHEL 8

Once installed, you can check the version of Ansible installed by running the command.

```
# ansible --version
```

```
(root@rhel-ansible:~) # ansible --version
ansible 2.8.5
  config file = /etc/ansible/ansible.cfg
  configured module search path = ['/root/.ansible/plugins/modules', '/usr/share/ansible/plugins/modules']
  ansible python module location = /root/.local/lib/python3.6/site-packages/ansible
  executable location = /usr/bin/ansible
  python version = 3.6.8 (default, Jun 12 2019, 01:12:31) [GCC 8.2.1 20180905 (Red Hat 8.2.1-3)]
```

Check Ansible Version

Step 4: Creating a Static Host Inventory File

So far, we have successfully installed ansible on the Control Node which is our RHEL 8 server. The remote nodes to be managed by the control node need to be defined in a file called the inventory file. The inventory file is a plain text file that resides on the control node and consists of the remote hosts' hostnames or IP addresses.

A static host file is a plain text file that contains a list of managed nodes defined by their IP addresses or hostnames. Let's create a static file 'hosts' in the `/etc/ansible/` directory.

```
# vi /etc/ansible/hosts
```

Next, define a group or groups for your managed hosts. We have 2 managed hosts as earlier seen in the setup at the introduction of this topic. From the setup, the static host file will be defined as follows:

```
[webserver]
192.168.0.15

[database_server]
192.168.0.200
```

Save and exit the inventory file.

To list managed hosts run:

```
# ansible all -i hosts --list-hosts
```

```
[root@rhel-ansible:~]# ansible all --list-hosts
hosts (2):
  192.168.0.15
  192.168.0.200
[root@rhel-ansible:~]# _
```

Check Host Inventory File

Thus far, we have managed to install Ansible in the control node and define the managed hosts in a static Host file residing on the control node.

Next, we are going to see how we can manage or control our remote or managed hosts.

Step 5: Setup the Ansible Control Node to Connect with the Remote Nodes

For the Ansible control node (RHEL 8) to manage the remote host systems (Debian 10 and CentOS 8) we need to set up [passwordless SSH authentication](#) to the remote hosts. For this to happen, you need to generate an SSH key pair and save the public key to the remote nodes.

On the Ansible control node, log in as a normal user and generate the SSH key pair by running the command.

```
# su tecmint
$ ssh-keygen
```

```
[root@rhel-ansible:~]# su tecmint
[tecmint@rhel-ansible:/root]$ ssh-keygen
Generating public/private rsa key pair.
Enter file in which to save the key (/home/tecmint/.ssh/id_rsa):
Created directory '/home/tecmint/.ssh'.
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in /home/tecmint/.ssh/id_rsa.
Your public key has been saved in /home/tecmint/.ssh/id_rsa.pub.
The key fingerprint is:
SHA256:ulxV9Bz5Z152XBIIj+vEMFUhKjgSagtsbARn1gBSf3A tecmint@rhel-ansible
The key's randomart image is:
+---[RSA 2048]-----+
|o.*o. E    +.o.    |
|+=.oo+   o = .    |
|o*..+oo + . + o    |
|= .. o.. + o . =.  |
| .      S = ..=    |
|      . +      oo|
|      . . .      o|
|      . o      ++|
|      o        .|
+---[SHA256]-----+
[tecmint@rhel-ansible:/root]$ _
```

Generate SSH Keys

Next, copy the public ssh key to remote nodes as shown.

```
$ ssh-copy-id tecmint@192.168.0.15          (For Debian 10 node)
$ ssh-copy-id tecmint@192.168.0.200       (For CentOS 8 node)
```

```
[tecmint@rhel-ansible:~]$ ssh-copy-id tecmint@192.168.0.15
/usr/bin/ssh-copy-id: INFO: Source of key(s) to be installed: "/home/tecmint/.ssh/id_rsa.pub"
/usr/bin/ssh-copy-id: INFO: attempting to log in with the new key(s), to filter out any that are already installed
/usr/bin/ssh-copy-id: INFO: 1 key(s) remain to be installed -- if you are prompted now it is to install the new keys
tecmint@192.168.0.15's password:

Number of key(s) added: 1

Now try logging into the machine, with: "ssh 'tecmint@192.168.0.15'"
and check to make sure that only the key(s) you wanted were added.

[tecmint@rhel-ansible:~]$ ssh-copy-id tecmint@192.168.0.200
/usr/bin/ssh-copy-id: INFO: Source of key(s) to be installed: "/home/tecmint/.ssh/id_rsa.pub"
The authenticity of host '192.168.0.200 (192.168.0.200)' can't be established.
ECDSA key fingerprint is SHA256:U4Izbtdu0zW1vr62pm06JfCjvM4QdC+htS6mHqKaT4.
Are you sure you want to continue connecting (yes/no)? yes
/usr/bin/ssh-copy-id: INFO: attempting to log in with the new key(s), to filter out any that are already installed
/usr/bin/ssh-copy-id: INFO: 1 key(s) remain to be installed -- if you are prompted now it is to install the new keys
tecmint@192.168.0.200's password:

Number of key(s) added: 1

Now try logging into the machine, with: "ssh 'tecmint@192.168.0.200'"
and check to make sure that only the key(s) you wanted were added.

[tecmint@rhel-ansible:~]$ _
```

Copy SSH Key to Remote Host

Having added the public keys to all of our remote nodes, we are going to issue a [ping command](#) from the Ansible Control node to ensure that they are reachable.

```
$ ansible -m ping all
```

```
[tecmint@rhel-ansible:~]$ ansible -m ping all
[WARNING]: Platform linux on host 192.168.0.15 is using the discovered Python in
change this. See https://docs.ansible.com/ansible/2.8/reference_appendices/interp

192.168.0.15 | SUCCESS => {
  "ansible_facts": {
    "discovered_interpreter_python": "/usr/bin/python"
  },
  "changed": false,
  "ping": "pong"
}
192.168.0.200 | SUCCESS => {
  "ansible_facts": {
    "discovered_interpreter_python": "/usr/libexec/platform-python"
  },
  "changed": false,
  "ping": "pong"
}
[tecmint@rhel-ansible:~]$ _
```

Ping All Remote Nodes

From the output above, we can clearly see that the [ping command](#) was successful and we were able to test reachability to all the nodes.

Conclusion

In this guide, we successfully installed and set up Ansible on the control node running RHEL 8. We later defined the remote hosts in a static host file and configured the control node to connect and control the managed hosts by setting up SSH passwordless authentication.

🔖 [Ansible Exam Guide](#), [Ansible Tips](#)

Hey TecMint readers,

Exciting news! Every month, our top blog commenters will have the chance to win fantastic rewards, like free Linux eBooks such as RHCE, RHCSA, LFCS, Learn Linux, and Awk, each worth \$20!

Learn [more about the contest](#) and stand a chance to win by [sharing your thoughts below!](#)

GIVEAWAY!

Win eBooks



www.tecmint.com

PREVIOUS ARTICLE:

[How to Check Debian Linux Version](#)

NEXT ARTICLE:

How to Fix 'semanage command' Not Found Error in CentOS/RHEL



Ravi Saive

I am an experienced GNU/Linux expert and a full-stack software developer with over a decade in the field of Linux and Open Source technologies

Each tutorial at TecMint is created by a team of experienced Linux system administrators so that it meets our high-quality standards.

Join the [TecMint Weekly Newsletter](#) (More Than 156,129 Linux Enthusiasts Have Subscribed)

Was this article helpful? Please [add a comment](#) or [buy me a coffee](#) to show your appreciation.

Related Posts

```
aaronk@tecmint:~$ ansible prod_servers -a "systemctl status firewalld" -u root
[REDACTED].235 | FAILED! => {
  "changed": false,
  "module_stderr": "Shared connection to [REDACTED].235 closed.\r\n",
  "module_stdout": "/bin/sh: /usr/bin/python: No such file or directory\r\n",
  "msg": "MODULE FAILURE",
  "rc": 127
}
[REDACTED] 80 | FAILED! => {
  "changed": false,
  "module_stderr": "Shared connection to [REDACTED] 80 closed.\r\n",
  "module_stdout": "/bin/sh: /usr/bin/python: No such file or directory\r\n",
  "msg": "MODULE FAILURE",
  "rc": 127
}
aaronk@tecmint:~$
```

How to Fix “Shared connection to x.x.xx closed” Ansible Error



RedHat Certified Specialist in Ansible Automation Study Guide

eBook by Tecmint.com

Tecmint's Guide to RedHat Ansible Automation Exam Preparation Guide



RED HAT[®] **ANSIBLE[®]** **Certification Guide**

How to Use Ansible Vault in Playbooks to Protect Sensitive Data - Part 10

How to Use Ansible Vault in Playbooks to Protect Sensitive Data – Part 10



RED HAT[®] **ANSIBLE[®]** **Certification Guide**

How to Create and Download Roles on Ansible Galaxy and Use Them - Part 9

How to Create and Download Roles on Ansible Galaxy and Use Them – Part 9



RED HAT[®] **ANSIBLE[®]** Certification Guide

How to Work with Ansible Variables and Facts - Part 8

How to Work with Ansible Variables and Facts – Part 8



RED HAT[®] **ANSIBLE[®]** Certification Guide

How to Create and Use Templates to Create Customized Configuration Files - Part 7

How to Create Templates in Ansible to Create Configurations On Managed Nodes – Part 7

 **1 Comment**

[Leave a Reply](#)

ahmet

June 8, 2020 at 6:54 pm

I didn't understand how managed nodes trust to control node. In this way any people can do this with their server, so they can connect my server. Don't we have to authenticate the ansible control node at our local systems (managed nodes)?

[Reply](#)

Got Something to Say? Join the Discussion...

Thank you for taking the time to share your thoughts with us. We appreciate your decision to leave a comment and value your contribution to the discussion. It's important to note that we moderate all comments in accordance with our [comment policy](#) to ensure a respectful and constructive conversation.

Rest assured that your email address will remain private and will not be published or shared with anyone. We prioritize the privacy and security of our users.

☐ Save my name, email, and website in this browser for the next time I comment.

Post Comment

Search...

Do You Enjoy My Blog?

Support from readers like YOU keeps this blog running. Buying me a cup of coffee is a simple and affordable way to show your appreciation and help keep the posts coming!

Buy Me a Coffee

Linux Commands and Tools

[How to Stop and Disable Unwanted Services from Linux System](#)

[How to Create Multiple User Accounts in Linux](#)

[8 Parted Commands to Manage Disk Partitions in Linux](#)

[4 Useful Way to Know Plugged USB Device Name in Linux](#)

[How to Test Website Loading Speed in Linux Terminal](#)

[7 Interesting 'sort' Command Examples in Linux – Part 2](#)

Linux Server Monitoring Tools

[Limit CPU Usage of a Process in Linux with CPULimit Tool](#)

[How to Install Zabbix Agent and Add Windows Host to Zabbix Monitoring – Part 4](#)

[Nethogs – Monitor Linux Network Traffic Usage Per Process](#)

[How to Check Integrity of File and Directory Using “AIDE” in Linux](#)

[VnStat PHP: A Web Based Interface for Monitoring Network Bandwidth Usage](#)

[How to Install Zabbix on RHEL 8](#)

Learn Linux Tricks & Tips

[How to Find and Remove Duplicate/Unwanted Files in Linux Using ‘FSlint’ Tool](#)

[How to Switch \(su\) to Another User Account without Password](#)

[How to Save Command Output to a File in Linux](#)

[How to Find Files With SUID and SGID Permissions in Linux](#)

[How to Identify Working Directories Using Shell Characters and Variables](#)

[How to Create a Shared Directory for All Users in Linux](#)

Best Linux Tools

[16 Best Markdown Editors for Linux](#)

[19 Best Open Source WYSIWYG HTML Editors in 2023](#)

[6 Best Linux Apps for Downloading Movie Subtitles](#)

[9 Best Self-Hosted Alternatives to Google Photos](#)

[15 Best Open Source Music Making Software for Linux in 2024](#)

[5 Best Microsoft Word Alternatives for Linux in 2024](#)

Tecmint: Linux Howtos, Tutorials & Guides © 2024. All Rights Reserved.

The material in this site cannot be republished either online or offline, without our permission.

Hosting Sponsored by : [Linode Cloud Hosting](#)