

- Server World

[Privacy Policy](#)

[Support/Contact us](#)

33409 / 114452926

[illegible]

- (00) [Setup Hosts](#)
- (01) [Install Graphic Driver](#)
- (02) [Display Disk Settings Info](#)
- (03) [Install Container Toolkit](#)
- (04) [Configure Network Bonding](#)
- (05) [Configure Network Bonding](#)
- (06) [CentOS Stream 8](#)
- (07) [Configure OS/Kernel/Hostnames](#)
- (08) [Configure Network \(Network\)](#)
- (09) [Configure Network \(Node\)](#)
- (10) [Configure Network \(Node\)](#)
- (11) [Configure Network \(Node\)](#)
- (12) [Configure Network \(Node\)](#)
- (13) [Configure Network \(Node\)](#)
- (14) [Configure Network \(Node\)](#)
- (15) [Configure Network \(Node\)](#)
- (16) [Configure Network \(Node\)](#)
- (17) [Configure Network \(Node\)](#)
- (18) [Configure Network \(Node\)](#)
- (19) [Configure Network \(Node\)](#)
- (20) [Configure Network \(Node\)](#)
- (21) [Configure Network \(Node\)](#)
- (22) [Configure Network \(Node\)](#)
- (23) [Configure Network \(Node\)](#)
- (24) [Configure Network \(Node\)](#)
- (25) [Configure Network \(Node\)](#)
- (26) [Configure Network \(Node\)](#)
- (27) [Configure Network \(Node\)](#)
- (28) [Configure Network \(Node\)](#)
- (29) [Configure Network \(Node\)](#)
- (30) [Configure Network \(Node\)](#)
- (31) [Configure Network \(Node\)](#)
- (32) [Configure Network \(Node\)](#)
- (33) [Configure Network \(Node\)](#)
- (34) [Configure Network \(Node\)](#)
- (35) [Configure Network \(Node\)](#)
- (36) [Configure Network \(Node\)](#)
- (37) [Configure Network \(Node\)](#)
- (38) [Configure Network \(Node\)](#)
- (39) [Configure Network \(Node\)](#)
- (40) [Configure Network \(Node\)](#)
- (41) [Configure Network \(Node\)](#)
- (42) [Configure Network \(Node\)](#)
- (43) [Configure Network \(Node\)](#)
- (44) [Configure Network \(Node\)](#)
- (45) [Configure Network \(Node\)](#)
- (46) [Configure Network \(Node\)](#)
- (47) [Configure Network \(Node\)](#)
- (48) [Configure Network \(Node\)](#)
- (49) [Configure Network \(Node\)](#)
- (50) [Configure Network \(Node\)](#)
- (51) [Configure Network \(Node\)](#)
- (52) [Configure Network \(Node\)](#)
- (53) [Configure Network \(Node\)](#)
- (54) [Configure Network \(Node\)](#)
- (55) [Configure Network \(Node\)](#)
- (56) [Configure Network \(Node\)](#)
- (57) [Configure Network \(Node\)](#)
- (58) [Configure Network \(Node\)](#)
- (59) [Configure Network \(Node\)](#)
- (60) [Configure Network \(Node\)](#)
- (61) [Configure Network \(Node\)](#)
- (62) [Configure Network \(Node\)](#)
- (63) [Configure Network \(Node\)](#)
- (64) [Configure Network \(Node\)](#)
- (65) [Configure Network \(Node\)](#)
- (66) [Configure Network \(Node\)](#)
- (67) [Configure Network \(Node\)](#)
- (68) [Configure Network \(Node\)](#)
- (69) [Configure Network \(Node\)](#)
- (70) [Configure Network \(Node\)](#)
- (71) [Configure Network \(Node\)](#)
- (72) [Configure Network \(Node\)](#)
- (73) [Configure Network \(Node\)](#)
- (74) [Configure Network \(Node\)](#)
- (75) [Configure Network \(Node\)](#)
- (76) [Configure Network \(Node\)](#)
- (77) [Configure Network \(Node\)](#)
- (78) [Configure Network \(Node\)](#)
- (79) [Configure Network \(Node\)](#)
- (80) [Configure Network \(Node\)](#)
- (81) [Configure Network \(Node\)](#)
- (82) [Configure Network \(Node\)](#)
- (83) [Configure Network \(Node\)](#)
- (84) [Configure Network \(Node\)](#)
- (85) [Configure Network \(Node\)](#)
- (86) [Configure Network \(Node\)](#)
- (87) [Configure Network \(Node\)](#)
- (88) [Configure Network \(Node\)](#)
- (89) [Configure Network \(Node\)](#)
- (90) [Configure Network \(Node\)](#)
- (91) [Configure Network \(Node\)](#)
- (92) [Configure Network \(Node\)](#)
- (93) [Configure Network \(Node\)](#)
- (94) [Configure Network \(Node\)](#)
- (95) [Configure Network \(Node\)](#)
- (96) [Configure Network \(Node\)](#)
- (97) [Configure Network \(Node\)](#)
- (98) [Configure Network \(Node\)](#)
- (99) [Configure Network \(Node\)](#)

- CentOS 8
- CentOS 6
- CentOS 5
- Debian 10
- Debian 9
- Debian 8
- Debian 7
- Debian 6
- Fedora 39
- Fedora 38
- Fedora 37
- Fedora 36
- Fedora 35
- Fedora 34
- Fedora 33
- Fedora 32
- Fedora 31 (Local Device)
- Fedora 30 (Control Node)
- Fedora 30 (Network Node)
- Fedora 29 Designate
- Fedora 28 (Control Node)
- Fedora 28 (Network Node)
- Fedora 27 Balancer Image
- Fedora 26 Octavia
- Fedora 25 Snocchi
- Fedora 24 Ceilometer (Network)
- Fedora 23 Ceilometer (Compute)
- Other Linux Distributions
- How to use Ceilometer (Nova)
- How to use Ceilometer (Glance)
- How to use Ceilometer (Cinder)
- Configure CloudKitty
- How to use CloudKitty
- Conf Trove (Control Node)
- Conf Trove (Network Node)
- How to use Trove
- OpenStack Caracal
- OpenStack Antelope
- OpenStack Zed
- OpenStack Yoga

Apache2 : Web Mail : RoundCube2022/05/17

[www.srv.world]	10.0.0.31	10.0.0.32	[mail.srv.world]
Apache httpd			Postfix
(Roundcube)			Dovecot
MariaDB			

- [1] [Install and Configure SMTP Server, refer to here.](#)
- [2] [Install and Configure IMAP Server, refer to here.](#)
- [3] [Configure SSL/TLS settings for SMTP/IMAP Server, refer to here.](#) (Optional)
- [4] [Install PHP on Apache2 Server, refer to here.](#)
- [5] [Configure SSL/TLS settings on Apache2 Server, refer to here.](#)
- [6] [Install and Configure MariaDB Server on httpd Server, refer to here.](#)
- [7] Create a Database for RoundCube.

```
root@www:~#  
mysql
```

```
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 37
Server version: 10.6.7-MariaDB-2ubuntu1 Ubuntu 22.04
```

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

```
# create [roundcube] database
# replace [password] to your own password you'd like to set
MariaDB [(none)]> create database roundcube;
Query OK, 1 row affected (0.00 sec)
```

```
MariaDB [(none)]> grant all privileges on roundcube.* to roundcube@'localhost' identified by 'password';
Query OK, 0 rows affected (0.00 sec)
```

```
MariaDB [(none)]> exit
Bye
```

[8] Install and Configure RoundCube.

```
root@www:~#
```

```
apt -y install roundcube roundcube-mysql
# select [No] on this example (set manually later)
```

```
+-----+ Configuring roundcube-core +-----+
|
| The roundcube package must have a database installed and configured
| before it can be used. This can be optionally handled with
| dbconfig-common.
|
| If you are an advanced database administrator and know that you want to
| perform this configuration manually, or if your database has already
| been installed and configured, you should refuse this option. Details
| on what needs to be done should most likely be provided in
| /usr/share/doc/roundcube.
|
| Otherwise, you should probably choose this option.
|
| Configure database for roundcube with dbconfig-common?
|
|                                     <Yes>                                     <No>
|
+-----+
```

```
root@www:~#
```

```
cd /usr/share/dbconfig-common/data/roundcube/install
```

```
root@www:/usr/share/dbconfig-common/data/roundcube/install#
mysql -u roundcube -D roundcube -p < mysql
```

Enter password:

```
# MariaDB roundcube password
```

```
root@www:/usr/share/dbconfig-common/data/roundcube/install#
```

```
cd
```

```
root@www:~#
```

```
vi /etc/roundcube/debian-db.php
// set database info
```

```
$dbuser='
roundcube
';
$dbpass='
password
';
$basepath="";
$dbname='
roundcube
';
$dbserver='localhost';
$dbport='3306';
$dbtype='
mysql
';
```

```
root@www:~#
```

```
vi /etc/roundcube/config.inc.php
// line 36 : specify IMAP server (STARTTLS setting)
```

```
$config['default_host'] = 'tls://mail.srv.world';
// line 50 : specify SMTP server (STARTTLS setting)
```

```
$config['smtp_server'] = 'tls://mail.srv.world';
// line 53 : specify SMTP port (STARTTLS setting)
```

```
$config['smtp_port'] = 587;
// line 57 : change (use the same user for SMTP auth and IMAP auth)
```

```
$config['smtp_user'] = '%u';
// line 61 : change (use the same password for SMTP auth and IMAP auth)
```

```
$config['smtp_pass'] = '%p';
// line 68 : change to any title you like
```

```
$config['product_name'] = 'Server World Webmail';
```

```
// add follows to the end
// specify IMAP port (STARTTLS setting)
```

```

$config['default_port'] = 143;

// specify SMTP auth type
$config['smtp_auth_type'] = 'LOGIN';

// specify SMTP HELO host
$config['smtp_helo_host'] = 'mail.srv.world';

// specify domain name
$config['mail_domain'] = 'srv.world';

// specify UserAgent
$config['useragent'] = 'Server World Webmail';

// specify SMTP and IMAP connection option
$config['imap_conn_options'] = array(
    'ssl' => array(
        'verify_peer' => true,
        'CN_match' => 'srv.world',
        'allow_self_signed' => true,
        'ciphers' => 'HIGH:!SSLv2:!SSLv3',
    ),
);
$config['smtp_conn_options'] = array(
    'ssl' => array(
        'verify_peer' => true,
        'CN_match' => 'srv.world',
        'allow_self_signed' => true,
        'ciphers' => 'HIGH:!SSLv2:!SSLv3',
    ),
);


root@www:~#
vi /etc/apache2/conf-enabled/roundcube.conf
# line 3 : uncomment

Alias /roundcube /var/lib/roundcube/public_html
# line 11 : change access permission if need


Require
ip 127.0.0.1 10.0.0.0/24
root@www:~#
systemctl restart apache2

```

[9] Access to [https://(your server's hostname or IP address)/roundcube/], then Roundcube login form is shown, authenticate with any user on Mail Server.



[10] After successfully logged in, verify possible to send or receive emails normally.



M a t c h e d C o n t e n t

Ubuntu 22.04 : Apache2

- [\(16\) Configure mod_http2](#)
- [\(17\) Configure mod_evasive](#)
- [\(18\) Log Report : AWStats](#)
- [\(19\) Blog System : WordPress](#)
- [\(20\) Web Mail : RoundCube](#)
-

[\[Previous Page \]](#)

Sponsored Link

Copyright © 2007-2024 Server World All Rights Reserved.