




- Server World

[Privacy Policy](#)

[Support/Contact us](#)

33404 / 114452921



the [mod_security] module to configure Web Application Firewall (WAF).

```
[1] Install [mod security].
```

```
root@www:~#
```

```
apt -y install libapache2-mod-security2
```

[2] Enable [mod security].

```
root@www:~#
```

```
cp -p /etc/modsecurity/modsecurity.conf-recommended /etc/modsecurity/modsecurity.conf
```

```
root@www:~#
```

vi /etc/modsecurity/modsecurity.conf

```
line 7 : [SecRuleEngine DetectionOnly] is set as default, it does not block actions
# if you'd like to block actions, change to [SecRuleEngine On]
SecRuleEngine DetectionOnly
```

• • • • •

• • • • •

It's possible to write a rule like follows.

$$\Rightarrow \text{SecRule VARIABLES OPERATOR [ACTIONS]}$$

[3] Each parameter has many kind of values, refer to official documents below.
<https://github.com/SpiderLabs/ModSecurity/wiki>

[4] For Example, set some rules and verify it works normally.

root@www:~#

```
vi /etc/modsecurity/localrules.conf
```

```
# default action when matching rules
```

SecDefaultAction "phase:2.deny.log.status:406"

[etc/passwd] is included in request URI

SecRule REQUEST_URI "etc/passwd" "id:'500001'"

[./] is included in request URI

SecRule REQUEST_URI "\.\/" "id:'500002'"


[**<SCRIPT**] is included in arguments

```
SecRule ARGS "<[Ss][Cc][Rr][Ii][Pp][Tt]" "id:'500003'"
```

[SELECT FROM] is included in arguments

```
SecRule ARGS "[Ss][Ee][Ll][Ee][Cc][Tt][:space:]+[Ff][Rr][Oo][Mm]" "id:'500004'"
```

```
root@www:~#
systemctl restart apache2
[5] Access to the URI which includes words you set and verify it works normally.
```



```
[6] The logs for [mod_security] is placed in the directory like follows.
root@www:~#
cat /var/log/apache2/modsec_audit.log

--622ba619-H--
Message: Access denied with code 406 (phase 2). Pattern match "<[Ss][Cc][Rr][Ii][Pp][Tt]" at ARGS:q. [file "/etc/modsecurity
Apache-Error: [file "apache2_util.c"] [line 271] [level 3] [client 10.0.0.5] ModSecurity: Access denied with code 406 (ph
Action: Intercepted (phase 2)
Stopwatch: 1652331282078532 1929 (- - -)
Stopwatch2: 1652331282078532 1929; combined=928, p1=759, p2=34, p3=0, p4=0, p5=135, sr=103, sw=0, l=0, gc=0
Response-Body-Transformed: Dechunked
Producer: ModSecurity for Apache/2.9.5 (http://www.modsecurity.org/); OWASP_CRS/3.3.2.
Server: Apache/2.4.52 (Ubuntu)
Engine-Mode: "ENABLED"

.....
```

```
[7] General rules are provided and applied by default under the directory below. However maybe you need to customize them for your own web sites not to block
necessary requests.
root@www:~#
ll /usr/share/modsecurity-crs/rules

total 676
drwxr-xr-x 2 root root 4096 May 12 04:48 ./
drwxr-xr-x 4 root root 4096 May 12 04:48 ../
-rw-r--r-- 1 root root 13513 Aug 24 2021 REQUEST-901-INITIALIZATION.conf
-rw-r--r-- 1 root root 13555 Aug 24 2021 REQUEST-903.9001-DRUPAL-EXCLUSION-RULES.conf
-rw-r--r-- 1 root root 25812 Aug 24 2021 REQUEST-903.9002-WORDPRESS-EXCLUSION-RULES.conf
-rw-r--r-- 1 root root 10642 Aug 24 2021 REQUEST-903.9003-NEXTCLOUD-EXCLUSION-RULES.conf
-rw-r--r-- 1 root root 7822 Aug 24 2021 REQUEST-903.9004-DOKUWIKI-EXCLUSION-RULES.conf
-rw-r--r-- 1 root root 1876 Aug 24 2021 REQUEST-903.9005-CPANEL-EXCLUSION-RULES.conf
.....
```

M a t c h e d C o n t e n t

- Ubuntu 22.04 : Apache2
- [\(01\) Install Apache2](#)
 - [\(02\) Configure Virtual Hostings](#)
 - [\(03\) Configure SSL/TLS](#)
 - [\(04\) Enable Userdir](#)
 - [\(05\) Use CGI Scripts](#)
 - [\(06\) Use PHP Scripts](#)
 - [\(07\) PHP + PHP-FPM](#)
 - [\(08\) Basic Authentication](#)
 - [\(09\) Configure WebDAV Folder](#)
 - [\(10\) Basic Authentication + PAM](#)
 - [\(11\) Kerberos Authentication](#)
 - [\(12\) Configure mod_md](#)

- [\(13\) Configure mod_proxy.](#)
- [\(14\) Configure mod_security.](#)
- [\(15\) Configure mod_ratelimit](#)
-

[\[Next Page \]](#)

Sponsored Link

Copyright © 2007-2024 Server World All Rights Reserved.