

18 - Exception Handling

December 1, 2022

COMP2404

Darryl Hill

Contents

1. Faults and Exceptions
2. Error Handling
3. Exception Handling
4. Stack Unwinding

No Program is Perfect

Your program can fail or act unexpectedly in many ways:

- ▶ Every program of reasonable size has bugs.
 - ▶ Bug - an implementation error.
- ▶ It is very difficult to anticipate every combination of inputs.
- ▶ Your code might interact with faulty hardware, other faulty code.
- ▶ etc.

Code ***Robustness***: Ability of your program to handle **faults** or **exceptions**.

Fault:

- ▶ Defect, bug, something causing your program to crash.

Exception:

- ▶ An event outside of the expected.

Types of fault:

- ▶ Bad input
 - ▶ Wrong data type
 - ▶ Unexpected format
 - ▶ Network failure
- ▶ Software bugs
 - ▶ Array out of bounds
 - ▶ Segmentation faults
 - ▶ Null pointers, dereferencing bad pointers

Stage 1: Fault Prevention

Write software in a way that minimizes faults.

- ▶ Follow good OO design
 - ▶ Easy to isolate and test a class with a well-defined, simple purpose
 - ▶ Difficult to test an entire program with multiple sub-purposes
- ▶ Code reviews
 - ▶ Your brain can trick you into not seeing your mistakes
 - ▶ Other people can see them
- ▶ Testing
 - ▶ Unit-testing
 - ▶ Integration testing
 - ▶ System testing
- ▶ You should unit test new code, then integrate it and test your program as a whole, then test it in real world

Aim: discover faults before the user does.

- ▶ Testing
 - ▶ Part of the software development life cycle.
 - ▶ Usually a planned (systematic) approach.
- ▶ Debugging
 - ▶ Systematic approach has failed, time to use the debugger / print statements
 - ▶ Not planned
- ▶ Beta-testing
 - ▶ People using your code is a good way to discover faults.
 - ▶ When a fault is discovered use debugging to find it.

Test success paths:

- ▶ Assume things go right
 - ▶ Data is sanitized (error checked beforehand)
 - ▶ Users use your software properly

Test failure paths:

- ▶ Assume things go wrong
 - ▶ Bad input, null pointers
 - ▶ Real users

Crashing?

- ▶ Use print statements or debugger to find **exactly** where it is crashing.

Bad data?

- ▶ Print out the variable every step of the way
- ▶ Find **exactly** where it is getting corrupted
 - ▶ Often different from where crash occurs

Debugging is not guess-work

Finding **exactly** where the problem is occurring is half the battle

Sometimes works, sometimes crashes?

- ▶ Are you accessing bad memory? Did you initialize your variables?
 - ▶ Sometimes in C++ bad memory will still work `^_(\\^)_/`

Once you know **exactly** where the problem is, if you cannot figure it out, ask someone else.

Code Robustness: the ability of a program to tolerate faults and keep running in a useful way.

Keeping our code robust:

- ▶ Error checking:
 - ▶ Assertions or contracts.
 - ▶ Inline error checking.
 - ▶ Goal is to detect a potential error state before it becomes part of your program.
- ▶ Exception handling:
 - ▶ When an unexpected (possibly faulty) state is reached.
 - ▶ Handled using an alternate flow of control.
 - ▶ Typically this alternate flow is programmatically expensive.
 - ▶ We may try and rejoin normal control flow or simply crash gracefully.

Difference between errors and exceptions:

- ▶ Errors ways that we expect things could go wrong.
 - ▶ Someone tries to enter a value out of range.
 - ▶ Someone makes a spelling mistake on their username.
- ▶ Simple, anticipated problems
- ▶ Handled during regular program flow using inline error handling.
- ▶ Exceptions are more rare and unexpected:
 - ▶ File system crashed
 - ▶ A system call did not work
- ▶ Handled outside of regular flow by an alternate control flow.

Inline error handling.

- ▶ Intermixing of program and error-handling logic.

```
do thing
if thing doesn't work
    process error
else
    proceed as normal
```

Good for simple error checking.

- ▶ Too much or too complex and code is difficult to read.
- ▶ Basic data sanitation is ok.

Exception Handling

- ▶ Used to resolve errors that are
 - ▶ less frequent
 - ▶ harder to check
 - ▶ harder to predict

Possible courses of action:

- ▶ Allow execution to continue.
- ▶ Notify the user there is a problem and continue.
 - ▶ We may not be sure of the state.
 - ▶ Did that file save or load properly?
 - ▶ An inconsistent state may cause problems later.
- ▶ Terminate the program and exit in a controlled manner

Exception handling (EH) is elegant in some ways, because it separates

- ▶ Error reporting - finding the problem
- ▶ Error handling - handling the problem

These things can occur in different parts of the program.

- ▶ EH provides an alternate return structure.
- ▶ Normal program stack return method is bypassed.

These things come at a price.

- ▶ Slow and expensive compared to inline error checking.
- ▶ Alternate control flow can cause important code to be skipped.

C++ library has an `exception` class:

- ▶ Used as a base class of user-defined `exception` classes.
- ▶ Constructor takes a `string message` argument
- ▶ Member function `what()` returns that message
- ▶ `exception` is “thrown” when there is an error.

We don't have to use `exception`

- ▶ We can throw anything, but
- ▶ Users of your class will likely try and catch an `exception` rather than your custom class.

Exception Handling Example

```
void func(){
    float x, num, den
    //initialize num and den
    try{
        if (den==0){
            throw "Divided by 0";
        }
        x = num / den;
    }
    catch (char* error){
        cout<<error;
    }
}
```

Error checking

Error reporting

Error handling

if we **throw** something the code execution exits the **try** block

Code after is not executed:
x = num / den;
is skipped

Enters the **catch** block

coding examples <p1>
and <p2>

- ▶ Stack of function calls with a `try` block at the top
- ▶ `cin.good()` tells if there was an input error
- ▶ We can `throw` whatever we like
 - ▶ not just `exceptions`
- ▶ Observe that we can throw local objects.
 - ▶ The temporary object is an `lvalue` that is copied into the catch parameter, however
 - ▶ Sometimes the compiler optimizes the two copies into a single object.
 - ▶ You might notice there is no call to a copy or move constructor.
- ▶ Processing continues after the `catch` block.

`try:`

- ▶ Block of potentially dangerous code
- ▶ If something goes wrong here, we would like to handle it
- ▶ What goes wrong may not be in the try block, but perhaps within a function within the try block

throw:

- ▶ We've detected some inconsistencies that we were not prepared for, so we "pass the buck" by **throwing** an exception
- ▶ May be in a **try** block, or within a function call within a **try** block, or within a function within a function within...
- ▶ If we throw something, and there is no **try/catch** block somewhere up the call stack, the program will terminate.

`catch:`

- ▶ Block that deals with the problem (by catching the exception)
- ▶ Try and figure out what went wrong and handle it gracefully.
- ▶ This block must immediately follow the `try` block
 - ▶ think `if-else` blocks

Throw in Called Function Example

```
void func(){
    float x, num, den;
    //initialize num and den
    try{
        x = divide(num, den);
    } catch (char* error){
        cout<<error;}
}

float divide(float a, float b){
    if (b == 0) throw "Divided by 0";
    return a/b;
}
```

We **throw** within a function within the **try** block.

- ▶ When an exception is thrown, control is transferred to the `catch` block
 - ▶ If the `catch` block is down the stack, then all stack frames between the `throw` and `catch` are popped off.
- ▶ Separation of error reporting and error handling is good software engineering.
- ▶ You might write Classes used by others
 - ▶ You don't know the circumstances when the error occurs.
 - ▶ There might be no console to print to!
 - ▶ Your code might be a library for some other app
 - ▶ Whoever made the app should decide how to handle errors.

Throw in Called Function Example

```
float divide(float a, float b){  
    if (b == 0) throw "Divided by 0";  
    return a/b;  
}  
float middle(float a, float b){  
    return divides(a,b);  
}  
void func(){  
    float x, num, den;  
    //initialize num and den  
    try{  
        x = middle(num, den);  
    } catch (char* error){  
        cout<<error;}  
}
```

This is the call stack. This stack frame is popped.

No **try** block here, so this stack frame is popped.

Control is returned to this function, within the **catch** block.

coding examples <p3> and <p4>

- ▶ Note how control is transferred, and how this affects (potentially) return values
- ▶ Putting the `try/catch` block inside or outside of a `for`-loop can affect behaviour
 - ▶ In one case the for-loop terminates
 - ▶ In the other the for-loop continues
- ▶ When making `try/catch` blocks should take note of how the control flow is interrupted and possible repercussions.

Multiple catch blocks

A `throw` statement has one parameter

- ▶ Compiler looks for the `catch` block with a matching parameter
- ▶ If we want to catch everything, then use `catch(...)`
 - ▶ the `throw` parameter cannot be used here
 - ▶ compiler does not know the types of the arguments


coding example <p5>

Example p5 Notes:

- ▶ We see examples of different catch blocks.
- ▶ The order of the catch blocks matter when using inheritance.

Multiple Catch Blocks - Order Matters

```
void func(){  
    try{  
        if (/*condition*/)  
            throw Car();  
    }  
    catch (Vehicle& v){ }  
    catch (Aircraft& a){ }  
    catch (Boat& b){ }  
    catch (Mazda& m){ }  
    catch (Car& c){ }  
    catch (...) { }  
}
```



The order of **catch** blocks matters!

- derived class
- base class
- catch all

Re-Thrown Exceptions

```
float divide(float a, float b){  
    if (b == 0) throw "Divided by 0";  
    return a/b;  
}
```

```
float middle(float a, float b){  
    try{ return divides(a,b); }  
    catch (char*){  
        cout<<"Caught! Throw again!";  
        throw; // no parameter ok here} }  
}
```

```
void func(){  
    try{  
        x = middle(num, den);  
    } catch (char* error){  
        cout<<error;}  
}
```

Throw the initial exception.

We need to do some cleanup here, throw again. We may throw the same exception or a different one.

Catch the re-thrown exception.

coding example <p6>

Exception Specifications

In C++, throw declarations are optional

```
int func(int x) throw (int, exception) { <body> }
```

- ▶ May throw `int` or `exception`

```
int func(int x) { <body> }
```

- ▶ May throw anything

```
int func( int x ) throw(){ <body> }
```

- ▶ May NOT throw anything

Throws that are not caught call `terminate()`

Stack unwinding is when an exception is thrown and the call stack is popped down to the catch block

- ▶ throw and catch bypass normal return structure
- ▶ May cause problems
 - ▶ local variables are destroyed
 - ▶ return values never returned
 - ▶ memory not deallocated
- ▶ Can cause an inconsistent state
 - ▶ `cout<<"This code should never execute";`
 - ▶ (I hate when this code executes)

Put all pointers in the catch parameter

- ▶ Cleanup occurs in the catch block
- ▶ Violates OO design
 - ▶ Are you sure someone will clean it for you?

Put a catch block in every called function that might potentially need it

- ▶ Each function does its own cleanup
- ▶ Good encapsulation

Make everything an object.

- ▶ Destructors are invoked on scope exit
 - ▶ Even when exiting via a thrown exception
- ▶ Cleanup is automatic

coding example <p7>

- ▶ 1st example - memory to be deallocated is placed in the Error object
- ▶ 2nd - destructor deletes the array
- ▶ 3rd - array is an object which destroys itself

```
class Error_message{  
    public:  
        Error_message(char* str, int* p):  
            message(str), arrayPtr(p){}  
        char* message;  
        int* arrayPtr;  
}
```

```
void g(){ try { f();}  
    catch (Error_message& m){  
        delete [ ] m.arrayPtr;  
        cout<<m.message;  
    }  
}
```

```
void f(){  
    int* a = new int[10];  
    if (/*condition*/)  
        throw Error_message("error",a);  
}
```


Better: Unwinding with Re-throw

```
void f(){  
    int* a = new int[10];  
    try { d(); }  
    catch (char*){  
        delete [ ] a;  
        throw;  
    }  
}
```

```
void g(){ try { f();}  
    catch (char* error){  
        cout<<error;  
    }  
}
```

```
void d(){  
    if (/*condition*/)   
        throw "error";  
}
```

Best: Unwinding with Destructors

```
void g(){ try { f();}  
        catch (char* error){  
            cout<<error;  
        }  
}
```

```
class MyArray{  
public:  
    MyArray(int size){arr = new int[size];}  
    ~MyArray(){delete [ ] arr;}  
private:  
    int* arr;  
}
```

```
void f(){  
    MyArray a(10);  
    d();  
}
```

```
void d(){  
    if (/*condition*/)  
        throw "error";  
}
```