

## 4 - Class Definitions

September 21, 2022

COMP2404

Darryl Hill

1. Class Members
2. Access Specifiers
3. Code Organization
4. Variable Scope
5. Namespaces

## Class Definitions

- ▶ `class` keyword followed by class name followed by braces `{}`, followed by semi-colon `;`

In the `class` block are the `class` members

- ▶ data members (instance variables)
- ▶ member functions (methods)

Each of these should be preceded by an access specifier

- ▶ `public`, `private`, `protected`
- ▶ default access level for classes is `private`

Industrial grade software is typically huge

- ▶ Millions of lines of code
- ▶ Hundreds of libraries and packages
- ▶ Must protect your code from unauthorized changes



Restrict access to unnecessary details, information, access whenever possible

- ▶ **Principle of Least Privilege**
- ▶ everything should be as close to private as possible
- ▶ example – you only want qualified people to access the inner workings of your car

Of course, some ([public](#)) access is necessary

## Public access

- ▶ class member is visible to all objects and global functions

## Protected access

- ▶ class member is visible by subclasses only
- ▶ different from Java
- ▶ make use of this only when using inheritance

## Private access

- ▶ not visible to other classes or global functions
- ▶ visible to other members of the **same class**
  - ▶ different from Java

# Objects in Memory

```
Student casey("100999999", "Casey");  
Student joe;
```

Observe there is no “new” here. How did we make new objects?

- ▶ C++ gives you the option of putting your objects on the **Stack** or the **Heap**
- ▶ It is faster to allocate objects to the **stack**
  - ▶ But when the **stackframe** is popped off, the object is gone
  - ▶ Convenient for temporary objects
- ▶ **Heap** is slower to allocate objects to
  - ▶ but the objects last as long as we like
- ▶ More on this later

# Member Function Implementations

A function implementation is the code for a function

For very small programs, we may include implementation in the class definition

- ▶ Getters for example
- ▶ This gets messy quickly – discouraged for larger programs

For all other programs, the implementation should be separate

- ▶ There are a couple of reasons:
  - ▶ Principle of Least Privilege
  - ▶ Can help avoid circular `#includes` between your files

Each class should have 2 files:

- ▶ A header file (using the `.h` extension) contains the class definition
  - ▶ Data member declarations
  - ▶ Member function prototypes (not the code!)
- ▶ A source file (using the `.cc` extension)
  - ▶ This contains the member function implementation (the actual code)
  - ▶ Static data member initializations
  - ▶ Related global function



# Standard Member Functions: Constructors

Job of a constructor to *initialize all data members*

- ▶ There are a few ways to initialize data members
- ▶ We will start with the most conventional
  - ▶ assignment operators

Constructor with no arguments – **default constructor**

- ▶ can be very important for things like arrays
- ▶ we decide if there is a default constructor

C++ classes can have multiple constructors

- ▶ cannot call “super” as with Java to make use of multiple constructors
- ▶ C++ can leverage other constructors, but uses a different syntax

## Other Standard Functions

There is no `toString()` function in C++

- ▶ initially we will use `print()` functions
- ▶ later we will see how to overload the stream insertion operator `<<`
  - ▶ C++ equivalent to `toString()`

Example **<p4>** from previous slides is bad – body of functions are within the class definition.

- ▶ against C++ conventions (though the compiler is fine with it)
- ▶ Keeping headers and source separate has actual advantages:
  - ▶ Compiler only needs the function prototype (header) to report usage errors
  - ▶ Header can be `#include`-d, and the source still compiled separately and linked.
  - ▶ Can help mitigate circular references.

**programming example <p1>**

Like primitive variables, we have choice in how to allocate classes.

- ▶ Statically allocated means memory is allocated where it is declared.
- ▶ Dynamically allocated means allocated on the Heap.

There is an extra complication using **classes** with **arrays**.

For now we will ***statically allocate*** arrays, but we still have 2 choices in the type of array:

- ▶ Array of objects, or
- ▶ array of object ***pointers***.
- ▶ Arrays of **objects** automatically call the **default constructor** of the **class**.

programming example <p2>

The C++ compiler is (deliberately) primitive

- ▶ It does not organize the code for you (like Java)

Consider the command: `g++ -c Date.cc`

- ▶ The compiler starts reading `Date.cc`.
- ▶ When it sees `#include "Date.h"` it jumps to that file and continues reading.
- ▶ Think of all `#include`-d files as one large file, in order.
  - ▶ If the compiler reads it top to bottom, will it make sense?
  - ▶ What information does the compiler need to ensure no errors?
  - ▶ What are the potential pitfalls?

# Class Interface

A **Class Interface** is *not* the same as a Java interface.

The **Interface** refers to the part of the class that can be accessed and used by other classes. It consists of

- ▶ class name and
- ▶ public members.

This defines how the user interacts with your class.

In C++, this is contained in the header file.

- ▶ Though there are also private and protected members in the header.

# Class Interface

To use a class, you `#include` the header file.

- ▶ This contains the public interface.
- ▶ This is enough information for the compiler to ensure that you use the class correctly.
- ▶ It is exactly like forward referencing your functions.

To make an executable using this class, you then must link your code to the object code.

- ▶ I.e., the implementation.

Users of your class do not need to see the source code.

- ▶ The interface and documentation give enough information for other developers to use your class.


Who will be using your class?

- ▶ Mostly other developers
- ▶ Even when writing end user code, you may want API's or other developers to contribute.

Other developers need to know:

- ▶ Class name,
- ▶ public members,
- ▶ descriptions of functions where appropriate, and
- ▶ (sometimes) protected members.

# Class Interface



- ▶ If we change our source code, we can recompile this separately from applications that use it.
- ▶ User only needs to re-link this source, not re-compile.



# Class Header File

Make sure to include the *header guards*.

- ▶ These guard against multiple `#include`-s.

`#include`-ing source code is inefficient.

- ▶ Unnecessarily forces recompilation of all code.
- ▶ This is frowned upon...mostly.
- ▶ **Source** file should `#include` the **header**, not vice-versa.

Understand what belongs in the header file (essentially your class API) vs the source file

- ▶ All source files should be compiled separately.
- ▶ Class users will only have to **relink** your code (for bug fixes, etc), which is fast.

Source files contain:

- ▶ All class related source code
  - ▶ (i.e., member function implementations).
- ▶ By default, all functions are global!
- ▶ Use the **scope resolution operator** of the *class* to inform the compiler of what is a class member.
  - ▶ This lets the compiler resolve the visibility of variables and other functions from the class definition (**public**, **protected**, **private**).
  - ▶ Or to identify static data member initializations...
    - ▶ ...more on this later.

**Variable scope** refers to where in the program a variable is visible.

- ▶ Block scope
  - ▶ including Class blocks.
- ▶ File scope
  - ▶ is outside of any block.
- ▶ Function scope for labels (we don't cover labels).
- ▶ Function prototype scope for parameters (we won't cover this either).
  - ▶ `int foo(int n, int x[n])`

A variable declared within a block has **block scope**.

- ▶ Visible within that block and all inner blocks (unless shadowed).
- ▶ Once we exit the block, the variable disappears and its value is discarded.
- ▶ Variables in inner blocks can hide variables in outer blocks.
  - ▶ Shadowing.
- ▶ If variables in nested blocks have the same name, the innermost block variable is the one used.
  - ▶ Try to avoid this - use unique identifiers when possible.
- ▶ Can always use the unary resolution operator to access a global value.
  - ▶ Other shadowed variables remain invisible, unless blocks are *namespaces*.
  - ▶ Coming soon.

A variable in File scope:

- ▶ Is declared outside of all blocks
- ▶ Visible everywhere in that file.
  - ▶ Global variables, or
  - ▶ global functions.

Such a variable can be accessed from another file using the **extern** keyword.

- ▶ Without **extern** the compiler will think it is a new variable declaration.

**Coding example** <p3>

# Namespaces

What is a **Namespace**?

- ▶ Not a class! Not a package! Has properties of both.
- ▶ Closest equivalent is Java ***package***, but more flexible.
- ▶ It is the definition of a (named) scope.

To use an element from a **namespace** you must scope it in by either

- ▶ using the **using** keyword
- ▶ use the ***scope resolution operator*** **::**

A **namespace** may be unnamed, then it is automatically scoped in.

- ▶ Has only ***internal*** linkage.
- ▶ Visible only to the current ***translation unit***
  - ▶ Current source and `#include-d` headers.
  - ▶ I.e., everything that makes this object file.