Name ⇒ Keshav Datta
Section ⇒ 23BCS-KRG 2B
UID ⇒ 23BCS10423

Q ⇒ Brute force Approach

→ For every query string s:
Compare with every stored string t
→ Check : ⊙ Same length
⊙ Exactly 1 mismatch

Time Complexity ⇒ O(nml)

Optimized Approach

1.) Insert all string into set
2.) for string s :
for i in range 0 to len(s) :
original = s[i]
for c in {a, b, c} :
if c != original :
s[i] = c
if s exists in set :
print "Yes"
restore s[i]

3.) Else Print "No"

Time Complexity :⇒ O(mL)
where m = No. of Queries
L = Length of String

Code ⇒

```
#include <bits/stdc++.h>
Using namespace std;
int main(){
    int n,m;
    cin>>n>>m;
    unordered_set<string> st;
    for (int i=0; i<n; i++){
        string s;
        cin>>s;
        st.insert(s);
    }
    while (m--){
        string s;
        cin>>s;
        bool found = false;
    for (int i=0; i<s.size(); i++){
        Char original = s[i];
    for (char c='a'; c<='c'; c++){
        if (c==original) continue;
        s[i] = c;
        if (st.count(s)) {
            found = true;
            break;
    }   }
        s[i] = original;
        if (found) break;
    }
    if (found)      cout << "Yes";
    else            cout << "No";
}
}
```