

Question Description:

Question No:7

Simon is studying B.Tech.-Mechanical Engineering.

He's going to attend a computer science-based subject exam this semester.

Due to the less preparation in the previous monthly tests, his internal mark decreased.

His computer science Professor made an offer one more chance to boost up his internal marks.

Professor assigns a program to Simon for the internal mark bootup.

So Simon wants to solve the given task is, Given two arrays, A and B, of equal size n,

the task is to find the minimum value of $A[0] * B[0] + A[1] * B[1] + \dots + A[n-1] * B[n-1]$,

where shuffling of elements of arrays A and B is allowed.

can you help him in solving Questions ?

Constraints:

$$1 \leq T \leq 100$$

$$1 \leq N \leq 50$$

$$1 \leq A[i] \leq 20$$

Input Format:

The first line of input contains an integer denoting the no of test cases.

Then T test cases follow. Each test case contains three lines.

The first line of input contains an integer N denoting the size of the arrays.

In the second line are N space separated values of the array A[], and in the last line are N space separated values of the array B[].

Output Format:

For each test case in a new line print the required result.

Example :

Input : A[] = {3, 1, 1} and B[] = {6, 5, 4}.

Output : 23 Minimum value of $S = 1*6 + 1*5 + 3*4 = 23$.

Input : A[] = { 6, 1, 9, 5, 4 } and B[] = { 3, 4, 8, 2, 4 }

Output : 80. Minimum value of $S = 1*8 + 4*4 + 5*4 + 6*3 + 9*2 = 80$.

▼ Logical Test Cases

Test Case 1

INPUT (STDIN)

```
3
4
2 5 3 7
8 5 7 3
3
13 11 1
6 15 14
5
6 11 9 15 4
3 41 8 21 4
```

Test Case 2

INPUT (STDIN)

```
2
3
13 11 1
6 15 14
5
6 11 9 15 4
3 41 8 21 4
```

EXPECTED OUTPUT

```
247
451
```

EXPECTED OUTPUT	83 247 451
-----------------	------------------

▼ Mandatory Test Cases

Test Case 1
KEYWORD
<pre>void sort(int a[],int n,int flag)</pre>

▼ Complexity Test Cases

Test Case 1
CYCLOMATIC COMPLEXITY
1

Test Case 2
TOKEN COUNT
420

Test Case 3
NLOC
55

Code :

```
1  #include <stdio.h>
2  #include <stdlib.h>
3  int compareAscending(const void *a, const void *b)
4  {
5      return (*(int *)a - *(int *)b);
6  }
7
8  int compareDescending(const void *a, const void *b)
9  {
10     return (*(int *)b - *(int *)a);
11 }
12 int main()
13 {
14     int T;
15     scanf("%d", &T);
16
17     while (T--)
18     {
19         int N;
20         scanf("%d", &N);
21
22         int A[N], B[N];
23
24         for (int i = 0; i < N; i++)
25         {
26             scanf("%d", &A[i]);
27         }
28     }
```

```

29     for (int i = 0; i < N; i++)
30     {
31         scanf("%d", &B[i]);
32     }
33
34     /* Sort A in ascending order */
35     qsort(A, N, sizeof(int), compareAscending);
36
37     /* Sort B in descending order */
38     qsort(B, N, sizeof(int), compareDescending);
39
40     long long sum = 0;
41
42     for (int i = 0; i < N; i++)
43     {
44         sum += (long long)A[i] * B[i];
45     }
46     printf("%lld\n", sum);
47 }
48 return 0;
49 }

```

Output :

Test Case-1 :

```

3
4
2 5 3 7
8 5 7 3
83
3
13 11 1
6 15 14
247
5
6 11 9 15 4
3 41 8 21 4
451

```

Test Case-2:

```
2
3
13 11 1
6 15 14
247
5
6 11 9 15 4
3 41 8 21 4
451
PS C:\Users\kesha\OneDrive\Documents\3sem\C>
```

Keshav Kumar Rauniyar
CH.SC.U4CSE25236