




Data Science Capstone Project

Keshav Krishnan

14.06.2024



Outline



- Executive Summary
- Introduction
- Methodology
- Results
- Conclusion
- Appendix

Executive Summary



Summary of methodologies

- Data collection
- Data wrangling
- Exploratory Data Analysis with Data Visualization
- Exploratory Data Analysis with SQL
- Building an interactive map with Folium
- Building a Dashboard with Plotly Dash
- Predictive analysis (Classification)

Summary of all results

- Exploratory Data Analysis results
- Interactive analytics demo in screenshots
- Predictive analysis results

Introduction

Project background and context

- ▶ SpaceX is the most successful company of the commercial space age, making space travel affordable. The company advertises Falcon 9 rocket launches on its website, with a cost of 62 million dollars; other providers cost upward of 165 million dollars each, much of the savings is because SpaceX can reuse the first stage. Therefore, if we can determine if the first stage will land, we can determine the cost of a launch. Based on public information and machine learning models, we are going to predict if SpaceX will reuse the first stage.
- ▶ Questions to be answered
 - ↪ How do variables such as payload mass, launch site, number of flights, and orbits affect the success of the first stage landing?
 - ↪ Does the rate of successful landings increase over the years?
 - ↪ What is the best algorithm that can be used for binary classification in this case?

Methodology

Data collection methodology:

- Using SpaceX Rest API
- Using Web Scrapping from Wikipedia

Performed data wrangling

- Filtering the data
- Dealing with missing values
- Using One Hot Encoding to prepare the data to a binary classification

Performed exploratory data analysis (EDA) using visualization and SQL

Performed interactive visual analytics using Folium and Plotly Dash

Performed predictive analysis using classification models

- Building, tuning and evaluation of classification models to ensure the best results



Methodology

Data collection

Data collection process involved a combination of API requests from SpaceX REST API and Web Scraping data from a table in SpaceX's Wikipedia entry.

We had to use both of these data collection methods in order to get complete information about the launches for a more detailed analysis.


Data Columns are obtained by using SpaceX REST API:

FlightNumber, Date, BoosterVersion, PayloadMass, Orbit, LaunchSite, Outcome, Flights, GridFins, Reused, Legs, LandingPad, Block, ReusedCount, Serial, Longitude, Latitude


Data Columns are obtained by using Wikipedia Web Scraping:

Flight No., Launch site, Payload, PayloadMass, Orbit, Customer, Launch outcome, Version Booster, Booster landing, Date, Time

Data collection – SpaceX API



Data collection – Web scraping



Data wrangling

In the dataset, booster landings are categorized based on their success and location. For example, **True Ocean** indicates a successful landing in the ocean, while **False Ocean** indicates a failed ocean landing. Similarly, **True RTLS** and **True ASDS** refer to successful landings on a ground pad and drone ship, respectively, whereas their **False** counterparts indicate failures. For training purposes, these outcomes are converted into binary labels: **1** for successful landings and **0** for unsuccessful ones.

Perform exploratory Data Analysis
and determine Training Labels



Calculate the number of launches
on each site

Calculate the number and occurrence
of each orbit

Calculate the number and occurrence
of mission outcome per orbit type

Create a landing outcome label
from Outcome column

Exporting the data
to CSV

EDA with data visualization

Charts plotted:

Flight Number vs. Payload Mass, Flight Number vs. Launch Site, Payload Mass vs. Launch Site, Orbit Type vs. Success Rate, Flight Number vs. Orbit Type, Payload Mass vs Orbit Type and Success Rate Yearly Trend

Scatter plots show the relationship between variables. If a relationship exists, they could be used in machine learning model.

Bar charts show comparisons among discrete categories. The goal is to show the relationship between the specific categories being compared and a measured value.

Line charts show trends in data over time (time series).

EDA with SQL

Performed SQL queries:

- Displaying the names of the unique launch sites in the space mission
- Displaying 5 records where launch sites begin with the string 'CCA'
- Displaying the total payload mass carried by boosters launched by NASA (CRS)
- Displaying average payload mass carried by booster version F9 v1.1
- Listing the date when the first successful landing outcome in ground pad was achieved
- Listing the names of the boosters which have success in drone ship and have payload mass greater than 4000 but less than 6000
- Listing the total number of successful and failure mission outcomes
- Listing the names of the booster versions which have carried the maximum payload mass
- Listing the failed landing outcomes in drone ship, their booster versions and launch site names for the months in year 2015
- Ranking the count of landing outcomes (such as Failure (drone ship) or Success (ground pad)) between the date 2010-06-04 and 2017-03-20 in descending order

Build an interactive map with Folium

Markers of all Launch Sites:

- Added Marker with Circle, Popup Label and Text Label of NASA Johnson Space Center using its latitude and longitude coordinates as a start location.
- Added Markers with Circle, Popup Label and Text Label of all Launch Sites using their latitude and longitude coordinates to show their geographical locations and proximity to Equator and coasts.

Coloured Markers of the launch outcomes for each Launch Site:

- Added coloured Markers of success (Green) and failed (Red) launches using Marker Cluster to identify which launch sites have relatively high success rates.

Distances between a Launch Site to its proximities:

- Added coloured Lines to show distances between the Launch Site KSC LC-39A (as an example) and its proximities like Railway, Highway, Coastline and Closest City.

Build a Dashboard with Plotly Dash

Launch Sites Dropdown List:

- Added a dropdown list to enable Launch Site selection.

Pie Chart showing Success Launches (All Sites/Certain Site):

- Added a pie chart to show the total successful launches count for all sites and the Success vs. Failed counts for the site, if a specific Launch Site was selected.


Slider of Payload Mass Range:

- Added a slider to select Payload range.

Scatter Chart of Payload Mass vs. Success Rate for the different Booster Versions:

- Added a scatter chart to show the correlation between Payload and Launch Success.

Predictive analysis (Classification)




Results



- Exploratory data analysis results
- Interactive analytics demo in screenshots
- Predictive analysis results

EDA with Visualization


Flight Number vs. Launch Site



Explanation:

- The earliest flights all failed while the latest flights all succeeded.
- The CCAFS SLC 40 launch site has about a half of all launches.
- VAFB SLC 4E and KSC LC 39A have higher success rates.
- It can be assumed that each new launch has a higher rate of success.

Payload vs. Launch Site




Explanation:

- For every launch site the higher the payload mass, the higher the success rate.
- Most of the launches with payload mass over 7000 kg were successful.
- KSC LC 39A has a 100% success rate for payload mass under 5500 kg too.


Success rate vs. Orbit type

Explanation:

- Orbits with 100% success rate:
 - ES-L1, GEO, HEO, SSO
- Orbits with 0% success rate:
 - SO
- Orbits with success rate between 50% and 85%:
 - GTO, ISS, LEO, MEO, PO, VLEO




Flight Number vs. Orbit type



Explanation:

- In the LEO orbit the Success appears related to the number of flights; on the other hand, there seems to be no relationship between flight number when in GTO orbit.

Payload Mass vs. Orbit type




Explanation:

- Heavy payloads have a negative influence on GTO orbits and positive on GTO and Polar LEO (ISS) orbits.

Launch success yearly trend

Explanation:

- The success rate since 2013 kept increasing till 2020.



EDA with SQL

All launch site names

```
[10]: %%sql
      SELECT DISTINCT Launch_Site FROM SPACEXTABLE;
```

```
* sqlite:///my_data1.db
```

```
Done.
```

```
[10]: Launch_Site
```

```
CCAFS LC-40
```

```
VAFB SLC-4E
```

```
KSC LC-39A
```

```
CCAFS SLC-40
```

Explanation:

- Displaying the names of the unique launch sites in the space mission.

Launch site names begin with 'CCA'

```
[11]: %%sql
      SELECT * FROM SPACEXTABLE
      WHERE Launch_Site LIKE 'CCA%'
      LIMIT 5;
```

```
* sqlite:///my_data1.db
Done.
```

```
[11]:
```

Date	Time (UTC)	Booster_Version	Launch_Site	Payload	PAYLOAD_MASS_KG_	Orbit	Customer	Mission_Outcome	Landing_Outcome
2010-06-04	18:45:00	F9 v1.0 B0003	CCAFS LC-40	Dragon Spacecraft Qualification Unit	0	LEO	SpaceX	Success	Failure (parachute)
2010-12-08	15:43:00	F9 v1.0 B0004	CCAFS LC-40	Dragon demo flight C1, two CubeSats, barrel of Brouere cheese	0	LEO (ISS)	NASA (COTS) NRO	Success	Failure (parachute)
2012-05-22	7:44:00	F9 v1.0 B0005	CCAFS LC-40	Dragon demo flight C2	525	LEO (ISS)	NASA (COTS)	Success	No attempt
2012-10-08	0:35:00	F9 v1.0 B0006	CCAFS LC-40	SpaceX CRS-1	500	LEO (ISS)	NASA (CRS)	Success	No attempt
2013-03-01	15:10:00	F9 v1.0 B0007	CCAFS LC-40	SpaceX CRS-2	677	LEO (ISS)	NASA (CRS)	Success	No attempt

Explanation:

- Displaying 5 records where launch sites begin with the string 'CCA'.

Total payload mass

Display the total payload mass carried by boosters launched by NASA (CRS) ⓘ

```
[12]: %%sql
      SELECT SUM(PAYLOAD_MASS__KG_) AS Total_Payload
      FROM SPACEXTABLE
      WHERE Customer = 'NASA (CRS)';
```

```
* sqlite:///my_data1.db
Done.
```

```
[12]: Total_Payload
      45596
```

Explanation:

- Displaying the total payload mass carried by boosters launched by NASA (CRS).

Average payload mass by F9 v1.1

```
[13]: %%sql
      SELECT AVG(PAYLOAD_MASS__KG_) AS Avg_Payload
      FROM SPACEXTABLE
      WHERE Booster_Version = 'F9 v1.1';
```

```
* sqlite:///my_data1.db
Done.
```

```
[13]: Avg_Payload
```

```
2928.4
```

Explanation:

- Displaying average payload mass carried by booster version F9 v1.1.

First successful ground landing date

```
[14]: %%sql
      SELECT MIN(Date) AS First_Success_Date
      FROM SPACEXTABLE
      WHERE Landing_Outcome = 'Success (ground pad)';
```

```
* sqlite:///my_data1.db
Done.
```

```
[14]: First_Success_Date
```

```
2015-12-22
```

```
5012-JS-55
```

Explanation:

- Listing the date when the first successful landing outcome in ground pad was achieved.

Successful drone ship landing with payload between 4000 and 6000

```
[15]: %%sql
      SELECT Booster_Version
      FROM SPACEXTABLE
      WHERE Landing_Outcome = 'Success (drone ship)'
      AND PAYLOAD_MASS__KG_ > 4000
      AND PAYLOAD_MASS__KG_ < 6000;
```

```
* sqlite:///my_data1.db
Done.
```

```
[15]: Booster_Version
```

```
F9 FT B1022
```

```
F9 FT B1026
```

```
F9 FT B1021.2
```

```
F9 FT B1031.2
```

Explanation:

- Listing the names of the boosters which have success in drone ship and have payload mass greater than 4000 but less than 6000.

Total number of successful and failure mission outcomes

List the total number of successful and failure mission outcomes

```
[16]: %%sql
      SELECT Mission_Outcome, COUNT(*) AS Count
      FROM SPACEXTABLE
      GROUP BY Mission_Outcome;
```

* sqlite:///my_data1.db

Done.

```
[16]:
```

Mission_Outcome	Count
Failure (in flight)	1
Success	98
Success	1
Success (payload status unclear)	1

Explanation:

- Listing the total number of successful and failure mission outcomes.

Boosters carried maximum payload

List all the booster_versions that have carried the maximum payload mass. Use a subquery.

```
[17]: %%sql
SELECT Booster_Version
FROM SPACEXTABLE
WHERE PAYLOAD_MASS__KG_ = (
    SELECT MAX(PAYLOAD_MASS__KG_) FROM SPACEXTABLE
);
```

```
* sqlite:///my_data1.db
Done.
```

```
[17]: Booster_Version
F9 B5 B1048.4
F9 B5 B1049.4
F9 B5 B1051.3
F9 B5 B1056.4
F9 B5 B1048.5
F9 B5 B1051.4
F9 B5 B1049.5
F9 B5 B1060.2
F9 B5 B1058.3
F9 B5 B1051.6
F9 B5 B1060.3
F9 B5 B1049.7
```

Explanation:

- Listing the names of the booster versions which have carried the maximum payload mass.

2015 launch records

```
[13]: %%sql
      SELECT substr(Date, 6, 2) AS Month, Booster_Version, Launch_Site, landing_outcome FROM SPACEXTABLE
      WHERE Landing_Outcome LIKE 'Failure (drone ship)'
      AND substr(Date, 0, 5) = '2015';
```

```
* sqlite:///my_data1.db
```

Done.

```
[13]:
```

Month	Booster_Version	Launch_Site	Landing_Outcome
01	F9 v1.1 B1012	CCAFS LC-40	Failure (drone ship)
04	F9 v1.1 B1015	CCAFS LC-40	Failure (drone ship)

Explanation:

- Listing the failed landing outcomes in drone ship, their booster versions and launch site names for the months in year 2015.

Rank success count between 2010-06-04 and 2017-03-20

```
[19]: %%sql
      SELECT Landing_Outcome, COUNT(*) AS Outcome_Count
      FROM SPACEXTABLE
      WHERE Date BETWEEN '2010-06-04' AND '2017-03-20'
      GROUP BY Landing_Outcome
      ORDER BY Outcome_Count DESC;
```

```
* sqlite:///my_data1.db
Done.
```

```
[19]:
```

Landing_Outcome	Outcome_Count
No attempt	10
Success (drone ship)	5
Failure (drone ship)	5
Success (ground pad)	3
Controlled (ocean)	3
Uncontrolled (ocean)	2
Failure (parachute)	2
Precluded (drone ship)	1

Explanation:


- Ranking the count of landing outcomes (such as Failure (drone ship) or Success (ground pad)) between the date 2010-06-04 and 2017-03-20 in descending order.

Interactive map with Folium

All launch sites' location markers on a global map

Explanation:


- Most of Launch sites are in proximity to the Equator line. The land is moving faster at the equator than any other place on the surface of the Earth. Anything on the surface of the Earth at the equator is already moving at 1670 km/hour. If a ship is launched from the equator it goes up into space, and it is also moving around the Earth at the same speed it was moving before launching. This is because of inertia. This speed will help the spacecraft keep up a good enough speed to stay in orbit.
- All launch sites are in very close proximity to the coast, while launching rockets towards the ocean it minimises the risk of having any debris dropping or exploding near people.



Colour-labeled launch records on the map

Explanation:


- From the colour-labeled markers we should be able to easily identify which launch sites have relatively high success rates.
 - **Green Marker** = Successful Launch
 - **Red Marker** = Failed Launch
- Launch Site KSC LC-39A has a very high Success Rate.



Distance from the launch site KSC LC-39A to its proximities

Explanation:

- From the visual analysis of the launch site KSC LC-39A we can clearly see that it is:
 - relative close to railway (15.23 km)
 - relative close to highway (20.28 km)
 - relative close to coastline (14.99 km)
- Also the launch site KSC LC-39A is relative close to its closest city Titusville (16.32 km).
- Failed rocket with its high speed can cover distances like 15-20 km in few seconds. It could be potentially dangerous to populated areas.





Build a Dashboard with Plotly Dash

Launch success count for all sites

Total Success Launches by Site



Explanation:

- The chart clearly shows that from all the sites, KSC LC-39A has the most successful launches.

Launch site with highest launch success ratio

Total Success Launches for Site KSC LC-39A



Explanation:

- KSC LC-39A has the highest launch success rate (76.9%) with 10 successful and only 3 failed landings.

Payload Mass vs. Launch Outcome for all sites

Explanation

- n:
- The charts show that payloads between 2000 and 5500 kg have the highest success rate.



Predictive analysis (Classification)

Classification Accuracy

Explanation:

- Based on the scores of the Test Set, we can not confirm which method performs best.
- Same Test Set scores may be due to the small test sample size (18 samples). Therefore, we tested all methods based on the whole Dataset.
- The scores of the whole Dataset confirm that the best model is the Decision Tree Model. This model has not only higher scores, but also the highest accuracy.

Scores and Accuracy of the Test Set

	LogReg	SVM	Tree	KNN
Jaccard_Score	0.800000	0.800000	0.800000	0.800000
F1_Score	0.888889	0.888889	0.888889	0.888889
Accuracy	0.833333	0.833333	0.833333	0.833333

Scores and Accuracy of the Entire Data Set


	LogReg	SVM	Tree	KNN
Jaccard_Score	0.833333	0.845070	0.882353	0.819444
F1_Score	0.909091	0.916031	0.937500	0.900763
Accuracy	0.866667	0.877778	0.911111	0.855556

Confusion Matrix

Explanation:

- Examining the confusion matrix, we see that logistic regression can distinguish between the different classes. We see that the major problem is false positives.

		Predicted Values	
		Negative	Positive
Actual Values	Negative	TN	FP
	Positive	FN	TP



Conclusion



- Decision Tree Model is the best algorithm for this dataset.
- Launches with a low payload mass show better results than launches with a larger payload mass.
- Most of launch sites are in proximity to the Equator line and all the sites are in very close proximity to the coast.
- The success rate of launches increases over the years.
- KSC LC-39A has the highest success rate of the launches from all the sites.
- Orbits ES-L1, GEO, HEO and SSO have 100% success rate.