AI Response Analysis and Prompt Engineering Platform

Keshav Batla
Roll No.: *[editable placeholder]*
Email: *[editable placeholder]*

Diviyansh
Roll No.: *[editable placeholder]*
Email: *[editable placeholder]*

Gurshant
Roll No.: *[editable placeholder]*
Email: *[editable placeholder]*

October 2026

Project Report – Prototype Stage

Submitted for UCS503P – Software Engineering Project
Thapar Institute of Engineering and Technology

Repository: AI Response Analysis and Prompt Engineering Platform

1 Prototype objective

working vertical slice

The prototype demonstrates one complete user journey: enter a non-empty prompt, generate a response through Anthropic when the backend has a server-side API key (or explicitly labelled deterministic demo text when demo mode is enabled), and inspect five explained heuristic indicators. The platform does not train a language model, persist interactions, or claim to reveal hidden reasoning.

2 Problem and project requirements

Users can receive answers that are unclear, long, incomplete, or poorly formatted without a useful way to examine observable response characteristics. The prototype integrates response generation with simple transparent signals to support review; it is not a fact-checker or an objective quality oracle.

ID	Requirement
FR-01	Submit a non-empty prompt from a responsive browser interface.
FR-02	Generate a live answer through the Anthropic Messages API using a backend-only environment key.
FR-03	With no key, allow a deterministic response only when `DEMO_MODE=true`, and label it as demo output.
FR-04	Analyze a prompt/answer pair and return five integer scores (0–100) and at least one explanation.
FR-05	Display the answer, five readable indicators, explanations, loading feedback, and useful errors.
FR-06	Expose `GET /api/health`; reject empty generation and analysis inputs.
NFR-01	Never send the provider key to the browser; restrict local CORS origins and bound provider timeouts.
NFR-02	Keep analysis scores explicitly heuristic, not factuality or correctness guarantees.
NFR-03	Do not claim prompt history is persisted; persistence is outside the prototype.

3 Implemented architecture

The React 18/Vite frontend (`Diviyansh/`) calls the FastAPI backend (`KeshavBatla/backend_main.py`) using a configurable `VITE_API_BASE_URL`. The backend calls Anthropic's Messages API only on the server, or responds with an explicitly labelled deterministic sample if demo mode is enabled and no key is configured. Both generation and standalone analysis are API endpoints. The shared heuristic analyzer remains in `Gurshant/database_analysis.py`. The existing SQLAlchemy model definitions are not connected to runtime operations; no database is required.




Figure 1: Implemented frontend, API, shared analyzer, provider and labelled demo path.

4 Data-flow diagrams

4.1 DFD Level 0 – system context




Figure 2: Prompt and evaluation exchange with the user; live generation with the external provider.

4.2 DFD Level 1 – processing detail




Figure 3: Prompt validation, response generation, heuristic analysis and browser results. No data store is implemented.

5 Core workflow and interfaces

1. The user types a prompt or loads the sample prompt. The UI rejects an empty submission, shows a character count and prevents repeated submission while working.
2. `POST /api/generate` validates the prompt. With `ANTHROPIC_API_KEY`, the server calls Anthropic's Messages endpoint with finite timeouts. Provider failures return a generic HTTP 502 response without exposing provider details.
3. Without a key, generation returns HTTP 503 unless `DEMO_MODE=true`. The deterministic response is marked `mode=demo`, names the deterministic model, and explicitly states that it was not generated by an AI model.
4. After generation, the browser posts the same prompt and generated response to `POST /api/analyze`.
5. The analyzer calculates relevance (keyword overlap), clarity (average sentence length), conciseness (word count), completeness (prompt-part coverage), and structure (formatting markers). Each score is clamped to 0–100 and accompanied by an observation.
6. The UI displays the generated text, all five indicators, observation notes, and, for sample output, a persistent visible demo-mode banner.

6 Analysis method and limitations

These inexpensive rule-based measures are inspectable proxies, not validated judgements. Keyword overlap can miss paraphrases; sentence length is not the same as comprehensibility; word count cannot determine whether content is concise for its task; the comma/"and" prompt split is a rough completeness proxy; and formatting markers cannot establish logical organization. Scores cannot establish factual correctness, safety, or model reasoning. Demo mode illustrates wiring only and its sample is deliberately not presented as live AI output. API keys must be supplied privately via environment variables; do not commit a key or local environment file.

7 Implementation status

Component	Status at this checkpoint
Prompt dashboard	Implemented React/Vite interface with sample prompt, responsive layout, request state, five score bars, explanations, and errors.
FastAPI	Implemented generation, analysis and health endpoints; input limits, restricted local CORS, environment-based provider configuration, bounded timeouts and sanitized provider errors.
Anthropic integration	Implemented but a live provider request has not been run in the no-key demonstration environment.
Demo mode	Implemented; opt-in only, deterministic and labelled in API output, visible banner, and response content.
Heuristic analyzer	Integrated from the existing shared analysis module, validates empty inputs and clamps all five scores.
Tests	15 unit and API tests pass. External generation is stubbed in the live-mode and error tests; no test issues a paid API request.
Persistence/history	Not implemented; interactions are not saved. SQLAlchemy models remain legacy definitions only.
Prompt optimization/comparison	Not implemented; future scope.

8 Test cases and observed results

Executed with `.venv\Scripts\python.exe -m pytest -q`: **15 passed, 1 warning, 0 failed**. The warning is Starlette's deprecation notice about `httpx` in its test client; it did not fail tests. No paid provider calls are made by the suite.

ID	Tested behaviour	Result
T-01	Health route returns {`"status":"ok"`}.	Pass
T-02	Blank generation prompt is rejected without a provider request.	Pass
T-03	Blank prompt or response is rejected by analysis endpoint and analyzer.	Pass
T-04	Analysis schema has exactly five bounded integer scores and explanations.	Pass
T-05	Long unstructured response returns bounded scores and length feedback.	Pass
T-06	Missing key without demo mode returns an explicit configuration error.	Pass
T-07	Deterministic demo response is returned and explicitly labelled.	Pass
T-08	Live generation path is tested using a stubbed provider; no external request.	Pass
T-09	Stubbed provider failure returns generic error without sensitive detail.	Pass

The Vite production build completed successfully. A browser smoke test also completed the demo-mode journey: the sample prompt produced the labelled response, all five score cards and an explanation. Live Anthropic connectivity was not tested without a real key. No database or persistence test is claimed.

9 Risks and mitigations

- **Provider outage, invalid key or quota:** bounded outbound timeout, generic actionable error and a separately enabled demo path.
- **Secret exposure:** API key remains backend-only and comes from an environment variable; local `.env` files and keys are ignored by Git.
- **Misleading heuristic values:** label the five values as indicators, list their observable basis, and state that they are not factuality scores.

- **Data retention expectations:** interactions are not persisted; the UI and documentation do not promise history.
- **Local port conflicts:** use the documented API-base setting and allowed frontend origin if the default port is already occupied.

10 Future plans

1. Evaluate and calibrate the heuristic indicators on human-reviewed prompt/response examples.
2. Add optional, explicitly configured database persistence and user-visible history with appropriate retention controls.
3. Add targeted prompt-improvement suggestions and revised-response comparison after the core analyzer is evaluated.
4. Expand integration and accessibility checks; configure production deployment and security controls only after local prototype requirements are stable.

11 Team responsibilities

- **Keshav Batla – Backend / AI integration:** FastAPI routes, Anthropic adapter, environment configuration and API error handling.
- **Diviyansh – Frontend:** prompt dashboard, request state, score visualisation, explanations and responsive layout.
- **Gurshant – Analysis / data layer:** transparent response-quality heuristics and existing SQLAlchemy model definitions.

Student details: roll numbers and email addresses are editable placeholders on the title page and must be filled in by the team.

12 Conclusion

The checkpoint delivers and tests the primary prompt-to-response-to-analysis workflow with a real Anthropic integration path and a clearly marked no-key demonstration path. The test suite passes locally and the frontend has a production build. Live API behavior and persistence remain intentionally unclaimed; heuristic scores remain interpretable but limited proxies.