

DSA ASSIGNMENT 8

QUESTION 1

```
#include <iostream>
using namespace std;
```

```
struct Node {
    int data;
    Node* left;
    Node* right;
};
```

```
Node* createNode(int value) {
    Node* newNode=new Node();
    newNode->data=value;
    newNode->left=nullptr;
    newNode->right=nullptr;
    return newNode;
}
```

```
void preorder(Node* root) {
    if(root==nullptr)
        return;
    cout<<root->data<<" ";
    preorder(root->left);
    preorder(root->right);
}
```

```
void inorder(Node* root) {
```

```
    if(root==nullptr)
        return;
    inorder(root->left);
    cout<<root->data<<" ";
    inorder(root->right);
}
```

```
void postorder(Node* root) {
    if(root==nullptr)
        return;
    postorder(root->left);
    postorder(root->right);
    cout<<root->data<<" ";
}
```

```
int main(){
    Node* root = createNode(1);
    root->left = createNode(2);
    root->right = createNode(3);
    root->left->left = createNode(4);
    root->left->right = createNode(5);

    cout<<"Preorder traversal: ";
    preorder(root);
    cout<<endl;

    cout<<"Inorder traversal: ";
    inorder(root);
    cout<<endl;
```

```
cout<<"Postorder traversal: ";  
postorder(root);  
cout<<endl;  
  
return 0;  
}
```

```
Preorder traversal: 1 2 4 5 3  
Inorder traversal: 4 2 5 1 3  
Postorder traversal: 4 5 2 3 1
```

```
=== Code Execution Successful ===
```

QUESTION 2

```
#include <iostream>
```

```
using namespace std;
```

```
struct Node {
```

```
    int data;
```

```
    Node* left;
```

```
    Node* right;
```

```
    Node(int val) {
```

```
        data = val;
```

```
        left = right = nullptr;
```

```
    }
```

```
};
```

```
Node* insertNode(Node* root, int value) {
```

```
    if (root == nullptr) {
```

```
        return new Node(value);
```

```
    }
```

```
    if (value < root->data) {
```

```
        root->left = insertNode(root->left, value);
```

```
    }
```

```
    else if (value > root->data) {
```

```
        root->right = insertNode(root->right, value);
```

```
    }
```

```
    return root;
```

```
}
```

```

bool searchRecursive(Node* root, int value) {
    if (root == nullptr) {
        return false;
    }
    if (root->data == value) {
        return true;
    }
    if (value < root->data) {
        return searchRecursive(root->left, value);
    } else {
        return searchRecursive(root->right, value);
    }

    return false; // FIX for warning
}

```

```

bool searchNonRecursive(Node* root, int value) {
    Node* curr = root;

    while (curr != nullptr) {
        if (value == curr->data) {
            return true;
        }
        else if (value < curr->data) {
            curr = curr->left;
        }
        else {
            curr = curr->right;
        }
    }
    return false;
}

```

```

int maximumElement(Node* root) {
    if (root == nullptr)
        return -1;

    Node* curr = root;
    while (curr->right != nullptr) {
        curr = curr->right;
    }
    return curr->data;
}

```

```

int minimumElement(Node* root) {
    if (root == nullptr)
        return -1;

    Node* curr = root;
    while (curr->left != nullptr) {
        curr = curr->left;
    }
    return curr->data;
}

```

```

Node* inorderSuccessor(Node* root, Node* target) {
    Node* succ = nullptr;

    while (root != nullptr) {
        if (target->data < root->data) {
            succ = root;
            root = root->left;
        }
        else if (target->data > root->data) {

```

```

        root = root->right;
    }
    else {
        if (root->right != nullptr) {
            Node* temp = root->right;
            while (temp->left != nullptr)
                temp = temp->left;
            succ = temp;
        }
        break;
    }
}
return succ;
}

```

```

Node* inorderPredecessor(Node* root, Node* target) {
    Node* pred = nullptr;

    while (root != nullptr) {
        if (target->data > root->data) {
            pred = root;
            root = root->right;
        }
        else if (target->data < root->data) {
            root = root->left;
        }
        else {
            if (root->left != nullptr) {
                Node* temp = root->left;
                while (temp->right != nullptr)
                    temp = temp->right;
                pred = temp;
            }
        }
    }
}

```

```
    }  
    break;  
}  
}  
return pred;  
}
```

```
int main() {  
    Node* root = nullptr;  
    root = insertNode(root, 10);  
    root = insertNode(root, 40);  
    root = insertNode(root, 30);  
    root = insertNode(root, 50);  
    root = insertNode(root, 20);  
  
    bool found;  
    found = searchNonRecursive(root, 20);  
    cout << found << endl;  
  
    found = searchRecursive(root, 60);  
    cout << found << endl;  
  
    int max, min;  
    max = maximumElement(root);  
    min = minimumElement(root);  
    cout << "Maximum: " << max << " Minimum: " << min << endl;  
  
    return 0;  
}
```


Output

1

0

Maximum: 50 Minimum: 10

=== Code Execution Successful ===

QUESTION 3

```
#include <iostream>

using namespace std;

struct Node{

    int data;

    Node*left;

    Node*right;

    Node(int val){

        data=val;

        left=right=nullptr;

    }

};

Node* insertElement(Node*root, int value){

    if (root==nullptr){

        return new Node(value);

    }

    if(value==root->data){

        return root;}

    if(value<root->data){

        root->left=insertElement(root->left, value);

    }

    else if(value>root->data){

        root->right=insertElement(root->right,value);

    }

    return root;

}
```

```

Node* findMin(Node* root) {
    while(root->left!=nullptr)
        root=root->left;
    return root;
}

```

```

Node* deleteElement(Node*root, int value){
    if(root==nullptr){
        return root;
    }
    if (value<root->data){
        root->left=deleteElement(root->left, value);
    }
    else if(value>root->data){
        root->right=deleteElement(root->right,value);
    }
    else{
        if(root->left==nullptr && root->right==nullptr){
            delete root;
            root=nullptr;
        }
        else if(root->left==nullptr){
            Node*temp=root;
            root=root->right;
            delete temp;
        }
        else if(root->right==nullptr){
            Node*temp=root;
            root=root->left;
            delete temp;
        }
    }
}

```

```

        else{
            Node*temp=findMin(root->right);
            root->data=temp->data;
            root->right=deleteElement(root->right,temp->data);
        }

    }
    return root;
}

int maxDepth(Node*root){
    if (root==nullptr){
        return 0;
    }
    int leftDepth=maxDepth(root->left);
    int rightDepth=maxDepth(root->right);

    return 1+max(leftDepth,rightDepth);
}

int minDepth(Node*root){
    if (root==nullptr){
        return 0;
    }
    if (root->left==nullptr){
        return 1+minDepth(root->right);
    }
    if(root->right==nullptr){
        return 1+minDepth(root->left);
    }

    return 1+min(minDepth(root->left), minDepth(root->right));
}

```

```
}
```

```
int main(){
```

```
    Node*root=nullptr;
```

```
    root=insertElement(root,10);
```

```
    root=insertElement(root,40);
```

```
    root=insertElement(root,30);
```

```
    root=insertElement(root,50);
```

```
    root=insertElement(root,20);
```

```
    root=deleteElement(root,10);
```


```
    int maxmDepth=maxDepth(root);
```

```
    int minmDepth=minDepth(root);
```

```
    cout<<"Minimum depth: "<<minmDepth<<"\nMaximum Depth: "<<maxmDepth;
```

```
    return 0;
```

```
}
```



```
Minimum depth: 2
```

```
Maximum Depth: 3
```

```
=== Code Execution Successful ===
```

QUESTION 4

```
#include <iostream>

#include <limits.h>

using namespace std;

struct Node{

    int data;

    Node* left;

    Node* right;

    Node(int value){

        data=value;

        left=right=nullptr;

    }

};

bool isBSTUtil(Node* root, int minVal, int maxVal){

    if (root == nullptr){

        return true;

    }

    if (root->data <= minVal || root->data >= maxVal){

        return false;

    }

    return isBSTUtil(root->left, minVal, root->data) && isBSTUtil(root->right, root->data, maxVal);

}


bool isBST(Node* root){

    return isBSTUtil(root, INT_MIN, INT_MAX);

}
```

```
}
```

```
int main(){  
    Node* root=new Node(10);  
    root->left=new Node(5);  
    root->right=new Node(20);  
    root->left->left=new Node(3);  
    root->left->right=new Node(7);  
  
    if(isBST(root))  
        cout << "Yes, it is a BST";  
    else  
        cout << "No, it is NOT a BST";  
  
    return 0;  
}
```



The screenshot shows a dark-themed output window. At the top, the word "Output" is written in a light blue font. Below it, the text "Yes, it is a BST" is displayed in a light blue monospace font. At the bottom, the text "=== Code Execution Successful ===" is shown in a light green monospace font.

QUESTION 5

```
#include <iostream>

using namespace std;

void heapifyMax(int arr[], int n, int i) {
    int largest=i;
    int left=2*i+1;
    int right=2*i+2;

    if(left < n && arr[left] > arr[largest])
        largest = left;

    if(right < n && arr[right] > arr[largest])
        largest = right;

    if(largest != i){
        swap(arr[i], arr[largest]);
        heapifyMax(arr, n, largest);
    }
}

void heapSortIncreasing(int arr[], int n){
    for (int i=n/2-1;i>=0;i--)
        heapifyMax(arr, n, i);

    for (int i=n-1;i>0;i--) {
        swap(arr[0], arr[i]);
        heapifyMax(arr, i, 0);
    }
}
```



```

void heapifyMin(int arr[], int n, int i) {
    int smallest=i;
    int left=2*i+1;
    int right=2*i+2;
    if (left<n && arr[left]<arr[smallest])
        smallest = left;

    if (right< n && arr[right]<arr[smallest])
        smallest=right;

    if (smallest!=i){
        swap(arr[i], arr[smallest]);
        heapifyMin(arr, n, smallest);
    }
}

```

```

void heapSortDecreasing(int arr[], int n){
    for (int i=n/2-1;i>=0;i--)
        heapifyMin(arr, n, i);

    for (int i=n-1;i>0;i--){
        swap(arr[0], arr[i]);
        heapifyMin(arr, i, 0);
    }
}

```

```

int main(){
    int arr[]={12, 3, 19, 8, 5, 7};
    int n = sizeof(arr)/sizeof(arr[0]);

    heapSortIncreasing(arr, n);

    cout << "Sorted array: ";
}

```

```
for (int x : arr) cout << x << " ";  
}
```

Output

Sorted array: 3 5 7 8 12 19

=== Code Execution Successful ===

QUESTION 6

```
#include <iostream>
```

```
using namespace std;
```

```
#define MAX 100
```

```
int heapArr[MAX];
```

```
int heapSize = 0;
```

```
void heapifyUp(int index){
```

```
    while (index > 0){
```

```
        int parent = (index - 1) / 2;
```

```
        if (heapArr[parent] < heapArr[index]) {
```

```
            swap(heapArr[parent], heapArr[index]);
```

```
            index = parent;
```

```
        } else break;
```

```
    }
```

```
}
```

```
void heapifyDown(int index){
```

```
    while (true){
```

```
        int left = 2 * index + 1;
```

```
        int right = 2 * index + 2;
```

```
        int largest = index;
```

```
        if (left < heapSize && heapArr[left] > heapArr[largest])
```

```
            largest = left;
```

```
        if (right < heapSize && heapArr[right] > heapArr[largest])
```

```
            largest = right;
```

```
        if (largest != index) {
```

```
            swap(heapArr[index], heapArr[largest]);
```

```
        index = largest;
    } else break;
}
}
```

```
void insertElement(int value){
    if (heapSize >= MAX) {
        cout << "Heap overflow!\n";
        return;
    }
    heapArr[heapSize] = value;
    heapifyUp(heapSize);
    heapSize++;
}
```

```
int getMax(){
    if (heapSize == 0){
        cout << "Heap empty!\n";
        return -1;
    }
    return heapArr[0];
}
```

```
void deleteMax(){
    if (heapSize == 0){
        cout << "Heap empty!\n";
        return;
    }
}
```

```
heapArr[0] = heapArr[heapSize - 1];
heapSize--;
```

```
heapifyDown(0);
```

```

}

void printHeap(){
    for (int i = 0; i < heapSize; i++)
        cout << heapArr[i]<<" ";
    cout << endl;
}

int main(){
    insertElement(40);
    insertElement(10);
    insertElement(50);
    insertElement(30);
    insertElement(20);

    cout<<"Max element: "<<getMax()<<endl;

    deleteMax();
    cout << "After deleting max: ";
    printHeap();

    return 0;
}

```

Output

```

Max element: 50
After deleting max: 40 30 20 10

```

```

=== Code Execution Successful ===

```