

Specware 4.1 Language Manual

Specware 4.1 Language Manual

Copyright © 2001-2004 by Kestrel Development Corporation

Copyright © 2001-2004 by Kestrel Technology LLC

All rights reserved

The name Specware® is a registered trademark of Kestrel Development Corporation

Table of Contents

Disclaimer	i
1. Introduction to Specware	1
1.1. What Is Specware?.....	1
1.2. What Is Specware For?	1
1.3. The Design Process in Specware	2
1.4. Stages of Application Building	3
1.4.1. Building a Specification.....	3
1.4.2. Refining Your Specifications to Constructive Specifications.....	4
1.5. Reasoning About Your Code	5
1.5.1. Abstractness in Specware	5
1.5.2. Logical Inference in Specware.....	6
2. Metaslang.....	7
2.1. Preliminaries	7
2.1.1. The Grammar Description Formalism	7
2.1.2. Models.....	8
2.1.3. Type-correctness	9
2.1.4. Constructive	11
2.2. Lexical conventions	11
2.2.1. Symbols and Names.....	12
2.2.2. Comments	14
2.3. Units.....	15
2.3.1. Unit Identifiers	17
2.3.2. Specs	18
2.3.2.1. Spec Forms.....	18
2.3.2.2. Qualifications	19
2.3.2.3. Translations.....	22
2.3.2.4. Substitutions.....	23
2.3.2.5. Diagram Colimits.....	25
2.3.2.6. Obligators.....	25
2.3.3. Morphisms	25
2.3.4. Diagrams	27
2.3.5. Target Code Terms	28
2.3.6. Proof Terms.....	28
2.4. Declarations	29
2.4.1. Import-declarations	30
2.4.2. Type-declarations	32
2.4.3. Type-definitions	32

2.4.4. Op-declarations	33
2.4.5. Op-definitions	35
2.4.6. Claim-definitions	38
2.5. Type-descriptors	39
2.5.1. Type-sums	40
2.5.2. Type-arrows	42
2.5.3. Type-products	43
2.5.4. Type-instantiations	43
2.5.5. Type-names	44
2.5.6. Type-records	44
2.5.7. Type-restrictions	45
2.5.8. Type-comprehensions	46
2.5.9. Type-quotients	47
2.6. Expressions	47
2.6.1. Lambda-forms	49
2.6.2. Case-expressions	50
2.6.3. Let-expressions	50
2.6.4. If-expressions	51
2.6.5. Quantifications	52
2.6.6. Annotated-expressions	53
2.6.7. Applications	53
2.6.8. Restrict-expressions	56
2.6.9. Op-names	57
2.6.10. Literals	57
2.6.10.1. Boolean-literals	58
2.6.10.2. Nat-literals	58
2.6.10.3. Char-literals	58
2.6.10.4. String-literals	60
2.6.11. Field-selections	61
2.6.12. Tuple-displays	62
2.6.13. Record-displays	62
2.6.14. Sequential-expressions	63
2.6.15. List-displays	63
2.6.16. Structors	64
2.6.16.1. Projectors	65
2.6.16.2. Relaxators	65
2.6.16.3. Quotienters	66
2.6.16.4. Choosers	67
2.6.16.5. Embedders	68
2.6.16.6. Embedding-tests	69

2.7. Matches and Patterns	69
2.7.1. Matches	69
2.7.2. Patterns	71
A. Metaslang Grammar.....	77
B. Inbuilts and Base Libraries	93
B.1. Inbuilts	93
B.2. Boolean.....	94
B.3. Integer.....	94
B.4. Nat	96
B.5. Char	97
B.6. String	98
B.7. List.....	100
B.8. Compare	103
B.9. Option.....	104
B.10. Functions	105

Disclaimer

As experience is gained with Specware 4.1, both the operation of the Specware system and the Metaslang language are bound to undergo changes, which may not always be fully “backwards compatible”.

For updates, news and bug reports, visit the Specware web site
<http://www.specware.org>.

Disclaimer

Chapter 1. Introduction to Specware

1.1. What Is Specware?

Specware is a tool for building and manipulating a collection of related specifications. Specware can be considered:

- a design tool, because it can represent and manipulate designs for complex systems, software or otherwise
- a logic, because it can describe concepts in a formal language with rules of deduction
- a programming language, because it can express programs and their properties
- a database, because it can store and manipulate collections of concepts, facts, and relationships

Specifications are the primary units of information in Specware. A specification, or theory, describes a concept to some degree of detail. To add properties and extend definitions, you create new specifications that import or combine earlier specifications. Within a specification, you can reason about objects and their relationships. You declare types (data types) and operations (ops, functions), axioms that state properties of operations, and theorems that follow logically from axioms.

A morphism is a relationship between specifications that describes how the properties of one map to the properties of another. Morphisms describe both part-of and is-a relationships. You can propagate theorems from one specification to another using morphisms; for example, if the QEII is a ship, and ships cannot fly, then the QEII cannot fly.

1.2. What Is Specware For?

Specware is a general-purpose tool that you can use to develop specifications for any system or realm of knowledge. You can do this as an abstract process, with no reference to computer programming; or you can produce a computer program that is provably a correct implementation of a specification; or you can use the process to redesign an existing program.

You can use Specware to:

- **Develop domain theories**

You can use Specware to do “ontological engineering” -- that is, to describe a real-world domain of knowledge in explicit or rigorous terms. You might wish to develop a domain theory in abstract terms that are not necessarily intended to become a computer program. You can use the inference engine to test the internal logic of your theory, derive conclusions, and propose theorems.

You can use specifications and morphisms to represent abstract knowledge, with no refinement to any kind of concrete implementation.

More commonly, you would use Specware to model expert knowledge of engineering design. In this case you would refine your theoretical specifications and morphisms to more concrete levels.

- **Develop code from specifications**

You can use Specware to develop computer programs from specifications. One advantage of using Specware for this task is that you can prove that the generated code does implement the specification correctly. Another advantage is that you can develop and compare different implementations of the same specification.

- **Develop specifications from code**

You can use Specware for reverse engineering -- that is, to help you derive a specification from existing code. To do this, you must examine the code to determine what problems are being solved by it, then use Specware’s language Metaslang to express the problems as specifications. In addition to providing a notation tool for this process, Specware allows you to operate on the derived specification. Once you have derived a specification from the original code, you can analyze the specification for correctness and completeness, and also generate different and correct implementations for it.

1.3. The Design Process in Specware

To solve real problems, programs typically combine domain theories about the physical world with problem solving theories about the computational world. Your domain theory is an abstract representation of a real-world problem domain. To implement it,

you must transform the domain theory to a concrete computational model. The built-in specification libraries describe mathematical and computational concepts, which are building blocks for an implementation. Your specifications combine real-world knowledge with this built-in computational knowledge to generate program code that solves real-world problems in a rigorous and provable way.

You interpret designs relative to an initial universe of models. In software design, for example, the models are programs, while in engineering design, they are circuits or pieces of metal. To design an object is to choose it from among the universe of possible models. You make this choice by beginning with an initial description and augmenting it until it uniquely describes the model you desire. In Specware, this process is called refinement.

Composition and refinement are the basic techniques of application building in Specware. You compose simpler specifications into more complex ones, and refine more abstract specifications into more concrete ones. When you refine a specification, you create a more specific case of it; that is, you reduce the number of possible models of it.

The process of refinement is also one of composition. To begin the refinement, you construct primitive refinements that show how to implement an abstract concept in terms of a concrete concept. You then compose refinements to deepen and widen the refinement.

For example, suppose you are designing a house. A wide but not deep view of the design specifies several rooms but gives no details. A deep but not wide view of the design specifies one room in complete detail. To complete the refinement, you must create a view that is both wide and deep; however, it makes no difference which view you create first.

The final refinement implements a complex, abstract specification from which code can be generated.

1.4. Stages of Application Building

Conceptually, there are two major stages in producing a Specware application. In the actual process, steps from these two stages may alternate.

1. Building a specification
2. Refining your specifications to constructive specifications

1.4.1. Building a Specification

You must build a specification that describes your domain theory in rigorous terms. To do this, you first create small specifications for basic, abstract concepts, then specialize and combine these to make them more concrete and complex.

To relate concepts to each other in Specware, you use specification morphisms. A specification morphism shows how one concept is a specialization or part of another. For example, the concept “fast car” specializes both “car” and “fast thing”. The concept “room” is part of the concept “house”. You can specialize “room” in different ways, one for each room of the house.

You specialize in order to derive a more concrete specification from a more abstract specification. Because the specialization relation is transitive (if A specializes B and B specializes C, then A specializes C as well), you can combine a series of morphisms to achieve a step-wise refinement of abstract specifications into increasingly concrete ones.

You combine specifications in order to construct a more complex concept from a collection of simpler parts. In general, you increase the complexity of a specification by adding more structural detail.

Specware helps you to handle complexity and scale by providing composition operators that take small specifications and combine them in a rigorous way to produce a complex specification that retains the logic of its parts. Specware provides several techniques for combining specifications, that can be used in combination:

- The import operation allows you to include earlier specifications in a later one.
- The translate operation allows you to rename the parts of a specification.
- The colimit operation glues concepts together into a shared union along shared subconcepts.

A shared union specification combines specializations of a concept. For example, if you combine “red car” with “fast car” sharing the concept “car”, you obtain the shared union “fast, red car”. If you combine them sharing nothing, you obtain “red car and fast car”, which is two cars rather than one. Both choices are available.

1.4.2. Refining Your Specifications to Constructive Specifications

You combine specifications to extend the refinement iteratively. The goal is to create a

refinement between the abstract specification of your problem domain and a concrete implementation of the problem solution in terms of types and operations that ultimately are defined in the Specware libraries of mathematical and computational theories.

For example, suppose you want to create a specification for a card game. An abstract specification of a card game would include concepts such as card, suit, and hand. A refinement for this specification might map cards to natural numbers and hands to lists containing natural numbers.

The Specware libraries contains constructive specifications for various types, including natural numbers and lists.

To refine your abstract specification, you build a refinement between the abstract Hand specification and the List-based specification. When all types and operations are refined to concrete library-defined types and operations, the Specware system can generate code from the specification.

1.5. Reasoning About Your Code

Writing software in Metaslang, the specification and programming language used in Specware, brings many advantages. Along with the previously-mentioned possibilities for incremental development, you have the option to perform rigorous verification of the design and implementation of your code, leading to the a high level of assurance in the correctness of the final application.

1.5.1. Abstractness in Specware

Specware allows you to work directly with abstract concepts independently of implementation decisions. You can put off making implementation decisions by describing the problem domain in general terms, specifying only those properties you need for the task at hand.

In most languages, you can declare either everything about a function or nothing about it. That is, you can declare only its type, or its complete definition. In Specware you must declare the signature of an operation, but after that you have almost complete freedom in stating properties of the operation. You can declare nothing or anything about it. Any properties you have stated can be used for program transformation.

For example, you can describe how squaring distributes over multiplication:

```
axiom square_distributes_over_times is
  fa(a, b) square(a * b) = square(a) * square(b)
```

This property is not a complete definition of the squaring operation, but it is true. The truth of this axiom must be preserved as you refine the operation. However, unless you are going to generate code for `square`, you do not need to supply a complete definition.

The completeness of your definitions determines the extent to which you can generate code. A complete refinement must completely define the operations of the source theory in terms of the target theory. This guarantees that, if the target is implementable, the source is also implementable.

1.5.2. Logical Inference in Specware

Specware performs inference using external theorem provers; the distribution includes SRI's SNARK theorem prover. External provers are connected to Specware through logic morphisms, which relate logics to each other.

You can apply external reasoning agents to refinements in different ways (although only verification is fully implemented in the current release of Specware).

- Verification tests the correctness of a refinement. For example, you can prove that quicksort is a correct refinement of the sorting specification.
- Simplification is a complexity-reducing refinement. For example, given appropriate axioms, you can rewrite $3*a+3*b$ to $3*(a+b)$.
- Synthesis derives a refinement for a given specification by combining the domain theory with computational theory. For example, you can derive quicksort semi-automatically from the sorting specification as a solution to a sorting problem, if you describe exactly how the problem is a sorting problem.

Chapter 2. Metaslang

This chapter introduces the Metaslang specification language.

The following sections give the grammar rules and meaning for each Metaslang language construct.

2.1. Preliminaries

2.1.1. The Grammar Description Formalism

The grammar rules used to describe the Metaslang language use the conventions of (extended) BNF. For example, a grammar rule like:

$$\text{waffle} ::= \text{waffle} \ [\ \text{waffle-tail} \] \ | \ \text{piffle} \ \{ \ + \ \text{piffle} \ }^*$$

defines a **waffle** to be: either a **waffle** optionally followed by a **waffle-tail**, or a sequence of one or more **piffles** separated by terminal symbols **+**. (Further rules would be needed for **waffle**, **waffle-tail** and **piffle**.) In a grammar rule the left-hand side of $::=$ shows the kind of construct being defined, and the right-hand side shows how it is defined in terms of other constructs. The sign **|** separates alternatives, the square brackets **[...]** enclose optional parts, and the curly braces plus asterisk **{ ... }*** enclose a part that may be repeated any number of times, including zero times. All other signs stand for themselves, like the symbol **+** in the example rule above.

In the grammar rules terminal symbols appear in a bold font. Some of the terminal symbols used, like **|** and **{**, are very similar to the grammar signs like **|** and **{** as described above. They can hopefully be distinguished by their bold appearance.

Grammar rules may be *recursive*: a construct may be defined in terms of itself, directly or indirectly. For example, given the rule:

$$\text{piffle} ::= \mathbf{1} \ | \ \mathbf{M} \ \{ \ \text{piffle} \ }^*$$

here are some possible **piffles**:

1 M M1 M111 MMMM M1M1

Note that the last two examples of **piffles** are ambiguous. For example, **M1M1** can be interpreted as: **M** followed by the two **piffles** **1** and **M1**, but also as: **M** followed by the

three piffles 1, M, and another 1. Some of the actual grammar rules allow ambiguities; the accompanying text will indicate how they are to be resolved.

2.1.2. Models

`op ::= op-name`

In Metaslang, *op* is used as an abbreviation for “op-name”, where op-names are declared **names** representing values. (*Op* for *operator*, a term used for historical reasons, although including things normally not considered operators.)

`spec ::= spec-form`

The term **spec** is used as short for **spec-form**. The *semantics* of Metaslang **specs** is given in terms of classes of *models*. A model is an assignment of sets of values (called “types”) to all the **type-names** and of “typed” values to all the **ops** declared -- explicitly or implicitly -- in the **spec**. The notion of *value* includes numbers, strings, arrays, functions, etcetera. A typed value can be thought of as a pair (T, V) , in which T is a type and V is a value that is an inhabitant of T . For example, the expressions `0 : Nat` and `0 : Integer` correspond, semantically, to the typed values $(N, 0)$ and $(Z, 0)$, respectively, in which N stands for the set of natural numbers $\{0, 1, 2, \dots\}$, and Z for the set of integers $\{\dots, -2, -1, 0, 1, 2, \dots\}$. For example, given this **spec**:

```
spec
  type Even
  op next : Even -> Even
  axiom nextEffect is
    fa(x : Even) ~(next x = x)
endspec
```

one possible model (out of many!) is the assignment of the even integers to **Even**, and of the function that increments an even number by 2 to **next**.

Each model has to *respect typing*; for example, given the above assignment to **Even**, the function that increments a number by 1 does not map all even numbers to even numbers, and therefore can not -- in the same model -- be assigned to **next**.

Additionally, the **claims** (axioms, theorems and conjectures) of the **spec** have to be satisfied in the model. The axiom labeled `nextEffect` above states that the function assigned to **op next** maps any value of the type assigned to **type-name Even** to a

different value. So the squaring function, although type-respecting, could not be assigned to `next` since it maps 0 to itself.

If all type-respecting combinations of assignments of types to **type-names** and values to **ops** fail the one or more **claims**, the **spec** has no models and is called *inconsistent*. Although usually undesirable, an inconsistent **spec** is not by itself considered ill formed. The Specware system does not attempt to detect inconsistencies, but associated provers can sometimes be used to find them. Not always; in general it is undecidable whether a **spec** is consistent or not.

In general, the meaning of a construct in a model depends on the assignments of that model, and more generally on an *environment*: a model possibly extended with assignments to **local-variables**. For example, the meaning of the claim `fa(x : Even) ~ (next x = x)` in axiom `nextEffect` depends on the meanings of `Even` and `next`, while the sub-expression `next x`, for example, also depends on an assignment (of an “even” value) to `x`. To avoid laborious phrasings, the semantic descriptions use language like “the function `next` applied to `x`” as shorthand for this lengthy phrase: “the function assigned in the environment to `next` applied to the value assigned in the environment to `x`”.

When an environment is extended with an assignment to a **local-variable**, any assignments to synonymous **ops** or other **local-variables** are superseded by the new assignment in the new environment. In terms of Metaslang text, within the scope of the binding of **local-variables**, synonymous **ops** and earlier introduced **local-variables** (that is, having the same **simple-name**) are “hidden”; any use of the **simple-name** in that scope refers to the textually most recently introduced **local-variable**. For example, given:

```
def x = "op-x"
def y = let v = "let-v" in x
def z = let x = "let-x" in x
```

the value of `y` is `"op-x"` (`op x` is not hidden by the **local-variable** `v` of the **let-binding**), whereas the value of `z` is `"let-x"` (`op x` is hidden by the **local-variable** `x` of the **let-binding**).

2.1.3. Type-correctness

Next to the general requirement that each model respects typing, there are specific restrictions for various constructs that constrain the possible types for the components. For example, in an **application** `f(x)`, the type of the **actual-parameter** `x` has to match

the domain type of function f . These requirements are stated in the relevant sections of this language manual. If no type-respecting combinations of assignments meeting all these requirements exist for a given `spec`, it is considered *type-incorrect* and therefore *ill formed*. This is determined by Specware while elaborating the `spec`, and signaled as an error. Type-incorrectness differs from inconsistency in that the meaning of the `claims` does not come into play, and the question whether an ill-formed `spec` is consistent is moot.

To be precise, there are subtle and less subtle differences between type-incorrectness of a `spec` and its having no type-respecting combinations of assignments. For example, the following `spec` is type-correct but has no models:

```
spec
  type Empty = | Just Empty
  op IdNotExist : Empty
endspec
```

The explanation is that the **type-definition** for `Empty` generates an *implicit* axiom that all inhabitants of the type `Empty` must satisfy, and for this recursive definition the axiom effectively states that such creatures can't exist: the type `Empty` is uninhabited. That by itself is no problem, but precludes a type-respecting assignment of an inhabitant of `Empty` to `op IdNotExist`. So the `spec`, while type-correct, is actually inconsistent. See further under *Type-definitions*.

Here is a type-incorrect `spec` that has type-respecting combinations of assignments:

```
spec
  type Outcome = | Positive | Negative
  type Sign = | Positive | Zero | Negative
  def whatAmI = Positive
endspec
```

Here there are two constructors `Positive` of different types, the type `Outcome` and the type `Sign`. That by itself is fine, but when such “overloaded” constructors are used, the context must give sufficient information which is meant. Here, the use of `Positive` in the definition for `op whatAmI` leaves both possibilities open; as used it is *type-ambiguous*. Metaslang allows omitting type information provided that, given a type assignment to all **local-type-variables** in scope, unique types for all typed constructs, such as **expressions** and **patterns**, can be inferred from the context. If no complete and unambiguous type-assignment can be made, the `spec` is not accepted by the Specware system. Type-ambiguous **expressions** can be disambiguated by using a type annotation, as described under *Annotated-expressions*. In the example, the definition of `whatAmI` can be disambiguated in either of the following ways:

```
def whatAmI : Sign = Positive
def whatAmI = Positive : Sign
```

Also, if the `spec` elsewhere contains something along the lines of:

```
op signToNat : Sign -> Nat
def sw = signToNat whatAmI
```

that is sufficient to establish that `whatAmI` has type `Sign` and thereby disambiguate the use of `Positive`. See further under *Op-definitions* and *Structors*.

2.1.4. Constructive

When code is generated for a `spec`, complete “self-contained” code is only generated for type-definitions and op-definitions that are fully *constructive*.

Non-constructiveness is “contagious”: a definition is only constructive if all components of the definition are. The type of a type-name without definition is not constructive. A type is only constructive if all component types are. An `op` without definition is non-constructive, and so is an `op` whose type is non-constructive. A quantification is non-constructive. The polymorphic `inbuilt-op` `=` for testing equality and its inequality counterpart `~=` are only constructive for *discrete types* (see below).

A type is called discrete if the equality predicate `=` for that type is constructive. The `inbuilt` and base-library types `Boolean`, `Integer`, `NonZeroInteger`, `Nat`, `PosNat`, `Char`, `String` and `Compare` are all discrete. Types `List T` and `Option T` are discrete when `T` is. All function types are non-discrete (even when the domain type is the unit type). Sum types, product types and record types are discrete whenever all component types are. Subtype $(T \mid P)$ is discrete when supertype `T` is. (Predicate `P` need not be constructive: the equality test is that of the supertype.) Quotient type T / Q is discrete when predicate `Q` is constructive. (Type `T` need not be discrete: the equality test on the quotient type is just the predicate `Q` applied to pairs of members of the `Q`-equivalence classes.)

2.2. Lexical conventions

A Metaslang text consists of a sequence of symbols, possibly interspersed with whitespace. The term *whitespace* refers to any non-empty sequence of spaces, tabs, newlines, and comments (described below). A symbol is presented in the text as a

sequence of one or more “marks” (ASCII characters). Within a composite (multi-mark) symbol, no whitespace is allowed, but whitespace may be needed between two symbols if together they could be taken for one symbol; in particular, two simple-names that follow each other should be separated by whitespace. More precisely, whitespace is required between two adjacent symbols for each of the following combinations, in which “abc” stands for an arbitrary word-symbol, “<*>” stands for an arbitrary non-word-symbol, “?:!” stands for an arbitrary non-word-symbol starting with a ?-mark, and “123” stands for an arbitrary literal (see below for the definitions of the various classes of symbols):

```

abc  abc
abc  ? : !
abc  123
<*>  <*>
123  abc
123  123
abc  _
(    *
```

Apart from the last two cases, no whitespace is ever needed adjacent to a special-symbol.

Inside literals (constant-denotations) whitespace is also disallowed, except for “significant-whitespace” as described under *String-literals*.

Other than that, whitespace -- or the lack of it -- has no significance. Whitespace can be used to lay-out the text for readability, but as far as only the meaning is concerned, the following two presentations of the same spec are entirely equivalent:

```

spec
  type Even
  op next : Even -> Even
  axiom nextEffect is
    fa(x : Even) ~(next x = x)
endspec

spec type    Even op    next : Even -> Even axiom nextEffect
is fa(x : Even)~(next      x              = x)endspec
```

2.2.1. Symbols and Names

symbol ::= simple-name | literal | special-symbol

simple-name ::= word-symbol | non-word-symbol

word-symbol ::= word-start-mark { word-continue-mark }*

word-start-mark ::= letter

word-continue-mark ::=
letter | decimal-digit | _ | ?

letter ::=

A	B	C	D	E	F	G	H	I	J	K	L	M
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
a	b	c	d	e	f	g	h	i	j	k	l	m
n	o	p	q	r	s	t	u	v	w	x	y	z

decimal-digit ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

non-word-symbol ::= non-word-mark { non-word-mark }*

non-word-mark ::=

`	~	!	@	\$	^	&	*	-
=	+	\		:	<	>	/	?

special-symbol ::= _ | (|) | [|] | { | } | ; | , | .

Sample simple-names:

Date	\$\$?!
yymmdd2date	<*>	:::
well_ordered?	~==	

For convenience, here are the 14 printing ASCII marks that, next to letters and decimal-digits, can *not* occur in a non-word-symbol:

#	%	'	"	_	()
[]	{	}	;	,	.

Restriction. As mentioned before, no whitespace is allowed in symbols: while a node is a single simple-name, both a node and an ode consist of two simple-names.

Further, the case (lower or upper) of letters in **simple-names** is significant: `grandparent`, `grandParent` and `grandpaRent` are three different **simple-names**.

Restriction. In general, **simple-names** can be chosen freely. However, the following *reserved symbols* have a special meaning and must not be used for **simple-names**:

<code>as</code>	<code>endspec</code>	<code>infixr</code>	<code>relax</code>
<code>axiom</code>	<code>ex</code>	<code>is</code>	<code>restrict</code>
<code>case</code>	<code>fa</code>	<code>let</code>	<code>spec</code>
<code>choose</code>	<code>false</code>	<code>morphism</code>	<code>then</code>
<code>colimit</code>	<code>fn</code>	<code>obligations</code>	<code>theorem</code>
<code>conjecture</code>	<code>from</code>	<code>of</code>	<code>translate</code>
<code>def</code>	<code>generate</code>	<code>op</code>	<code>true</code>
<code>diagram</code>	<code>if</code>	<code>project</code>	<code>type</code>
<code>else</code>	<code>import</code>	<code>prove</code>	<code>where</code>
<code>embed</code>	<code>in</code>	<code>qualifying</code>	
<code>embed?</code>	<code>infixl</code>	<code>quotient</code>	

<code>:</code>	<code>::</code>	<code> </code>	<code>=></code>	<code> </code>	<code>&&</code>
<code><-</code>	<code>-></code>	<code>+--></code>	<code>=</code>	<code>~=</code>	<code><<</code>

They each count as a single **symbol**, and no whitespace is allowed inside any reserved symbol.

Non-word-symbols can be used to choose convenient **simple-names** for operators that, conventionally, are written with non-alphabetic marks.

Some Metaslang users follow the convention of using **simple-names** that start with a capital letter for **unit-identifiers** and **type-names** and for **constructors**, while **word-symbols** chosen for **ops** and **field-names** start with a lower-case letter. Both plain **local-variables** and **local-type-variables** are often chosen to be single lower-case letters: `x`, `y`, `z`, `a`, `b`, `c`, with the start of the alphabet preferred for **local-type-variables**. **Op-names** of predicates (that is, having some type $T \rightarrow \text{Boolean}$) often end with the mark `?`. These are just conventions that users are free to follow or ignore, but in particular some convention distinguishing **constructors** from **ops** and **local-variables** is recommended.

2.2.2. Comments

`comment ::= line-end-comment | block-comment`

`line-end-comment ::= % line-end-comment-body`

```
line-end-comment-body ::=
  any-text-up-to-end-of-line
```

```
block-comment ::= ( * block-comment-body * )
```

```
block-comment-body ::=
  any-text-including-newlines-and-nested-block-comments
```

Sample comments:

```
% keys must be unique
( * op yymdd2Date : String -> Date * )
```

Metaslang allows two styles of comments. The %-style is light-weight, for adding comment on a line *after* the formal text (or taking a line on its own, but always confined to a single line). The (*...*)-style can be used for blocks of text, spanning several lines, or stay within a line. Any text remaining on the line after the closing *) is processed as formal text. Block-comments may be nested, so the pairs of brackets (* and *) must be balanced.

A block-comment can not contain a line-end-comment and vice versa: whichever starts first has “the right of way”. For example, (* 100 % or more! *) is a block-comment with block-comment-body 100 % or more! . The % here is a mark like any other; it does not introduce a line-end-comment. Conversely, in the line-end-comment % op <*> stands for (*) the (* is part of the line-end-comment-body; it does not introduce a block-comment. Note also that % and (* have no special significance in literals (which must not contain whitespace, including comments): "100 % or more!" is a well-formed string-literal.

2.3. Units

A “unit” is an identifiable unit-term, where “identifiable” means that the unit-term can be referred to by a unit-identifier. Unit-terms can be “elaborated”, resulting in specs, morphisms, diagrams or other entities. The effect of elaborating a unit-definition is that its unit-term is elaborated and becomes associated with its unit-identifier.

For the elaboration of a unit-term to be meaningful, it has to be well formed and result in a well-formed -- and therefore type-correct -- entity. Well-formedness is a stricter requirement than type-correctness. If a unit-term or one of its constituent parts does

not meet any of the restrictions stated in this language manual, it is ill formed. This holds throughout, also if it is not mentioned explicitly for some syntactic construct. Well-formedness is more than a syntactic property; in general, to establish well-formedness it may be necessary to “discharge” (prove) proof obligations engendered by the **unit-term**.

A Specware project consists of a collection of Metaslang **unit-definitions**. They can be recorded in one or more Specware files. There are basically two styles for recording **unit-definitions** using Specware files. In the single-unit style, the file, when processed by Specware, contributes a single **unit-definition** to the project. In the multiple-unit style, the file may contribute several **unit-definitions**. The two styles may be freely mixed in a project (but not in the same Specware file). This is explained in more detail in what follows.

unit-definition ::= **unit-identifier** = **unit-term**

unit-term ::=
 spec-term
 | **morphism-term**
 | **diagram-term**
 | **target-code-term**
 | **proof-term**

specware-file-contents ::=
 unit-term
 | **infile-unit-definition** { **infile-unit-definition** } *

infile-unit-definition ::= **fragment-identifier** = **unit-term**

fragment-identifier ::= **word-symbol**

Unit-definitions may use other **unit-definitions**, including standard libraries, which in Specware 4.1 are supposed to be part of each project. However, the dependencies between units must not form a cycle; it must always be possible to arrange the **unit-definitions** in an order in which later **unit-definitions** only depend on earlier ones. How **unit-definitions** are processed by Specware is further dealt with in the Specware User Manual.

As mentioned above, **unit-definitions** are collected in Specware files, which in Specware 4.1 must have an `.sw` extension. The Specware files do not directly contain the **unit-definitions** that form the project. In fact, a user never writes **unit-definition**

explicitly. These are instead determined from the contents of the Specware files using the following rules. There are two possibilities here. The first is that the **specware-file-contents** consists of a single **unit-term**. If $P.sw$ is the path for the Specware file, the unit being defined has as its **unit-identifier** P . For example, if file `C:/units/Layout/Fixture.sw` contains a single **unit-term** U , the **unit-identifier** is `/units/Layout/Fixture`, and the **unit-definition** it contributes to the project is

```
/units/Layout/Fixture = U
```

(Note that this is not allowed as an **infile-unit-definition** in a **specware-file-contents**, since the **unit-identifier** is not a **fragment-identifier**.)

The second possibility is that the Specware file contains one or more **infile-unit-definitions**. If I is the **fragment-identifier** of such an **infile-unit-definition**, and $P.sw$ is the path for the Specware file, the unit being defined has as its **unit-identifier** $P\#I$. For example, if file `C:/units/Layout/Cart.sw` contains an **infile-unit-definition** `Pos = U`, the **unit-identifier** is `/units/Layout/Cart#Pos`, and the **unit-definition** it contributes to the project is

```
/units/Layout/Cart#Pos = U
```

2.3.1. Unit Identifiers

```
unit-identifier ::= swpath-based-path | relative-path
```

```
swpath-based-path ::= / relative-path
```

```
relative-path ::= { path-element / } * path-element [ # fragment-identifier ]
```

```
path-element ::= word-symbol
```

Warning. Note that **unit-identifiers** are processed by the tokenizer like everything else. This means that whitespace is removed and marks not allowed in **word-symbols**, even if otherwise permitted in filenames (such as `.`), cannot appear in **unit-identifiers**. For this reason, some care must be taken when naming units.

Unit-identifiers are used to identify **unit-terms**. Typically, only a final part of the full **unit-identifier** is used. When Specware is started with environment variable `SWPATH`

set to a semicolon-separated list of pathnames for directories, the Specware files are searched for relative to these pathnames; for example, if `SWPATH` is set to `C:/units/Layout;C:/units/Layout/Cart`, then `C:/units/Layout/Fixture.sw` may be shortened to `/Fixture`, and `C:/units/Layout/Cart.sw` to `/Cart`. How **unit-definitions** are processed by Specware is further dealt with in the Specware User Manual.

Further, **unit-identifiers** can be relative to the directory containing the Specware file in which they occur. So, for example, both in file `C:/units/Layout/Fixture.sw` and in file `C:/units/Layout/Cart.sw`, **unit-identifier** `Tools/Pivot` refers to the **unit-term** contained in file `C:/units/Layout/Tools/Pivot.sw`, while `Props#SDF` refers to the **unit-term** of **infile-unit-definition** `SDF = ...` contained in file `C:/units/Layout/Props.sw`. As a special case, a **unit-term** with the same **name** as the file may be referenced without a **fragment-identifier**. For example, in the current case, if the file `C:/units/Layout/Props.sw` contains the **unit-term** of **infile-unit-definition** `Props = ...`, then this **unit-term** can be referred to either by `Props#Props` or `Props`.

The **unit-identifier** must identify a **unit-definition** as described above; the elaboration of the **unit-identifier** is then the result of elaborating the corresponding **unit-term**, yielding a **spec**, **morphism**, **diagram**, or other entity.

2.3.2. Specs

```
spec-term ::=
    unit-identifier
  | spec-form
  | spec-qualification
  | spec-translation
  | spec-substitution
  | diagram-colimit
  | obligator
```

Restriction. When used as a **spec-term**, the elaboration of a **unit-identifier** must yield a **spec**.

The elaboration of a **spec-term**, if defined, yields an “expanded” **spec-form** as defined in the next subsection.

2.3.2.1. Spec Forms

```
spec-form ::= spec { declaration }* endspec
```

Sample spec-forms:

```
spec import Measures import Valuta endspec
```

An *expanded* spec-form is a spec-form containing no import-declarations.

The elaboration of a spec-form yields the Metaslang text which is that **spec** itself, after expanding any import-declarations. The *meaning* of that text is the class of models of the **spec**, as described throughout this Chapter.

2.3.2.2. Qualifications

Names of types and ops may be *simple* or *qualified*. The difference is that simple-names are “unqualified”: they do not contain a dot sign “.”, while qualified-names are prefixed with a “qualifier” followed by a dot. Examples of simple-names are `Date`, `today` and `<*>`. Examples of qualified-names are `Calendar.Date`, `Calendar.today` and `Monoid.<*>`.

Qualifiers can be used to disambiguate. For example, there may be reason to use two different ops called `union` in the same context: one for set union, and one for bag (multiset) union. They could then more fully be called `Set.union` and `Bag.union`, respectively. Unlike in earlier versions of Specware, there is no rigid relationship between qualifiers and the unit-identifiers identifying specs. The author of a collection of specs may use the qualifier deemed most appropriate for any type- or op-name. For example, there could be a single spec dubbed `SetsAndBags` that introduces two new ops, one called `Set.union` and one called `Bag.union`. Generally, types and ops that “belong together” should receive the same qualifier. It is up to the author of the specs to determine what belongs together.

Type-names and ops are *introduced* in a declaration or definition, and may then be *employed* elsewhere in the same spec. Thus, all occurrences of a type- or op-name can be divided into “introductions” and “employs”. The name as introduced in an introduction is the *full* name of the type or op. If that name is a simple-name, the full name is a simple-name. If the name as introduced is a qualified-name, then so is the full name.

For employs the rules are slightly different. First, if the **name** employed occurs just like that in an introduction, then it is the full **name**. Also, if the **name** employed is qualified, it is the full **name**. Otherwise, the **name** as employed may be unqualified shorthand for a qualified full **name**. For example, given an employ of the unqualified **type-name** `Date`, possible qualified full **names** for it are `Calendar.Date`, `DateAndTime.Date`, `Diary.Date`, and so on. But, of course, the full **name** must be one that is introduced in the **spec**. If there is precisely one **qualified-name** introduced whose last part is the same as the **simple-name** employed, then that **name** is the full **name**. Otherwise, type information may be employed to disambiguate (“resolve overloading”).

Here is an illustration of the various possibilities:

```
spec
  type Apple
  type Fruit.Apple
  type Fruit.Pear
  type Fruit.Date
  type Calendar.Date
  type Fruit.Basket = Apple * Pear * Date
endspec
```

In the definition of type `Fruit.Basket` we have three unqualified employs of **type-names**, viz. `Apple`, `Pear` and `Date`. The **name** `Apple` is introduced like that, so the employ `Apple` already uses the full **name**; it does not refer to `Fruit.Apple`. The **name** `Pear` is nowhere introduced just like that, so the employ must be shorthand for some qualified full **name**. There is only one applicable introduction, namely `Fruit.Pear`. Finally, for `Date` there are two candidates: `Fruit.Date` and `Calendar.Date`. This is ambiguous, and in fact an error. To correct the error, the employ of `Date` should be changed into either `Fruit.Date` or `Calendar.Date`, depending on the intention.

It is possible to give a qualification in one go to all **simple-names** introduced in a **spec**. If Q is a qualifier, and S is a term denoting a **spec**, then the term Q *qualifying* S denotes the same **spec** as S , except that each introduction of an **simple-name** N is replaced by an introduction of the **qualified-name** $Q.N$. Employs that before referred to the unqualified introduction are also accordingly qualified, so that they now refer to the qualified introduction. For example, the value of

```
Company qualifying spec
  type Apple
  type Fruit.Apple
  type Fruit.Pear
```

```

    type Fruit.Basket = Apple * Pear
endspec

```

is the same as that of

```

spec
  type Company.Apple
  type Fruit.Apple
  type Fruit.Pear
  type Fruit.Basket = Company.Apple * Fruit.Pear
endspec

```

spec-qualification ::= qualifier **qualifying spec-term**

qualifier ::= word-symbol

name ::= simple-name | qualified-name

qualified-name ::= qualifier . simple-name

Restriction. Qualifiers cannot be reserved symbols, with the exception of `Boolean`, which is allowed as a qualifier.

Sample spec-qualification:

```

    Weight qualifying /Units#Weights

```

Sample names:

```

    Key
    $
    Calendar.Date
    Monoid.<*>

```

Let R be the result of elaborating spec-term S . Then the elaboration of qualification Q **qualifying** S , where Q is a **qualifier**, is R with each unqualified type-name, op-name or claim-name N introduced there replaced by the qualified-name $Q.N$. The same replacement applies to all employs of N identifying that introduced simple-name. As always, the result of the replacement is required to be a well-formed spec.

For example, the elaboration of

```
Buffer qualifying spec
  op size : Nat
  axiom LargeSize is size >= 1024
endspec
```

results in:

```
spec
  op Buffer.size : Nat
  axiom Buffer.LargeSize is Buffer.size >= 1024
endspec
```

2.3.2.3. Translations

`spec-translation ::= translate spec-term by name-map`

`name-map ::= { [name-map-item { , name-map-item }*] }`

`name-map-item ::= type-name-map-item | op-name-map-item`

`type-name-map-item ::= [type] name --> name`

`op-name-map-item ::= [op] annotable-name --> annotable-name`

`annotable-name ::= name [: type-descriptor]`

Restriction. A `spec-translation` may not map two different `type-names` or two different `op-names` to the same `simple-name`. Note that this implies that `type-` and `op-names` cannot be translated to `simple-names` defined in the base libraries.

Sample `spec-translation`:

```
translate A by {Counter --> Register, tally --> incr}
```

Let R be the result of elaborating `spec-term` S . Then the elaboration of `translate` S `by` $\{ M_1 \text{ --> } N_1, \dots, M_n \text{ --> } N_n \}$ is R with each occurrence of a `name` M_i replaced by N_i . All other `names` are mapped to themselves, i.e., they are unchanged.

The presence of a type annotation in a `name-map-item`, as in `x:E --> cross`, indicates that the `name-map-item` refers to an `op-name`; additionally, on the left-hand side such an annotation may serve to disambiguate between several synonymous `ops`,

and then there must be an **op** in R of the type given by the **type-descriptor**. If the right-hand side of a **name-map-item** carries a type annotation, its **type-descriptor** must conform to the type of the **op-name** in the resulting **spec**. Without such annotation on either side, if a **name** to be translated is introduced both as a **type-name** and as an **op-name** in R , it must be preceded by **type** or **op** to indicate which of the two is meant. Otherwise the indication **type** or **op** is not required, but allowed; if present, it must correspond to the kind of **simple-name** (**type-name** or **op-name**) to be translated.

For example, the elaboration of

```
translate spec
  type E
  op i : E
endspec by {
  E +-> Counter,
  i +-> reset
}
```

results in:

```
spec
  type Counter
  op reset : Counter
endspec
```

2.3.2.4. Substitutions

spec-substitution ::= **spec-term** [**morphism-term**]

Sample **spec-substitution**:

```
Routing#Basis[morphism /Coll/Lattice ->
               /Coll/LatticeWithTop {} ]
```

The elaboration of **spec-substitution** $S[M]$ yields the **spec** T obtained as follows. Let **spec** R be the result of elaborating S , and **morphism** N that of M . Let **specs** D and C be the domain and codomain of N . First, remove from R all **declarations** of D , and subject the result to the effect of N , meaning that all **name** translations of N and all

extensions with **declarations** are performed. Then add the **declarations** of C , but without duplications, i.e., as if C is imported. The result obtained is T .

Restriction. $\text{Spec } D$ must be a “sub-spec” of $\text{spec } R$, meaning that each **declaration** of D is also a **declaration** of R .

Informally, T is to R as C is to D .

Except when R introduces, next to the **type-** and **op-names** it has in common with D , new **type-** or **op-names** that also occur in C , the result $\text{spec } T$ is a categorical colimit of this pushout diagram:

$$\begin{array}{ccc} D & \xrightarrow{\quad\quad\quad} & R \\ | & & | \\ | & & | \\ | & & | \\ \vee & & \vee \\ C & \xrightarrow{\quad\quad\quad} & T \end{array}$$

Although isomorphic to the result that would be obtained by using a **diagram-colimit**, T is more “user-oriented” in two ways: the **names** in T are **names** from C , and **claims** of D not repeated in C are not repeated here either.

For example, assume we have:

```
A = spec
  type Counter
  op reset: Counter
  op tally : Counter -> Counter
  axiom Effect is
    fa (c : Counter) ~(tally c = c)
endspec
```

```
B = spec
  type Register = Nat
  def reset = 0
  def incr c = c+1
endspec
```

```
M = morphism A -> B {Counter +-> Register, tally +-> incr}
```

```
AA = spec
  import A
  type Interval = {start: Counter, stop: Counter}
  op isEmptyInterval? : Interval -> Boolean
  def isEmptyInterval? {start = x, stop = y} = (x = y)
```



```
endspec
```

Then the result of `AA[M]` is the same as that of this `spec`:

```
spec
  import B
  type Interval = {start: Register, stop: Register}
  op isEmptyInterval? : Interval -> Boolean
  def isEmptyInterval? {start = x, stop = y} = (x = y)
endspec
```

2.3.2.5. Diagram Colimits

`diagram-colimit ::= colimit diagram-term`

The result of elaborating a `diagram-colimit` is the `spec` which is the apex of the cocone forming the colimit in the category of `specs` and `spec-morphisms`. As always, the result is required to be well formed. See further the Specware Tutorial.

2.3.2.6. Obligators

`obligator ::= obligations unit-term`

Restriction. The `unit-term` of an `obligator` must either be a `spec-term` or a `morphism-term`.

The result of elaborating an `obligator` is a `spec` containing the proof obligations engendered by the `spec` or `morphism` resulting from elaborating its `unit-term`. These proof obligations are expressed as `conjectures`; they can be discharged by proving them, using `proof-terms`. See further the Specware User Manual.

2.3.3. Morphisms

```
morphism-term ::=
  unit-identifier
  | spec-morphism
```

`spec-morphism ::= morphism spec-term -> spec-term name-map`

A morphism is a formal mapping between two expanded **spec-forms** that describes exactly how one is translated or extended into the other. It consists of the two **specs**, referred to as “domain” and “codomain”, and a mapping of all **type-** and **op-names** introduced in the domain **spec** to **type-** and **op-names** of the codomain **spec**. To be well-formed, a morphism must obey conditions that express that it is a proper refinement of the domain into the codomain ‘spec’.

Restriction. When used as a **morphism-term**, the elaboration of a **unit-identifier** must yield a morphism.

Restriction (“proof obligations”). Given **spec-morphism** `morphism S -> T { M1 +-> N1, ... Mn +-> Nn }` let *R* be the result of elaborating *S*, and let *S′* be *R* with each occurrence of a name *M_i* replaced by *N_i*. The same rules apply as for **spec-translation** `translate S by {...}`, and the result *S′* must be well formed, with the exception that the restriction on **spec-translations** requiring different **type-** or **op-names** to be mapped to different **simple-names** does not apply here. Let *T′* be the result of elaborating *T*. Then, first, each **type-name** or **op-name** introduced in *S′* must also be introduced in *T′*. Further, no **type-name** or **op-name** originating from a library **spec** may have been subject to translation. Finally, each claim in *S′* must be a theorem that follows from the claims of *T′*. Collectively, the claims in *S′* are known as the *proof obligations* engendered by the morphism. They are the formal expression of the requirement that the step from *S′* to *T′* is a proper refinement.

For example, in

```
S = spec endspec
T = spec type Bullion = (Char | isAlpha) endspec
M = morphism S -> T {Boolean -> Bullion}
```

the type-name `Boolean`, which originates from a library **spec**, is subject to translation. Therefore, *M* is not a proper morphism. Further, in

```
S = spec
  op f : Nat -> Nat
  axiom ff is fa(n:Nat) f(n) ~= f(n+1)
endspec

T = spec
  def f(n:Nat) = n*n rem 5
endspec
```

`M = morphism S -> T`

axiom `ff` does not follow from (the axiom implied by) the **op-definition** for `f` in `spec T`, since `f(2) = f(3) = 4`. Therefore, `M` is not a proper morphism here either.

Sample **spec-morphism**:

`morphism A -> B {Counter ++> Register, tally ++> incr}`

The elaboration of **spec-morphism** `morphism S -> T {M}` results in the morphism whose domain and codomain are the result of elaborating `S` and `T`, respectively, and whose mapping is given by the list of **name-map-items** in `M`, using type annotations and indicators `type` and `op` as described for **spec-translations**, and extended to all domain **type-** and **op-names** not yet covered by having these map to themselves. (In particular, **simple-names** from the base-libraries always map to themselves.)

2.3.4. Diagrams

`diagram-term ::=`
 `unit-identifier`
 | `diagram-form`

`diagram-form ::= diagram { diagram-element { , diagram-element }* }`

`diagram-element ::=`
 `diagram-node`
 | `diagram-edge`

`diagram-node ::= simple-name ++> spec-term`

`diagram-edge ::= simple-name : simple-name -> simple-name ++> morphism-term`

Restriction. When used as a **diagram-term**, the elaboration of a **unit-identifier** must yield a **diagram**.

Restriction. In a **diagram**, the first **simple-name** of each **diagram-node** and **diagram-edge** must be unique (i.e., not be used more than once in that **diagram**).

Further, for each **diagram-edge** `E : ND -> NC ++> M`, there must be

diagram-nodes $ND \mapsto D$ and $NC \mapsto C$ of the diagram such that, after elaboration, M is a morphism from D to C .

Sample diagram:

```

diagram {
  A          +-> /Coll/Lattice,
  B          +-> /Coll/LatticeWithTop,
  m : A -> B +-> /Coll/AddTop,
  C          +-> Routing#Basis,
  i : A -> C +-> morphism /Coll/Lattice ->
                                Routing#Basis {}
}

```

The result of elaborating a diagram-form is the categorical diagram whose nodes are labeled with the specs and whose edges are labeled with the morphisms that result from elaborating the corresponding spec-terms and morphism-terms.

2.3.5. Target Code Terms

```

target-code-term ::=
  generate target-language-name spec-term [ in string-literal ]

```

```

target-language-name ::= c | java | lisp

```

Sample target-code-term:

```

generate lisp /Vessel#Contour
           in "C:/Projects/Vessel/Contour.lisp"

```

The elaboration of a target-code-term for a well-formed spec-term generates code in the language suggested by the target-language-name (currently only C, Java, and Common Lisp); see further the Specware User Manual.

2.3.6. Proof Terms

```

proof-term ::=
  prove claim-name in spec-term

```

```
[ with prover-name ]
[ using claim-list ]
[ options prover-options ]
```

```
prover-name ::= snark
```

```
claim-list ::= claim-name { , claim-name }*
```

```
prover-options ::= string-literal
```

Restriction. The claim-names must occur as claim-names in the spec that results from elaborating the spec-term.

Sample proof-term:

```
prove Effect in obligations M
      options "(use-paramodulation t)"
```

The elaboration of a proof-term invokes the prover suggested by the prover-name (currently only SNARK). The property to be proved is the claim of the first claim-name; the claim-list lists the hypotheses (assumptions) that may be used in the proof. The prover-options are prover-specific and are not further described here. For details, see the Specware User Manual.

2.4. Declarations

```
declaration ::=
    import-declaration
  | type-declaration
  | op-declaration
  | definition
```

```
definition ::=
    type-definition
  | op-definition
  | claim-definition
```

```
equals ::= is | =
```

Sample declarations:

```
import Lookup
type Key
op present : Database * Key -> Boolean
type Key = String
def present(db, k) = embed? Some (lookup (db, k))
axiom norm_idempotent is fa(x) norm (norm x) = norm x
```

2.4.1. Import-declarations

A **spec** may contain one or more **import-declarations**. On elaboration, these are “expanded”. The effect is as if the bodies of these imported **specs** (themselves in elaborated form, which means that all **import-declarations** have been expanded, all translations performed and all shorthand employs of **names** have been resolved to full **names**, after which only declarations or definitions of types, **ops** and **claims** are left) is inserted in place in the receiving **spec**.

For example, the result of

```
spec
  import spec
    type A.Z
    op b : Nat -> Z
  end
  type A.Z = String
  def b = toString
endspec
```

is this “expanded” **spec**:

```
spec
  type A.Z
  op b : Nat -> A.Z
  type A.Z = String
  def b = toString
endspec
```

For this to be well formed, the imported **specs** must be well formed by themselves; in addition, the result of expanding them in place must result in a well-formed **spec**.

There are a few restrictions, which are meant to catch unintentional naming mistakes. First, if two different imported **specs** each introduce a type or **op** with the same (full) **name**, the introductions must be identical declarations or definitions, or one may be a declaration and the other a “compatible” definition. For example, given

```
S1 = spec op e : Integer end
S2 = spec op e : Char end
S3 = spec def e = 0 end
```

the **specs** *S1* and *S3* can be imported together, but all other combinations of two or more co-imported **specs** result in an ill-formed **spec**. This restriction is in fact a special case of the general requirement that import expansion must result in a well-formed **spec**. Secondly, a **type-name** introduced in any of the imported **specs** cannot be re-introduced in the receiving **spec** except for the case of an “imported” declaration together with a definition in the receiving **spec**. Similarly for **op-names**, with the addition that an **op-definition** in the receiving **spec** must be compatible with an **op-declaration** for the same **name** in an imported **spec**. The latter is again a special case of the general requirement that import expansion must result in a well-formed **spec**.

What is specifically excluded by the above, is giving a definition of a type or **op** in some **spec**, import it, and then redefining or declaring that type or **op** with the same full **name** in the receiving **spec**.

import-declaration ::= **import** **spec-term**

Sample import-declarations

```
import Lookup
```

An **import-declaration** is contained in some **spec-form**, and to elaborate that **spec-form** the **spec-term** of the **import-declaration** is elaborated first, giving some **spec** *S*. The **import-declaration** has then the effect as if the declarations of the imported **spec** *S* are expanded in place. This cascades: if **spec** *A* imports *B*, and **spec** *B* imports *C*, then effectively **spec** *A* also imports *C*. An important difference with earlier versions of Specware than version 4 is that multiple imports of the same **spec** have the same effect as a single import.

If **spec** *A* is imported by *B*, each model of *B* is necessarily a model of *A* (after “forgetting” any **simple-names** newly introduced by *B*). So *A* is then refined by *B*, and

the morphism from A to B is known as the “import morphism”. As it does not involve translation of `type`- or `op`-names, it can be denoted by `morphism A -> B { }`.

2.4.2. Type-declarations

`type-declaration ::= type type-name [formal-type-parameters]`

`formal-type-parameters ::= local-type-variable | (local-type-variable-list)`

`local-type-variable ::= simple-name`

`local-type-variable-list ::= local-type-variable { , local-type-variable }*`

Restriction. Each `local-type-variable` of the `formal-type-parameters` must be a different `simple-name`.

Sample type-declarations:

```
type Date
type Array a
type Map(a, b)
```

Every `type-name` used in a `spec` must be declared (in the same `spec` or in an imported `spec`, included the “base-library” `specs` that are always implicitly imported). A `type-name` may have *type parameters*. Given the example `type-declarations` above, some valid `type-descriptors` that can be used in this context are `Array Date`, `Array (Array Date)` and `Map (Nat, Boolean)`.

In a model of the `spec`, a type is assigned to each unparameterized `type-name`, while an infinite *family* of types is assigned to parameterized `type-names` “indexed” by tuples of types, that is, there is one family member, a type, for each possible assignment of types to the `local-type-variables`. So for the above example `type-declaration` of `Array` one type must be assigned to `Array Nat`, one to `Array Boolean`, one to `Array (Array Date)`, and so on. These assigned types could all be the same type, or perhaps all different, as long as the model respects typing.

2.4.3. Type-definitions

type-definition ::= **type** type-name [formal-type-parameters] equals type-descriptor

Sample type-definitions:

```
type Date = {year : Nat, month : Nat, day : Nat}
type Array a = List a
type Map(a, b) = (Array (a * b) | key_uniq?)
```

In each model, the type assigned to the **type-name** must be the same as the right-hand-side **type-descriptor**. For parameterized types, this extends to all possible assignments of types to the **local-type-variables**, taking the right-hand **type-descriptors** as interpreted under each of these assignments. So, for the example, `Map(Nat, Char)` is the same type as `(Array (Nat * Char) | key_uniq?)`, and so on.

With *recursive* type-definitions, there are additional requirements. For example, consider

```
type Stack a =
  | Empty
  | Push {top : a, pop : Stack a}
```

This means that for each type `a` there is a value `Empty` of type `Stack a`, and further a function `Push` that maps values of type `{top : a, pop : Stack a}` to `Stack a`. Furthermore, the type assigned to `Stack a` must be such that all its inhabitants can be constructed *exclusively* and *uniquely* in this way: there is one inhabitant `Empty`, and all others are the result of a `Push`. Finally -- this is the point -- the type in the model must be such that its inhabitants can be constructed this way in *a finite number of steps*. So there can be no “bottom-less” stacks: deconstructing a stack using

```
def [a] hasBottom? (s : Stack a) : Boolean =
  case s of
  | Empty -> true
  | Push {top, pop = rest} -> hasBottom? rest
```

is a procedure that is guaranteed to terminate, always resulting in `true`.

In general, **type-definitions** generate implicit axioms, which for recursive definitions imply that the type is not “larger” than necessary. In technical terms, in each model the type is the least fixpoint of a recursive domain equation.

2.4.4. Op-declarations

op-declaration ::= **op** op-name [fixity] : type-scheme

fixity ::= associativity priority

associativity ::= **infixl** | **infixr**

priority ::= nat-literal

type-scheme ::= [type-variable-binder] type-descriptor

type-variable-binder ::= `[local-type-variable-list `]

Sample op-declarations:

```
op usage : String
```

```
op o infixl 24 : [a,b,c] (b -> c) * (a -> b) -> a -> c
```

An op-declaration introduces an **op** with an associated type. The type can be “monomorphic”, like `String`, or “polymorphic” (indicated by a **type-variable-binder**). In the latter case, an indexed family of values is assigned to parameterized **type-names** “indexed” by tuples of types, that is, there is one family member, a typed value, for each possible assignment of types to the **local-type-variables** of the **type-variable-binder**, and the type of that value is the result of the corresponding substitution of types for **local-type-variables** on the polymorphic type of the **op**. In the example above, the declaration of polymorphic `o` can be thought of as introducing a family of (fictitious) **ops**, one for each possible assignment to the **local-type-variables** `a`, `b` and `c`:

```
oNat,String,Char : (String -> Char) * (Nat -> String) -> Nat -> Char
```

```
oNat,Nat,Boolean : (Nat -> Boolean) * (Nat -> Nat) -> Nat -> Boolean
```

```
oChar,Boolean,Nat : (Boolean -> Nat) * (Char -> Boolean) -> Char -> Nat
```

and so on. Any **op-definition** for `o` must be likewise accommodating.

Only binary **ops** (those having some type $S * T \rightarrow U$) may be declared with a **fixity**. When declared with a **fixity**, the **op** may be used in infix notation, and then it is called an **infix-operator**. For `o` above, this means that `o(f, g)` and `f o g` may be used,

interchangeably, with no difference in meaning. If the **associativity** is `infixl`, the **infix-operator** is called *left-associative*; otherwise, if the **associativity** is `infixr`, it is called *right-associative*. If the **priority** is `priority N`, the operator is said to have *priority N*. The **nat-literal** `N` stands for a natural number; if **infix-operator** `O1` has priority `N1`, and `O2` has priority `N2`, with $N1 < N2$, we say that `O1` has *lower priority* than `O2`, and that `O2` has *higher priority* than (or *takes priority over*) `O1`. For the role of the associativity and priority, see further at *Infix-applications*.

2.4.5. Op-definitions

```
op-definition ::=
  def [ type-variable-binder ] formal-expression [ : type-descriptor ] equals
    expression
```

```
formal-expression ::= op-name | formal-application
```

```
formal-application ::= formal-application-head formal-parameter
```

```
formal-application-head ::= op-name | formal-application
```

```
formal-parameter ::= closed-pattern
```

Sample op-definitions:

```
def usage = "Usage: Lookup key [database]"

def [a,b,c] o(f : b -> c, g: a -> b) : a -> c =
  fn (x : a) -> f(g x)

def o(f, g) x = f(g x)
```

Restriction. See the restriction under *Op-declarations* on redeclaring/redefining ops.

Note that a **formal-expression** always contains precisely one **op-name**, which is the *op being defined* by the **op-definition**. Note further that the **formal-application** of an **op-definition** always uses prefix notation, also for **infix-operators**.

An **op** can be defined without having been declared. In that case the **op-definition** generates an implicit **op-declaration** for the **op**, provided a monomorphic type for the **op** can be unambiguously determined from the **op-definition** together with the uses of the **op** in **applications** and other contexts. In general, typing information on **ops** may be omitted, but sufficient information must be supplied when used, so that all

expressions can be assigned a type in the context in which they occur while uniquely associating the ops with op-declarations or op-definitions. If two different associations both give type-correct specs, the spec is ambiguous and ill formed.

As for op-definitions, the presence of a type-variable-binder signals that the op being defined is polymorphic. Note that the optional type annotation in an op-definition can not be a polymorphic type-scheme, unlike for op-declarations. For example, the following is ungrammatical:

```
def o : [a,b,c] (b -> c) * (a -> b) -> a -> c =
  fn (f, g) -> fn (x) -> f(g x)
```

The presumably intended effect is achieved by

```
def [a,b,c] o : (b -> c) * (a -> b) -> a -> c =
  fn (f, g) -> fn (x) -> f(g x)
```

In a model of the spec, an indexed family of typed values is assigned to a polymorphic op, with one family member for each possible assignment of types to the local-type-variables of the type-variable-binder, and the type of that value is the result of the corresponding type-instantiation for the polymorphic type of the op. Thus, we can reduce the meaning of a polymorphic op-definition to a family of (fictitious) monomorphic op-definitions.

An op-definition with formal-prefix-application

```
def H P = E
```

in which H is a formal-application-head, P is a formal-parameter and E an expression, is equivalent to the op-definition

```
def H = fn P -> E
```

For example,

```
def o (f, g) x = f(g x)
```

is equivalent to

```
def o (f, g) = fn x -> f(g x)
```

which in turn is equivalent to

```
def o = fn (f, g) -> fn x -> f(g x)
```

By this deparameterizing transformation for each formal-parameter, an equivalent unparameterized **op-definition** is reached. The semantics is described in terms of such **op-definitions**.

In each model, the typed value assigned to the **op** being defined must be the same as the value of the right-hand-side **expression**. For polymorphic **op-definitions**, this extends to all possible assignments of types to the **local-type-variables**.

An **op-definition** can be thought of as a special notation for an axiom. For example,

```
def [a] double (x : a) = (x, x)
```

can be thought of as standing for:

```
op double : [a] a -> a * a

axiom double_def is
  [a] fa(x : a) double x = (x, x)
```

In fact, Specware generates such axioms for use by provers. But in the case of recursive definitions, this form of axiomatization does not adequately capture the meaning. For example,

```
def f (n : Nat) : Nat = 0 * f n
```

is an improper definition, while

```
axiom f_def is
  fa(n : Nat) f n = 0 * f n
```

characterizes the function that maps every natural number to 0. The issue is the following. Values in models can not be *undefined* and functions assigned to **ops** must be *total*. But in assigning a meaning to a recursive **op-definition**, we -- temporarily -- allow *undefined* and partial functions (functions that are not everywhere defined on their domain type) to be assigned to recursively defined **ops**. In the thus extended class of models, the recursive **ops** must be the least-defined solution to the “axiomatic” equation (the least fixpoint as in domain theory), given the assignment to the other **ops**. For the example of *f* above this results in the everywhere undefined function, since 0 times *undefined* is *undefined*. If the solution results in an undefined value or a function that is not total (or for higher-order functions, functions that may return non-total functions, and so on), the **op-definition** is improper. Although Specware 4.1 does attempt to generate proof obligations for this condition, it currently covers only “simple” recursion, and not mutual recursion or recursion introduced by means of higher-order functions.

Functions that are determined to be the value of an **expression**, but that are not assigned to **ops**, need not be total, but the context must enforce that the function can not be applied to values for which it is undefined. Otherwise, the **spec** is ill formed.

2.4.6. Claim-definitions

claim-definition ::= **claim-kind** **claim-name** **equals** **claim**

claim-kind ::= **axiom** | **theorem** | **conjecture**

claim-name ::= **simple-name**

claim ::= [**type-variable-binder**] **expression**

Sample claim-definitions:

```
axiom norm_idempotent is
  norm o norm = norm

theorem o_assoc is
  [a,b,c,d] fa(f : c -> d, g : b -> c, h : a -> b)
    f o (g o h) = (f o g) o h

conjecture pivot_hold is
  let p = pivot hold in
    fa (n : {n : Nat | n < p}) ~(hold n = hold p)
```

Restriction. The type of the **claim** must be **Boolean**.

When a **type-quantification** is present, the **claim** is polymorphic. The **claim** may be thought of as standing for an infinite family of monomorphic **claims**, one for each possible assignment of types to the **local-type-variables**.

The **claim-kind** **theorem** should only be used for **claims** that have actually been proved to follow from the (explicit or implicit) axioms. In other words, giving them axiom status should not change the class of models. Theorems can be used by provers.

Conjectures are meant to represent proof obligations that should eventually attain theoremhood. Like theorems, they can be used by provers. This is only sound if circularities (vicious circles) are avoided. This kind of **claim** is usually created automatically by the elaboration of an **obligator**, but can also be created manually.

The Specware system passes on the `claim-name` of the `claim-definition` with the `claim` for purposes of identification. Both may be transformed to fit the requirements of the prover, and appear differently there. Not all `claims` can be faithfully represented in all provers, and even when they can, the logic of the prover may not be up to dealing with them.

Remark. It is a common mistake to omit the part “`claim-name equals`” from a `claim-definition`. A defensive style against this mistake is to have the `claim` always start on a new text line. This is additionally recommended because it may become required in future revisions of Metaslang.

2.5. Type-descriptors

```

type-descriptor ::=
    type-sum
  | type-arrow
  | slack-type-descriptor

slack-type-descriptor ::=
    type-product
  | tight-type-descriptor

tight-type-descriptor ::=
    type-instantiation
  | closed-type-descriptor

closed-type-descriptor ::=
    type-name
  | Boolean
  | local-type-variable
  | type-record
  | type-restriction
  | type-comprehension
  | type-quotient
  | ( type-descriptor )

```

(The distinctions “`slack-`”, “`tight-`” and “`closed-`” before “`type-descriptor`” have no semantic significance. The distinction merely serves the purpose of diminishing the need for parenthesizing in order to avoid grammatical ambiguities.)

Sample type-descriptors:

```
| Point XYpos | Line XYpos * XYpos
List String * Nat -> Option String
a * Order a * a
PartialFunction (Key, Value)
Key
Boolean
a
{center : XYpos, radius : Length}
(Nat | even)
{k : Key | present (db, k)}
Nat / (fn (m, n) -> m rem 3 = n rem 3)
(Nat * Nat)
```

The meaning of the **type-descriptor** `Boolean` is the “inbuilt” type inhabited by the two logical (truth) values `true` and `false`. The meaning of a parenthesized **type-descriptor** (T) is the same as that of the enclosed **type-descriptor** T .

The various other kinds of **type-descriptors** not defined here are described each in their following respective sections, with the exception of **local-type-variable**, whose (lack of) meaning as a **type-descriptor** is described below.

Restriction. A **local-type-variable** may only be used as a **type-descriptor** if it occurs in the scope of a **formal-type-parameters** or **type-variable-binder** in which it is introduced.

Disambiguation. A single **simple-name** used as a **type-descriptor** is a **local-type-variable** when it occurs in the scope of a **formal-type-parameters** or **type-variable-binder** in which it is introduced, and then it identifies the textually most recent introduction. Otherwise, the **simple-name** is a **type-name**.

A **local-type-variable** used as a **type-descriptor** has no meaning by itself, and where relevant to the semantics is either “indexed away” (for parameterized types) or “instantiated away” (when introduced in a **formal-type-parameters** or **type-variable-binder**) before a meaning is ascribed to the construct in which it occurs. Textually, it has a scope just like a plain **local-variable**.

2.5.1. Type-sums

type-sum ::= **type-summand** { **type-summand** }*

type-summand ::= | **constructor** [**slack-type-descriptor**]

constructor ::= simple-name

Sample type-sum:

```
| Point XYpos | Line XYpos * XYpos
```

Restriction. The constructors of a type-sum must all be different simple-names.

The ordering of the type-summands has no significance: `| Zero | Succ Peano` denotes the same “sum type” as `| Succ Peano | Zero`.

A type-sum denotes a *sum type*, which is a type that is inhabited by “tagged values”. A tagged value is a pair (C, v) , in which C is a constructor and v is a typed value.

A type-sum introduces a number of embedders, one for each type-summand. In the discussion, we omit the optional `embed` keyword of the embedders. The embedders are similar to ops, and are explained as if they were ops, but note the Restriction specified under *Structors*.

For a type-sum T with type-summand $C\ S$, in which C is a constructor and S a type-descriptor, the corresponding pseudo-op introduced is typed as follows:

$$\text{op } C : S \rightarrow T$$

It maps a value v of type S to the tagged value (C, v) . If the type-summand is a single *parameter-less* constructor (the slack-type-descriptor is missing), the pseudo-op introduced is typed as follows:

$$\text{op } C : T$$

It denotes the tagged value $(C, ())$, in which $()$ is the inhabitant of the unit type (see under *Type-records*).

The sum type denoted by the type-sum then consists of the union of the ranges (for parameter-less constructors the values) of the pseudo-ops for all constructors.

The embedders are individually, jointly and severally *injective*, and jointly *surjective*.

This means, first, that for any pair of constructors $C1$ and $C2$ of *any* type-sum, and for any pair of values $v1$ and $v2$ of the appropriate type (to be omitted for parameter-less constructors), the value of $C1\ v1$ is only equal to $C2\ v2$ when $C1$ and $C2$ are the same constructor of the *same* sum type, and $v1$ and $v2$ (which then are either both absent, or else must have the same type) are both absent or are the same value. In other words, whenever the constructors are different, or are from different type-sums, or the values are different, the results are different. (The fact that

synonymous **constructors** of different types yield different values already follows from the fact that values in the models are typed.)

Secondly, for any value u of any sum type, there is a **constructor** C of that sum type and a value v of the appropriate type (to be omitted for parameter-less **constructors**), such that the value of $C\ v$ is u . In other words, all values of a sum type can be constructed with an **embedder**.

For example, consider

```
type Peano =
  | Zero
  | Succ Peano

type Unique =
  | Zero
```

This means that there is a value `Zero` of type `Peano`, and further a function `Succ` that maps values of type `Peano` to type `Peano`. Then `Zero` and `Succ n` are guaranteed to be different, and each value of type `Peano` is either `Zero : Peano`, or expressible in the form `Succ (n : Peano)` for a suitable expression n . The **expressions** `Zero : Peano` and `Zero : Unique` denote different, entirely unrelated, values. (Note that `Unique` is *not* a subtype of `Peano`. Subtypes of a type can only be made with a **type-restriction**, for instance as in `(Peano | embed? Zero)`.) For recursively defined **type-sums**, see also the discussion under *Type-definitions*.

Note. Although the sum types `| Mono` and `| Mono ()` have exactly the same set of inhabitants when considered as untyped values, these two types are different, and the pseudo-ops they introduce have different types, only the second of which is a function type:

```
Mono : | Mono

Mono : ( ) -> | Mono ( )
```

2.5.2. Type-arrows

`type-arrow ::= arrow-source -> type-descriptor`

`arrow-source ::= type-sum | slack-type-descriptor`

Sample type-arrow:

```
(a -> b) * b -> List a -> List b
```

In this example, the **arrow-source** is $(a \rightarrow b) * b$, and the (target) **type-descriptor** $List\ a \rightarrow List\ b$.

The *function type* $S \rightarrow T$ is inhabited by precisely all *partial or total* functions from S to T . That is, function f has type $S \rightarrow T$ if, and only if, for each value x of type S such that the value of $f\ x$ is defined, that value has type T . Functions can be constructed with **lambda-forms**, and be used in **applications**.

In considering whether two functions (of the same type) are equal, only the meaning on the domain type is relevant. Whether a function is undefined outside its domain type, or might return some value of some type, is immaterial to the semantics of Metaslang. (For a type-correct **spec**, the difference is unobservable.)

2.5.3. Type-products

```
type-product ::= tight-type-descriptor * tight-type-descriptor { * tight-type-descriptor } *
```

Sample type-product:

```
(a -> b) * b * List a
```

Note that a **type-product** contains at least two constituent **tight-type-descriptors**.

A **type-product** denotes a *product type* that has at least two “component types”, represented by its **tight-type-descriptors**. The ordering of the component types is significant: unless S and T are the same type, the product type $S * T$ is different from the type $T * S$. Further, the three types $(S * T) * U$, $S * (T * U)$ and $S * T * U$ are all different; the first two have two component types, while the last one has three. The inhabitants of the product type $T_1 * T_2 * \dots * T_n$ are precisely all n -tuples (v_1, v_2, \dots, v_n) , where each v_i has type T_i , for $i = 1, 2, \dots, n$. Values of a product type can be constructed with **tuple-displays**, and component values can be extracted with **tuple-patterns** as well as with **projectors**.

2.5.4. Type-instantiations

```
type-instantiation ::= type-name actual-type-parameters
```

`actual-type-parameters ::= closed-type-descriptor | (proper-type-list)`
`proper-type-list ::= type-descriptor , type-descriptor { , type-descriptor }*`

Sample type-instantiation:

`Map (Nat, Boolean)`

Restriction. The **type-name** must have been declared or defined as a parameterized type (see *Type-declarations*), and the number of **type-descriptors** in the **actual-type-parameters** must match the number of **local-type-variables** in the **formal-type-parameters** of the type-declaration and/or type-definition.

The **type-descriptor** represented by a type-instantiation is the type assigned for the combination of types of the **actual-type-parameters** in the indexed family of types for the **type-name** of the type-instantiation.

2.5.5. Type-names

`type-name ::= name`

Sample type-names:

`Key`
`Calendar.Date`

Restriction. At the spec level, a **type-name** may only be used if there is a **type-declaration** and/or **type-definition** for it in the current **spec** or in some **spec** that is imported (directly or indirectly) in the current **spec**. If there is a unique **qualified-name** for a given unqualified ending, the qualification may be omitted for a **type-name** used as a **type-descriptor**.

The type of a **type-name** is the type assigned to it in the model. (In this case, the context can not have superseded the original assignment.)

2.5.6. Type-records

`type-record ::= { [field-type-list] } | ()`

field-typers-list ::= field-typers { , field-typers }*

field-typers ::= field-name : type-descriptor

field-name ::= simple-name

Sample type-record:

```
{center : XYpos, radius : Length}
```

Restriction. The field-names of a type-record must all be different.

Note that a type-record contains either no constituent field-typers, or else at least two.

A type-record is like a type-product, except that the components, called “fields”, are identified by name instead of by position. The ordering of the field-typers has no significance: {center : XYpos, radius : Length} denotes the same *record type* as {radius : Length, center : XYpos}. Therefore we assume in the following, without loss of generality, that the fields are ordered lexicographically according to their field-names (as in a dictionary: a comes before ab comes before b) using some fixed collating order for all marks that may comprise a name. Then each field of a record type with n fields has a *position* in the range 1 to n . The inhabitants of the record type $\{F_1 : T_1, F_2 : T_2, \dots, F_n : T_n\}$ are precisely all n -tuples (v_1, v_2, \dots, v_n) , where each v_i has type T_i , for $i = 1, 2, \dots, n$. The field-names of that record type are the field-names F_1, \dots, F_n , and, given the lexicographic ordering, field-name F_i selects position i , for $i = 1, 2, \dots, n$. Values of a record type can be constructed with record-displays, and field values can be extracted with record-patterns and (as for product types) with projectors.

For the type-record {}, which may be equivalently written as (), the record type it denotes has zero components, and therefore no field-names. This zero-component type has precisely one inhabitant, and is called the *unit type*. The unit type may equally well be considered a product type, and is the only type that is both a product and a record type.

2.5.7. Type-restrictions

type-restriction ::= (slack-type-descriptor | expression)

Sample type-restriction:

```
(Nat | even)
```

Restriction. In a **type-restriction** $(T \mid P)$, the **expression** P must be a predicate on the type T , that is, P must be a function of type $T \rightarrow \text{Boolean}$.

Note that the parentheses in $(T \mid P)$ are mandatory.

The inhabitants of type $(T \mid P)$ are precisely the inhabitants of type T that satisfy the predicate P , that is, they are those values v for which the value of $P\ v$ is `true`.

If $P1$ and $P2$ are the same function, then $(T \mid P1)$ and $(T \mid P2)$ are equivalent, that is, they denote the same type. Furthermore, $(T \mid \text{fn } _ \rightarrow \text{true})$ is equivalent to T .

The type $(T \mid P)$ is called a *subtype* of *supertype* T . Values can be shuttled between a subtype and its supertype and vice versa with **relaxators** and **restrict-expressions**; see also *Relax-patterns*.

Metaslang does not require the explicit use of a **relaxator** to relax an **expression** from a subtype to its supertype if the context requires the latter. Implicit relaxation will take place when needed. For example, in the **expression** `-1` the **nat-literal** `1` of type `Nat` is implicitly relaxed to type `Integer` to accommodate the unary negation operator `-`, which has type `Integer → Integer`.

Likewise, Metaslang does not require the explicit use of a **restrict-expression** to restrict an **expression** from a type to a subtype if the context requires the latter. Implicit restriction will take place when needed. For example, in the **expression** `7 div 2` the **nat-literal** `2` of type `Nat` is implicitly restricted to type `PosNat`, a subtype of `Nat`, to accommodate the division operator `div`, whose second argument has type `PosNat`. But note that implicit restriction engenders the same proof obligation as results when using an explicit **restrict-expression**.

2.5.8. Type-comprehensions

type-comprehension ::= { annotated-pattern | expression }

Sample **type-comprehension**:

`{n : Nat | even n}`

Restriction. In a **type-comprehension** $\{P : T \mid E\}$, the **expression** E must have type `Boolean`.

Type-comprehensions provide an alternative notation for **type-restrictions** that is akin to the common mathematical notation for set comprehensions. The meaning of **type-comprehension** $\{P : T \mid E\}$ is the same as that of the **type-restriction** $(T \mid$

`fn P -> E`). So the meaning of the example type-comprehension above is `(Nat | fn n -> even n)`.

2.5.9. Type-quotients

`type-quotient ::= closed-type-descriptor / closed-expression`

Sample type-quotient:

```
Nat / (fn (m, n) -> m rem 3 = n rem 3)
```

Restriction. In a type-quotient T / Q , the expression Q must be a (binary) predicate on the type $T * T$ that is an equivalence relation, as explained below.

Equivalence relation. Call two values x and y of type T “ Q -related” if (x, y) satisfies Q . Then Q is an *equivalence relation* if, for all values x, y and z of type T , x is Q -related to itself, y is Q -related to x whenever x is Q -related to y , and x is Q -related to z whenever x is Q -related to y and y is Q -related to z . The equivalence relation Q then partitions the inhabitants of T into *equivalence classes*, being the maximal subsets of T containing mutually Q -related members. These equivalence classes will be called “ Q -equivalence classes”.

The inhabitants of the *quotient type* T / Q are precisely the Q -equivalence classes into which the inhabitants of T are partitioned by Q . For the example above, there are three equivalence classes of natural numbers leaving the same remainder on division by 3: the sets $\{0, 3, 6, \dots\}$, $\{1, 4, 7, \dots\}$ and $\{2, 5, 8, \dots\}$, and so the quotient type has three inhabitants.

2.6. Expressions

```
expression ::=
  lambda-form
  | case-expression
  | let-expression
  | if-expression
  | quantification
  | annotated-expression
  | tight-expression
```

```

tight-expression ::=
  application
  | restrict-expression
  | closed-expression

closed-expression ::=
  op-name
  | local-variable
  | literal
  | field-selection
  | tuple-display
  | record-display
  | sequential-expression
  | list-display
  | structor
  | ( expression )
  | ( inbuilt-op )

```

```

inbuilt-op ::= inbuilt-prefix-op | inbuilt-infix-op

```

```

inbuilt-prefix-op ::= ~

```

```

inbuilt-infix-op ::= => | <=> | || | && | = | ~= | <<

```

(The distinctions **tight-** and **closed-** for expressions lack semantic significance, and merely serve the purpose of avoiding grammatical ambiguities.)

Sample expressions:

```

fn (s : String) -> s ^ "."
case z of {re = x, im = y} -> {re = x, im = -y}
let x = x + 1 in f(x, x)
if x <= y then x else y
fa(x,y) (x <= y)  <=>  ((x < y) or (x = y))
f(x, x)
[] : List Arg
abs(x-y)
restrict posNat? (n+1)
++
x
3260
z.re
("George", Poodle : Dog, 10)
{name = "George", kind = Poodle : Dog, age = 10}

```



```

(writeLine "key not found"; embed Missing)
["Sun", "Mon", "Tue", "Wed", "Thu", "Fri", "Sat"]
project 2
(n + 1)
(| |)

```

Restriction. Like all polymorphic or type-ambiguous constructs, an **expression** can only be used in a context if its type can be inferred uniquely, given the **expression** and the context. This restriction will not be repeated for the various kinds of **expressions** defined in the following subsections.

The meaning of a parenthesized **expression** (E) is the same as that of the enclosed **expression** E . The meaning of the parenthesized **inbuilt-prefix-op** (P) is the same as that of the **lambda-form** $\text{fn } x \rightarrow P \ x$. The meaning of a parenthesized **inbuilt-infix-op** (I) is the same as that of the **lambda-form** $\text{fn } (x, y) \rightarrow x \ I \ y$. Note that this function is strict in both arguments, unlike I itself.

The various other kinds of **expressions** not defined here are described each in their following respective sections, with the exception of **local-variable**, whose meaning as an **expression** is described below.

Restriction. A **local-variable** may only be used as an **expression** if it occurs in the scope of the **local-variable-list** of a **quantification** or of a **variable-pattern** in which it is introduced.

Disambiguation. A single **simple-name** used as an **expression** is a **local-variable** when it occurs in the scope of a **local-variable-list** or **variable-pattern** in which a synonymous **local-variable** is introduced, and then it identifies the textually most recent introduction. Otherwise, the **simple-name** is an **op-name** or an **embedder**; for the disambiguation between the latter two, see *Embedders*.

A **local-variable** used as an **expression** has the typed value assigned to it in the environment.

2.6.1. Lambda-forms

lambda-form ::= **fn** match

Sample **lambda-form**:

```
fn (s : String) -> s ^ "."
```

The value of a **lambda-form** is a partial or total function. If the value determined for a **lambda-form** as described below is not a total function, the context must enforce that the function can not be applied to values for which it is undefined. Otherwise, the **spec** is ill formed. Specware 4.1 does not attempt to generate proof obligations for establishing this.

The type of a **lambda-form** is that of its **match**. The meaning of a given **lambda-form** of type $S \rightarrow T$ is the function f mapping each inhabitant x of S to a value y of type T , where y is the return value of x for the **match** of the **lambda-form**. If the **match** accepts each x of type S (for acceptance and return value, see the section on *Matches*) function f is total; otherwise it is partial, and undefined for those values x rejected.

In case of a recursive definition, the above procedure may fail to determine a value for y , in which case function f is not total, but undefined for x .

2.6.2. Case-expressions

case-expression ::= **case** expression **of** match

Sample case-expressions:

```
case z of {re = x, im = y} -> {re = x, im = -y}

case s of
| Empty -> true
| Push {top = _, pop = rest} -> hasBottom? rest
```

The value of a **case-expression** **case** E **of** M is the same as that of the application $(\text{fn } M) (E)$.

2.6.3. Let-expressions

let-expression ::= **let** let-bindings **in** expression

let-bindings ::= recless-let-binding | rec-let-binding-sequence

recless-let-binding ::= pattern equals expression

rec-let-binding-sequence ::= rec-let-binding { rec-let-binding }*

rec-let-binding ::=

def simple-name formal-parameter-sequence [: type-descriptor] equals expression

formal-parameter-sequence ::= formal-parameter { formal-parameter }*

Sample let-expressions:

```
let x = x + e in f(x, x)
let def f x = x + e in f (f x)
```

In the case of a **recless-let-binding** (recless = recursion-less), the value of the **let-expression** `let P = A in E` is the same as that of the **application** `(fn P -> E) (A)`. For the first example above, this amounts to `f(x + e, x + e)`. Note that `x = x + e` is not interpreted as a recursive definition.

In case of a **rec-let-binding-sequence** (rec = recursive), the **rec-let-bindings** have the role of “local” **op-definitions**; that is, they are treated exactly like **op-definitions** except that they are interpreted in the local environment instead of the global model. For the second example above, this amounts to `(x + e) + e`. (If `e` is a **local-variable** in this scope, the definition of `f` can not be “promoted” to an **op-definition**, which would be outside the scope binding `e`.) A **spec** with **rec-let-bindings** can be transformed into one without such by creating **op-definitions** for each **rec-let-binding** that take additional arguments, one for each of the **local-variables** referenced. For the example, in which `f` references **local-variable** `e`, the **op-definition** for the “extended” **op** `f+` would be `def f+ e x = x + e`, and the **let-expression** would become `f+ e (f+ e x)`. The only difference in meaning is that the models of the transformed **spec** assign a value to the newly introduced **op** `f+`.

Note that the first occurrence of `x` in the above example of a **rec-let-binding** is a **variable-pattern** and the second-occurrence is in its scope; the third and last occurrence of `x`, however, is outside the scope of the first `x` and identifies an **op** or **local-variable** `x` introduced elsewhere. So, without change in meaning, the **rec-let-binding** can be changed to:

```
let def f xena = xena + e in f (f x)
```

2.6.4. If-expressions

if-expression ::= **if** expression **then** expression **else** expression

Sample if-expression:

```
if x <= y then x else y
```

The value of an if-expression `if B then T else F` is the same as that of the case-expression `case B of true -> (T) | false -> (F).`

2.6.5. Quantifications

quantification ::= quantifier (local-variable-list) expression

quantifier ::= **fa** | **ex**

local-variable-list ::= annotable-variable { , annotable-variable }*

annotable-variable ::= local-variable [: type-descriptor]

local-variable ::= simple-name

Sample quantifications:

```
fa(x) norm (norm x) = norm x
ex(e : M) fa(x : M) x <*> e = x & e <*> x = x
```

Restriction. Each local-variable of the local-variable-list must be a different simple-name.

Quantifications are non-constructive, even when the domain type is finitely enumerable. The main uses are in type-restrictions and type-comprehensions, and claims. The type of a quantification is `Boolean`. There are two kinds of quantifications: **fa**-quantifications (or “universal quantifications”; **fa** = for all), and **ex**-quantifications (or “existential quantifications”; **ex** = there exists).

The value of a **fa**-quantification `fa V E` , in which V is a local-variable-list and E is an expression, is determined as follows. Let M be the match $V \rightarrow E$. If M has return value `true` for each value x in its domain (note that rejection cannot happen here), the value of the quantification is `true`; otherwise it is `false`.

The value of an `ex`-quantification `ex V E` is the same as that of the `fa`-quantification `~(fa V ~(E))`.

Note that `fa` and `ex` must be followed by an opening parenthesis `(`. So `fa x (x = x)`, for example, is ungrammatical.

2.6.6. Annotated-expressions

`annotated-expression ::= tight-expression : type-descriptor`

Restriction. In an annotated-expression `E : T`, the expression `E` must have type `T`.

Sample annotated-expression:

```
[] : List Arg
Positive : Sign
```

The value of an annotated-expression `E : T` is the value of `E`.

The type of some expressions is polymorphic. For example, for any type `T`, `[]` denotes the empty list of type `List T`. Likewise, constructors of parameterized sum types can be polymorphic, as the constructor `None` of

```
type Option a = | Some a | None
```

Further, overloaded constructors have an ambiguous type. By annotating such polymorphic or type-ambiguous expressions with a type-descriptor, their type can be disambiguated, which is required unless an unambiguous type can already be inferred from the context. Annotation, even when redundant, can further help to increase clarity.

2.6.7. Applications

`application ::= prefix-application | infix-application`

`prefix-application ::= application-head actual-parameter`

```
application-head ::=
    closed-expression
  | inbuilt-prefix-op
  | prefix-application
```

`actual-parameter ::= closed-expression`

`infix-application ::= operand infix-operator operand`

`operand ::= tight-expression`

`infix-operator ::= op-name | inbuilt-infix-op`

Sample applications:

```
f (x, x)
f x (g y)
x + 1
```

Restriction. An **infix-operator**, whether qualified or unqualified, can not be used without more as an **actual-parameter** or **operand** (and in the case of an **inbuilt-op**, it can not be used without more as any other kind of **expression** either). To use an **infix-operator** in such cases, it must be enclosed in parentheses, as for example in the **prefix-applications** `foldl (+) 0` and `foldl (*) 1` or the **infix-application** `(<) o ival`. Note the space between “(” and “*”, since without space “(*” signals the start of a **comment**.

Restriction. An **op-name** can be used as an **infix-operator** only if it has been declared as such in an **op-declaration** (see under *Op-declarations*).

Disambiguation. An **infix-application** $P \ M \ Q \ N \ R$, in which P , Q and R are **operands** and M and N are **infix-operators**, is interpreted as either $(P \ M \ Q) \ N \ R$ or $P \ M \ (Q \ N \ R)$. The choice is made as follows. If M has higher priority than N , or the priorities are the same but M is left-associative, the interpretation is $(P \ M \ Q) \ N \ R$. In all other cases the interpretation is $P \ M \ (Q \ N \ R)$. For example, given

```
op @ infixl 10: Nat * Nat -> Nat
op $ infixr 20: Nat * Nat -> Nat
```

the following interpretations hold:

```
1 $ 2 @ 3 = (1 $ 2) @ 3
1 @ 2 @ 3 = (1 @ 2) @ 3
1 @ 2 $ 3 = 1 @ (2 $ 3)
1 $ 2 $ 3 = 1 $ (2 $ 3)
```

Note that no type information is used in the disambiguation. If $(1 \ @ \ 2) \ \$ \ 3$ is type-correct but $1 \ @ \ (2 \ \$ \ 3)$ is not, the formula $1 \ @ \ 2 \ \$ \ 3$ is type-incorrect, since its interpretation is.

For the application of this disambiguation rule, the inbuilt-ops have fixity as suggested by the following pseudo-op-declarations:

```

op =>  infixr 13 : Boolean * Boolean -> Boolean
op ||  infixr 14 : Boolean * Boolean -> Boolean
op &&  infixr 15 : Boolean * Boolean -> Boolean
op =   infixr 20 : [a]    a * a      -> Boolean
op ~=  infixr 20 : [a]    a * a      -> Boolean
op <<  infixl 25 : {x:A, ... , y:B, ...} * {x:A, ... , z:C, ...}
        -> {x:A, ... , y:B, ... , z:C, ...}

```

Restriction. In an application $H\ P$, in which H is an application-head and P an actual-parameter, the type of (H) must be some function type $S \rightarrow T$, and then P must have the domain type S . The type of the whole application is then T . In particular, in an application $\sim P$ the type of both P and the application is `Boolean`.

The meaning of prefix-application $\sim P$ is the same as that of the if-expression `if P then false else true`.

The value of prefix-application $H\ P$, in which application-head H is a closed-expression or another prefix-application, is the value returned by function (H) for the argument value P .

The meaning of infix-application $P\ N\ Q$, in which P and Q are operands and N is an op-name, is the same as that of the prefix-application $N(P, Q)$.

The meaning of infix-application $P\ =>\ Q$, in which P and Q are operands, is the same as that of the if-expression `if P then Q else true`.

The meaning of infix-application $P\ ||\ Q$, in which P and Q are operands, is the same as that of the if-expression `if P then true else Q`.

The meaning of infix-application $P\ \&\&\ Q$, in which P and Q are operands, is the same as that of the if-expression `if P then Q else false`.

The value of infix-application $P\ =\ Q$, in which P and Q are operands, is `true` if P and Q have the same value, and `false` otherwise. P and Q must have the same type, or else have types that are subtypes of the same supertype. In the latter case, the comparison is the same as for the values of the operands relaxed to the supertype, so, for example, the value of $(1:\text{Nat})=(1:\text{PosNat})$ is `true`.

The meaning of infix-application $P\ \sim=\ Q$, in which P and Q are operands, is the same as that of the prefix-application $\sim(P\ =\ Q)$.

An infix-application $P \ll Q$ is also called a “record update”. In a record update $P \ll Q$, in which P and Q are **operands**, P and Q must have record types, referred to as S and T , respectively. Moreover, for each **field-name** F these types S and T have in common, the field types for F in S and T must be the same, or be subtypes of the same supertype. The type of $P \ll Q$ is then the record type R whose **field-names** are formed by the union of the **field-names** of S and T , where for each **field-name** F in that union, the type of field F in R is that of field F in T if F is a field of T , and otherwise the type of field F in S . Likewise, the value of $P \ll Q$ is the record value of type R whose field value of each field F is that of field F in Q if F is a field of T , and otherwise the field value of field F in P . So, for example, the value of $\{a=1, b=\#z\} \ll \{a=2, c=true\}$ is $\{a=2, b=\#z, c=true\}$: fields of the right-hand side operand take precedence over the left-hand side when present in both.

2.6.8. Restrict-expressions

restrict-expression ::= **restrict** closed-expression closed-expression

Sample **restrict-expression**:

```
restrict posNat? (n+1)
```

Restriction. In a **restrict-expression** **restrict** $P E$ the **expression** P must have function type $T \rightarrow \text{Boolean}$ and the **expression** E must have type T for some T .

The type of a **restrict-expression** **restrict** $P E$, where P has type $T \rightarrow \text{Boolean}$, is the type $(T \mid P)$.

A **restrict-expression** **restrict** $P E$ is a convenient notation for the **let-expression** **let** $\text{relax } P V = E \text{ in } V$, where V is some unique fresh **simple-name**, that is, it is any **simple-name** that does not already occur in the **spec**, directly or indirectly through an **import**.

The use of this **restrict-expression** engenders a proof obligation that the value of E satisfies predicate P .

For example, assuming the **definitions** from the Base Library for **Nat**, the **restrict-expression** **restrict** $\text{posNat? } (n+1)$ has type **PosNat**. The proof obligation here is that, in the context, $(n+1) > 0$.

The purpose of **restrict-expressions** is to make it explicit that an **expression** whose a-priori type is some supertype T actually is guaranteed (or required) to have subtype $(T \mid P)$. Note, however, that Metaslang does not require the explicit use of a

restrict-expression to restrict an **expression** from a type to a subtype if the context requires the latter. Implicit restriction will take place when needed. For example, in the **expression** `7 div 2` the **nat-literal** `2` of type `Nat` is implicitly restricted to type `PosNat`, a subtype of `Nat`, to accommodate the division operator `div`, whose second argument has type `PosNat`. But note that implicit restriction engenders the same proof obligation as results when using an explicit **restrict-expression**.

2.6.9. Op-names

op-name ::= name

Sample **op-names**:

```
length
>=
DB_LOOKUP.Lookup
```

Restriction. An **op-name** may only be used if there is an **op-declaration** and/or **op-definition** for it in the current **spec** or in some **spec** that is imported (directly or indirectly) in the current **spec**. If there is a unique **qualified-name** for a given unqualified ending that is type-correct in the context, the qualification may be omitted for an **op-name** used as an **expression**. So overloaded **ops** may only be used as such when their type can be disambiguated in the context.

The value of an **op-name** is the value assigned to it in the model. (In this case, the context can not have superseded the original assignment.)

2.6.10. Literals

```
literal ::=
  boolean-literal
  | nat-literal
  | char-literal
  | string-literal
```

Sample **literals**:

```
true
3260
```

```
#z
"On/Off switch"
```

Restriction: No whitespace is allowed anywhere inside any kind of **literal**, except for “significant” whitespace in **string-literals**, as explained there.

Literals provide denotations for the inhabitants of the inbuilt and “base-library” types `Boolean`, `Nat`, `Char` and `String`. The value of a **literal** is independent of the environment.

(There are no **literals** for the base-library type `Integer`. For nonnegative integers, a **nat-literal** can be used. For negative integers, apply the unary base-library **op** `-`, which negates an integer: `-1` denote the negative integer `-1`.)

2.6.10.1. Boolean-literals

```
boolean-literal ::= true | false
```

Sample boolean-literals:

```
true
false
```

The type `Boolean` has precisely two inhabitants, the values of `true` and `false`.

Note that `true` and `false` are not **constructors**. So `embed true` is ungrammatical.

2.6.10.2. Nat-literals

```
nat-literal ::= decimal-digit { decimal-digit }*
```

Sample nat-literals:

```
3260
007
```

The **type-descriptor** `Nat` is, by definition, the subtype of `Integer` restricted to the nonnegative integers `0`, `1`, `2`, ... , which we identify with the natural numbers. The value of a **nat-literal** is the natural number of which it is a decimal representation; for example, the **nat-literal** `3260` denotes the natural number `3260`. Leading **decimal-digits** `0` have no significance: both `007` and `7` denote the number `7`.

2.6.10.3. Char-literals

`char-literal` ::= `#char-literal-glyph`

`char-literal-glyph` ::= `char-glyph` | `"`

`char-glyph` ::=
 `letter`
 | `decimal-digit`
 | `other-char-glyph`

`other-char-glyph` ::=
 `!` | `:` | `@` | `#` | `$` | `%` | `^` | `&` | `*` | `(` | `)` | `_` | `-` | `+` | `=`
 | `|` | `~` | ``` | `.` | `,` | `<` | `>` | `?` | `/` | `;` | `'` | `[` | `]` | `{` | `}`
 | `\\` | `\"`
 | `\a` | `\b` | `\t` | `\n` | `\v` | `\f` | `\r` | `\s`
 | `\x` `hexadecimal-digit` `hexadecimal-digit`

`hexadecimal-digit` ::=
 `decimal-digit`
 | `a` | `b` | `c` | `d` | `e` | `f`
 | `A` | `B` | `C` | `D` | `E` | `F`

Sample char-literals:

```
#z
#\x7a
```

The type `Char` is inhabited by the 256 8-bit *characters* occupying decimal positions 0 through 255 (hexadecimal positions 00 through FF) in the ISO 8859-1 code table. The first 128 characters of that code table are the traditional ASCII characters (ISO 646). (Depending on the operating environment, in particular the second set of 128 characters -- those with “the high bit set” -- may print or otherwise be visually presented differently than intended by the ISO 8859-1 code.) The value of a **char-literal** is a character of type `Char`.

The value of a **char-literal** `#G`, where `G` is a **char-glyph**, is the character denoted by `G`. For example, `#z` is the character that prints as `z`. The two-mark **char-literal** `#"` provides a variant notation of the three-mark **char-literal** `#\"` and yields the character `"` (decimal position 34).

Each one-mark **char-glyph** C denotes the character that “prints” as C . The two-mark **char-glyph** $\backslash \backslash$ denotes the character \backslash (decimal position 92), and the two-mark **char-glyph** $\backslash "$ denotes the character $"$ (decimal position 34).

Notations are provided for denoting eight “non-printing” characters, which, with the exception of the first, are meant to regulate lay-out in printing; the actual effect may depend on the operating environment:

glyph	decimal	name
$\backslash a$	7	bell
$\backslash b$	8	backspace
$\backslash t$	9	horizontal tab
$\backslash n$	10	newline
$\backslash v$	11	vertical tab
$\backslash f$	12	form feed
$\backslash r$	13	return
$\backslash s$	32	space

Finally, every character can be obtained using the hexadecimal representation of its position. The four-mark **char-glyph** $\backslash x H_1 H_0$ denotes the character with hexadecimal position $H_1 H_0$, which is decimal position 16 times the decimal value of **hexadecimal-digit** H_1 plus the decimal value of **hexadecimal-digit** H_0 , where the decimal value of the digits 0 through 9 is conventional, while the six extra digits A through F correspond to 10 through 15. The case (lower or upper) of the six extra digits is not significant. For example, $\backslash x7A$ or equivalently $\backslash x7a$ has decimal position 16 times 7 plus 10 = 122, and either version denotes the character z. The “null” character can be obtained by using $\backslash x00$.

2.6.10.4. String-literals

string-literal ::= " string-body "

string-body ::= { **string-literal-glyph** } *

string-literal-glyph ::= **char-glyph** | **significant-whitespace**

significant-whitespace ::= space | tab | newline

The presentation of a **significant-whitespace** is the whitespace suggested by the name (space, tab or newline).

Sample string-literals:

```
" "
"see page"
"see\spage"
"the symbol ' is a single quote"
"the symbol \" is a double quote"
```

The type `String` is inhabited by the *strings*, which are (possibly empty) sequences of characters. The type `String` is primitive; it is a different type than the isomorphic type `List Char`, and the list operations can not be directly applied to strings.

The value of a **string-literal** is the sequence of characters denoted by the **string-literal-glyphs** comprising its **string-body**, where the value of a **significant-whitespace** is the whitespace character suggested by the **name** (space, horizontal tab or newline). For example, the **string-literal** `"seepage"` is different from `"see page"`; the latter denotes an eight-character string of which the fourth character is a space. The space can be made explicit by using the **char-glyph** `\s`.

When a double-quote character `"` is needed in a string, it must be escaped, as in `"[6 ' 2 \"]"`, which would print like this: `[6 ' 2 "]`.

2.6.11. Field-selections

`field-selection ::= closed-expression . field-selector`

`field-selector ::= nat-literal | field-name`

Disambiguation. A **closed-expression** of the form $M.N$, in which M is a **word-symbol** and N is a **simple-name**, is interpreted as an **op** if $M.N$ occurs as the **op-name** of an **op-declaration** or **op-definition** in the **spec** in which it occurs or in the set of **simple-names** imported from another **spec** through an **import-declaration**. Otherwise, $M.N$ is interpreted as a **field-selection**. (The effect of a **field-selection** can always be obtained with a **projector**.)

Sample field-selections:

```
triple.2
z.re
```

A field-selection $E.F$ is a convenient notation for the equivalent expression `(project F E)`. (See under *Projectors*.)

2.6.12. Tuple-displays

`tuple-display ::= (tuple-display-body)`

`tuple-display-body ::= [expression , expression { , expression }*]`

Sample tuple-display:

```
("George", Poodle : Dog, 10)
```

Note that a `tuple-display-body` contains either no expressions, or else at least two.

The value of a `tuple-display` whose `tuple-display-body` is not empty, is the tuple whose components are the respective values of the expressions of the `tuple-display-body`, taken in textual order. The type of that tuple is the “product” of the corresponding types of the components. The value of `()` is the empty tuple, which is the sole inhabitant of the unit type `()`. (The fact that the notation `()` does double duty, for a `type-descriptor` and as an `expression`, creates no ambiguity. Note also that -- unlike the empty `list-display` `[]` -- the expression `()` is monomorphic, so there is no need to ever annotate it with a `type-descriptor`.)

2.6.13. Record-displays

`record-display ::= { record-display-body }`

`record-display-body ::= [field-filler { , field-filler }*]`

`field-filler ::= field-name equals expression`

Sample record-display:

```
{name = "George", kind = Poodle : Dog, age = 10}
```

The value of a `record-display` is the record whose components are the respective values of the expressions of the `record-display-body`, taken in the lexicographic order of the field-names, as discussed under *Type-records*. The type of that record is

the record type with the same set of field-names, where the type for each field-name F is the type of the corresponding type of the component selected by F in the record. The value of $\{ \}$ is the empty tuple, which is the sole inhabitant of the unit type $()$. (For expressions as well as for type-descriptors, the notations $\{ \}$ and $()$ are fully interchangeable.)

2.6.14. Sequential-expressions

sequential-expression ::= (open-sequential-expression)

open-sequential-expression ::= void-expression ; sequential-tail

void-expression ::= expression

sequential-tail ::= expression | open-sequential-expression

Sample sequential-expression:

```
(writeLine "key not found"; embed Missing)
```

A sequential-expression $(V ; T)$ is equivalent to the let-expression `let _ = V in (T)`. So the value of a sequential-expression $(V_1 ; \dots ; V_n ; E)$ is the value of its last constituent expression E .

Sequential-expressions can be used to achieve non-functional “side effects”, effectuated by the elaboration of the void-expressions, in particular the output of a message. This is useful for tracing the execution of generated code. The equivalent effect of the example above can be achieved by a let-binding:

```
let _ = writeLine "key not found" in
embed Missing
```

(If the intent is to temporarily add, and later remove or disable the tracing output, this is probably a more convenient style, as the modifications needed concern a single full text line.) Any values resulting from elaborating the void-expressions are discarded.

2.6.15. List-displays

list-display ::= [list-display-body]

`list-display-body ::= [expression { , expression }*]`

Sample list-display:

```
[ "Sun", "Mon", "Tue", "Wed", "Thu", "Fri", "Sat" ]
```

Restriction. All expressions of the list-display-body must have the same type.

Note that a list-display `[]` with empty list-display-body is polymorphic, and may need to be type-disambiguated, for example with a type annotation. In a case like `[]`, `[1]`, there is no need to disambiguate `[]`, since the above restriction already implies that `[]` here has the same type as `[1]`, which has type `List Nat`.

The parameterized type `List`, although a base-library type, is actually not primitive, but defined by:

```
type List a =
  | Nil
  | Cons a * List a
```

The empty list-display `[]` denotes the same list as the expression `Nil`, a singleton list-display `[E]` denotes the same list as the expression `Cons (E, Nil)`, and a multi-element list-display `[E1, E2, ... , En]` denotes the same list as the expression `Cons (E1, [E2, ... , En])`.

2.6.16. Structors

```
structor ::=
  projector
  | relaxator
  | quotienter
  | chooser
  | embedder
  | embedding-test
```

The **structors** are a medley of constructs, all having polymorphic or type-ambiguous function types and denoting special functions that go between structurally related types, such as the constructors of sum types and the destructors of product types.

Restriction. Like all polymorphic or type-ambiguous constructs, a **structor** can only be used in a context where its type can be inferred uniquely. This restriction will not be repeated for the various kinds of **structors** described in the following subsections.

For example, the following well-formed **spec** becomes ill formed when any of the type annotations is omitted:

```
spec
  def [a] p2 = project 2 : String * a -> a
  def      q2 = project 2 : String * Nat -> Nat
endspec
```

2.6.16.1. Projectors

projector ::= **project** field-selector

Sample projectors:

```
project 2
project re
```

When the field-selector is some nat-literal with value i , it is required that i be at least 1. The type of the **projector** is a function type (whose domain type is a product type) of the form $T_1 * T_2 * \dots * T_n \rightarrow T_i$, where n is at least i , and the value of the **projector** is the function that maps each n -tuple (v_1, v_2, \dots, v_n) inhabiting the domain type to its i th component v_i .

When the field-selector is some field-name F , the type of the **projector** is a function type (whose domain type is a record type) of the form $\{F_1 : T_1, F_2 : T_2, \dots, F_n : T_n\} \rightarrow T_i$, where F is the same field-name as F_i for some natural number i in the range 1 through n . Assuming that the fields are lexicographically ordered by field-name (see under *Type-records*), the value of the **projector** is the function that maps each n -tuple (v_1, v_2, \dots, v_n) inhabiting the domain type to its i th component v_i .

2.6.16.2. Relaxators

relaxator ::= **relax** closed-expression

Sample relaxator:

```
relax even
```

Restriction. The closed-expression of a **relaxator** must have some function type $T \rightarrow \text{Boolean}$.

The type of **relaxator** `relax P`, where P has type $T \rightarrow \text{Boolean}$, is the function type (whose domain is a subtype) $(T \mid P) \rightarrow T$. The value of the **relaxator** is the function that maps each inhabitant of subtype $(T \mid P)$ to the same value -- apart from the type information -- inhabiting supertype T .

For example, given

```
type Even = (Nat | even)
```

we have the typing

```
relax even : Even -> Nat
```

for the function that injects the even natural numbers back into the supertype of `Even`.

Metaslang does not require the explicit use of a **relaxator** to relax an **expression** from a subtype to its supertype if the context requires the latter. Implicit relaxation will take place when needed. For example, in the **expression** `-1` the **nat-literal** `1` of type `Nat` is implicitly relaxed to type `Integer` to accommodate the unary negation operator `-`, which has type `Integer -> Integer`.

Note the remarks about equivalence of type-restrictions in the corresponding section.

2.6.16.3. Quotienters

quotienter ::= **quotient** closed-expression

Sample quotienter:

```
quotient (fn (m, n) -> m rem 3 = n rem 3)
```

Restriction. The closed-expression of a **quotienter** must have some type $T * T \rightarrow \text{Boolean}$; in addition, it must be an equivalence relation, as explained under *Type-quotients*.

The type of **quotienter** `quotient Q`, where Q has type $T * T \rightarrow \text{Boolean}$, is the function type $T \rightarrow T / Q$, that is, it goes from some type to one of its quotient types. The value of the **quotienter** is the function that maps each inhabitant of type T to the Q -equivalence class inhabiting T / Q of which it is a member.

For example, given

```
def congMod3 : Nat * Nat -> Boolean =
  (fn (m, n) -> m rem 3 = n rem 3)

type Z3 = Nat / congMod3
```

we have the typing

```
quotient congMod3 : Nat -> Z3
```

and the function maps, for example, the number 5 to the equivalence class $\{2, 5, 8, \dots\}$, which is one of the three inhabitants of $Z3$.

2.6.16.4. Choosers

chooser ::= **choose** closed-expression

Sample chooser:

```
choose congMod3
```

Restriction. In a **chooser** **choose** Q , **expression** Q must have some type $T * T \rightarrow \text{Boolean}$, and must be an equivalence relation (see under *Type-quotients*).

The type of a **chooser** **choose** Q , where Q has type $S * S \rightarrow \text{Boolean}$, is a function type of the form $R \rightarrow (S / Q \rightarrow T)$, where R is the subtype of $S \rightarrow T$ consisting of the Q -constant (explained below) functions. Expressed more formally, R is the type $\{f : S \rightarrow T \mid \text{fa}((x, y) : S * S) Q(x, y) \Rightarrow f\ x = f\ y\}$, where the simple-names f , x and y must be replaced by “fresh” simple-names not clashing with simple-names already in use in S , T or Q .

The value of the **chooser** is the function mapping each Q -constant (explained below) function f inhabiting type $S \rightarrow T$ to the function that maps each inhabitant C of S / Q to $f\ x$, where x is any member of C . Expressed symbolically, using a pseudo-function **any** that arbitrarily picks any member from a nonempty set, this is the function

```
fn f -> fn C -> f (any C)
```

The requirement of Q -constancy is precisely what is needed to make this function insensitive to the choice made by **any**.

Function f is Q -constant if, for each Q -equivalence class C inhabiting S / Q , $f\ x$ equals $f\ y$ for any two values x and y that are members of C , or f is undefined on all

members of C . (Since the result of f is constant across each equivalence class, it does not matter which of its elements is selected by `any`.) For example -- continuing the example of the previous section -- function `fn n -> n*n rem 3` is `congMod3-constant`; for the equivalence class $\{2, 5, 8, \dots\}$, for example, it maps each member to the same value 1. So `choose congMod3 (fn n -> n*n rem 3)` maps the inhabitant $\{2, 5, 8, \dots\}$ of type \mathbb{Z}_3 to the natural number 1.

The most discriminating Q -constant function is `quotient Q`, and `choose Q` `quotient Q` is the identity function on the quotient type for Q .

The meaning of `choose Q (fn x -> E) A` is the same as that of the `let-expression` `let quotient Q x = A in E`. Indeed, often a `quotient-pattern` offers a more convenient way of expressing the intention of a `chooser`. Note, however, the remarks on the proof obligations for `quotient-patterns`.

2.6.16.5. Embedders

`embedder ::= [embed] constructor`

Sample embedders:

```
Nil
embed Nil
Cons
embed Cons
```

Disambiguation. If an `expression` consists of a single `simple-name`, which, in the context, is both the `simple-name` of a `constructor` and the `simple-name` of an `op` or a `local-variable` in scope, then it is interpreted as the latter of the various possibilities. For example, in the context of

```
type Answer = | yes | no

def yes = no : Answer

def which (a : Answer) = case a of
  | yes -> "Yes!"
  | no  -> "Oh, no!"
```

the value of `which yes` is "Oh, no!", since `yes` here is disambiguated as identifying the `op` `yes`, which has value `no`. The interpretation as `embedder` is forced by using the `embed` keyword: the value of `which embed yes` is "Yes!". By using `simple-names`

that begin with a capital letter for constructors, and simple-names that do not begin with a capital letter for ops and local-variables, the risk of an accidental wrong interpretation can be avoided.

The semantics of **embedders** is described in the section on *Type-sums*. The presence or absence of the keyword `embed` is not significant for the meaning of the construct (although it may be required for grammatical disambiguation, as described above).

2.6.16.6. Embedding-tests

`embedding-test ::= embed? constructor`

Sample embedding-test:

```
embed? Cons
```

Restriction. The type of an **embedding-test** `embed? C` must be of the form $T \rightarrow \text{Boolean}$, where T is a sum type that has a **constructor** C .

The value of **embedding-test** `embed? C` is the predicate that returns `true` if the argument value -- which, as inhabitant of a sum type, is tagged -- has tag C , and otherwise `false`. The **embedding-test** can be equivalently rewritten as

```
fn
  | C _ -> true
  | _   -> false
```

where the wildcard `_` in the first branch is omitted when C is parameter-less.

In plain words, `embed? C` tests whether its sum-typed argument has been constructed with the constructor C . It is an error when C is not a constructor of the sum type.

2.7. Matches and Patterns

2.7.1. Matches

`match ::= [|] branch { | branch }*`

`branch ::= pattern -> expression`

Sample matches:

```
{re = x, im = y} -> {re = x, im = -y}

Empty -> true
| Push {top = _, pop = rest} -> hasBottom? rest

Empty -> true
| Push {top = _, pop = rest} -> hasBottom? rest
```

Restriction. In a **match**, given the environment, there must be a unique type T to which the **pattern** of each **branch** conforms, and a unique type T to which the **expression** of each **branch** conforms, and then the **match** has type $S \rightarrow T$. The **pattern** of each **branch** then has type S .

Disambiguation. If a **branch** could belong to several open **matches**, it is interpreted as being a **branch** of the textually most recently introduced **match**. For example,

```
case x of
| A -> a
| B -> case y of
| C -> c
| D -> d
```

is not interpreted as suggested by the indentation, but as

```
case x of
| A -> a
| B -> (case y of
| C -> c
| D -> d)
```

If the other interpretation is intended, the **expression** introducing the inner **match** needs to be parenthesized:

```
case x of
| A -> a
| B -> (case y of
| C -> c)
| D -> d
```

Acceptance and return value y , if any, of a value x for a given **match** are determined as follows. If each **branch** of the **match** rejects x (see below), the whole **match** rejects x , and does not return a value. Otherwise, let B stand for the textually first **branch** accepting x . Then y is the return value of x for B .

Acceptance and return value y , if any, of a value x for a **branch** $P \rightarrow E$ in an environment C are determined as follows. If **pattern** P rejects x , the **branch** rejects x , and does not return a value. (For acceptance by a **pattern**, see under *Patterns*.) Otherwise, y is the value of **expression** E in the environment C extended with the acceptance binding of **pattern** P for x .

For example, in

```
case z of
  | (x, true)  -> Some x
  | (_, false) -> None
```

if z has value $(3, \text{true})$, the first branch accepts this value with acceptance binding $x = 3$. The value of `Some x` in the extended environment is then `Some 3`. If z has value $(3, \text{false})$, the second branch accepts this value with empty acceptance binding (empty since there are no “accepting” local-variables in **pattern** `(_, false)`), and the return value is `None` (interpreted in the original environment).

2.7.2. Patterns

```
pattern ::=
  annotated-pattern
  | tight-pattern
```

```
tight-pattern ::=
  aliased-pattern
  | cons-pattern
  | embed-pattern
  | quotient-pattern
  | relax-pattern
  | closed-pattern
```

```
closed-pattern ::=
  variable-pattern
  | wildcard-pattern
  | literal-pattern
  | list-pattern
```

```

| tuple-pattern
| record-pattern
| ( pattern )

```

(As for **expressions**, the distinctions **tight-** and **closed-** for **patterns** have no semantic significance, but merely serve to avoid grammatical ambiguities.)

annotated-pattern ::= **pattern** : **type-descriptor**

aliased-pattern ::= **variable-pattern** **as** **tight-pattern**

cons-pattern ::= **closed-pattern** :: **tight-pattern**

embed-pattern ::= **constructor** [**closed-pattern**]

quotient-pattern ::= **quotient** **closed-expression** **tight-pattern**

relax-pattern ::= **relax** **closed-expression** **tight-pattern**

variable-pattern ::= **local-variable**

wildcard-pattern ::= **_**

literal-pattern ::= **literal**

list-pattern ::= [**list-pattern-body**]

list-pattern-body ::= [**pattern** { **,** **pattern** }^{*}]

tuple-pattern ::= (**tuple-pattern-body**)

tuple-pattern-body ::= [**pattern** **,** **pattern** { **,** **pattern** }^{*}]

record-pattern ::= { **record-pattern-body** }

record-pattern-body ::= [**field-patterner** { **,** **field-patterner** }^{*}]

field-patterner ::= **field-name** [**equals** **pattern**]

Sample patterns:

```

(i, p) : Integer * Boolean
z as {re = x, im = y}
hd :: tail

```



```

Push {top, pop = rest}
embed Empty
quotient congMod3 n
relax even e
x
-
#z
[0, x]
(cl as (0, _), x)
{top, pop = rest}

```

Restriction. Like all polymorphic or type-ambiguous constructs, a **pattern** may only be used in a context where its type can be uniquely inferred.

Disambiguation. A single **simple-name** used as a **pattern** is an **embed-pattern** if it is a **constructor** of the type of the **pattern**. Otherwise, the **simple-name** is a **variable-pattern**.

Restriction. Each **local-variable** in a **pattern** must be a different **simple-name**, disregarding any **local-variables** introduced in **expressions** or **type-descriptors** contained in the **pattern**. (For example, `Line (z, z)` is not a lawful **pattern**, since `z` is repeated; but `n : {n : Nat | n < p}` is lawful: the second `n` is “shielded” by the **type-comprehension** in which it occurs.)

Restriction. The **closed-expression** of a **quotient-pattern** must have some type $T \rightarrow T \rightarrow \text{Boolean}$; in addition, it must be an equivalence relation, as explained under *Type-quotients*.

Restriction. **Quotient-patterns** may only be used in a **definition** or **claim** if the result is insensitive to the choice of representative from the equivalence class. Specware 4.1 does not attempt to generate proof obligations for establishing this.

Restriction. The **closed-expression** of a **relax-pattern** must have some function type $T \rightarrow \text{Boolean}$.

To define acceptance and acceptance binding (if any) for a value and a **pattern**, we introduce a number of auxiliary definitions.

The *accepting* **local-variables** of a **pattern** P are the collection of **local-variables** occurring in P , disregarding any **local-variables** introduced in **expressions** or **type-descriptors** contained in the P . For example, in **pattern** $u : \{v : S \mid p\ v\}$, u is an accepting **local-variable**, but v is not. (The latter is an accepting **local-variable** of **pattern** $v : S$, but not of the larger **pattern**.)

The *expressive descendants* of a pattern are a finite set of expressions having the syntactic form of patterns, as determined in the following three steps (of which the order of steps 1 and 2 is actually immaterial).

Step 1. From pattern P , form some *tame variant* P_t by replacing each field-patterner consisting of a single field-name F by the field-patterner $F = F$ and replacing each wildcard-pattern $_$ in P by a unique fresh simple-name, that is, any simple-name that does not already occur in the spec, directly or indirectly through an import. For example, assuming that the simple-name `v7944` is fresh, a tame variant of

```
s0 as _ :: s1 as (Push {top, pop = rest}) :: ss
```

is

```
s0 as v7944 :: s1 as (Push {top = top, pop = rest}) :: ss
```

Step 2. Next, from P_t , form a (tamed) *construed version* P_{tc} by replacing each constituent cons-pattern $H :: T$ by the embed-pattern $\text{Cons } (H, T)$, where Cons denotes the constructor of the parameterized type `List`. For the example, the construed version is:

```
s0 as Cons (v7944,
            s1 as Cons (Push {top = top, pop = rest}, ss))
```

Step 3. Finally, from P_{tc} , form the set ED_P of *expressive descendants* of P , where expression E is an expressive descendant if E can be obtained by repeatedly replacing some constituent aliased-pattern $L \text{ as } R$ of P_{tc} by one of the two patterns L and R until no aliased-patterns remain, and then interpreting the result as an expression. For the example, the expressive descendants are the three expressions:

```
s0
Cons (v7944, s1)
Cons (v7944, Cons (Push {top = top, pop = rest}, ss))
```

An *accepting binding* of a pattern P for a value x in an environment C is some binding B of typed values to the accepting local-variables of the tame variant P_t , such that the value of each expressive descendant E in ED_P in the environment C extended with binding B , is the same typed value as x .

Acceptance and acceptance binding, if any, for a value x and a pattern P are then determined as follows. If there is no accepting binding of P for x , x is rejected. If an accepting binding exists, the value x is accepted by pattern P . There is a unique binding B among the accepting bindings in which the type of each assigned value is as “restricted” as possible in the subtype-supertype hierarchy without violating well-typedness constraints (in other words, there are no avoidable implicit relaxations). The acceptance binding is then the binding B *projected on* the accepting local-variables of P .

For the example, the accepting local-variables of P_t are the six local-variables $s0$, $s1$, ss , $rest$ and $v7944$. In general, they are the accepting local-variables of the original pattern together with any fresh simple-names used for taming. Let the value x being matched against the pattern be

```
Cons (Empty, Cons (Push {top = 200, pop = Empty}, Nil))
```

Under the accepting binding

```
s0 = Cons (Empty, Cons (Push {top = 200, pop = Empty}, Nil))
s1 = Cons (Push {top = 200, pop = Empty}, Nil)
ss = Nil
top = 200
rest = Empty
v7944 = Empty
```

the value of each E in ED_p amounts to the value x . Therefore, x is accepted by the original pattern, with acceptance binding

```
s0 = Cons (Empty, Cons (Push {top = 200, pop = Empty}, Nil))
s1 = Cons (Push {top = 200, pop = Empty}, Nil)
ss = Nil
top = 200
rest = Empty
```

obtained by “forgetting” the fresh simple-name $v7944$.

Appendix A. Metaslang Grammar

This appendix lists the grammar rules of the Metaslang specification language. These rules are identical to those of the Chapter on *Metaslang*. They are brought together here, without additional text, for easy reference.

The Grammar Description Formalism.

wiffle ::= waffle [waffle-tail] | piffle { + piffle }*

piffle ::= 1 | m { piffle }*

Models.

op ::= op-name

spec ::= spec-form

Symbols and Names.

symbol ::= simple-name | literal | special-symbol

simple-name ::= word-symbol | non-word-symbol

word-symbol ::= word-start-mark { word-continue-mark }*

word-start-mark ::= letter

word-continue-mark ::=
letter | decimal-digit | _ | ?

letter ::=

A	B	C	D	E	F	G	H	I	J	K	L	M
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
a	b	c	d	e	f	g	h	i	j	k	l	m
n	o	p	q	r	s	t	u	v	w	x	y	z

decimal-digit ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

non-word-symbol ::= non-word-mark { non-word-mark }*

non-word-mark ::=

` | ~ | ! | @ | \$ | ^ | & | * | -

Appendix A. Metaslang Grammar

| = | + | \ | | | : | < | > | / | ?

special-symbol ::= _ | (|) | [|] | { | } | ; | , | .

Comments.

comment ::= line-end-comment | block-comment

line-end-comment ::= % line-end-comment-body

line-end-comment-body ::=
any-text-up-to-end-of-line

block-comment ::= (* block-comment-body *)

block-comment-body ::=
any-text-including-newlines-and-nested-block-comments

Units.

unit-definition ::= unit-identifier = unit-term

unit-term ::=
spec-term
| morphism-term
| diagram-term
| target-code-term
| proof-term

specware-file-contents ::=
unit-term
| infile-unit-definition { infile-unit-definition } *

infile-unit-definition ::= fragment-identifier = unit-term

fragment-identifier ::= word-symbol

Unit Identifiers.

unit-identifier ::= swpath-based-path | relative-path

swpath-based-path ::= / relative-path

relative-path ::= { path-element / }^{*} path-element [# fragment-identifier]

path-element ::= word-symbol

Specs.

spec-term ::=
 | unit-identifier
 | spec-form
 | spec-qualification
 | spec-translation
 | spec-substitution
 | diagram-colimit
 | obligator

Spec Forms.

spec-form ::= **spec** { declaration }^{*} **endspec**

Qualifications.

spec-qualification ::= qualifier **qualifying** spec-term

qualifier ::= word-symbol

name ::= simple-name | qualified-name

qualified-name ::= qualifier . simple-name

Translations.

spec-translation ::= **translate** spec-term **by** name-map

name-map ::= { [name-map-item { , name-map-item }^{*}] }

name-map-item ::= type-name-map-item | op-name-map-item

type-name-map-item ::= [**type**] name +-> name

op-name-map-item ::= [**op**] annotable-name +-> annotable-name

annotable-name ::= name [: type-descriptor]

Substitutions.

spec-substitution ::= spec-term [morphism-term]

Diagram Colimits.

diagram-colimit ::= **colimit** diagram-term

Obligators.

obligator ::= **obligations** unit-term

Morphisms.

morphism-term ::=
 unit-identifier
 | spec-morphism

spec-morphism ::= **morphism** spec-term -> spec-term name-map

Diagrams.

diagram-term ::=
 unit-identifier
 | diagram-form

diagram-form ::= **diagram** { diagram-element { , diagram-element }* }

diagram-element ::=
 diagram-node
 | diagram-edge

diagram-node ::= simple-name +-> spec-term

diagram-edge ::= simple-name : simple-name -> simple-name +-> morphism-term

Target Code Terms.

target-code-term ::=
 generate target-language-name spec-term [**in** string-literal]

target-language-name ::= **c** | **java** | **lisp**

Proof Terms.

proof-term ::=
 prove claim-name **in** spec-term
 [**with** prover-name]
 [**using** claim-list]
 [**options** prover-options]

prover-name ::= **snark**

claim-list ::= claim-name { **,** claim-name }*

prover-options ::= string-literal

Declarations.

declaration ::=
 import-declaration
 | type-declaration
 | op-declaration
 | definition

definition ::=
 type-definition
 | op-definition
 | claim-definition

equals ::= **is** | **=**

Import-declarations.

import-declaration ::= **import** spec-term

Type-declarations.

type-declaration ::= **type** type-name [formal-type-parameters]

formal-type-parameters ::= local-type-variable | (local-type-variable-list)

local-type-variable ::= simple-name

Appendix A. Metaslang Grammar

local-type-variable-list ::= local-type-variable { , local-type-variable }*

Type-definitions.

type-definition ::= **type** type-name [formal-type-parameters] equals type-descriptor

Op-declarations.

op-declaration ::= **op** op-name [fixity] : type-scheme

fixity ::= associativity priority

associativity ::= **infixl** | **infixr**

priority ::= nat-literal

type-scheme ::= [type-variable-binder] type-descriptor

type-variable-binder ::= `[local-type-variable-list `]

Op-definitions.

op-definition ::=

def [type-variable-binder] formal-expression [: type-descriptor] equals
expression

formal-expression ::= op-name | formal-application

formal-application ::= formal-application-head formal-parameter

formal-application-head ::= op-name | formal-application

formal-parameter ::= closed-pattern

Claim-definitions.

claim-definition ::= claim-kind claim-name equals claim

claim-kind ::= **axiom** | **theorem** | **conjecture**

claim-name ::= simple-name

claim ::= [type-variable-binder] expression

Type-descriptors.

type-descriptor ::=
 type-sum
 | type-arrow
 | slack-type-descriptor

slack-type-descriptor ::=
 type-product
 | tight-type-descriptor

tight-type-descriptor ::=
 type-instantiation
 | closed-type-descriptor

closed-type-descriptor ::=
 type-name
 | **Boolean**
 | local-type-variable
 | type-record
 | type-restriction
 | type-comprehension
 | type-quotient
 | (type-descriptor)

Type-sums.

type-sum ::= type-summand { type-summand }*

type-summand ::= | constructor [slack-type-descriptor]

constructor ::= simple-name

Type-arrows.

type-arrow ::= arrow-source -> type-descriptor

arrow-source ::= type-sum | slack-type-descriptor

Type-products.

type-product ::= tight-type-descriptor * tight-type-descriptor { * tight-type-descriptor }*

Type-instantiations.

type-instantiation ::= type-name actual-type-parameters

actual-type-parameters ::= closed-type-descriptor | (proper-type-list)

proper-type-list ::= type-descriptor , type-descriptor { , type-descriptor }*

Type-names.

type-name ::= name

Type-records.

type-record ::= { [field-typer-list] } | ()

field-typer-list ::= field-typer { , field-typer }*

field-typer ::= field-name : type-descriptor

field-name ::= simple-name

Type-restrictions.

type-restriction ::= (slack-type-descriptor | expression)

Type-comprehensions.

type-comprehension ::= { annotated-pattern | expression }

Type-quotients.

type-quotient ::= closed-type-descriptor / closed-expression

Expressions.

expression ::=
 lambda-form
 | case-expression
 | let-expression
 | if-expression
 | quantification
 | annotated-expression
 | tight-expression

tight-expression ::=
 application
 | restrict-expression
 | closed-expression

closed-expression ::=
 op-name
 | local-variable
 | literal
 | field-selection
 | tuple-display
 | record-display
 | sequential-expression
 | list-display
 | structor
 | (expression)
 | (inbuilt-op)

inbuilt-op ::= inbuilt-prefix-op | inbuilt-infix-op

inbuilt-prefix-op ::= ~

inbuilt-infix-op ::= => | <=> | || | && | = | ~= | <<

Lambda-forms.

lambda-form ::= fn match

Case-expressions.

case-expression ::= **case** expression **of** match

Let-expressions.

let-expression ::= **let** let-bindings **in** expression

let-bindings ::= recless-let-binding | rec-let-binding-sequence

recless-let-binding ::= pattern equals expression

rec-let-binding-sequence ::= rec-let-binding { rec-let-binding }*

rec-let-binding ::=

def simple-name formal-parameter-sequence [: type-descriptor] equals expression

formal-parameter-sequence ::= formal-parameter { formal-parameter }*

If-expressions.

if-expression ::= **if** expression **then** expression **else** expression

Quantifications.

quantification ::= quantifier (local-variable-list) expression

quantifier ::= **fa** | **ex**

local-variable-list ::= annotable-variable { , annotable-variable }*

annotable-variable ::= local-variable [: type-descriptor]

local-variable ::= simple-name

Annotated-expressions.

annotated-expression ::= tight-expression : type-descriptor

Applications.

`application ::= prefix-application | infix-application`

`prefix-application ::= application-head actual-parameter`

`application-head ::=`
 `closed-expression`
 `| inbuilt-prefix-op`
 `| prefix-application`

`actual-parameter ::= closed-expression`

`infix-application ::= operand infix-operator operand`

`operand ::= tight-expression`

`infix-operator ::= op-name | inbuilt-infix-op`

Restrict-expressions.

`restrict-expression ::= restrict closed-expression closed-expression`

Op-names.

`op-name ::= name`

Literals.

`literal ::=`
 `boolean-literal`
 `| nat-literal`
 `| char-literal`
 `| string-literal`

Boolean-literals.

`boolean-literal ::= true | false`

Nat-literals.

`nat-literal ::= decimal-digit { decimal-digit }*`

Char-literals.

char-literal ::= #char-literal-glyph

char-literal-glyph ::= char-glyph | "

char-glyph ::=
letter
| decimal-digit
| other-char-glyph

other-char-glyph ::=
! | : | @ | # | \$ | % | ^ | & | * | (|) | _ | - | + | =
| | ~ | \ | . | , | < | > | ? | / | ; | ' | [|] | { | }
| \ \ | \"
| \a | \b | \t | \n | \v | \f | \r | \s
| \x hexadecimal-digit hexadecimal-digit

hexadecimal-digit ::=
decimal-digit
| a | b | c | d | e | f
| A | B | C | D | E | F

String-literals.

string-literal ::= " string-body "

string-body ::= { string-literal-glyph }*

string-literal-glyph ::= char-glyph | significant-whitespace

significant-whitespace ::= space | tab | newline

Field-selections.

field-selection ::= closed-expression . field-selector

field-selector ::= nat-literal | field-name

Tuple-displays.

tuple-display ::= (tuple-display-body)

`tuple-display-body ::= [expression , expression { , expression }*]`

Record-displays.

`record-display ::= { record-display-body }`

`record-display-body ::= [field-filler { , field-filler }*]`

`field-filler ::= field-name equals expression`

Sequential-expressions.

`sequential-expression ::= (open-sequential-expression)`

`open-sequential-expression ::= void-expression ; sequential-tail`

`void-expression ::= expression`

`sequential-tail ::= expression | open-sequential-expression`

List-displays.

`list-display ::= [list-display-body]`

`list-display-body ::= [expression { , expression }*]`

Structors.

`structor ::=`
 `projector`
 `| relaxator`
 `| quotienter`
 `| chooser`
 `| embedder`
 `| embedding-test`

`projector ::= project field-selector`

`relaxator ::= relax closed-expression`

`quotienter ::= quotient closed-expression`

Appendix A. Metaslang Grammar

chooser ::= **choose** closed-expression

embedder ::= [**embed**] constructor

embedding-test ::= **embed?** constructor

Matches.

match ::= [|] branch { | branch }*

branch ::= pattern -> expression

Patterns.

pattern ::=
 annotated-pattern
 | tight-pattern

tight-pattern ::=
 aliased-pattern
 | cons-pattern
 | embed-pattern
 | quotient-pattern
 | relax-pattern
 | closed-pattern

closed-pattern ::=
 variable-pattern
 | wildcard-pattern
 | literal-pattern
 | list-pattern
 | tuple-pattern
 | record-pattern
 | (pattern)

annotated-pattern ::= pattern : type-descriptor

aliased-pattern ::= variable-pattern **as** tight-pattern

cons-pattern ::= closed-pattern :: tight-pattern

embed-pattern ::= constructor [closed-pattern]

quotient-pattern ::= **quotient** closed-expression tight-pattern

relax-pattern ::= **relax** closed-expression tight-pattern

variable-pattern ::= local-variable

wildcard-pattern ::= **_**

literal-pattern ::= literal

list-pattern ::= [list-pattern-body]

list-pattern-body ::= [pattern { , pattern }^{*}]

tuple-pattern ::= (tuple-pattern-body)

tuple-pattern-body ::= [pattern , pattern { , pattern }^{*}]

record-pattern ::= { record-pattern-body }

record-pattern-body ::= [field-patterner { , field-patterner }^{*}]

field-patterner ::= field-name [equals pattern]

Appendix B. Inbuilts and Base Libraries

This appendix provides a brief description of the types and operators that are either “inbuilt” or provided by the current base libraries. The base libraries are automatically imported by every user-defined `spec`. The title of each section of this appendix is the qualifier of the `type`- and `op`-names given therein. For example, the full name for `op ++` described in Section “List” is `List.++`. However, for the *unary* operator `-` on integers, the qualifier is `Integer_`. Note, also, that inbuilts cannot be qualified.

For the sake of brevity, `infixl` is abbreviated below to `L` and `infixr` to `R`.

B.1. Inbuilts

Inbuilt Type

`Boolean`

Inbuilt Ops

Name	Fixity	Type	Description
<code>=</code>	R 20	<code>[a] a * a -> a</code>	tests if the parameters are equal
<code>~=</code>	R 20	<code>[a] a * a -> a</code>	tests if the parameters are unequal
<code>~</code>		<code>Boolean -> Boolean</code>	logical negation
<code>&&</code>	R 15	<code>Boolean * Boolean -> Boolean</code>	non-strict logical and
<code> </code>	R 14	<code>Boolean * Boolean -> Boolean</code>	non-strict logical or
<code>=></code>	R 13	<code>Boolean * Boolean -> Boolean</code>	non-strict logical implication
<code><=></code>	R 12	<code>Boolean * Boolean -> Boolean</code>	logical equivalence

Name	Fixity	Type	Description
<<	L 25	$\{x:A, \dots, y:B, \dots\} * \{x:A, \dots, z:C, \dots\} \rightarrow \{x:A, \dots, y:B, \dots, z:C, \dots\}$	see Section Applications under <i>record update</i>

B.2. Boolean

Ops

Name	Fixity	Type	Description
toString		Boolean -> String	converts logical value to string
show		Boolean -> String	same as toString
compare		Boolean * Boolean -> Comparison	compares two logical values

B.3. Integer

Types

```

type Integer
type NonZeroInteger = {i : Integer | i ~= 0}

```

Ops

Name	Fixity	Type	Description
-		Integer -> Integer	unary minus (has qualifier Integer_!)
+	L 25	Integer * Integer -> Integer	addition
-	L 25	Integer * Integer -> Integer	subtraction
*	L 27	Integer * Integer -> Integer	multiplication
div	L 26	Integer * NonZeroInteger -> Integer	division (truncates towards 0)
rem	L 26	Integer * NonZeroInteger -> Integer	remainder ($x \text{ rem } y = x - y * (x \text{ div } y)$)
<	L 20	Integer * Integer -> Boolean	less-than
<=	L 20	Integer * Integer -> Boolean	less-than-or-equal
>	L 20	Integer * Integer -> Boolean	greater-than
>=	L 20	Integer * Integer -> Boolean	greater-than-or-equal
abs		Integer -> Integer	absolute value
min		Integer * Integer -> Integer	minimum
max		Integer * Integer -> Integer	maximum
compare		Integer * Integer -> Comparison	compares two integers
toString		Integer -> String	converts integer to string
show		Integer -> String	same as toString
intToString		Integer -> String	same as toString

Name	Fixity	Type	Description
<code>intConvertible</code>		<code>String -> Boolean</code>	tests if string is representation of integer
<code>stringToInt</code>		<code>(String intConvertible) -> Integer</code>	converts “convertible” string to integer

B.4. Nat

Types

```

type Nat = {n : Integer | n >= 0}
type PosNat = {n : Nat | n > 0 }

```

Ops

Name	Fixity	Type	Description
<code>succ</code>		<code>Nat -> Nat</code>	successor
<code>pred</code>		<code>Nat -> Integer</code>	predecessor
<code>zero</code>		<code>Nat</code>	the natural number 0
<code>one</code>		<code>Nat</code>	the natural number 1
<code>two</code>		<code>Nat</code>	the natural number 2
<code>posNat?</code>		<code>Nat -> Boolean</code>	yields false for 0, true otherwise
<code>toString</code>		<code>Nat -> String</code>	converts natural number to string
<code>show</code>		<code>Nat -> String</code>	same as <code>toString</code>

Name	Fixity	Type	Description
<code>natToString</code>		<code>Nat -> String</code>	same as <code>toString</code>
<code>natConvertible</code>		<code>String -> Boolean</code>	tests if string is representation of natural number
<code>stringToNat</code>		<code>(String natConvertible) -> Nat</code>	converts “convertible” string to natural number

B.5. Char

Type

```
type Char
```

Ops

Name	Fixity	Type	Description
<code>ord</code>		<code>Char -> Nat</code>	converts character to natural number
<code>chr</code>		<code>Nat -> Char</code>	converts natural number to character
<code>isAlpha</code>		<code>Char -> Boolean</code>	true for letters
<code>isNum</code>		<code>Char -> Boolean</code>	true for digits
<code>isAlphaNum</code>		<code>Char -> Boolean</code>	true for letters and digits
<code>isAscii</code>		<code>Char -> Boolean</code>	true for ASCII characters

Name	Fixity	Type	Description
isLowerCase		Char -> Boolean	true for lower-case letters
isUpperCase		Char -> Boolean	true for upper-case letters
toUpperCase		Char -> Char	converts to upper case
toLowerCase		Char -> Char	converts to lower case
compare		Char * Char -> Comparison	compares two character values
toString		Char -> String	converts character to string
show		Char -> String	same as toString

B.6. String

Type

```
type String
```

Ops

Name	Fixity	Type	Description
explode		String -> List(Char)	converts string to list of characters
implode		List(Char) -> String	converts list of characters to string
length		String -> Nat	length of a string

Name	Fixity	Type	Description
leq	L 20	String * String -> Boolean	lexicographic less-than-or-equal
lt	L 20	String * String -> Boolean	lexicographic less-than
++	L 25	String * String -> String	string concatenation
^	L 25	String * String -> String	same as ++
concat		String * String -> String	prefix op for string concatenation
concatList		List String -> String	returns the concatenation of the list elements
sub		String * Nat -> Char	returns the n th character in a string, counting from 0
substring		String * Nat * Nat -> String	substring(s , m , n) returns the substring of s from position m through position $n-1$, counting from 0
map		(Char -> Char) * String -> String	returns the concatenation of the results of applying the function given as first parameter to each character of the string
translate		(Char -> String) * String -> String	returns the concatenation of the results of applying the function given as first parameter to each character of the string
all		(Char -> Boolean) * String	true if all characters in the string satisfy the predicate given as first parameter
exists		(Char -> Boolean) * String	true if some character in the string satisfies the predicate given as first parameter
newline		String	the string representing a line break

Name	Fixity	Type	Description
toScreen		String -> ()	prints the string on the terminal
writeLine		String -> ()	same with a newline appended
compare		String * String -> Comparison	compares two strings

B.7. List

Type

```
type List a = | Nil | Cons a * List a
```

Ops

Name	Fixity	Type	Description
nil		[a] List a	the empty list
null		[a] List a -> Boolean	true for empty lists
length		List a -> Nat	length of a list
cons		[a] a * List a -> List a	constructs a list consisting of a first element and a list tail
insert		[a] a * List a -> List a	same as cons
hd		[a] List a -> a	returns the first element of the list
tl		[a] List a -> List a	returns the list tail without the first element
++	L 25	[a] List a * List a -> List a	list concatenation

Name	Fixity	Type	Description
concat		$[a] \text{ List } a * \text{ List } a \rightarrow \text{ List } a$	prefix op for list concatenation
flatten		$[a] \text{ List}(\text{List}(a)) \rightarrow \text{ List } a$	returns the concatenation of the list elements
diff		$[a] \text{ List } a * \text{ List } a \rightarrow \text{ List } a$	list subtraction: $\text{diff}(x, y)$ returns a list containing the elements of x that are not in y , preserving the order of the elements in x
member		$[a] a * \text{ List } a \rightarrow \text{ Boolean}$	list membership
nth		$[a] \text{ List } a * \text{ Nat} \rightarrow a$	$\text{nth}(x, n)$ returns the element at position n of list x , counting from 0
nthTail		$[a] \text{ List } a * \text{ Nat} \rightarrow \text{ List } a$	$\text{nthTail}(x, n)$ returns the tail of list x , starting after position n , counting from 0
sublist		$[a] \text{ List } a * \text{ Nat} * \text{ Nat} \rightarrow \text{ List } a$	$\text{sublist}(x, m, n)]$ returns the tail of list x , from position m up to but not including n , counting from 0
foldl		$[a, b] (a * b \rightarrow b) \rightarrow b \rightarrow \text{ List } a \rightarrow b$	$\text{foldl } f \ e \ x$ successively applies function f to the elements of list x from left to right. The second argument to f is initially e and at each next step the result of the previous invocation of f
foldr		$[a, b] (a * b \rightarrow b) \rightarrow b \rightarrow \text{ List } a \rightarrow b$	like foldl , but the elements of the list are processed from right to left
map		$[a, b] (a \rightarrow b) \rightarrow \text{ List } a \rightarrow \text{ List } b$	applies function to each element of a list and returns the list consisting of the results

Appendix B. Inbuilts and Base Libraries

Name	Fixity	Type	Description
mapPartial		<code>[a,b] (a -> Option b) -> List a -> List b</code>	like map but replacing each result <code>Some y</code> by <code>y</code> and deleting <code>None</code> results.
filter		<code>[a] (a -> Boolean) -> List a -> List a</code>	returns the list of elements satisfying the given predicate
rev		<code>[a] List a -> List a</code>	reverse list
all		<code>[a] (a -> Boolean) -> List a -> Boolean</code>	true if all elements of the list satisfy the predicate given as first parameter
exists		<code>[a] (a -> Boolean) -> List a -> Boolean</code>	true if some element of the list satisfies the predicate given as first parameter
find		<code>[a] (a -> Boolean) -> List a -> Option(a)</code>	returns <code>Some x</code> where <code>x</code> is the first element in the list (from left to right) for which the given predicate yields true; if no such element exists, <code>None</code> is returned
tabulate		<code>[a] Nat * (Nat -> a) -> List a</code>	<code>tabulate(n, f)</code> returns the list <code>[f(0), f(1), ..., f(n-1)]</code>
firstUpTo		<code>[a] (a -> Boolean) -> List a -> Option (a * List a)</code>	returns <code>Some(e, x)</code> where <code>e</code> is the first element in the list (from left to right) satisfying the given predicate and <code>x</code> the initial list segment preceding <code>e</code> ; if no such element exists, <code>None</code> is returned
splitList		<code>[a] (a -> Boolean) -> List a -> Option (List a * a * List a)</code>	returns <code>Some(x, e, y)</code> where <code>e</code> is the first element in the list (from left to right) satisfying the given predicate, <code>x</code> the initial list segment preceding <code>e</code> , and <code>y</code> the list tail following <code>e</code> ; if no such element exists, <code>None</code> is returned

Name	Fixity	Type	Description
locationOf		<code>[a] List a * List a -> Option (Nat * List a)</code>	<code>locationOf(s, t)</code> returns <code>Some(n, x)</code> where <code>n</code> is the first position in list <code>t</code> (counting from left to right) where list <code>s</code> occurs as a contiguous sublist, and <code>x</code> the list tail segment following <code>s</code> in <code>t</code> ; if <code>s</code> does not occur in <code>t</code> , <code>None</code> is returned
compare		<code>[a] (a * a -> Comparison) -> List a * List a -> Comparison</code>	compares two list using the comparison function given as first parameter
show		<code>[a] String -> List String -> String</code>	<code>show(s, x)</code> returns the element strings in <code>x</code> concatenated, with string <code>s</code> inserted between any two elements

B.8. Compare

Type

```
type Comparison = | Less | Equal | Greater
```

Ops

Name	Fixity	Type	Description
compare		<code>Comparison * Comparison -> Comparison</code>	compares comparison values

Name	Fixity	Type	Description
show		Comparison -> String	converts comparison value to string

B.9. Option

Type

```
type Option a = | Some a | None
```

Ops

Name	Fixity	Type	Description
some		[a] a -> Option a	op that constructs Some x
none		[a] Option a	op that constructs None
some?		[a] Option a -> Boolean	tests if the parameter is of the form Some x
none?		[a] Option a -> Boolean	tests if the parameter is None
compare		[a] (a * a -> Comparison) -> Option a * Option a -> Comparison	returns the result of the comparison of the two optional values, where None is less than Some x for all x; if both optional values are of the form Some x, the comparison function given as first parameter is used to compute the result
mapOption		[a,b] (a -> b) -> Option a -> Option b	applies the function given as first parameter to the optional value if it is Some x, otherwise None is returned

Name	Fixity	Type	Description
show		<code>[a,b] (a -> String) -> Option a -> String</code>	converts optional value to string; if the optional value is <code>Some x</code> , it uses the function given as first parameter to convert <code>x</code> to a string

B.10. Functions

Types

```

type Injective(a,b) = ((a -> b) | injective?)
type Surjective(a,b) = ((a -> b) | surjective?)
type Bijective(a,b) = ((a -> b) | bijective?)

```

Ops

Name	Fixity	Type	Description
id		<code>[a] a -> a</code>	identity function
o	L 24	<code>[a,b,c] (b -> c) * (a -> b) -> (a -> c)</code>	function composition
injective?		<code>[a,b] (a -> b) -> Boolean</code>	injectivity predicate; non-constructive
surjective?		<code>[a,b] (a -> b) -> Boolean</code>	surjectivity predicate; non-constructive
bijective?		<code>[a,b] (a -> b) -> Boolean</code>	bijectivity predicate; non-constructive

Appendix B. Inbuilts and Base Libraries

Name	Fixity	Type	Description
inverse		<code>[a,b] Bijective(a,b)</code> <code>-> Bijective(b,a)</code>	inverts bijective function; non-constructive